Business and Personal.

The Charge for Insertion under this head is \$1 a Line.

The Fagin Flour Mill, Newark, New Jersey has been purchased by Messrs. F. G. a I. N. Van Vleit, of New York, for a Malt House. All the Machin ry is for Sale—nearly new, and in perfect order—being one 500. Horse Power Eng ne, with Condenser and 25 ton Fly Wheel, made by Hewes & Phi lips, and has given best results ever attained, making Flour with 18½ lbs. coal to the barrel. Also, 20 Runs French Burrs, made by Baxter & Co., of Chicago, 4 ft. 6 in. diameter—1 Corn Mill, made by John T. Noye, 36 in.—8 Smut Machines—4 Fagin Brush Smutters—4 Trimmer Separators—6 Bran Dusters—1 Mat-tison and 3 Taggart Packers—1 Barre! and Man Elevator for 9 Stories-Conveyors, Elevators, Belts, Pulleys, Gears, Frictions, Reels, Screens, Bolting Cloths, etc., etc. etc. This Mi I has made only about 200,030 barrels of Flour, and the Stones are better than new. Attention of Millers and Millwrights throughout the country is called to this Sale. Apply on the premises, or by mail, to Henry Hill, late of Fagin & Co., P.O. Box 26 Newark, New Jersey.

Wanted—A Horizontal Engine with reversing valve gear, C, l.nder 5x6 or 8 in. Address, with full particulars and Price, Box 553, Owego, Tioga Co., N. Y.

The New Elastic Truss presses uniformly all around the body, and holds the Rupture easy, night and lay, till cured. Sold cheap by the Elastic Truss Co. 683 Broadway, New York.

Bogardus Wet Mills to exchange for Bogardus Dry Mills. Address Charles C. Fuller, St. Louis, Mo. Cheap non-patent d self-operating Earth Closet. Specifications and plans drawn to scale sent for 25 cents. H. Kay, Box 210 Jamaica Plain, Mass.

Wanted—To purchase the right to manufacture in Canada some patented article which is likely to come into general use, made up principally of cast iron, requiring lettle labor or machine work on it. Address X. Y.Z., Dundas, Ontario, Canada.

Wanted - A g pri second hand Steam Fire Engine. Add ess Michigan Car Co., Detroit, Mich.

Those who wish to purchase Horse Powers and Machines for Threshing and Cleaning Grain and Sawing Wood, will do well to send for circ.lar, &c., of A. W. Gray and Sons, Middletown, Vermont.

Prov. Pump Co., Providence, R. I., Dealers, want illustrated Circulars and Prices of all kinds of Pumps, and Steam and water Appliances generally.

A perfect Cockle Separator and Wheat Grader for Flouring Mills. Balch & Giddings, Hingham, Wis.

The Cornell University, Ithaca, N.Y., offers iberthand practical courses for agriculturists, architects, civil engineers, master mechanics, mechanical engineers, agricultural and manufacturing chemists, printers, veterinary surgeons, etc., with laboratories, draughting rooms, farms and work shops. In agriculture and mechanic arts, various courses are provided to meet wants of all students; also general courses in arts, lite rature and science preparatory to the other professions. Over five hundred free scholarships. Next year begins Sept. 8. For Registers, with full information, address

Buy Gear's New Emery Grinding Machine

Treatise on "Soluble Glass," new edition just out, \$1, mailed by L. & J. W. Feuchtwanger, 55 Cedar Street, New York.

Hydrofluoric Acid, for Etching and Cleaning Glass, put up in all size Lead and Rabber Bottles, for sale by L. & J. W. Feuchtwanger, Chemists, 55 Cedar Street, New York.

Manganese Black Oxide, for Steel M'f'ct'rs and Oil Bollers, for sale by L. & J. W Feuchtwanger, 55 Cedar Street, New York.

Write to L. & J. W. Feuchtwanger, New York, for all Crude Minerals, Metals, Ores, Drugs and Che nicals, at lowest rate :.

Boult's Patent Upright Single Spindle Com-bined Moulding, Paneling, and Dovetailing Machine. No infringement on the combination guide head Shaper. Does the greatest variety of work with the simplest changes of any machine made. Furniture, Car, Carriage House, Sash, Door and Blind Makers all use it to advantage. Battle Creek Machinery Company, Manufacturers Battle Creek, Michigan.

Buy Planing and Moulding Machines of Gear, Boston, Mass.

Lathes, Planers, Drills, Milling and Index achines. Geo. S. Lincoln & Co., Hartford, Conn.

Scale in Steam Boilers—How to Remove and Prevent it. Address Geo. W. Lord, Philadelphia, Pa. Williamson's Road Steamer and Steam Plow, with rubber Tires. Address D. D. Williamson, 32 Broadway, New York, or Box 1809.

Nickel and its Uses for Plating, with general description. Price 50c.a copy, mailed free, by L. & J. W. Feucht a anger, 55 Cedar Street, New York.

Catalogue on Transmission of Power by Wire Rope. T. R. Bailey & Vail.

No Bolts, no Keys, no Set Screws used in Coupling or Pulley Fastening. Shortt's Patent Couplings, Pulleys, Hangers and Shafting a Specialty. Orders promptly filled. Circulars free. Address Shortt Manufacturing Company, Curthage, N. Y.

Root's Wrought Iron Sectional Safety Boiler. 1,0.0 in use. Address Root Steam Engine Co. 2d Avenue and 28th Street, New York.

For Solid Emery Wheels and Machinery, send to the Union Stone Co., Boston, Mass. for circular. All Fruit-can Tools, Ferracute, Bridgeton, N.J.

To Manufacturers—Built expressly to rent, New Brick Building. 60x300 ft., 3 stories hish, divided by free proof walls, with ample water power. Room and will probably be only half an inch in thickness. Will it power in quantities to suit. Address Industrial M'f'g besafe to run the engine so, and was the cylinder of an Company, Rock Falls, Whiteside Co., Ill.

The Best Smutter and Separator Combined in America. Address M. Deal & Co., Bucyrus, Ohio.

Damper Regulators and Gage Cocks—For the best, address Murrill & Keizer, Baltimore, Md.

Covering for Boilers and Pipes. The most economical and durablearticle in use. Took first prize at American Institute Fair. Van Tuyl Manufacturing Company, 528 Water Street, New York.

The Berryman Heater and Regulator for Steam Boilers—No one using Steam Boilers can afford to be without them. 1. B. Davis & Co.

Five different sizes of Gatling Guns are now manufactured at Cole's Armory, Hartford, Conn. The larger sizes have a range of over two miles. These arms are indispensable in modern warfare.

Gauge Lathe for Cabinet and all kinds of handles. Shaping Machine for Woodworking. T. R. Bailey & Vail, Lockport, N. Y.

Manufacturers who wish to be represented in New York can make arrangements with a reliable Houseby addressing Sterling & Noble, 27 Park Place, N.Y.

Houses have it.

Bookkeepers should try the Olmsted Patent Bill File and Letter Clip. They are admirable for all papers. Save their cost in one day's business. Sold by

Peck's Patent Drop Press. For circulars, address Milo, Peck & Co., New Haven, Conn.

Mining, Wrecking, Pumping, Prainage, or trigating Machinery, forsale or rent, See advertisement, Andrew's Patent, inside page.

Machinists—Price List of small Tools free; Gear Wheels for Models, Price List free; Chucks and Prills, Price List free. Goodnow & Wightman, 23 Cornnill. Boston, Mass.

The Berryman Steam Trap excels all others. The best is always the cheapest. Address 1. B. Davis & Co., Hartford, Conn.

For best Presses, Dies and Fruit Can Tools, Bliss & Williams. cor. of Plymouth & Jay, Brooklyn, N. T. For Solid Wrought-iron Beams, etc., see advertisement. Address Union Iron Mills, Pittsburgh, Pa.,

Parties desiring Steam Machinery for quar-ing stone, address Steam Stone Cutter Co., Rutland, Vt. Boring Machine for Pulleys—no limit to apacity. T. R. Bailey & Vail, Lockbort, N. Y.

Brown's Coalyard Quarry & Contractors' Apparatus forhoisting and conveying material by iron cable, V.D. Andrews & Bro. 414 Waterst.N. Y.

The Berryman Manuf. Co. make a specialty of the economy and safety in working Steam Boilers. 8. Davis & Co., Hartford, Conn.

Key Seat Cutting Machine.T.R.Bailey & Vail.

Cheap Wood-Working Machinery. Address M. B. Cochran & Co., Pittsburgh, Pa.

Steam Fire Engines, R.J. Gould, Newark, N.J.

Sure cure for Slipping Belts-Sutton's pat-t Pulley Cover is warranted to do double the work before the belt will slip. See Sci. Am. June 21st, 1873, Page 389. Circularsfree. J. W.Sutton,95 Liberty St., N. Y.

The Ellis Vapor Engines, with late improvements, manufactured by Haskins Machine Company,



E. R. would like to know how to soften pearl shells, and how to stain them in any color.

O. C. W. asks: Which is the easiest, to n:ake steam with high water or with low water in the

P. asks: What is the best oil to keep pat ent leather from cracking?

D. & Co. ask: 1. Is hemp preyed upon by any insect? Is it offensive to insects of her than its parasites; and if so, within what radius? Might it be made efficacious in protecting cotton from the ravages of the cotton worm? Could any other plant be utilized in this

J. M. R. asks: Why the images of objects being reversed upon the retina of the eye, are yet appa rent to us in their proper positions?

W. J. M. asks: How many gold fish can I keep in a tank holding 32 gallons of water, and how many plants will Ineed?

A. S. Jr. asks how to make the so-called scintillettes, or Japanese parlor fireworks



 $J.\ K.\ S.$ can remove rust from steel articles by following the directions given on p. 26. vot. 25.—The process of polishing shirt bosoms, collars, etc., asked for by J. A. M., is given on p. 114, vol. 24.—A. W. can obtain Stülzel's work on metallurgy through any of the booksellers who advertise in our columns. The book, we believe, has never been translated into English.—E. S.'s query about preservir g vegetables and fruits is too comprehensive to be answered in these columns. Apply to some one who is a preserver by trade.

E. B. G. says: 1. We have had two very dry seasons during 1871 and 1872, only a third or one half of our usual rain having fallen; consequently the wells became very low, and some entirely dry. When the ground froze, about November last, we had only five or six inches of water in our well. From that time, the ground being constantly frozen, the water began to increase; and at the time of the spring thaw, about the middle of March, the water measured five feet, and after the spring rains about six feet. How is the rise of water to be ac-1,0.0 in use. Address Root Steam Engine Co. 2d Avenue and 28th Street, New York.

Cabinet Makers' Machinery. T.R.Bailey&Vail.

Belting—Best Philadelphia Oak Tanned.

C. W. Arny, 301 and 383 Cherry Street, Philadelphia, Pa.

Cabinet Makers' Machinery. T.R.Bailey&Vail.

Belting—Best Philadelphia, Pa.

S. C. says: Suppose that two upright tubular boilers are placed 30 feet apart, and connected with lex to the door (it was necessary to place it crossways of 25 inches wrought from steam pipe, and two horizontal C. W. Arny, 301 and 383 Cherry Street, Philadelphia, Pa. ashes out? 3. I am boring out a cylinder of a steam engine that was originally 10 inch bore and 20 inch stroke. but it has been reboredso many times that it is now 11 inches inside; consequently the cylinder is only about five eighths of an inch in thickness, and, when finished engine ever known to burst from the pressure of steam? Answers: 1. The well may be supplied from a distant source, which is subject to different climatic influences. pressure in the latter. 2. You do not send sufficient data to enable us to answer this question. 3. Cylinders have been known to burst when the engines were working. Your cylinder will be deficient in stiffness, and will have a tendency to become oval. You can stiffen it with bands, and it will then be safe for a reasonable pressure of steam,

> C. G. van P. asks: 1. Is there any sheet metal more pliable and not much more expensive than galvanized iron, on which any design can be pressed with a drop press, to a hight of ¾ inch, without crack ing? It is to be used for roofing purposes. 2. What is the Francis metal, from which life boats are made? Auswers: 1. Zinc possesses greater malleability and ductability than iron, and its price is less than that of galvanized iron. 2. The Francis life boat is constructed of corrugated iron.

outside of the building? Answer: A complete system of ventilation, to operate properly both in summer and winter, requires ventilating registers both at the floor and at the ceiling. In winter it is preferable to have the upper one closed, so that the heated air may not too readily escape, and the vitiated air be driven out of the lower one by the pressure of the warm air from the furnace. In summer, by opening the upper one, the warmed air will escape in that direction, and the fresh air be most prevalent at the lower part of the room, where it is most available for use. A similar duplex arrangement is desirable also in respect to the supply of air to the furnace. There should be a cold air shaft arranged to draw the pure air from the exterior of the house, and this should be the usual source of the supply; but on occasions of extreme cold weather, the heating of this very cold air maybe beyond the capacity of the furnace, and it may then be admissible to feed the furnace from as the interior air of the house, which may thus be warmed a second time; but the healthier way is to draw the air from the outside of the house.

J. W. S. asks (1) for a recipe for making matches. 2. Is the invention of the friction match patented? 3. Is not a steam engine that has no condenser called a high pressure engine? Answers: The mixtures actually used in the trade are kept secret, but the following recipes give some idea of the composition: Phos phorus 8 parts, dissolved in a sufficient quantity of bisul phide of carbon, glue21 parts, peroxide of lead 21-4 parts, nitrate of potash 24 parts. Another contains phosphorus 3 parts, gum senegal 3 parts, peroxide of lead 2 parts, fine sand and smalts 2 parts. The following composition was recommended by Wiederbold: Chlorate of potash 7.8 parts, hyposulphite of lead 2.6 parts, gum Arabic 1 part. The latter are known as non-poisonous matches, beingfree from phosphorus. 2. Some kinds are, others 3. A high pressure engine has no condenser and carries over 15 lbs. of steam.

J P. L. says: 1. Suppose a hot air engine working the air at a temperature of 500° or 600°, and I inject a very small or proper amount of water in the cylinder with the hot air, at each stroke of the engine or piston, this water to be hot and forced in as a spray. Would it be beneficial as to power, or would it be liable to create any explosive or dangerous gases? 2. Why have not the various hot air engines met with success as moters? 3. At about what degree of temperature do the Roper and other hot air engines use the air? Answers: 1. The effect of injecting the water would probably be to cool down the air, without producing a temperature, to form steam from the injected water. In any case, the injection of water into the cylinder of an any case, the injection of water into the cylinder of an air engine would have a bad effect; because an air furnace is mucn less efficient than that of a steam boiler, and consequently if steam were to be used, it would be better to form it in an ordinary boiler. 2. Air engines have been moderately successful, when working within the limits of temperature which the cylinder and valves can sustain. 3. The temperature of the air used in different forms varies greatly. Joule's engine uses air at 600° Fahr., and Wenham's, described in a late number of the Scientific American, employs air at a temperature of more than 1100°.

S. S. C. asks: What is phosphoric acid lime? Answer: The acid phosphate of lime has, in modern chemistry, the formula $\text{Ca}(H_2PO_4)_2$; in old chemistry CaO,2HO,PO₅. This is generally known as superphosphate of lime. When burned bones are treated with sulphuric acid, a portion of the line is combined with the sulphuric acid to form gypsum, and the soluble superphosphate remains, which is employed as fertilizer and in making phosphorus. $Ca_2(PO_4)_2+2H_2SO_4=2CaSO_4$ +Ca(H2PO4)2.

A. asks: Can you inform me how (1) sulphate of nickel and (2) protochloride of tin are made? Answer: 1. Sulphate of nickel is easily prepared by dissolving the metal or its oxide or carbonate in dilute sulphuric acid. If it be concentrated by evaporation, it will crystallize in beautiful emerald green crystals. 2. Protochloride of tin is formed by dissolving metallic tin in hydrochloric acid. To avoid the formation of any of the biclloride, it is well to employ an excess of metal, and only a moderate heat.

J. B. asks if any quality of glass is or can be manufactured that will withstand heat and cold as well as cast iron, and which, when heated and cooled suddenly by water or otherwise, is no more hable to crack thancastiron? Whatother transparent substances are there that will bear sudden and great changes of temperature, and where are they found? Answer: We do not know for what purpose you wish to use the glass; but if very well annealed, it will probably stand the tests

A. B. C. asks how to make a noon mark to obtain the correct time. Answer: See p.154, vol. XXVII The meridian can be obtained pretty nearly by suspending two plumb lines in an open field or on a house top, several feet apart, and placing them so that the two lines range with the north star. Of course, the sun is sometimes fast and sometimes slow

Stave & Shingle Machinery. T.R. Bailey & Vail. thereby getting about five feet additional length of belt. correct within 3 or 4 lbs. Why is it that we cannot fully too much heat to bring it out. Asswers: 1. See pp. 347 Will that compensate for carrying the coal in and the equalize the pressure? To a certain extent we do; but the horizontal boilers will blow off at 75 lbs. on their gage, and the uprights will also blow off at the same time, ferrous sulphate) is invisible until brushed over with a but the gages on the uprights will indicate 95 lbs. Why is this? Answer: We cannot give a decided opinion, in a case of which we do not know more particulars than writing is done with a weak solution of chloride of coour correspondent has given in his letter. It may be, however, that the horizontal boilers steam much more | This ink possesses the advantage of becoming invisible rapidly than the upright, so that the steam issues with much greater velocity from the first, and backs up the

T. M. E. says: In your answer to J. E. P., who asked what the effect of putting two pumps to work on the same discharge would ue, the conditions of both pumps being the same, you say: It will force more water tarough, increase the pressure, and throw the water farther. Does not the pressure depend on the weight out of the ground, or part come out and part descend of water in the column and the quantity of water distintor be absorbed by the earth? Answer; The frost charged? Will not the pressure be the same on both pumps and consequently will notth; motion bereduced absence of heat; it follows that, whenever heat enters to one half, each pump discharging one half the origiture soil, it counteracts the effects previously due to its nal quantity of water? Answer: Attaching a second absence. The frost cap be said to be annihilated. The pump, of exactly the same size and under the same conjoinion that frost goes down is que to the fact that frost ditions as the first, would be precisely similar to the is found at a distance below the surface where absent effect produced by doubling the size of the first pump; near the surface, and also that the earth sometimes and of course more water would be discharged, under freezes to a greater depth after a thaw sets in. Evapothese circumstances.

Manufacturers who wish to be represented in New York can make arrangements with a reliable House by addressing Sterling & Noble, 27 Park Place, N. Y. The Olmsted Oiler is the best; it is self-righting, strong and cheap. All Hardware and Tin Houses have it magnet, with a core 18 inches long and 1 inch in diame ter, with 200 feet of No.16 insulated copper wire in the helix, and excited with the electricity from a single ce of a Grove's battery, would hold about 1½ lbs. of wrought iron, placed in contict with either pole. One cell of Grove's battery will cost about \$2.50. Mccury nitric and sulphuric acids, sufficient to last two weeks, 50 cents. Davis'"Treatise on Magnetism" is well re commended.

> S. S. asks: What is the strength of wrought iron shafting? We have now in op ration a 31/2 inches wroughtshaftconveying 110 horse power. Is it large enough to give 160 horse power, or will a 4½ inchesshaft be better? Will it be strong enough under all circumstances? The length of the shafting is 130 feet. Answer: You do not tell us the speed at which you desire to run the shafting. Send this and also the diameter of largest pulley on the shaft, and we will answer your onery. Neither the 3% nor the 4% inch shaft would be trong enough under all circumstances

> J. A. S. says: In the practical working of a small steam engine, that will do all our work with 40 lbs. of steam, I find that our wood fire will vary in spite of all we can do, so that we often have 80 lbs. steam blowing off at the safety valve, during a considerable portion of the time. This fact has raised the enquiry in my mind: Why not have a "governor" to do for the fire what the regular steam governor does for the engine, namely, keep it steady? But how? This led to the invention of a plan, or at least to a theory, which is to attach a pipe, to the safety valve pipe, that would discharge into the firebox, so that (when the gage was set, say at 50 lbs., and a fire going that would soon carry it up to 80, if not discharged) the surplus in the form of steam might be turned into the fire box; my theory is that it would check the fire just enough to lower the steam, and so soon as the steam was down to 50 lbs. the valve would close, and let the fire brighten up again; and so on continuously. Is the idea new or old, or a chimera? If you know it to be the latter, will you so inform me? If new and not absurd, what is your view of the invention? Answer: We should be afraid that the surplus steam would occasionally do its work too thoroughly, and put the fire out altogether. Ordinarily the common damper regulator is efficient in cases of this kind. Ani other plan that has been proposed is to place a pipe in the steam space of the boiler, that is supplied with water by the feed pump. This pipe is to have a number of small holes drilled in it, so that when the valve is opened a fine spray of water will be thrown upon the steam, and

> C. E. C says: I have water power sufficient for about 9 months in the year, and have a steam engine to use when the water gives out. The boiler (30 horse) I now have is not of sufficient capacity to drive the engine and do the other work required, but is large enough when I use water power. Shall I throw out the old boiler and put in a larger one (say 70 borse) or put a 40 horse boiler by the side of the old one, and use one when using water and both when using steam? Answer: We cannot give a definite opinion, without knowing the age and condition of the old boiler; but if it would be serviceable for some years, it would be best to retain it. We advise you to consult a reliable engineer, who will inspect your boiler, and can then tell you what is best to

> A. G. asks: 1. Why is it that a vacuum gage shows 26 lbs. or inches when the vacuum is only 13? 2. Why should the grate bars of a steam boiler be lower at the end next the bridge wall than at the front? Has-well says that they should be, but does not say why. Answers: 1. Mercurial gages were formerly used, almost exclusively, to indicate the vacuum. A column of mercury, one inch cross section and about 2 inches high (more accurately, 2.04 inches) weighs one pound. Hence it became customary to speak of "inches of vacu-um," and spring gages are graduated to conform to this nomenclature. 2. Principally for ease and convenience of firing. In a long furnace, with a small door, it would be very difficult to keep the back of the fire in proper condition, if the grate bars were level.

G. E. R. says: 1. I have tried the formula or connecting rods given in your issue of May 24, but cannot obtain the correct result. 2. How do you deermine the length of a rocker arm for a locomotive? . How do you obtain the length of a lever for a rotary valve? Answers: 1. We will assume the following data: Diameter of cylinder=24 inches. Maximum steam pressure=80 pounds. Length of connecting rod between centers=7 feet. Applying the rule: Square of diameter of cylinderxsteam pressurexsquare of length of rodis you mention. We do not give addresses in this column. $576\times80\times49=2,257,920$, which +20,000=112,896. Fourth root of 112,896 = 3.26. 3.26 $+_{8.5}$ of 24 = 3.56 inches = a bout 3.4 inches. This is the proper diameter for the rod at the center, according to the rule. 2 and 3. The lengths of arm will depend upon the relation between required throw or angular movement of valve, and given throw of eccentric. Thus, suppose the eccentric has a throw of 6 inches, and the valve must travel 4, the relative lengths of eccentric and valve levers will be as 6 to 4, or

> and 363, vol. 28, 2. There are several varieties of sympa theticinks. A very weak solution of green vitriol (or solution of yellow prussiate of potash or nut galls. The former produces a blue, and the latter a black. If the balt, it is invisible when cold, and blue when every time it gets cold, and hence may be used for secret diarles as well as correspondence. This is due to the absorption of hydroscopic moisture when cold, which is expelled by heat. Common ink, bleached out by oxalic acid, can usually be restored by ferrocyanide of potassi um, and thus alterations in legal documents are discov