Business and Lersonal

The Charge for Insertion under this head is One Dollar a Line. If the Notices exceed Four Lines, One Dollar and a Half per Line will be charged.

Dry steam dries green lumber in 2 days, and is thonly Cheap House Furnace. H G. Bulkley, Clevelana, O

For Sale—Machine Tools, 2d Hand, good order: Planer, 12 ft. x86 in.x22 in., \$800; Crank Planer, 2 ft. bed, 14 in. stroke, \$345; Wpright Spliner, 5 in. stroke, \$90; New Milling Machine, platen 15x8, \$387; Putnam 24 in. Gear Cutter, \$500; Upright Drill, 52 in. swing, \$325; ditto, 56 in. swing, \$250; Engine Lathes, as follows: 1—new 25½ ft. bed, 38 in. swing, \$150; 16 ft.x31 in. swing, \$600; 15½ ft.x30 in. swing, \$600; 15½ ft.x30 in. swing, \$500; 16 ft.x24 in., \$240; 12 ft.x24 in., \$425; 9 ft.x15 in., \$210; 6 ft.x15 in., \$230; 8 ft.x17 in., \$215; Double-headed 15 ft x 20 in., 11 ft.x12 in., and 16 ft.x20 in., \$150, \$155, and \$250, respectively; 8 ft.x20 in., \$209; 5 ft.x14 in., \$195; 5 ft.x15 in., \$210; 8 ft.x17 in., \$240; 6 ft.x17 in., \$225; 4 ft.x 9 in., \$140. Also speed or drill Lathes, as follows, viz: 5 new 6 ft.x12 in., each \$75; 6 ft.x13 in., \$50; 2 ft.x9 in., \$55; 3 ft.x8 in., \$55, 5 ft.x18 in., \$75; 6 ft.x14 in., \$105; 15 in., \$50, and 12 in., \$42; No.4 Wiley & Russell Power Bolt Cutter, \$170; 7 ft. helve Iron Frame Trip Hammer, \$150; Japanning Oven, \$20. For full printed lists, address Forsaith & Co., Manchester, N. H.

For Sale—Miscellaneous Machinery, 2d Hand Horse Power, with wood sawing rig, \$165; Hydraulic Presses and Pumps, weighing is,000 lbs., \$550; No. 4 Blake Pump, \$220; No. 1 Seldon Pump, \$80; No. 2 Knowles Pump, \$85; 5 ft. Whitney Water Wheel, complete, \$400; 5 ft. Blake Wheel, complete, \$375; 3 ft. Whitney Wheel, \$275; Lot ½ in. iron chain, 4½c. per lb.; No. 7 Sturtevant Blower, 4 ft. diam., with Steam Boiler for drying wool by heated air, almost new, cost \$1,100, price \$450. Iron Pulleys as follows, finished: 12 ft x25 n., 4c. lb.; 9 ft.x20 in., 5c. lb.; 6½ ft.x20 in., 4½c. per lb.; 5 ft.x25 in., 3½c. lb.; 5 ft.x12 in., 5c. lb.; 4 ft.x10½ in., 5c. lb.; 4 ft.x10 in., 4½c. lb.; 42 in.x22½ in., 5c. lb.; 3 Binder Rolls with shafts and boxes, 26x28 in., \$18; 25x21 in., \$19; 22x19 in., \$8. For printed lists, address Forsatth & Co., Manchester, N. H.

The largest newspaper mail which goes to any one firm in this country, is received by Geo. P. Rowell & Co., the New York Advertising Agents. Their place of business is at No. 4! Park Row.—[Exchange.]

25 per cent extra power or saving in fuel, guaranteed to steam engines, by applying the R. S. Condenser. T. Sault, Consulting Eng'r, Gen. Agt., New Haven, Ct. Solid Emery Vulcanite Wheels—The Original Solid Emery Wheel—other kinds imitations and inferior. Caution—Our name is stamped in full on all our best Standard Belting, Packing, and Hose. Buy that only. The best is the cheapest. New York Belting and Packing Company, 37 and 38 Park Row, New York.

Wanted—A First Class Tinner. One accustomed co small work, such as Saddlery Hardware, preferred. Address Factor, Philadelphia P. O.

Parties wanting articles made, wholesa e, on wood-working machinery, call on or address C. E. Phillips, Vandalla, Ill.

Capitalists or Manufacturers Wanted—To take interest in the manufacturing of Toepperwein's new Repeating Guns. Address E.A.F.Toepperwein, Boerne, Kendall Co., Texas.

Gothic Furnace, for coal and wood, heats houses churches. Send for book. A.M.Lesley. 226 W.23d st., N.Y. 'raction Engines, good order, for Sale cheap—International Chemical Works, 10th St., Hunter's Point, N.Y.

Double-Entry Book-Keeping Simplified. The most successful Book on the subject ever published. Cloth, \$1. Boards, 75 cts. Sent post paid. Catalogue free. D. B Waggener & Co., 424 Walnut St. Philadelphia, Pa.

Buit Headers, both power and foot, and Power Hammers, a specialty. S. C. Forsaith & Co., Manchester, N. A.

Main Driving Belts—Pat'd improvement. Address for circular, Alexander Bro's, 412N. 3d, Philadelphia, Pa. Boult's Paneling, Moulding and Dovetailing Machine is a complete success. Send for pamphlet and san ple of work. B. C. Mach'y Co., Battle Creek, Mich.

For best and cheapest Surface Planers and Universal Wood Workers, address Bentel. Margedar & Co. H milton, Ohio.

Patent Scroll and Band Saws, best and cheapes in use. Cordesman, Egan & Co., Cincinnati, Ohio.

Small Engines. N. Twiss, New Haven, Conn. The Original Skinner Portable Engine (Improved), 2 to 8 H.P. L. G. Skinner, Erie, Pa.

Camp Lounge, \$5. C. L. Co., Troy, N.Y., and Norwalk, Ct. N. Y. City Salesroom. 177 Broadway.

Hotohkiss Air Spring Forge Hammet, nest in the market. Prices low. D. Frisble & Co. New Haven. Ct.

Saw Teeth Indicator—Showing improved form for filing teeth on Saws for use in different kinds of wood, &c. Sent free for 50c. E. Roth, New Oxford, Pa. For reduced prices of Surface Planers and Mitre Dovetaller's Machines, send to A. Davis, Lowell, Mass.

Dovetailer's Machines, send to A. Davis, Lowell, Mass. "Pantect," or Universal Worker—Best combination of Lathe, Drill, Circuiar, and Scroll Saw. E. O. Chase, 7 Alling Street, Newark, N. J.

To Manufacturers—Pure Lubricating Oil, Sample Package (24 gals.), \$7. Send to Geo. Allen, Franklin.Pa. Educational Lantern Slides—Send for Catalogue to Prof. W. A. Anthony, Cornell University, Ithaca, N. Y.

Hotchkiss & Ball, Meriden, Conn., Foundrymen and workers of sheet metal. Fine Gray Iron Castings to order. Job work solicited.

For Sale—Second Hand Wood Working Machin ery. D. J. Lattimore, 31st & Chestnut St., Phil:1, Pa.

Price only \$3.50.—The Tom Thumb Electric Telegraph. A compact working Telegraph Apparatus, for sending messages, making magnets, the electric light, giving alarms, and various other purposes. Can be put in operation by any lad. Includes battery, key, and wires. Neatly packed and sent to all parts of the world on receipt of price. F.C. Beach & Co.,246 Canal St., New York Small Tools and Gear Wheels for Models. List

Smail Tools and Gear Wheels for Models. List ree. Goodnow & Wightman, 23 Cornhill, Boston, Mass. Peck's Patent Drop Press. Still the best in use Address ailo Peck, New Haven, Conn.

For Solid Emery Wheels and Machinery, send to the Union Stone Co., Boston, Mass., for circular.

All Fruit-can Tools, Ferracute W'ks, Bridgeton, N.J.

Hydraulic Presses and Jacks, new and second hand. Lathes and Machinery for Polishing and Buffing Metals. E. Lyon, 470 Grand Street, New York.

Spinning Rings of a Superior Quality—Whitins-ville Spinning Ring Co., Whitinsville, Mass.

For best Presses, Dies, and Fruit Can Tools, Bliss Williams, cor. of Plymouth and Jay, Brooklyn, N. Y.

For Solid Wrought-iron Beams, etc., see advertisement. Address Vnion Iron Mills, Pittsburgh, Pa., for lithograph &c.

Brass Gear Wheels, for Models, &c., on hand and made to order, by D. Gilbert & Son, 212 Chester St., Philadelphia, Pa. (List free.) Light manufacturing solicited

american Metaline Co., 61 Warren St., N.Y. City.

Genune Concord exice—Brown, Fisherville, N.H.

Faught's Patent Round Braided Beiting—The Best thing out—Manufactured only by C. W. Arny, 148 North 3d St., Philadelphia, Pa. Send for Circulat.

For 13, 15, 16 and 18 inch Swing Engine Lathes, dress Star Tool Co.. Providence, R. I.

Diamond Tools—J. Dickinson, 64 Nassau St., N.Y. Magic Lanterns and Stereopticons of all sizes and prices. Views illustrating every subject for Parlor Amusement and Public Exhibitions. Pays well on small investments, 72 Page Catalogue free. McAllister 49 Nassau St., New York.

Temples and Oilcans. Draper, Hopedale, Mass.

Water, Gas, and Steam Goods—New Catalogue packed with first order of goods, or mailed on receipt of eight stamps. Balley, Farrell & Co., Pittsburgh, Pa.

The "Scientific America." Office, New York, is fitted with the Miniature; Electric Telegraph. By touching little buttons on the desks of the managers, signals are sent to persons in the various departments of the establishment. Cheap and effective. Spiendid for shops, offices, dwellings. Works for any distance. Price \$6, with good Battery. F. C. Beach & Co., 246 Canal St., New York, Makers. Send for free illustrated Catalogue.

For best Bolt Cutter, at greatly reduced prices ddress H. B. Brown & Co., New Haven Conn.

The Baxter Engine—A 48 Page Pamphlet, containing detail drawings of all parts and full particulars, now ready, and will be mailed gratis. W. D. Russell 18 Park Place. New York.



N. G.'s directions for placing an engine on the center originally appeared in the SCIENTIFIC AMERICAN .- P. T. will find an article on glue on p. 8, vol. 32, which will probably answer his purpose.-T. S. can copper his malleable iron castings by following the instructions on p. 90, vol. 31.—D. J. W. and others are informed that we have so frequently recommended courses of study to young engineers that we cannot repeat them. -F. B. L. can make a waterproof varnish for cloth by following the instructions on p. 74, vol. 31.-G. M can can solder brass to iron by following the directions on p. 251, vol. 28.-F. D. will find directions for drying raisins on p. 409, vol. 31.—S. C. D. will and directions for making fulminate of silver on p. 90, vol. 31.—S. E. S. can produce a dead black on brass work by the process given on p. 362, vol. 25. —W. H. L. can transfer pictures to glass by using the process detailed on p. 123, vol. 30.—C. E. F. will find an answer to the question as to the ball falling through the earth on pp. 158, 250, vol. 31.—C. J. will find directions for obtaining albumen from blood on p.344, vol. 31.-C. R. can use up his coal dust by following the directions given on p. 371, vol. 24.—G. can temper turning and boring tools by following the process described on p. 21, vol. 31. As to horse power of an engine, see p. 33, vol. 33.-S. H. D. will find a recipe for an alloy for making models, etc., on p. 91, vol. 30.-W. S. will find direc tions for making matches on p. 75, vol. 29.-L. E. O. will find that the gyroscope is lucidly described on p. 91, vol. 31.-W. B. T. can preserve leaves and flowers by the process given on p. 266, vol. 31.-F. S. will find a description of a wooden railroad on p. 358, vol. 31.-J. M. McC. can detect cotton in line 1 goods by the method described on p. 102, vol. 28.-T.K. G. will find a recipe for a composition for explosive bullets on p. 300, vol. 33.-L. J. F. will find directions for refining cotton seed oil on p. 19, vol. 30.—C. S. can glue his rubber rollers to the wooden spindles. For a recipe for utilizing old rubber, see p. 33, vol. 27.—D. A. R. can clean ivory by the process described on p. 10, vol. 32.— M. R. W. will find rules for calculating the proper cut-off of an engine on pp. 37, 69, vol. 32.

- (1) C. R. M says: I am going to cover a boiler with staves one inch thick, tongued and grooved; the staves do not fit close to the surface on account of rivet heads. Would charcoal dust mixed with clay be a good thing to put between the boiler and the staves? A. Clayalone will probably answer as well.
- (2) G. C. H. and others desirous of entering government service as engineers should apply to the Secretary of the Treasury; and if there are any vacancies in the engineer corps, they will receive full information.
- (3) T. B. J. asks: 1. What power should be obtained from steam issuing from a quarter inch round pipe at 80 lbs. pressure by a good non-condensing engine? A. We would like some further particulars. 2. Has any rotary engine hitherto constructed given as much power from the same steam as a plain reciprocating engine? A. There is not much information ir print about the performance of rotary engines; but as far as the records go, the advantage is with the reciprocating
- (4) A. H. asks: If the smoke stack on a locomotive be cut off about one foot above the boiler, will that reduce the power? If so, in what proportion may grate area and heating surface be increased to remedy the loss? A. If the blast continues effective, there would be little difference.
- (5) B. L. G. says: 1. I have a vertical stationary 4x8 engine, with a vertical boiler 6 feet high, 30 inches outside diameter, with 40 two inch tubes 4 feet long in it. How much power will I get with 50 lbs. steam? A. Probably between 3 and 4 horse power. 2. The heat as now arranged passes through the tubes and up the chimney. To economize fuel, I propose to put a sheet iron jacket over the boiler, to within 6 or 8 inches of the bottom, with another outside of that, reaching from the bottom and made tight, the pipe to the chimney leading from near the top of this. The season.

heat would then pass up the tubes, down between the shell of the boiler and the inner jacket, and up between the jackets to the chimney. Would this be advisable? If so, how much space would be necessary between boiler and jacket? The draft is good. 2. It might be better to leave off the second jacket. Make space about the same as the cross section of tubes. 3. I would like to use the exhaust for heating; would it be advisable to run it through 150 feet of pipe with 8 elbows? Should I use a back pressure valve? A. It would be advisable to have a back pressure valve in this case. 4. What size of pipe would be best? A. The larger the pipe you use, the better.

(6) H. M. says: 1. Please give me the dimensions of a boat for an engine 3x3 inches. A. Make a boat 20 feet long by 5 feet wide. 2. How large a wheel should I use? A. Use a propeller from 20 to 24 inches in diameter, and $2\frac{1}{2}$ to $2\frac{1}{2}$ feet pitch. 3. The boiler is 23 inches long and 14 inches in diameter, and has nineteen $1\frac{1}{2}$ inch flues, with firebox 13 incheshigh and 14 inches in diameter. It is make of $\frac{1}{2}$ inch plates. Heads are $\frac{5}{16}$ inch thick. How much steam can I carry? A. About 130 lbs. per square inch, if your boiler is well made.

(7) N. Y. says: 1. I wish to supply 90 gallons of water per hour at 160° Fah. through a 1 inch pipe. The temperature of the space about the pipe is 325°, and the incoming water 36°; what must be the length of pipe? A. You will have to determine the matter by experiment. 2. As it would take a different length to raise the temperature to 200°, or a different length still of 2 inch pipe to raise the same to 160° or 200°, by what formula can a solution be obtained? A. Possibly some of our readers may have information on the subject. If so, we would be glad to hear from them, as the subject is one of great interest. We could give you approximate formulas, but they would not be very safe guides.

(8) E. H. K. aaks: I have an upright boiler, 12 inches in diameter by 2 feet high, with nineteen 116 inch tubes, 6 inches water space above tube sheet, and 8 inches space below crown sheet. She lifts her water a great deal, and I think of carrying the water 6 inches above crown sheet. Is there any danger in having water below the tube sheet? Will the dampness of steam keep the tubes not surrounded with water or above the water safe from burming? A. It is very common to run vertical boilers with the water a few inches below the upper tube sheet.

(9) C. and B. say: We are building a boat, 18 feet in length by 4 feet beam and 6 inches draft forward and 8 inches aft, to run on very still water. What size of screw propeller will it require to run it at ten miles an hour? A. The boat will not carry the machinery necessary for that speed.

(10) W. H. asks: How can I make a compound of metal, such as is used for plugs in low water whistles for steam boilers? A. Mix bismuth, lead, and tin, charging the relative proportions of the different metals for different melting points.

(11) M. M. says: I have an upright tubular boiler, 6½ feet high by 3½ inches diameter. The tubes are 4½ feet by 2½ inches. The steam pressure never exceeds 70 lbs. Is it dangerous to use steam at that degree of heat? A. From your account, we do not think that you are carrying a dangerous pressure. 2. An ½ inch pipe, from near top of boiler, leading to a steam box, had a crack about 2 feet from boiler soldered over with common solder, and the steam melted the solder off. A. The solder was probably too soft, or had too low a melting point.

(12) A. B. C asks: In finishing my house, can the plaster be made to resemble porcelain? A. An extra hard surface and superior polish is given to plastering by the use of Keene's cement or the Parian cement, which is furnished by dealers in this city, being imported from Europe. These cements are used, either of them, in place of plaster of Paris, and probably will give the surface you require.

(13) R. S. N.—Much obliged to you for calling our attention to that curious exhibit.

(14) F. B. M. asks: 1. How can I solder silver with a blowpipe? A. Makesilver solder as follows Hard solder: Silver 4 parts, copper 1 part. Soft solder: Silver 2 parts, brass wire 1 part. 2. How can I make a good solution for cleaning silver? A. Cleansilver with hot water, followed by a mixture of equal parts of spirits of ammonia and turpentine; after this, if necessary, use prepared chalk, whiting, maguesia, or rouge. 3. How can I test gold with acid? A. See p. 283, vol. 33.

(15) E. T. M. asks: What solvents are more powerful than muriatic acid? A. This depends upon the nature of the substance. Some substances insoluble in muriatic acid dissolve readily in nitricacid. Andagain bodies, such as gold and platinum, insoluble in nitric or hydrochloric acid alone, are dissolved by a mixture of the two. Mineral substances, containing silicates, are dissolved by hydrofluoric acid, or in a mixture of hydrofluoric and sulphuric acids.


(16) A. H. asks: 1. Has the United S ates government offered any reward for an indelible ink or liquid for obliterating stamps with? A. We do not know. 2. Will a preparation answer whichno chemical can remove? A. The ink must, to be effective, be irremovable by chemicals or any other means.

(17) J. G. asks: What is lucern, and how is it prepared for fodder for cattle? A. Lucern is a forage plant, one of the leguminosæ; it is known in Spain, and in California and elsewhere, as alfalfa. Hay can be made from it, as is done with clover; but eaten green, it is an excellent food for cows. It is in full bearing in the third year, and may afterwards yield from three to five crops per season.

- (18) S. C. asks: How can I dissolve india rubber, to saturate thin linen cloth with, to make it waterproof? A. Make a solution of the gum rubber in bisulphide of carbon, steep the material in this for a short time, and allow to dry in the air.
- (19) W. M. B. asks: 1. Is there such an article as linoleum, made from flax seed? A. Yes it is now largely manufactured in this country. and used as a substitute for oilcloth. 2. Can it be used as a substitute for india rubber? A. We do not know that it has yet been used for this purpose.

(20) Referring to query No. 23 in our paper for October 30, an asbestos cement, recommended for verardah roofs, is manufactured by the inventor and patentee, H. W. Johns, 87 Maiden Lane, N. Y.

(21) W. F. C. says, in reply to S. P. and others who doubted the superior velocity of iceboats to the wind that drives them: It is clear that L. P. is no sailor, or he would know that a boat's best point of sailing is very often not before the wind, that is to say that some boats can sail faster with the wind abeam than with it behind them. Carrying this principle to iceboats, and assuming (not taking friction of ice and wind into account) that before the wind an iceboat can sail as fast as that wind, with the latter abeam it can sail much faster. Example: Suppose a field



of ice to be represented by a table, ABCD. The wedge, G E F, is an ice boat traveling from B to A. The sliding rod, M, represents the force and direction of the wind, and the raised ledge, L L, will answer for the grooves or edges of the runners that keep the boat on her course. We will further suppose all these parts to be lubricated so as to createa minimum of friction. The GF side of the wedge represents the sail of the boat, fixed at an angle of 45° to the line of direction. If the bolt is pressed forward one inch upon the side. G.F. of the wedge, the latter will be moved forward in the direction from B to A just one inch, and at equal speed. Therefore, if this one inch of motion of the boat represents the wind at 30 miles an hour, the corresponding motion of the wedge, E & G, will also be 30 miles per hour. If, however, the sail of the boat or the side of the wedge he not at an angle of 45° to the line of its direction, as at G F, but only at an angle of 2216°, as at H F, one inch of forward motion of the boat, M N, will produce two inches of motion on the wedge, HEF, so that, if the inch of motion of MN represents, as before, the wind at 30 miles an hour, the resultant motion of the wedge will represent progress of the boat at the rate of 60 miles an hour, being, of course, two to one. These figures are necessarily purely theoretical, as friction is not at all taken into account. They will, nevertheless, serve to demonstrate that which is apparently impossible-a boat traveling faster than the wind which drives it.

(22) H. A. says, in reply to L. P. S.'s query as to the running of fans: An old foundery foreman was in charge of a foundery, the proprietors of which had just put up a new fan, with wcoden trough connection with the cupola. The fan was so geared that the blast could not be varied by varying the speed of the fan, as had been the practice. So our foreman proceeded to make a long slot in the side of the air trough, and over the slot he carefully fitted a sliding cover. "Now," said he, "go ahead with your blast. I'm ready for you!" Finding very soon that the blast was too strong, he slightly opened the slide in the trough to let the blast escape outwardly. But, to use his own language, "the more he opened the more she blew," and his expedient was a total failure. The next day he put in a gate as the only means of reducing the blast.

MINERALS, ETC.—Specimens have been received from the following correspondents, and examined, with the results stated:

E. W. P.—It is decomposed mica, and consists of silex, alumina, magnesia, lime, potash, and soda.

—W. K.—We found no gold in your specimen.—D.

T. M.—We cannot say how they were made. They do not contain injurious substances.—H. M.—It is anartificial stone, and has been made apparently by cementing clay, of which it is mostly composed, together with graphite, by means of some lime cement.—H. N. P.—It is composed of zinc and tin.—R. J. B.—Your specimen did not come to hand.—W. J.—It is hydrated oxide of iron, but the percentage of iron istoo small to permit of its being worked profitably.

D A. R. says: I have a bar of iron 10½ x½x4 inches, supported at one end. I wish to know how to calculate the weight which, applied to the end, will break it?—J. D. asks: How can I best weigh flax before it is fed through the cards for manufacturing into bagging?—W. L. T. asks: How can I make papes with a black surface, to be drawn on so that the lines will show the white ground through the surfacing composition?—J. A. R. asks: How do you calculate the number of gallons of oil in an oil car tank of cylindrical form with hemispherical ends, at different depths?—M. asks: How can I prepare autumn leaves for preservation?