

SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY AND MANUFACTURES.

Vol. XLII.—No. 20.
[NEW SERIES.]

NEW YORK, MAY 15, 1880.

[\$3.20 per Annum.
POSTAGE PREPAID.]

AMERICAN INDUSTRIES.—No. 42. A SHIRT AND COLLAR FACTORY.

That a business of this kind could ever grow into a really important and considerable branch of American factory industry would never have been thought possible by our grandfathers. In fact, most men of middle age can remember when they shook their heads at the idea of buying ready-made shirts and collars, for the making of these necessary garments seemed an indispensable part of the duty of all exemplary wives and daughters, and any young woman who had not proved her capabilities in this direction was supposed to have had a faulty "bringing up." The advent of ready-made clothing and ready-made boots and shoes, however, was soon followed by that of ready-made shirts, collars, and cuffs, the manufacture of which, in a wholesale way, has been for some years a business of considerable consequence.


In the illustrations which are presented below are seen the principal departments in a representative factory of this description—that of Geo. P. Ide, Bruce & Co., Troy, N. Y. In a business of this kind, where all the details of the work are such as almost every one is more or less conversant with,

it necessarily follows that success is possible only by giving the closest attention to every item, so that, in the division of labor, in the cutting of stock, in the oversight of the great number of hands employed, both in and out of the factory—in a number of things that seem little in themselves—there be no room for waste, and the whole work shall move like one great machine, and always with the greatest possible economy. It is only in such a way that sufficient margin of profit can be figured out to support a business of this nature, where each individual customer could with little difficulty supply himself with the articles made, and would do so if the factory system did not produce them a little cheaper as well as better than the average of home-made goods. How this firm have succeeded in this line is best evidenced by the steady growth of their business and the great dimensions it has attained, their product for one year having exceeded that of one of the largest and oldest iron foundries in Troy. Their regular manufacture, during the busy season, amounts to 200 dozen shirts and 2,000 dozen collars per day, and so complete are the facilities of the establishment, so ample are their arrangements for obtaining the large number of hands wanted, that even this great pro-

duction could be exceeded if the wants of the trade should seem to call for such enlargement.

In the cutting department, as shown in the view on the right hand at the bottom of the page, there is room for spreading 6,000 yards of cloth at a time on the long tables. This work is all done by men, who use a knife particularly adapted for the purpose, known as the shirt-cutters' knife. Wood patterns are used, and 48 thicknesses of cloth are cut through at one time. Dies cannot be economically used for this purpose, as the springing of the cloth would cause more waste. Irish linen is principally used for the collars and cuffs, and the rags from this sell at the same price as those from the white muslin for the shirts, about twenty-five tons a year being made, which are sold to the paper manufacturers for making the finest ledger paper. Both white and colored shirts, of many different styles, are made; but in the latter class it is intended to keep the production close down to the actual immediate wants of the trade, as white goods only are staple, and sure to be in demand all the time. As many as eighteen different patterns are sometimes required for one size of shirts. The collar cutting includes

[Continued on page 309.]



MANUFACTURE OF SHIRTS AND COLLARS.—GEO. P. IDE, BRUCE & CO., TROY, N. Y.

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT NO. 37 PARK ROW, NEW YORK.

O. D. MUNN.

A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year postage included. \$3 20
One copy, six months, postage included 1 60

Clubs.—One extra copy of THE SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.20 each; additional copies at same proportionate rate. Postage prepaid.

Remit by postal order. Address

MUNN & CO., 37 Park Row, New York.

To Advertisers.—The regular circulation of the SCIENTIFIC AMERICAN is now Fifty Thousand Copies weekly. For 1880 the publishers anticipate a still larger circulation.

The Scientific American Supplement

Is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, postage paid, to subscribers. Single copies, 10 cents. Sold by all news dealers throughout the country.

Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, postage free, on receipt of seven dollars. Both papers to one address or different addresses, as desired. The safest way to remit is by draft, postal order, or registered letter. Address MUNN & CO., 37 Park Row, N. Y.

Scientific American Export Edition.

The SCIENTIFIC AMERICAN Export Edition is a large and splendid periodical, issued once a month. Each number contains about one hundred large quarto pages, profusely illustrated, embracing: (1.) Most of the plates and pages of the four preceding weekly issues of the SCIENTIFIC AMERICAN, with its splendid engravings and valuable information; (2.) Commercial, trade, and manufacturing announcements of leading houses. Terms for Export Edition, \$5.00 a year, sent prepaid to any part of the world. Single copies, 50 cents. Sanitary waters and others who desire to secure foreign trade may have large and handsomely displayed announcements published in this edition at a very moderate cost. The SCIENTIFIC AMERICAN Export Edition has a large guaranteed circulation in all commercial places throughout the world. Address MUNN & CO., 37 Park Row, New York.

NEW YORK, SATURDAY, MAY 15, 1880.

Contents.

(Illustrated articles are marked with an asterisk.)

Table listing various articles such as Agricultural inventions, American industries, Ammonia manufacture, Assaying gold and silver, etc., with corresponding page numbers.

TABLE OF CONTENTS OF

THE SCIENTIFIC AMERICAN SUPPLEMENT

No. 228.

For the Week ending May 15, 1880.

Price 10 cents. For sale by all newsdealers.

Table listing sections I through VI, including Engineering and Mechanics, Technology and Chemistry, Electricity, Heat, Light, etc., with sub-sections and page numbers.

THE USE OF STEEL FOR STRUCTURAL PURPOSES.

At the last meeting, in Pittsburg, of the Engineers' Society of Western Pennsylvania, the subject which most interested the iron and steel men of Pittsburg was the topic ably handled by Mr. A. F. Hill, C.E., of New York, in his paper entitled "Steel in Construction." The points presented embodied a series of interesting tests conducted by the gentleman named, with open hearth Pittsburg steel from the establishment now supplying the steel for the wire used in the East River Bridge cables.

"Within the past few years there has been developed in this country a tendency toward steel construction, which today is so pronounced as to command the most thoughtful consideration alike of constructors and manufacturers. The adaptability of steel to purposes of construction is probably no longer questioned, yet there is still a certain distrust of the material in minds of many thoughtful men, who believe steel to be endowed, more than any other material, with that exasperating quality which might fitly be called the 'innate cussedness' of inanimate objects. This arises undoubtedly from some of the remarkable and seemingly inexplicable failures which have occurred in finished parts of steel, some of them breaking under loads utterly inadequate to produce rupture, others breaking in some instances without any apparent cause at all. I use the expression 'seemingly inexplicable' advisedly, for I believe that every such extraordinary failure is susceptible of rational explanation, and can almost invariably be traced, not to the inherent defect in the material itself, but to the wrong treatment of the steel during the process of manufacture into parts of the structure. I propose to lay before you the results of some steel tests made under such conditions as would naturally arise when the material is to be used in a structure."

The samples tested ranged from 0.30 per cent to 0.50 per cent carbon, and were in the form of eye bars, plates, and girders. In the first named, the eye bars were from the Kloman machine, which rolls the bar complete from end to end; the Keystone "upset" bar, and bars made by welding and die forging. The tests showed that the first two classes gave best results, and the last named second best, and the process of welding and die forging "could not be recommended for general practice." The tensile strength of these bars ranged from 93,000 lb. per square inch in the 0.30 per cent and 102,000 lb. in the 0.50 per cent steel.

The tests made on plate steel were crucial. A 3/4 steel plate was tested in the direction of rolling, and across the same; also as to the relative strength of sheared and punched plates, and the effects of annealing and tempering. To ascertain just what such a plate, would stand, Mr. Hill punched out the edges of such a plate and then reduced its gauge by cold hammering to 1/8 of an inch. The sample was then heated to a bright cherry, and annealed forty-eight hours in lime. A test showed an elastic limit of 55,000 lb., and an ultimate strength of 100,400 lb. In tempering sheared and punched plates from a low heat in oil, the effect was contrary to what might be expected; instead of rendering the material hard and brittle, it restored its ductility and increased its ultimate strength. The last test was with a steel girder of 3/8 web plate, 12 inches high, with 1/2 top and bottom plate, and 1/2 x 2 1/2 x 2 1/2 steel angle. For such a girder (6 feet long) in iron the test load would have been not quite 22 tons distributed load. The steel girder was tested up to 65 tons distributed safe load; and under a continued application of 103 tons distributed load, acquired only a permanent set of half an inch.

Mr. Hill concluded his paper as follows: "The foregoing tests are a fair indication of the wide range of application steel is capable of in construction, and they also show very conclusively that our present methods of dimensioning will have to undergo modification; that our present safety factors, based as they are entirely upon an assumed ultimate strength, become almost meaningless when we have to proportion in steel; and last but not least, that our mechanics must learn to test steel as steel, and not as iron. Steel construction is undoubtedly the construction of the near future. The conservative element in our profession which to-day opposes it will still oppose it twenty years hence, just as it took them twenty years to learn that iron was better than wood. This conservative element is not without its use by any means; nor are the sand bags to the aerial navigator; they help to steady the flight of his air ship at the lower levels. To make the comparison complete, let me add, that to reach a higher altitude, they must both be thrown overboard."

TWO TONS OF SILVER PER WEEK.

There are five establishments in the United States where the smelting and refining of silver-bearing lead ores is carried on. One of the most extensive, if not the most extensive, of these works is that of the Pennsylvania Lead Company, of Pittsburg, Pa. Here the "base bullion" of Leadville and of Utah is brought to meet the cheap coke and coal of Pennsylvania, and though the freight per car averages \$300, the business has grown to great proportions. President Schwartz, of the above company, gives figures showing that 60 per cent of the "base bullion" output of Leadville is shipped to the Pittsburg refining works, besides 75 per cent of the output of Utah lead mines. "Base bul-

lion" is the product of the ore smelters of the mining regions, and bears about the same relation to refined silver as pig metal to refined steel. At the Pittsburg refining establishment this base bullion is converted into lead, silver, and gold. The precious metals find their way to New York, while the lead is consumed by the makers of white lead. The Utah ores are the richest in gold, sometimes reaching 40 ounces per ton. Of silver, the Pennsylvania Lead Company ships 50,000 ounces per week, or two tons, representing in value, at \$1.14 per ounce, \$57,000. This metal leaves the works in pretty bars of 2,000 ounces each.

THE TELEGRAPH SET SCREW.

The decision of Judge Blatchford sustaining the Page Electrical Patent was noted in our issue of March 6.

April 4 Judge Blatchford heard motions by the American Union Telegraph Company, the Wabash, St. Louis and Pacific Railway Company, and the Union Pacific Railway Company, praying to have the decision referred to so modified as to exempt them from the payment of royalty to the Western Union Telegraph Company, on the grounds that they have always used the machine and devices invented and patented by Prof. Morse, and that it could be proved that the original Morse instrument on exhibition in the office of the Western Union Telegraph Company was made by Prof. Morse as early as 1835, and contained all the essential parts of the apparatus and devices set forth in the eleventh, twelfth, and thirteenth claims of the Page patent.

The petitioners allege further that the defense in the previous suit could have proved (though they did not) that the testimony of Page in the suit of French against Rogers related to these essential parts of the Morse apparatus and devices; they could have proved by Thomas Hall of Boston that in 1847 he manufactured a machine under the Morse patent, which contained a device and combination adjusting or regulating the length of the vibration at the armature of an electro-magnet by means of a set screw as described in the 13th claim of the Page patent; they could have produced an affidavit of Mr. Page himself, taken in 1848, in the suit of Morse against O'Reilly; also, the defendants could have proved by the Rev. S. Irenæus Prime that Mr. Page wrote to the Hon. Amos Kendall in 1848 that he had never claimed the invention of the receiving magnet used in the Morse telegraph; and the defendants could have made use of the depositions of Professor Morse, taken in 1850, in the suit of French against Rogers, and of Leonard D. Gale in the suit of Morse against O'Reilly.

The petitioners further asserted that they were ready to produce before the court one of the machines now and for many years past used by them in telegraphing, and the machines used by Mr. Hall, and if aided by the process of the court they will cause to be produced by the Western Union Company the machine used by Prof. Morse and presented to the company after his death; upon a comparison of which it would be seen that the machines now used by the petitioners and that made by Mr. Hall and that used by Prof. Morse are alike in their essential parts, and that all of them have the designs and appliances mentioned in the eleventh, twelfth, and thirteenth claims of the Page reissued patent.

Two weeks were allowed by Judge Blatchford for the plaintiffs to make answer. When the case was called the counsel for the Western Union Telegraph Company denied that due diligence had not been used in obtaining evidence in the previous trial, and produced the original model of the Morse telegraph instrument, to show that the disputed set screw governing the play of the armature was not there and never had been. It was held by the opposite side that the original screw had been removed and another substituted, whereat an excited colloquy ensued between the opposing counsel; but no evidence would appear to have been brought to show the real function of the screw which the model now carries.

The arguments of the counsel being unfinished for lack of time, the case was carried over to Monday April 26, and again to April 30.

STEAM INJECTORS.

Among the most reliable and effective devices in this class the Rue's Little Giant Injector occupies a prominent place. It is made by the Rue Manufacturing Company, Philadelphia, Pa. The lawsuit for infringement, recently mentioned in our paper, has, we learn, been fully settled, and the company is now increasing its facilities and extending its sales. The Rue Company's advertisement will be found in another column.

THE REGISTRATION OF TRADE MARKS.

A bill to provide for the registration and protection of trade marks was passed by the House of Representatives, April 27. It included the first thirteen sections of Bill No. 5088, submitted by the Committee of the Judiciary as a substitute for H. R. 2573, and H. Res. 125.

The committee sought to re-enact substantially the trade mark legislation of 1870 (Rev. Stat., sections 4937-4947 inclusive) with the act of 1876, save that the operations of the proposed law were confined to trade marks used in commerce with the Indian tribes and foreign nations.

Before its passage the House struck out all the penal and search-warrant clauses (sections 14 to 21 inclusive); so that the proposed law re-enacts only so much of the old trade mark laws as are embraced in sections 4937-4942 of the Revised Statutes.

The bill as passed also provides that applicants for regis-

tration under it shall be credited for any fee, or part of a fee, heretofore paid by them into the Treasury of the United States with the intent to procure protection for the same trade mark, and that citizens wishing to register trade marks in foreign countries, where prior registration here is a condition precedent to registration there, may register here for such purpose.

RECENT TELEPHONE EXPERIMENTS.

At the suggestion of one of the proprietors of this journal—Mr. A. E. Beach—a series of interesting experiments relating to the electrical transmission of sound has lately been commenced in this vicinity, which seems likely to lead to a variety of useful results. In the introductory experiment the SCIENTIFIC AMERICAN office and Mr. Beach's dwelling, in the upper part of this city, were connected by wire with the auditorium of Plymouth Church—Rev. Henry Ward Beecher's—in Brooklyn, N. Y., and these points were also telegraphically joined by the wires of the Bell Telephone Company and those of the Gold and Stock Company, the electrical circuit being thus enlarged and ramified in all directions, communicating with offices and dwellings in New York, Brooklyn, Jersey City, Newark, Orange, Elizabeth, Yonkers, and other adjacent places. One object of the experiment was to determine approximately through how many united circuits and lines the voice of a public speaker might be simultaneously transmitted.

At Plymouth Church, in Brooklyn, the wire passed under the floor to the platform or pulpit, where it connected with two of the well known Blake transmitters, arranged upon a shelf under the speaker's desk. The general arrangements for the experiments were under the charge of Mr. Frederick C. Beach, Ph. B., of the SCIENTIFIC AMERICAN office.

When it became known at the Bell telephone office in Brooklyn that experiments were to be tried, the interesting news soon spread to all of the other telephone offices, and the various operators not only called into their offices parties of their friends to enjoy the treat, but gave notice to numbers of private persons having communicating wires, who in turn invited friends to their dwellings. Thus at many points on the great ramification of connecting wires were groups of persons waiting, with telephones at their ears, to hear the words of the distinguished speaker. At one of the stations fifteen telephones were in this way connected, the instruments being joined by wires, just as a circle of people join hands in sharing an electrical shock.

The first experiment was made on Sunday, April 18, and was on the whole perhaps more successful than could have been expected. The telephone listeners stationed in Brooklyn, and nearest the church, were enabled to hear the service with much satisfaction; but those in New York, Yonkers, and Orange, N. J., only heard the music and portions of Mr. Beecher's sermon. It was concluded on the whole that there were too many telephones in circuit; and it was subsequently ascertained that the wire leading to the church had been surreptitiously tapped where it passed over a dwelling, a ground made on the tin roof, and a considerable number of telephones smuggled in.

On the following Sunday, April 25, another trial was had, precautions having been taken not to allow so many tapping lines or instruments in circuit. Special care was also taken by Mr. Adeo, the adjuster of the Bell Telephone Company, to give the most delicate adjustment to the transmitting instruments at the church. The result was most successful and marvelous.

From the opening note of the organ prelude to the last word of the preacher's voice, at the close of the service, everything was delivered to the ears of the listening telephoners in the most perfect manner, the tones that came over the wires being so full, round, clear, and distinct, it almost seemed to the hearers in New York, Yonkers, and Elizabeth as if they were stationed within the church itself directly in front of the speaker.

The delivery of the music was equally perfect, every note of the organ and of the individuals of the choir being fully brought out. The majority of the participators in this experiment were persons accustomed to the use of the telephone, and their unanimous verdict was that the results obtained far surpassed anything of the kind within their previous experience.

In consequence of the successful progress of these experiments, several new improvements have been suggested for trial, and there seems to be every probability that in a short time some new and very effective instruments will be in use, by which all who desire may carry the sounds of church services into their dwellings, and may also enjoy the best lectures, musical and other entertainments with the utmost satisfaction in their homes. Heretofore, in listening to the telephone, it has required effort and strain of the ear on the part of the listener. But this experiment shows that all sounds may be delivered in full and easy tones, readily heard, with all the natural characteristics, modulations, and inflexions of the human voice.

We shall keep our readers informed of the further results accruing from this series of experiments. With the continued co-operation of the various electricians and managers of the lines it is believed that something of value to science may be adduced.

The progress and success of the experiments up to the present time have been greatly promoted by the active interest taken and assistance rendered by the gentlemen connected with the several telephone companies, to all of whom we return our sincere thanks. We are under especial obli-

gations to Mr. C. F. Wiley, Superintendent of the Gold and Stock Company; to Mr. H. R. Butler, Secretary of the company; to Mr. T. G. Ellsworth, Electrical Manager of the company, through whom the experimental circuits were in the first instance arranged; to Mr. Henry W. Pope, Superintendent of the Bell Telephone Company; to Mr. E. T. Greenfield, Assistant Superintendent; to Mr. C. N. Chinnock, Electrician of the company; to Mr. D. M. Adeo, Adjuster of the company; to Mr. Robert Brown, Superintendent of Construction; Mr. Grinstead, of the Orange office; Mr. William Hanford, manager of the Brooklyn office; Mr. Charles Walton, manager of the Nassau-street office, N. Y.; Mr. R. W. Macgowan; also to Col. Wm. H. Paine, C. E., and to C. C. Martin, C. E., Assistant Engineer of the great Suspension Bridge between New York and Brooklyn, for permission to lay a temporary experimental wire across the foot bridge.

THE COFFEE PRODUCT.

From an exhaustive review of the coffee trade of all countries by the managers of the Java Bank (Batavia), it appears the total crop of the world for 1855 was 330,165,000 kilos; for 1865, 421,950,000 kilos, and that the average of the three years 1876-7-8 was 490,840,000 kilos. The figures represent an increased consumption of 27 per cent over fifteen years ago, and of 47½ per cent over 1855. In the Dutch Indies the increase since 1855 has been below the average rate in other countries. In the British Indies and Ceylon the crop has nearly doubled. The total for Asiatic countries is in about the average ratio for the whole world. Brazil falls somewhat below the average ratio of progress; and the same is true of the West Indies; while the most notable increase is in the case of Central America, where the crop has risen from 3,500,000 kilos in 1855 to 32,500,000 in 1876-8. In the South American countries other than Brazil the production has risen from 22,300,000 kilos to 35,900,000, which also is above the average ratio.

It may not be generally known that Guatemala produces some of the best coffee that is grown in any country; but such is the fact. From the plantation of Mr. José Guardiola, of Chocoma, there has been sent to New York, the past year, a grade of coffee surpassing in quality either Java or the celebrated Mocha. The kernel of the Guatemala coffee is small and plump, resembling the best quality of wheat and but little larger.

Mr. Guardiola has introduced drying machines of his own invention, which enables him to cure his coffee in wet as well as sunny weather, and he has also patented in this and other countries a hulling and polishing machine, which he uses with great success on his extensive plantation. To the introduction of these machines is no doubt attributable the preservation of the delicious flavor and aroma of Guatemala coffee. Coffee growers in other countries will do well to introduce Mr. Guardiola's machines on their plantations.

IMPROVED TELEPHONE CENTRAL OFFICE SWITCH BOARD.

On page 15 of the current volume of this journal we illustrated and described one of the largest telephone central offices in this city, and alluded briefly to an improved switch board invented by Mr. T. G. Ellsworth, manager of the office. This switch board has been in use for a number of months, saving a great deal of labor and greatly facilitating the business of the office. A patent has just been issued to Mr. Ellsworth for this improvement. The invention consists in a board provided with a number of longitudinal bars used to connect the wires of the different subscribers. When these bars are in use they are turned to indicate that they are occupied, so that the switchman may know at a glance which rods are unoccupied.

This switch board has proved its utility by long use, and is especially adapted to small exchanges, and may be easily and cheaply applied.

Wind Pressure.

At a recent meeting of the Scottish Meteorological Society, Mr. St. John Vincent Day, C. E., spoke upon the great importance to engineers and bridge builders of having accurate records of the velocity of the wind. Having seen remarks in the newspapers that the Forth Bridge had been passed by the railway authorities and the Board of Trade, he had made inquiries respecting the calculations on which it had been based, and he had found, on the authority of the Astronomer Royal, that only 10 lb. per square foot had been allowed for wind pressure. Engineers had considered the matter, and he believed they had reported that with regard to wind pressures they had found nothing upon which they could place any dependence, except the old tables of Smeaton, which put down the pressure of the wind at from 7 lb. to 12 lb. and 13 lb. to the square foot. Numerous wind pressures, Mr. Day showed, had been recorded since then by Professor Rankine, Professor Piazzi Smith, and Dr. Robinson, Armagh, the last mentioned of whom had stated that the gusts of one particular storm, which was half a mile in breadth, blew at the rate of 125 miles an hour for six minutes continuously. What would become of the Forth Bridge in such a gale as that? But of course the bridge as at present devised was not going on. He had that from the Board of Trade. The report of the engineers had been set aside, and the strains as yet were still unsettled. As to the pressure on the Tay Bridge on the night when it fell, the wind would, of course, blow with much greater force down the conical valley of the Tay than it would in the open; and, according to Dr. Robinson, nearly one-third would have to

be added to its velocity near the bridge, owing to the contraction there of the Firth. Dr. Robinson had also said he had no doubt that the vertical effect of the wind resisted by the water below and by the pressure of the head above would tend to lift up the whole bridge off the piers. On February 20, 1877, a storm was recorded at Holyhead, the gusts of which blew at the rate of 200 miles per hour; and on November 16, of the same year, there was a storm which blew at 180 miles an hour.—*The Architect.*

The First American Iron Works.

In 1652 James and Henry Leonard established the first bloomery in America, at Taunton, Massachusetts. A correspondent of the *Evening Post* says that the Leonard establishment was about two and a half miles from Taunton Center, now Raynham. Henry Leonard, a brother of James, leaving the latter and his son to carry on the business in Taunton, went to New Jersey, and established a bloomery there. He removed to that State because the ore was much more profitable in its yield, and purer.

When the British Parliament prohibited the manufacture of iron in the colony, in 1750, there were three bloomeries at Taunton, carried on by the Leonards, Deans, Kings, and Halls, all akin by intermarriages. They dug their ore in the neighborhood, all along the streams which empty into Taunton River, mostly, however, along "Canoe River," now "Mill River," and also in the bogs of "Two Mile River." It is proper to add that the Parliamentary prohibition did not stop the work.

The first furnace for making pig iron, according to a recent letter to the *Philadelphia Press* from Principio Furnace, Maryland, was set up at that place in 1715, and its account books are preserved dating as far back as 1725. In 1727 the record shows the price of iron to have been £10 a ton. The writer says that it is probable that the first pig-iron ever exported from America to England—a small lot of three and one-half tons in the year 1718—was made at Principio. Prior to the Revolution Maryland and Virginia made and exported more iron than any other of the colonies. In the custom house returns in England the two colonies are always coupled together, because the Maryland iron was first sent to Virginia in small boats to be reshipped to England, and it is therefore impossible to allot to each colony its proper share of iron exported under the fostering care of the proprietary government. The production of iron increased in Maryland until 1751; it, with Virginia, exported to England 2,950 tons of pig-iron against 199 tons from Pennsylvania, 33 tons from New York, 9 tons from New England, and 17 tons from Carolina.

In 1761 the eight furnaces and ten forges in Maryland made 2,500 tons of pigs and 600 tons of bar iron, while the annual production of England herself at that period was only 17,000 tons of pig-iron. Some of the ore banks worked by the Principio Company were on the Patapsco River, below the site of the future Baltimore, and were first discovered by that wonderful man, Captain John Smith, in 1606. Augustine and Lawrence, the father and brother of George Washington, were among those who had an interest in the Principio Company, which was retained by the Washington family until after the close of the Revolution.

The Use of Atropine in Cataract.

At a recent meeting of the Société de Biologie in Paris (*L'Union Médicale*, January 17, 1880), M. Javal said that atropine might be useful at the outset of cataract before the necessity for operation was indicated. If it were employed, note must be taken of two conditions. If the opacities be central and well limited, the dilatation of the pupil allowing the entrance of a large amount of light into the eye will produce a marked improvement of vision. As regards the state of the refractive power of the media, atropine, besides dilating the pupil, brings on paralysis of accommodation. The patient will not benefit by the first of these effects, unless the inconveniences of the latter be compensated by the help of correcting glasses, which should be most carefully chosen. By combining the use of these two expedients—atropine and spectacles—a large proportion of the visual difficulties depending on cataract may be diminished.

Artesian Well in Boston.

At present an artesian well is being bored in Boston under the direction of Mr. J. A. Whipple, in order to determine whether or not there is under the city an adequate, available supply of pure water. The experience of the men engaged has been as follows: They first bored through six feet of hard filling; then met with a stratum of some soft black substance in a semi-fluid state, about forty to forty-five feet in thickness. Below this they found from ninety-three to ninety-seven feet of stiff blue clay, overlying a stratum of coarse gravel, in which they found a small stream of excellent pure water. After this they again encountered a twenty foot vein of the stiff blue clay mentioned before, having passed through which they struck a solid bed of hard slate rock or shale, which necessitated the use of the rock drill, which they are using up to the present time. At the depth of three hundred feet they struck a second small stream of good water in the slate rock. They have now reached a depth of about three hundred and seventy-five feet. The tubing they put down measures eight and one-half inches, outside diameter, and is one-fourth of an inch thick. The weight now operating on the rock is about 3,000 pounds. The drill itself weighing about 1,600 pounds.

IMPROVED GANG PLOW.


The annexed engraving represents a novel gang plow recently patented by Mr. Francis Stanley, of Toronto, Canada, and possessing many improved features, which render it very effective. This plow may be readily adjusted so as to cut furrows

inserted in place of the wheel, E, will act as an efficient cultivator.

The advantages possessed by the plow will be apparent to those familiar with the performance of this class of agricultural implements.

Further information may be obtained by addressing the

by ball and socket rockers, B, in the center, and by movable side bearings, C, on opposite sides of the rockers. The movable side bearings, C, are movable lengthwise of the car, and are connected in pairs with the rock shafts, D, so that the simultaneous movement of the two members of the pair on one side of the rockers is effected by the rocking of the shaft.



STANLEY'S GANG PLOW.

of different depths, and the plowshares may be raised clear of the ground without detaching any part of the implement.

Two or more plowshares, A, are pivoted to the main frame, as at B, and are provided with arms, C, projecting forward and carrying colters, D. The arms, C, are connected by rods with the lever, F, fulcrumed on the top of the plow frame, and extending to the driver's seat. By means of this lever the plowshares may be easily raised or lowered by the driver without moving from his seat. The forward end of the plow frame is supported by two wheels turning on an axle secured to the frame. The middle of the frame is supported by an adjusting wheel, E, that has a threaded spindle, G, provided with an adjusting nut, by which the distance of the wheel from the main frame may be varied and the shares be consequently raised or lowered. If it is desired to use the plow as a light cultivator, the wheel, E, is removed, and a wheel of peculiar construction is inserted in its place.

The nut on the spindle, G, is then turned so as to raise the plowshares clear of the ground, when the barbed wheel

inventor, Mr. Francis Stanley, care of J. Thompson, 364 Yonge St., Toronto, Canada.

NEW DUMP CAR.


We present herewith engravings of an improved dumping car patented by Mr. Matthew Van Wormer, of Dayton, O., and now being introduced by the New England Car Company, of 48 Congress street, Boston, Mass. This car possesses many points of novelty which are covered by separate patents. It has been improved from time to time until, as it now stands, it appears to fulfill all the requirements. In its construction it is as simple as well can be when all of its functions are considered. It is a full sized gondola car, and capable of running with the same steadiness and security as the ordinary cars of the same size, while at the same time it is as perfectly manageable as a common dumping wagon.

Fig. 1 shows the entire car in perspective while being dumped; Fig. 2 is a vertical transverse section, taken just in front of one of the trucks; and Fig. 3 is an inverted plan view, showing the apparatus for moving the side bearings.

The car body, A, when in its normal position, is supported

This operation removes the side bearings of one side of the car and puts it in condition to be dumped. Upon the outer end of the rock shaft there is a lever, E, which is connected with the lever, F, at the side of the car near its end. The lever, E, is connected with a bar, G, extending along the side of the car, and pivoted to four or more lever catches, H, which hold the side doors of the car in position to retain the load. By this arrangement of the levers and their connections the car doors may be released and the supports, B, moved, making the car ready to dump. The apparatus for dumping the car is very simple and effective, and capable of holding the car platform at any desired angle. It consists of a long shaft, I, extending along the body of the car, and provided at one end with a worm wheel, which is engaged by a worm on a vertical shaft, extending upward through the platform of the car, and provided with a lever or wheel by which it may be turned.

Upon drums carried by the shaft, I, are two drums, upon each of which are wound two chains, J K. The chain, J, runs downward around a sheave on the truck timber, thence upward over a sheave on the car body, then downward to



THE NEW ENGLAND CAR COMPANY'S DUMP CAR.

the end of the truck timber, where it is secured. The chain, K, runs directly down to the truck timber. By turning the shaft, I, in one direction the car is dumped on one side of the track, and by turning it in the other direction the load is discharged on the opposite side of the track. This result is secured by winding one of the chains, I J, while the other is unwound. The worm gear affords ample leverage for operating the shaft, I, so that the car may be dumped by one man standing on the platform.

The merits of this dumping car will be understood and appreciated by railroad engineers, superintendents, and managers, who are familiar with the imperfections of the ordinary cars.

Any further information in regard to this invention may be obtained by addressing the New England Car Company, 48 Congress street, Boston, Mass. Mr. Simeon Brownell is general manager and sole agent for the United States.

THE GOWER SYSTEM OF TELEPHONIC COMMUNICATION, PARIS.

At present there are two telephone companies in Paris, one using the Gower telephone, the other the Edison. A third company introduced the Blake transmitter, but was soon consolidated with the Gower Company, who were the first to introduce telephonic communication in Paris. The Gower telephone, of which an exterior view and sections are shown in Figs. 1, 2, and 3 of the annexed engravings, requires no battery, as the currents for transmission of sounds are generated by the instrument, and it is provided with a peculiarly arranged magnet, by means of which a sound resembling that of a trumpet can be produced for signaling. Each subscriber is provided with a telephone connected with the main central office by means of an insulated wire, which is laid underground. A great difficulty is experienced in insulating the wires sufficiently to avoid the effects of induction. When several wires pass in one direction they are united in a cable, and the covering of the wires is of different colors, so that a wire may be traced very readily in case of accidents. At the central office the cable is separated, and each wire is conducted to its special office connection. To better explain the operation of this telephone system we will describe it in action. Each subscriber is known by a certain number. Assuming that No. 5 desires to communi-




Fig. 1, 2, 3.—THE GOWER TELEPHONE.

cate with another subscriber, he gives the signal by blowing into the tube of his telephone.

The Gower Company, desiring to maintain the simplicity of the instrument, have adopted a signaling device invented by Mr. Ader, which answers in every respect. It is illustrated in Figs. 4 and 5. A is the magnet of a telephone, and the subscriber's wire communicates with the bobbins, B B. R is the vibratory tongue, fixed at its lower end. The signal consists of a white disk with the word "Answer" printed on it, and it may also bear the number of the corresponding subscriber. This disk is attached to a pivoted lever, which can be locked in an inclined position, so as to keep the disk out of sight by means of a rod attached to it and terminating in a triangular stud, which passes into a slot in the upper end of the vibratory tongue, R. The signal disk will drop until its lever arm is perpendicular, when released by the vibration of the tongue, R, and it will then be visible through an opening in the box of the apparatus. When the sound signal is given the plate, R, vibrates, and at each vibration the triangular stud, C, will slip out of the slot in the plate a very short distance and finally leave it altogether when the disk shows. The sound signal is required to operate this visible signal, as the vibrations produced by the ordinary speaking are not powerful enough to operate this mechanism.

A call bell is sometimes arranged so as to sound when the disk drops, and it is of great service in case the switchman is not at his post, as it calls attention to the fact that he is wanted. Generally six signaling devices are arranged in one box, as shown in Fig. 7, and the signal box with the call bell is arranged above the switch, as shown in Fig. 8.

The subscribers' wires are arranged in groups of about thirty, those persons communicating with each other very frequently being united in one group. Each switchman

has charge of a signal box and switch, represented in Fig. 8, which shows only ten subscribers, whereas there are twenty to thirty or more in each division, as before stated. A box




Fig. 4, 5.—THE SIGNALING APPARATUS.

containing the Ader signals is represented in the upper part of the cut, the white circles, with the numerals above them, representing the small windows or openings through which the disks can be seen when they have dropped. The call bell, which can be brought into action when required by means of a commutator, I, is mounted on top of the signal box. The plug switch, which is arranged below the signal box, consists of a series of vertical bars of metal, one for each subscriber, and a series of horizontal bars of metal arranged behind the vertical bars in such a manner that the two series do not touch each other, but are perforated at the crossings, so that a communication between a vertical and a horizontal bar can be established by passing a plug through the said perforations at the intersection of the bars. Each vertical bar is provided with a pin, and in Fig. 8 all the pins are represented as connecting the vertical bars with the lowest horizontal bar connected with a ground wire. Supposing the subscriber to have given his signal, and thus notified the switchman that he desires to communicate with another subscriber, the switchman takes the plug from the transverse bar and places it into the aperture at the crossing of the bar, No. 5, with the second horizontal bar, and he is now in communication with No. 5, and asks him with whom he desires to communicate. No. 5 replies that he desires to be connected with No. 9. The employe then resets the signal of No. 5, and connects No. 9 with the second bar by means of the plug in the manner described, and is thus in communication with No. 9, and gives the signal, which may be a simple sound




Fig. 7.—ANNUNCIATORS.

signal, the Ader visible signal, or the call bell, as the subscriber may have arranged it at his house or office. No. 9 is then notified that No. 5 wishes to communicate with

him, and No. 5 is notified that No. 9 is ready, the pins of the vertical bars, Nos. 5 and 9, having been placed above one and the same transverse bar, for instance, A, Nos. 5 and 9 are connected, and can converse with each other with complete privacy.

It must be stated that the disks of 5 and 9 have been raised, and as soon as their conversation is over Nos. 5 and 9 blow into the tubes of their telephones, thus notifying the switchman, who places the two plugs back in the bar connected with the ground wire. But if No. 3 and 7 wish to communicate at the same time that 5 and 9 are in communication, the pins belonging to 3 and 7 must be passed into the apertures at the intersection of the vertical bars, 3 and 7, with the second transverse bar, B, and in like manner, the next two subscribers are connected by means of the bar, C, and so on. These connections, however, only relate to subscribers of one and the same group or division. If the subscribers belong to separate divisions the connections are a little more complicated. If, for instance, No. 5 notifies the switchman that he desires to converse with No. 83, who is not in his group, which may be designated by A, and comprises the subscribers from 1 to 30, but probably will be found in group, C, comprising the subscribers from 60 to 90, the switchman passes the pin of No. 5 through one of a number of horizontal bars located between the bar, D, and the second bar, not shown in drawings, and then writes on a slip of paper: "The subscriber 5, group A, line 6 (for example), desires to be connected with No. 83, group C," and sends this slip to the group C. The switchman in charge of this group notifies No. 83, and then connects him with the line 6. He then sends the slip to the employe in charge of the grand commutator, where the groups A and C are connected in the line 6, thus permitting No. 5 to con-




Fig. 8.—ANNUNCIATORS AND SWITCHES.

verse with 83. As soon as they have completed their conversation they give the signals, and all the pins are replaced into their former position.

In the annexed cut we give an exact representation of the central station, showing the cases of each group arranged along the wall, and the grand commutator which connects 50 lines in the rear.

This system requires no batteries either for calling or transmitting. There are at present one hundred subscribers connected in Paris, and five hundred applications have been received.—*La Lumière Electrique.*


NEW INVENTIONS.

Messrs. Jacob Waggoner and George E. Waggoner, of Perrin, Mo., have patented an improved harrow so constructed that it may be adjusted wide or narrow, as the work to be done may require.

A simple and effective machine for moulding and pressing bricks has been patented by Mr. James A. Reeder, of Corinth, Miss. The invention consists in combining, with a brick machine plunger, graduated arms to raise and lower it, for the purpose of regulating the quantity of clay that enters the mud box.

A lamp stand or body of separate parts that fit within or over each other and are held together by one bolt, and provided with detachable handles or side ornaments, has been patented by Mr. Joseph Kintz, of West Meriden, Conn.

An improved salt cellar and pepper box, patented by Mr. William C. Beattie, of Taunton, Mass., consists in an oval-bottomed egg-shaped metal box, divided transversely, and having its sections connected detachably with a screw-thread, and having also one end perforated with holes through which the salt or pepper can be sifted, and the other end weighted or slightly flattened, or both, so as to cause the box to set upright.



CENTRAL OFFICE.

AGRICULTURAL INVENTIONS.

Mr. Joseph Amstutz, of Harlan, Ind., has patented an improved rake reel for reapers and mowers, which is so constructed as to raise and straighten fallen, lodged, tangled, and twisted grain and grass, and hold them in proper position while being cut, and thus allow the machine to cut short, tall, lodged, fallen, tangled, and twisted grain and grass with facility and thoroughness, leaving no scattered stalks and leaving grain in good condition for being bound.

Mr. William S. Neal, of Perdue Hill, Ala., has invented a combined cotton chopper and cultivator, so constructed that it may be readily adjusted as the character of the work to be done may require.

An improvement in the class of grain drills or seeders whose drill tubes have detachable points or hoes has been patented by Mr. William H. Wilson, of Xenia, Ohio. The improvement consists in constructing the point or hoe proper with a tubular shank, and in securing it to a drill tube by a wedge.

An improved grain rick frame has been patented by Mr. Cornelius Geiger, of Tarborough, Ga. This invention relates to portable grain supporters, the object of which is to secure small grains from damage when stacked in the straw, especially on bottom lands subject to overflow, and particularly adapted for the use of rice planters.

Correspondence.

The Edison Light

To the Editor of the Scientific American:

With this I send you the report of Profs. Brackett and Young on the efficiency of Mr. Edison's machine for generating electricity.

As undoubtedly comparisons will be drawn between the figures there given and those which have been given by Dr. Hopkinson for the Siemens machine, an analysis of his figures is not out of place. In *Engineering* for May 9, 1879, a full report of the tests of Dr. Hopkinson may be found.

He assumes, in calculating the work which is done in the circuit, that a gravity Daniell's cell has an electromotive force of 1.125 volts, though this form of cell is the weakest of any. In the calculations which the makers of other machines have rated the efficiency of their machines, 1.079 volts has been assumed as the electromotive force of a Daniell's cell. As the work varies with the square of the E. M. F., his figures for work in the current must be multiplied by $\left(\frac{1.079}{1.125}\right)^2 = 0.919$; that is, 91.9 per cent of the work given by his figures should be taken in comparing the Siemens with other machines. I take experiments 9, 10, 11, and 12 as representing very nearly the conditions of practical use. These show, according to his figures, 3.803 erg-tens in the current to 4.161 erg-tens given the machine by the belt, or 91.5 per cent as the efficiency of the machine. Using the correction mentioned, 84 per cent will be the true number. Taking the resistance of the machine as 0.683 ohm, which it would be after running a short time, these experiments show 52 per cent in outside work; that is, of 5.55 horse power given the machine by the belt, 2.89 horse power were effective outside.

Profs. Brackett and Young show 90.7 per cent converted, and 83.9 available outside.

I hope this statement will be sufficient to end the discussion into which I was drawn some time since regarding Mr. Edison's machine. He then claimed that $\frac{1}{10}$ of the power in the current could be made available; now tests show $\frac{1}{8}$ of the energy in current are available.

It is not "childish," then, to make an armature with about one eighth of an ohm resistance, as was claimed by others at the time.

Yours,

FRANCIS R. UPTON.

REPORT OF COMPARISON BETWEEN THE PRONY AND EDISON DYNAMOMETERS, AND UPON THE EFFICIENCY OF THE EDISON DYNAMO-ELECTRIC MACHINE, BY PROFS. C. F. BRACKETT AND C. A. YOUNG, OF THE COLLEGE OF NEW JERSEY, PRINCETON, N. J.—EXPERIMENTS MADE APRIL 3, 1880.

FIRST COMPARISON BETWEEN THE DYNAMOMETERS.

The lever arm of the Prony was held down by the action of a spring balance applied at division 12, corresponding to a virtual circumference of 12 feet. The weight of the balance was 5.41 pounds, which is to be added to all its readings. The balance was read by Mr. Upton. After the experiment, the Edison dynamometer, transmitting no work, as read by Prof. Brackett, indicated (the mean of five readings, ranging from 990 to 995) 994.2 pounds. During the experiment the readings were made by Prof. Brackett and recorded by Prof. Young.

Duration of test, 10 minutes.

Number of revolutions of Prony shaft, determined by counter, 5,664.

Number of revolutions of main shaft, 1,880.

Mean indication of Edison dynamometer, deduced from Prof. Brackett's ten readings, varying from 920 pounds at beginning to 935 at end of experiment, 925.7 pounds.

From this, taking the mean reading of the zero, 994.2 pounds, we have $\frac{994.2 - 925.7}{2} = 34.25$ pounds.

Mean tension on Prony arm, 9.011 pounds, varying gradually from 10.91 pounds at beginning to 7.66 pounds at end of experiment, including weight of scale.

Work registered by Prony, 9.011 (lb.) \times 12 (ft.) \times 5,664 (rev.) = 612,460 ft. lb.

The diameter of main pulley is 38 inches.

The angle between belts of Edison dynamometer is taken

at 44°. Assume $K = \left(\pi \times \sec. 22^\circ \times \frac{38}{12}\right) = 10.7297$. Then

the Edison dynamometer registered K (ft.) \times 1880 (rev.) \times 34.25 (lb.) = 690,880 ft. lb. That is, the Prony recorded 88.6 per cent of the work carried by the Edison dynamometer.

The comparison does not seem to us satisfactory on account of the considerable change in the conditions during the experiment.

SECOND COMPARISON.

Constants and observers as before.

Duration of test, 4 minutes.

Number revolutions of Prony, 2,281.

Number revolutions of main shaft, 752.

Mean tension on arm of Prony, 11.35 lb., varying from 11.60 to 10.97 in seven readings.

Initial reading of Edison dynamometer (mean of five), 994.2.

Final reading of Edison dynamometer (mean of five), 994.2.

Mean during comparison, 911.57.

(Mean of seven readings, varying from 910 to 915 lb.)

Work according to Prony, 11.35 (lb.) \times 12 (ft.) \times 2,281 (rev.) = 310,680 ft. lb.

Work according to Edison instrument, K (ft.) \times 752 \times $\left(\frac{994.2 - 911.57}{2}\right) = 333,360$ ft. lb.

In this comparison the Prony registers 93.2 per cent of work indicated by the Edison dynamometer.

We regard this test as fairly reliable, the conditions having been very constant, and the outstanding difference of 6.8 per cent being reasonably accounted for by slip of belts and friction of journals between the two dynamometers.

TESTS OF THE EFFICIENCY OF THE DYNAMO-ELECTRIC MACHINE.

During both these tests the thermometer of the calorimeter and the Edison dynamometer were read as often as every minute, and great pains were taken to keep the water thoroughly stirred. The calorimeter was a galvanized iron vessel, 16.42 inches in diameter and 24.1/2 deep.

The wire coil was wound upon a light wooden frame, so constructed as to serve as a very efficient stirrer.

The thermometer was an excellent instrument, by James Green, graduated to fifths of a Fahrenheit degree, each degree being about three-sixteenths of an inch in length.

Prof. Brackett read the dynamometer.

Prof. Young read the thermometer and made the records.

Mr. Upton and others, the speed of the main shaft and the indications of the high resistance galvanometer in the laboratory.

CONSTANTS.

- Weight of calorimeter (empty) 22.63 lb.
- Heat capacity of same (taking specific heat at 0.112) 2.53 lb.
- Weight of wooden frame 5.71 lb.
- Heat capacity of frame (s. taken at 0.30) 1.71 water lb.
- Weight of wire coil (54 1/4 turns, each turn weighing 5.84 grammes) 0.70 lb.
- Heat capacity of wire (s., 0.10) 0.07 water lb.
- Resistance of coil in calorimeter 1.720 ohms.
- Resistance of leading wires taken as 1/100 of coil 0.0057 ohm.
- Resistance of wire on revolving armature 0.140 ohm.
- Resistance of coil on field magnets, 1.470 ohms.

FIRST TEST.

- Total weight of calorimeter with contained water and everything in place 197.5 lb.
- Hence from preceding data the heat capacity of whole 172.77 water lb.
- Temperature of air 72.2°
- Temperature of water at beginning 63.8°
- Temperature of water at end 80.5°
- Gain during experiment 16.7°
- Duration of experiment 13m. 50s.
- Dynamometer at beginning (free) 994.2
- Dynamometer at end (free) 995.
- Mean dynamometer zero 994.6
- Speed of main shaft, beginning 174 per min.
- Speed of main shaft, end 170
- Mean 172
- Mean reading of dynamometer during experiment 771.75 lb.
- (Varying from 760 to 781, 16 readings.)

E. M. F. of current maintaining field was 61 divs. of galvanometer, on which 168 d. corresponded to 16 Daniell cells, i.e., E. M. F. = $\frac{61}{168} \times 16 \times 1.079$ volts.

Energy expended on driving armature, as indicated by dynamometer = K (ft.) \times 172 (rev.) \times 13.833 1/3 (min.) \times $\left(\frac{994.6 - 771.75}{2}\right) = 2,844,600$ foot pounds.

Energy expended on field of force, $\frac{6}{5} \times 45.25$ (ft. lb.) \times 13.833 (m.) \times $\left(\frac{61}{168} \times 16 \times 1.079\right)^2 = 19,634$ foot pounds.

Hence, total energy expended, 2,864,234 foot pounds.

Energy Realized.

- a. In calorimeter = 772 \times 172.77 \times 16.7° = 2,227,420 ft. lb.
 - b. In leading wires 1/100 of above 7,425 ft. lb.
 - c. In armature $\frac{14}{172}$ of calorimeter, 181,302 ft. lb.
- Hence,
Total energy realized 2,416,147
Total available (a + b) 2,234,845
- Hence,
Total efficiency 84.5 per cent.
Total available 78.2 per cent.

Remarks.

During this test the driving power was about 6 1/4 horse power; the electromotive force of the field current, 6.27 volts, giving a current through the magnet wires of about 4 1/2 webers; and the current developed by the machine was about 45.8 webers through a total resistance of 1.866 ohms.

SECOND TEST.

- Total weight calorimeter and contents 200.00 lb.
- Hence by preceding data, heat capacity = 175.27 water lb.
- Temperature of air 71.1° to 71.8°
- Initial temperature of water 63.2°
- Terminal temperature of water 79.9°
- Gain 16.7°
- Duration of experiment 9 minutes.
- Speed of main shaft, beginning 176 per m.
- Speed of main shaft, middle 173 per m.
- Speed of main shaft, end 177 per m.
- Mean 175.33
- Dynamometer reading before exp., 985
- Dynamometer reading after exp. 995
- Mean dynamometer zero 990
- Mean reading of dynamometer during the experiment (9 readings, between 645 and 666) 656
- Electromotive force of field (by high resistance galvanometer) = $\frac{145}{168} \times 16 \times 1.079 = 14,901$ volts.
- E. M. F. of dynamo current = $\frac{240}{51} \times 20 \times 1.079 = 101.55$ volts.
- E. M. F. of terminals of dynamo; current broken, $\frac{290}{51} \times 20 \times 1.079 = 122.71$ volts.

Energy Expended.

- a. In driving armature according to dynamometer, $K \times 175 1/2$ (rev.) \times 9.0 (m.) \times $\frac{990 - 656}{2} = 2,827,550$ ft. lb.
 - b. In maintenance of field of force, $\frac{6}{5} \times 44.25$ (ft. lb.) \times 9 (m.) \times $\frac{(14,901)^2}{1.47} = 72,180$ ft. lb.
- Hence,
Total energy expended 2,899,730 ft. lb.

Energy Realized.

- a. In calorimeter, 772 \times 175.27 \times 16.7° = 2,259,700 ft. lb.
 - b. In leading wires 1/100 of above 7,532 ft. lb.
 - c. In armature $\frac{0.14}{1.72}$ of a 183,930 ft. lb.
- Total energy realized (a + b + c) 2,451,162 ft. lb.
Available (outside of machine) (a + b), 2,267,232 ft. lb.
- Hence,
Total efficiency 84.5 per cent.
Available efficiency 78.2 per cent.

Remarks.

As a check we may compute the total efficiency from the galvanometer reading and the resistance: Energy developed, 44.25 (ft. lb.) \times 9 (m.) \times 101.55 (volts) \times 1.866 (ohms) = 2,200,500 ft. lb.

The discrepancy is fairly explained by the defective insulation of long wires leading to the galvanometer, as it was raining at the time.

During the experiment the driving power was about 9 1/2 horse power, and the current was 57.4 webers (according to galvanometer, 54.4).

Even with this current the spark at the commutator was very trifling.

SUMMARY.

	Total Efficiency.	Available Efficiency.
According to first test	84.5 p. c.	78.2 p. c.
According to second test	84.5 p. c.	78.2 p. c.

The Prony dynamometer is connected to the Edison dynamometer by a belt from the same countershaft, which is also belted to the electric generators. If we should assume the correctness of the Prony, and that the loss in the transmitting power between the Edison dynamometer and the arbor of the armature was only the same as between the two dynamometers, the above numbers would have to be increased in the ratio of 100 to 93.2 (see above), and we should have:

Total efficiency	90.7
Available efficiency	83.9

C. F. BRACKETT,
C. A. YOUNG.

Princeton, N. J., April 10, 1880.

AMERICAN INDUSTRIES.

[Continued from first page.]

also the cutting of the inner lining, which is of coarser and heavier muslin, to hold the starch better, and a collar is styled three, four, five, or six ply according as it has one to four pieces between its outer and inner sides.

From the cutters, the goods go to the room shown in one of the upper views, where the various pieces are "assembled," as it may be called, that is, a sufficient number of pieces of each kind to make two dozen shirts, with the stock necessary for their finishing, are put together in one bundle, ready to give to those who do work outside of the factory, or to send to the stitching room on the premises. All the orders for goods of different kinds and styles have here to be closely looked after to see that the work is started right.

The stitching room, as shown in the view on the left at the bottom of the page, presents no features of especial novelty, except for the great number of sewing machines at work. Great care must be taken to keep the work free from oil, and so preference is given to a machine which will require little lubricating, and at the same time can be run at a high rate of speed. A number of buttonhole machines are employed, but a portion of this work is also done by hand.

Making the folds on the edges of collars and cuffs and the plaits in bosoms is shown in the view at the top, in the center. A machine introduced for this purpose within the past two years has proved very successful. The edges are folded down or the plaits laid by a metal former, when they receive a quick pressure from heated plates, which puts them in the exact position required, and so that they retain the form thus given until the stitching is done. At the right of this picture is seen a representation of the turning room, where the collars, which have been stitched wrong side out, are turned and the seams pressed out. This work is all done by hand.

The view of the packing room, as seen in the middle, explains itself. The pasteboard boxes used are made for the firm by a local factory, where little else is done than supply this demand.

The laundering of the shirts and collars forms a separate department of the business, not shown in our engravings. In the collar laundry about 100 hands are employed, and rather more than that number in the shirt laundry. A good deal of machinery is used in this part of the work, including huge wash wheels, which will take in four to five hundred dozen collars and cuffs at one time; centrifugal wringers, which turn at the rate of a thousand revolutions a minute; immense starch wheels, steam ironers, etc. In addition to the starching done by machinery a large number of "hand starchers" are employed for the collars and cuffs, and the drying is all done by steam heat. The ironing machines consist of various arrangements of heated rollers and revolving drums, which give to the goods a smooth, fine finish, and all the work of washing, drying, starching, and ironing is performed so expeditiously that the laundry work is regularly kept close up to the production of the factory.

The cost of making a shirt runs from \$1.50 to \$3.50 a dozen, and, low as this price seems, and impossible as it would be for ordinary seamstresses to make a living in this way, there is never any difficulty found in obtaining all the help needed. There are about 300 hands employed in the building, of which 50 are men, but there are some 1,500 names on the pay-roll besides, of those who take out work to do at their homes in the city and for many miles around, so that, where the money thus earned does not go directly to the support of families and individuals, it enables those who are industrious and ambitious to supply themselves with many additional comforts and luxuries which they would not otherwise have. This is exclusive of the hands employed in the laundry work, which would make the total help engaged in shirt and collar making and laundering number fully 2,000.

The present firm was organized in 1865, but the business was established over twenty-eight years ago. The partners are all practically conversant with and take an active part in the work. Their goods are sold only to jobbers: in New York, from No. 87 Franklin street; in Boston, by Whittemore, Cabot & Co.; and in Philadelphia, by W. L. Wetherly.

The Nature of Light and its Action upon the Eye.

At a recent meeting of the Buffalo Microscopical Club, Dr. Lucien Howe presented the subject of the undulations of light and their perceptions by the eye. Brief mention was made of the different theories, accounting for the phenomena of optics previous to the present century. The difficulties of this subject were first solved by Thomas Young, who satisfactorily explained the undulatory theory of light. He showed that what we call light is an impression produced upon the retina by the wave-like motion of the particles of matter. Subsequently the lengths of these waves were measured. It would take 36,918 waves of red light, or 64,631 waves of violet light, placed end to end, to make an inch. From the speed of light, which has been measured, it is proved that at least four hundred and fifty one millions of millions of these minute waves flow into the eye and dash against the retina in each second. Dr. Howe proceeded with a minute description of the microscopical anatomy of the eye, more particularly relating to the "layer of rods and cones." These were stated as being in reality the terminal filaments of the optic nerve. These are shaken or acted on by the waves of light, and it is especially these with which we see.

The Proposed Illinois Ship Canal.

Mr. Daniel C. Jenne, Chief Engineer of the Illinois and Michigan Canal, contributes to the Chicago *Inter-Ocean* the following account of the proposed through water route from the great lakes, at Chicago, to the Mississippi River:

The first division of the project consists in the enlargement of the Illinois and Michigan Canal from Chicago to Joliet. The present canal was built 48 feet wide on the bottom, with side slopes 1 to 1 in earth, making 60 feet surface width at 6 feet deep, or below the low water of Lake Michigan, with a descent on the bottom of one-tenth foot per mile across the Summit level, toward Joliet. It is proposed to make the enlarged canal 144 feet wide on the bottom, side slopes 1 to 1 protected by slope wall in earth, and 160 feet wide at surface at 8 feet deep, or below low water of Lake Michigan, with a descent of two-tenths foot per mile. This will pass 112,321 cubic feet of water per minute, and give a current of 1.06 miles per hour. The average stage of water in Lake Michigan for the last eight years has been about 2 feet higher, which would make the water 10 feet deep, and would pass 158,533 cubic feet per minute, with a current of 1.19 miles per hour.

The canal enters the Desplaines River about one mile and a half north of the main street at Joliet, or nearly opposite the State Penitentiary, and will be about 33 miles long. The work of enlargement consists of about 15,000,000 cubic yards of excavation, including the removal of spoil banks made from the excavation of the present canal, of which there will be about 4,000,000 cubic yards of solid magnesian limestone to be excavated. Three lift-locks will be required at the southern end, one grand lock at Bridgeport or north end, six public road and street drawbridges, and one double railroad drawbridge, and a large water weir at Lockport. The locks are to be 350 feet long between the gates and 75 feet wide, to correspond with those now built on the Illinois River.

The second division extends from one and one-half miles above Joliet to La Salle, about 67 miles, and will consist of the improvement of the Desplaines and Illinois rivers by locks and dams, and an independent short piece of canal around the rapids at Marseilles. It will require the construction of eleven locks, nine dams, the raising of two dams, nine drawbridges, the independent piece of canal above referred to, and other incidental work.

The third division consists in the improvement of the Illinois River from La Salle to Grafton, on the Mississippi River, and was described in my former communication, distance 227 miles. Of this, 90 miles have been finished by the construction of two locks and dams.

COST OF THE WORK.

The estimated cost of the first division, 33 miles, is....	\$11,532,932
Estimated cost of the second division, 67 miles, is.....	4,327,879
Estimated cost of the third division, 227 miles, is.....	1,000,000
Total cost to complete 327 miles.....	\$16,860,811
There has been expended by the State on locks and dams.....	747,747
There has been expended by the United States on locks and dams.....	62,360
There has been expended by the United States on dredging wing, dams, etc.....	526,000
Amount already expended.....	\$1,336,107
Total estimated cost of the entire work.....	\$18,196,918

The item of work, quantity, and the estimate of cost on the first and second divisions are from the report of F. C. Doran, Esq., civil engineer, who made a survey of the same in the fall of 1874, under the direction of Colonel J. N. Macomb, Corps of Engineers, United States Army.

According to these estimates the canal, 327 miles long, will cost \$55,560 a mile, and will have twelve times the capacity of Erie Canal, which cost about \$90,000 a mile. This route opens an inland water communication between the Gulf of Mexico, New Orleans, St. Louis, and other cities of the great West and Southwest, through the city of Chicago, with the city of New York in one direction, and with the cities on the St. Lawrence River and the Gulf of St. Lawrence in another direction, and through both routes and the extremes with the Atlantic Ocean.

The dimensions of the proposed canal are sufficient to admit boats of 2,500 to 2,800 tons burden, being 80,000 to 85,000 bushels of grain, or one and a half to one and eight-tenths million feet of pine lumber; or fleets of smaller boats can pass the locks at the same time with about the same tonnage, or twelve of the boats of the Erie Canal, or the Illinois and Michigan Canal, can pass the locks at one lockage.

The summit level of the canal could be reduced to 100 feet on the bottom with the same slopes and declivity, and construct basins at every mile 500 feet long and 50 feet wide for boats to pass, and reduce the cost of the first division about \$4,000,000, and these at 10 feet deep would pass over 100,000 cubic feet of water per minute.

The Railway up Vesuvius.

The station is situated on a level spot on the west side of the mountain, about half an hour's walk from the observatory. The constructors of the railway have adopted the American double iron rope system. There are two lines of rails, each provided with a carriage divided into two compartments and capable of holding six persons. While one carriage goes up the other comes down, thus establishing a counterpoise, which considerably economizes the steam of the stationary traction engine. The incline is extremely steep, commencing at 40°, increasing to 63°, and continuing at 50° to the summit. Every possible precaution has been taken against accident, and the railway itself is protected against possible flows of lava by an enormous wall. The ascent will be made in eight to ten minutes, while before it required

from one to two hours. To obtain the necessary supply of water, large covered cisterns have been constructed, which in winter will be filled with the snow that often falls heavily on Vesuvius. This snow will be quickly melted by the internal heat, and, besides the water thus obtained, the frequent rainfall will also be conducted into the cisterns.

MISCELLANEOUS INVENTIONS.

Mr. Oscar Kleinberger, of New York City, has patented an improved material for suspender straps or ends. It is made of duck, muslin, or other woven fabric, faced with oil cloth, the two being attached together, with or without a filler, in a solid compact sheet, from which the ends and other portions are afterward cut.

An improved apparatus for flooding oil wells has been patented by Mr. Henry R. Davis, of Pioneer, Pa. The object of this invention is to continuously flood or lubricate oil wells other than flowing oil wells with oil, to prevent the accumulation on their sides of incrustations of salt, lime, paraffine, or other oil deposits.

A portable lantern combined with clockwork mechanism, by which flashing or other signals may be given, so that the number of the signals may convey the desired meaning, has been patented by Mr. Romeo W. Lewis, of Sacramento, Cal.

Mr. William H. Maxey, of Homer, La., has patented a tether for securing horses and other stock while grazing, so constructed as to prevent the animals from twisting the tethers or becoming entangled in them, and also to limit the grazing area without moving the tether.

Mr. John K. Hogan, of Placerville, Cal., has patented a machine intended for splitting peaches and other fruits in halves and removing the stones in preparing the fruit for preserving, and is especially adapted for the varieties of peaches known as "cling-stones," which are generally preserved whole on account of the difficulty experienced in freeing the stones by hand.

Messrs. Lewis B. White and Leonard Henderson, of Middleburg, N. C., have patented a smoke and dust arrester for railway cars, which consists in inclosing the trucks of the cars in a housing having doors at the ends, which housings communicate with a pipe extending through the entire train, through which the air and dust from the wheels is drawn by a fan located in the rear car. Smoke may be drawn from a hood located above the smoke stack of the locomotive by the same pipe.

Messrs. Henry P. Gray and William Gray, Jr., of South Manchester, Conn., have patented an improved apparatus for dyeing and washing yarn, cloth, etc., adapted for use in connection with any desired number of vats.

An improved device for fastening an umbrella to the body of a person who is exposed to the rays of the sun during his work, has been patented by Mr. Thomas Mora, of Franklin, La. The invention consists of a tubular socket provided with side springs and of a tube provided with a laterally projecting ring, both of which are buttoned or otherwise fastened to straps or bands that buckle about the body.

An improvement in heating stoves, patented by Mr. John P. Oeth, of Canton, Mo., is designed to increase the heating surface of stoves, to prevent accidental contact of the body or clothing with the heated surface of the stove, and to enhance the appearance of the stove.

Mr. Hubert Child, of Wichita, Kan., has invented improvements in transparent signs. It consists in "cutting in" a transparent letter on glass by means of an opaque color, and placing behind the glass a packing of broken glass contained between two independent panes of glass, so that when the light from the rear shines through the transparent letter the plane character of said letter is broken up and diversified by the crystals of glass, which may be of different colors to produce a very brilliant and tasteful design.

Mr. William H. Burk, of Greencastle, Ind., has recently patented an ornamental and attractive apparatus for roasting and warming peanuts.

Mr. David N. Smith, of San Bernardino, Cal., has patented improvements in the construction of safes for receiving vegetables, food, clothing, and other similar articles, the object of the invention being to prevent the access of insects to the articles placed within the safe.

An improvement in crates for carrying fruits, eggs, and other perishable articles, has been patented Mr. George E. Bender, of Everett, Pa. The object of the invention is to provide a crate that is perfectly ventilated, and at the same time is arranged to exclude the cold and protect the contents against injury from the outside.

Mr. Edward Barnard, of Rome, N. Y., has patented a quarter boot for horses, having a soft leather body with stiff pads on the quarters, and a stiffening sole strip, the whole adapted to be held in place by straps and buckles.


An improvement in gate latches, patented by Mr. Samuel B. Elzey, of Atlanta, Ga., consists in combining a pivoted latch carrying an arm, a sliding bar carrying an arm, and a spindle carrying an arm, so that the gate may be unlatched by turning the spindle.

Mr. William Linehan, of Chicago, Ill., has patented a device for automatically feeding the fluid for preventing incrustation into the boiler along with the feed water, when supplied by a pump or an injector. It consists of a reservoir for holding the fluid, from the bottom of which a siphon pipe leads to the pump barrel or injector at a point where the water is forced or drawn by suction into the boiler. The siphon pipe is supplied with a stopcock and check valve, to regulate the amount supplied and to prevent back pressure when pumping.

NOVEL TOOL HANDLE.

The annexed engraving shows an improvement in the class of tool sockets designed for application to wooden handles, and adapted for holding tools of various kinds, such as shovels, forks, spades, and other agricultural hand tools.

The socket is fitted to the lower end of the wooden handle, and has in its upper face a concave depression or groove for receiving the shank, B, of the shovel, spade, or other implement, in connection with which the handle is used. Over the groove in the socket there is at the upper end a keeper or loop, provided with a set screw, C, for holding the shank, and at the lower end of the socket there is a keeper or loop, A, that holds the larger part of the tool shank. The



IMPROVED TOOL HANDLE.

set screw is inclined at an angle to the shank, so that its tendency when tightened will be to draw the shank into the handle.

This handle may be readily applied to any tool having a shank adapted to it by simply inserting the shank and tightening the set screw.

This useful invention was recently patented by Messrs. J. H. Richardson and J. C. Calhoun, of Oakley, La., who may be addressed for further information.

NEW ROTARY ENGINE.

The annexed engraving represents an improved rotary engine recently patented by Mr. William N. De Groat, of Knoxville, Tenn., the patent being now owned by Messrs. W. N. De Groat and A. L. Maxwell, of same place.

The engine is shown in perspective in Fig. 1 and in section in Fig. 2. The revolving pistons are secured to a rotary disk, work in a stationary annular cylinder having three sliding abutments, C, which are operated at the proper instant by a cam, A, on the main shaft through a system of levers, B, and suitable connections. Steam and exhaust ports enter the disk at or near the center, and pass to its periphery in opposite directions, the steam supply port communicating with the cylinder through one face of the piston-head, and the exhaust port running through the opposite face. The exhaust ports are arranged so that the sliding abutments are relieved of steam pressure before it is moved, and it is restored to its place under a pressure which is balanced with the exception of the small area of the stem by which it is worked.

For convenience in reversing the engine there are steam ports on opposite sides of the piston, and a plug valve, D, in the disk is employed to change the direction of the steam supply and exhaust and thus reverse the engine. Steam is exhausted from the engine through the passage, a, and admitted through the central passage, b.

This engine has no dead points, and always works to its full power throughout its entire revolution. The inventor claims an advantage admitting and exhausting steam from the face of the piston, as the steam is not wiredrawn by passing through tortuous passages.

It is obvious that this engine requires no flywheel, as the motion is continuous, and not intermittent as in the case of reciprocating engines, and a great advantage in economy of steam is claimed, the power being applied directly and in the right place.

For marine engines the rotary form has many advantages that will be understood and appreciated by engineers. A study of the engraving, in connection with what has already been said, will be sufficient to make clear the construction and merits of this engine.

MECHANICAL INVENTIONS.


An improved device for use upon steam railroad cars, street railroad cars, at stations, and in other places, to indicate the name of the next station, street crossing, or other stopping place, the distance to it, and the time when due, and also, when used at stations, to indicate the next train and the time of departure or arrival, has been patented by Messrs. John B. Herbert and Charles Layton, of Old Bridge, N. J.

An improved pitman connection has been patented by William F. Rundell, of Genoa, N. Y. The invention consists in a wrist pin made of two diameters, a box having tangs or shanks to be bolted to the pitman, which box is arranged to bear in the plane of the larger diameter of the wrist pin, the pitman being prevented from slipping off by a flange on the inner sides of the box extending down to and fitting the smaller diameter of the wrist pin, while a gasket

and circular plate on the outside is screwed to the box to inclose the wrist pin and make an oil-tight bearing.

IMPROVED GUN WAD.

The annexed engraving represents a gun wad specially adapted for loading and discharging shot from a fowling-piece. Gun wads have been made of concavo-convex form in such a manner that when pushed into a gun barrel or cartridge shell by means of the square end of a ramrod or plunger they would expand under pressure to fit tightly upon the charge. Flat wads have also had their edges or perimeters scalloped or pinked, so that a wad larger than the bore of the gun or cartridge could be readily crowded in upon the charge, to be retained by the elasticity of the compressed serrated or pinked edge of the wad. In both instances the wad leaves the gun intact and impedes the flight of the shot and affects their direction and force. The invention shown in the engraving is intended to compress and pack a wad tightly upon a charge of shot in a gun barrel or cartridge shell, in such a way that it will remain intact until moved by the explosive force of the powder, when it will



NEIMEYER'S GUN WAD AND PUNCH.

open in its center and sever into quarter sections, and allow the charge of shot to virtually fly through the wad without being impeded or misdirected by the fragments of the wad. This is accomplished by forming a crosscut or a series of radial incisions in a wad by means of the combined hollow punch and a solid four-bladed cutter, shown in Fig. 1.

The wad is intended to be used only over the shot, and when the gun is discharged the parts of the wad will be found upon the ground from five to six feet ahead of the muzzle of the gun. By the use of this wad no obstruction to the direction or force of the shot is offered, and the pattern is thereby improved and the penetration increased.

Further information may be obtained by addressing Mr. Jacob Neimeyer, Atlantic, Ia.

Fig. 1





Fig. 2



DE GROAT'S ROTARY ENGINE.

A CHAPTER ON TROUT.

BY DANIEL C. BEARD.

Brook trout are always associated in my mind with delightful scenery, clear, swift running water, and bracing air, and I am sometimes tempted to think that it is the association that lends such a delicate flavor to their meat. As Aldrovandus quaintly expresses it, "The salmon, the grayling, and the trout, and all fish that live in clear and sharp streams, are made by their mother nature of such exact shape and pleasant colors purposely to wite us to joy and contentedness in feasting with her." St. Ambrose of old called the grayling the "flower fish." While making a drawing of the *Thymallus Americanus* at Fulton Market, Mr. Seth Green said: "Can you paint the rainbow? If not, do not attempt to reproduce the beautiful tints that glisten and flash upon the dorsal fin of the grayling." Not being able to "paint the bow upon the bended heavens," I was compelled to content myself with black and white, hoping at least to give some idea of the shape and form of this and other graceful and odd fish exhibited at the opening of the trout season by Mr. Eugene Blackford at his place in Fulton Market.

With the energy and goaheaditiveness for which Mr. Blackford is noted, he collected for the inspection of the pisciculturist, naturalist, and angler, all the procurable varieties of trout specimens of the *Salvelinus fontinalis* from England, Scotland, Ireland, France, Germany, Canada, Maine, New Hampshire, New York, Long Island, New Jersey, Wisconsin, Pennsylvania, Illinois, California, Maryland, Utah, and Colorado. There could also be seen trout from all the leading fish-culturists and fish commissioners of the United States, eggs and live trout, from those who just escaped the egg with the abdominal sac still attached, to the full grown fish disporting themselves in glass jars and tanks of crystal waters.

The first fish laid before me was a male trout from Shaster County, California, sent by B. B. Redding, Commissioner


of Fisheries, measuring a little over two feet in length and weighing five and three-quarter pounds, well shaped and plump; on its body a paucity of red spots, but large black dots are sprinkled thickly upon the shoulders and tail; the operculum is decorated with a bright red tint, vanishing or blending into a greenish brown or olive toward the eye. A broad red dash of color extending from tip of tail to cheek gives this fish a very gaudy appearance. "Here," said Mr. Blackford, "is a remarkable fellow from the hatching house, McCloud River, California. It is called the 'Dolly Varden.'" And he placed before me a five and a half pound trout, round and dumpy, large odd head, an abnormal adipose fin, the other fins and tail short. In the place of the usual markings of his family, this fish was covered with large red semi-annular blotches. A slit cut in its back by Mr. Seth Green showed the flesh to be a rich salmon color. After making a careful drawing of this odd Western trout, Mr. Green placed before me an interesting hybrid, a cross between the California salmon and the common brook trout of New York. It was two years old when killed, and measured nine and a half inches in length, of a bluish slate color, no red, but a few yellow dots sprinkled sparsely along each side of the lateral line; a rather small head and graceful body, it partook of the nature of both its parents, with a strong leaning to the brook trout. Another three year old hybrid, measuring fourteen inches, looked more like a salmon.

The *S. fontinalis*, from France, is a well shaped fish, the one drawn measuring fourteen inches in length. A few red spots dot the space between the dorsal fin and the tail; dark spots commence at the gills and scatter over the space above the lateral line on its side and back to the caudal fin. Hon. Thomas Clapham sent some very graceful dark colored trout, averaging about twelve inches in length and two and a half inches in width at the dorsal fin. Hugh McGovern's trout were very like Clapham's, but lighter in color. The fish from the South Side Club, Oakdale, are much lighter in

color, broader, and prettily marked. The specimen given me to sketch measured eleven inches in length and three and one-eighth inches greatest width. The silvery sheen of its abdomen contrasted strikingly with the carmine hue of the abdomen of some of the wild trout from Canada. It would be an interminable task to mention, much less describe, all the fish that lay upon the marble slabs or swam in the aquariums. Says Isaak Walton: "I am certain if I catch a trout in one meadow he shall be white and faint, and as certainly if I catch a trout in the next meadow he shall be strong and red and lusty," and such is the case. Even the same trout that is light colored upon a white pebbly bottom will, chameleon-like, change to a duskier hue if he swim over a dark mud bank.

At the bottom of the group of fish in the illustration is a picture of the German carp (*Cyprinus carpio*) sent to Mr. Blackford by the Smithsonian Institution. This fish will live in almost any half stagnant pond, and it is proposed to introduce it largely into this country. I have also drawn the portraits of a few of the marauders that pillage the fish ponds. It is wonderful, amid so many mortal foes, that a wild trout ever reaches maturity, but once gaining that age he revenges himself by feeding upon many of his former tyrants. Frogs, toads, lizards, aquatic insects, beetles and bugs, land rats, water rats, mice, minks, wild and tame ducks and geese, heron, and even cats never miss an opportunity and are ever upon the alert for a chance to devour the young trout or ova. Man lends a helping hand in this wholesale slaughter by turning the refuse of saw and paper mills and tanneries or other deleterious material into the streams. However, the sensible laws being enacted and enforced, and the efforts of a few enterprising men, will go far to counteract the mischief done.

The engineer of the Baltimore and Ohio Railroad who transported young black bass in the water tank of his engine and restocked barren streams, furnishes a noble example.



EXHIBITION OF FISH AT THE OPENING OF THE TROUT SEASON.

White Fish under the Microscope.

At a recent meeting of the Griffith Club of Microscopy (Detroit), Mr. J. C. Holmes, assisted by D. J. McGuire, M.D., gave a demonstration of the circulation of blood, illustrated by young whitefish from the Detroit "hatchery." The young fish, less than a week old, and looking not unlike a pair of eyes propelled about by an exceedingly active tail, were found, under the microscope, to be possessed of all necessary "interior" arrangements. As they are nearly as transparent as glass, the action of the heart in receiving and propelling blood, and the stream of blood corpuscles down one side to the tail, and back on the other, could be distinctly seen and examined.

The whitefish that are caught for this market are largely made to recognize their obligation to posterity, by passing through the "hatchery," where the *modus operandi*, as described by Mr. Holmes, is as follows: The eggs are stripped from the females by pressing the sides with the hands, and deposited in a large tin pan partly filled with cold water. Into this are placed two or three drops of milt, which is obtained by a similar process from one of the male fishes, and which contains the male principle of life—the microscopical spermatozoa. Each drop of the milt contains several thousands of these minute organisms, that would remain undeveloped but for the favorable conditions found in the female egg. These spermatozoa penetrate the eggs, and curling themselves up comfortably await the necessary five months to incubate. It is now the hatching season, and the unhatched eggs resemble a small pea, of a nearly transparent color, but with two distinct black dots on one side, which the microscope shows to be the eyes of the fish.

Temperature of the Soil during Winter.

The French physicists, Edmond and Henry Becquerel, took advantage of the intense cold prevailing at Paris last December, to study the changes in temperature below the surface of the soil under various conditions. It is a widely spread belief among farmers, that when protected by a layer of snow, crops sown in the autumn are effectually guarded against freezing. This opinion, however, must lose much of its weight in view of these late observations, which we will briefly summarize.

The observations were made by means of Becquerel's electric thermometer, which consists simply of two wires isolated by a coating of gutta percha, and soldered together at their extremities. Differences in temperature between the two places of junction cause electric currents varying in intensity with the greatness of the difference. A magnetic needle, brought under the influence of the current, registers on a dial these differences. The wires were inserted in the Jardin des Plantes at various depths, varying from 5 to 60 centimeters, and observations were made from November 26 to the close of December. Frost first appeared in the garden November 26. December 3 snow fell in abundance, and the temperature of the air sank to -11° C. The layer of snow was 25 centimeters deep. December 10, the temperature had sunk to -21° , and commenced then gradually to rise. December 15, the snow was 19 centimeters in depth.

Coming now to the observations made below the surface of the ground under the above circumstances, we find at once a striking difference between the results obtained in soil covered with grass and those obtained below a bare surface of the ground. In soil protected by grass, before as well as after the snowfall, at all depths below that of 5 centimeters, the temperature never descended below 0° C. Registering 3.5° at the depth of 5 centimeters on November 26, it slowly sank to 0.18° on December 14. The presence of grass would appear, then, to effectually protect the earth beneath it from freezing at the lowest temperatures attained in our climate. Quite different results, however, are yielded in the absence of grass. In this case, at a depth of 5 centimeters, the thermometer sank below zero on November 27. Two days later it registered -2.6° . On December 3, just before the snowfall, it reached its minimum of -3.17° . After being covered with snow it registered -0.8° , and later -1.4° . The snow here appears to act in a certain measure as a screen against changes in temperature, but its conductive properties are still too marked to prevent these changes from being felt sensibly at a certain depth in the earth. In the case of the agriculturist, this slow conduction, when united to the still slower conductive properties of a tolerably thick layer of dead shoots of cereal crops sown in autumn, may frequently insure immunity from freezing to the roots below the surface.—*T. H. N., in Nature.*


Manufacture of Ammonia.

A recent invention of J. P. Rickman, of London, for the manufacture of ammonia from the nitrogen of the atmosphere and the hydrogen of steam, may prove of some importance. The ammoniacal liquor produced in the manufacture of gas being now the chief source of ammonia, its value would considerably diminish should a cheaper source of that useful substance be discovered. Numerous endeavors have been made to convert into ammonia the nitrogen which forms the bulk of our atmosphere; but none have hitherto been a commercial success. We may mention Maxwell-Lyte's process of passing nitrogen and steam over an alloy of potassium and antimony, and Swindell's system of conducting a mixture of atmospheric air and steam through incandescent coke. Rickman's process is similar to that of Swindell. A series of inclined retorts are filled with coke and heated to 550° C. A mixture of twelve parts by volume

of steam and five parts of atmospheric air is then introduced, and ammonia is formed and afterwards condensed in water. The most important point in working this apparatus is to maintain uniformity of temperature. Should the apparatus be too cool, no ammonia is formed; if the heat be too great, any ammonia which may have been produced is dissociated, and again resolved into the elements to which it owed its origin. This regulation of temperature was found to be so difficult to attain that an improvement has been devised which promises to overcome the chief obstacle to the successful working of the process. It is well known that chloride of ammonium is less easily decomposed at a high temperature than ammonia alone. Mr. Rickman, therefore, converts the ammonia into chloride of ammonium at the moment it is generated, which is effected by mixing common salt with the coal or coke used. It is claimed that by these very simple means ammonia can be produced at less than 1d. per pound.

Novel Test for Stone and Ore Breakers.

The annexed engravings are perfect representations of opposite sides of a hardened steel stone hammer which accidentally fell into the jaws of one of Marsden's improved stone and ore crushers manufactured at the Farrel Foundry and Machine Company's Works, at Ansonia, Conn., and doing work at South Easton, Mass.

**Hammer Crushed by a Stone and Ore Breaker.**

This machine has positive motions and is constructed with outsprings or cushions to modify the action of the jaws. Nothing could exhibit the prodigious strength of this machine or its immense crushing power better than the sample of work presented in the engraving.

The hammer is of cast steel, hardened and tempered. It is eight inches long, three inches wide, two and a quarter inches thick, and weighs ten pounds.

The fractures and indentations in this solid piece of steel were made without the least injury to the machine.

ENGINEERING INVENTIONS.

Mr. John R. Jones, of Clarksville, Ia., has patented an improved railway car brake, the object of which is to give to the engineer of a train full control of the brakes without interfering with their operation by hand on each car. The invention consists in a pronged lever hung at each end of each car, the levers on each car being connected together and to the brake chains, and the levers being fitted for continuous contact throughout the train, so that when the brakes are applied on the tender by power from the engine there is a continuous or successive application of the brakes from the first to the rear car.

An improvement in governors, patented by Mr. William E. Crane, of Waterbury, Conn., consists in reciprocating a slide valve to regulate the supply of steam and the speed of machinery by connecting a pinion between two straight racks directly with the sleeve of the governor mechanism so as to raise and lower the pinion.

Mr. James N. Winn, of Darien, Ga., has invented an improvement in car couplings, so constructed that they may be readily adjusted to couple cars of different heights, that they will couple the cars automatically as they are run together, and will be readily uncoupled.

Mr. Allen A. Munson, of La Grange, Mich., has invented a combined elevator and carrier for unloading hay and depositing it in the mow, for loading and unloading vessels and cars, and for other uses.

Some improvements in steam engines have been patented by Mr. Samuel N. Silver, of Auburn, Me. These improvements relate to engines and pumps adapted for use with steam or water, and as stationary, marine, or locomotive engines, or as steam fire engines; and the object is to attain an engine of simple and durable construction adapted for running at high speed.

A spring draught attachment for horse powers has been patented by Mr. Asher E. Morris, of Janesville, Minn. The object of this invention is to connect the draught with the sweeps of horse powers in such a way that both the teams and the machines will be protected from jerk or strain should there be a sudden application of power.

The Mississippi River Commission.

The commission of engineers appointed to investigate the subject of levels and improvements along the Mississippi have submitted their reports.

The thirty-three navigable rivers of the Mississippi system comprise 14,000 miles of navigable waters, intersecting or bordering on eighteen States and two Territories. The extent of territory subject to overflow was, in 1874, estimated to be 41,193 square miles, an area as great as the combined areas of New Hampshire, Vermont, Massachusetts, Rhode Island, and New Jersey, and much more productive under proper conditions. Up to the year 1878 Congress had made for the improvement of the Mississippi river and its various tributaries about two hundred appropriations, amounting in all to the sum of \$18,500,000.

The commission consists of Brevet General Q. A. Gillmore, president; Major Charles R. Suter, United States Engineers; Brevet Brigadier General C. B. Comstock, United States Engineers; Professor Henry Mitchell, of the Coast Survey; Captain James B. Eads, B. Harrod, and Benjamin Harrison, civilians.

The work assigned to them was:

First—To direct and complete such surveys of the Mississippi river between the head of the Passes, near its mouth and its headwaters, as were then in progress, and to make such additional surveys and examinations of said river and its tributaries as might by it be deemed necessary.

Second—To take into consideration and mature such plan or plans as will correct, permanently locate and deepen the channel, and protect the banks of the Mississippi river, improve and give safety and ease to the navigation thereof, prevent destructive floods, and promote and facilitate commerce and the postal service, and with such plans to prepare and submit estimates of the cost of executing the work.

Third—To report specifically upon the practicability, feasibility, and probable cost of the plans known as the jetty system, the levee system, and the outlet system.

Many plans for the improvement of navigation and the protection of the alluvial lands have been advocated, chief among them these:

First—Improvement of navigation between St. Louis and the Gulf by the use of jetties to make the river of uniform width and scour out the channel.

Second—Drainage and reclamation of the alluvial lands by a system of outlets which divide the great river into several lesser streams.

Third—To cut away the bars obstructing navigation by building a wall across the river at its mouth.

Fourth—Construction of an entirely new line of levees a mile or more back of present ones.

Fifth—Repairing existing levees, closing all the outlets with wing dams to turn aside the current where the curves of the river are apt to cave in the banks.

There are also three other plans proposed:

First—The cut-off plan for straightening the course of the river.

Second—The diversion of tributaries, like the Red river, diverting them from pouring into the Mississippi.

Third—The reservoir plan, the creation of basins or reservoirs at the sources of the Mississippi and its tributaries to gather the surplus water in flood time and reserve it to add to the current at low water periods.

The majority report of the commission, signed by the president and engineers Suter, Mitchell, Eads, and Harrod, states that, "in a restricted sense as auxiliary to a plan of channel improvement only, the construction and maintenance of a levee system is not demanded. But, in a larger sense, as embracing not only beneficial effects upon the channel, but as a protection against destructive floods, a levee system is essential; and such system also promotes and facilitates commerce, trade, and the postal service."

The plan of improvement recommended is based upon the fact that the bad navigation of the river is produced by the caving and erosion of its banks and the excessive widths and the bars and shoals resulting directly therefrom. The work to be done, therefore, is to scour out and maintain a channel through the shoals and bars existing in those portions of the river where the width is excessive, and to build up new banks and develop new shore lines, so as to establish as far as practicable the requisite conditions of uniform velocity for all stages of the river. It is believed by the commission that this improvement can be accomplished below Cairo by contracting the low water channel way to an approximately uniform width of about 3,000 feet for the purpose of scouring out a channel through the shoals and bars, and by causing, through the action of appropriate works constructed at suitable localities, the deposition of sand and other earthy materials transported by water upon the dry bars and other portions of the present bed not embraced within the limits of the proposed low water channel. The ultimate effect sought to be produced by such deposits is a comparative uniformity in the width of the high water channel of the river. It is believed that the works estimated for in the report will create and establish a depth of at least ten feet at extreme low stages of the river over all the bars below Cairo, where they are located. It is also the opinion of the commission that, as a general rule, the channel should be fixed and maintained in its present location, and that no attempts should be made to straighten the river or to shorten it by cut-offs.

THE medicinal rule is that an elevation of 4,000 feet above the level of the sea confers immunity from yellow fever.

FLOWERS AND THE WEATHER.

The vegetable kingdom opens up a curious field of investigation, in which the meteorologist will learn much regarding the mutual interdependence of all departments of creation. If light and electricity be, as well known, influential in exciting the movements of animals breathing the vital air, plants are equally subject to the same potent agencies, and testify to their influence so visibly as to attract the notice alike of the scientific botanist and of the illiterate rustic. In some parts of England the peasants mark the blooming of the large water lily, and think that the number of its blossoms on a stem indicates the price of wheat per bushel for the ensuing year—each blossom being equivalent to a shilling. We smile at this as superstitious folly; but even philosophers have not deigned to despise the weather indications afforded by the shutting of the flowers of certain plants.

Lord Bacon, for example, who was remarkably attentive to all the appearances and changes of natural objects, is the author of some of the observations which follow:

The Pimpernel (*Anagallis arvensis*).—"When the flower of this plant," says Bacon, "expands boldly and fully, no rain will happen for four hours or upward; if it continues in that open state, no rain will disturb the summer's day; when it half conceals its miniature flower, the day is generally showery; but if it entirely shuts up or veils the flower with its green mantle, let the traveler put on his great-coat, and the plowman, with his beasts of draught, expects rest from his labor." This little plant, from its peculiar susceptibility, has long been known as the "Poor Man's Weather Glass."

"The Siberian sow thistle (*Sonchus*).—If the flowers of this plant keep open all night, rain will certainly fall the next day."

"The African marigold (*Tagetes erecta*).—If this plant opens not its flowers in the morning about seven o'clock, you may be sure it will rain that day unless it thunders."

"The trefoil (*Hedysarum*).—The different species of trefoil always contract their leaves at the approach of a storm; hence these plants have been termed the 'Husbandman's Barometer.'"

"White thorns and dog-rose bushes.—Wet summers are generally attended with an uncommon quantity of seeds on these shrubs, whence their unusual fruitfulness is a sign of severe winter."

Besides the above there are several plants, especially those with compound yellow flowers, which nod, and during the whole day turn their flowers toward the sun. Such flowers are designated as "heliotropes," and the movement which they thus exhibit is called their "nutiation." This is particularly observable in the common sow thistle (*Sonchus arvensis*); and it is a well known fact that a great part of the plants in a serene sky expand their flowers, but before rain they shut them up, as the tulip, for instance. The flowers of chick-wintergreen (*Trientalis Americana*) droop in the night, lest rain or moisture should injure the fertilizing pollen. One species of wood sorrel (*Oxalis*) shuts up or doubles its leaves before storms and tempests, but in a serene sky expands or unfolds them, so that husbandmen can foretell tempests from it. It is also well known that the sensitive plants and other species of *Cassia* observe the same rule. The flowers of the bindweed (*Convolvulus arvensis*), the wood anemone, and the common daisy (*Bellis*), even if already open, will shut up on the approach of rain. The last named flower appears to have derived its name—day's eye—from its sensitiveness to light. Such phenomena as these are probably determined by the action of light; and the flowers of such plants being shut at ten or eleven o'clock in the morning tell of clouds and gloom, and so predict rain.

Besides affording prognostics, many plants also fold themselves up at particular hours, with such regularity as to have acquired particular names from this property. Linnæus has enumerated forty-six flowers which possess this kind of sensibility. From an arrangement of such flowers it has been ingeniously proposed to form a floral timepiece. The flowers of the goat's beard (*Tragopogon*) open in the morning at the approach of the sun, and, regardless of the weather, shut about noon, and hence its common name of "go-to-bed-at-noon." The star of Bethlehem expands its flowers about eleven, and closes them at three in the afternoon. The evening primrose (*Oenothera*) is well known from its remarkable properties of regularly shutting with a loud popping noise about sunrise and opening at sunset. After six o'clock, these flowers regularly report the approach of night. The flowers of the garden lettuce open at seven o'clock and shut at ten. That light is the chief agent of these changes seems to be proved by the experiments of De Candolle, made at the Jardin des Plantes, in an underground cellar, illuminated by lamps giving a light equal to fifty-four ordinary wax candles. By lighting these he could cause the flowers of the star of Bethlehem to open at pleasure, and also those of the sea camomile, which keeps its flowers closely shut during the night; but he could produce no artificial effect with the strongest light upon several species of wood sorrel, whose flowers and leaves are both folded up at night. With the sensitive plant he succeeded in so completely changing the hour of closure that on the third day from being placed in the lighted cellar it began to fold its leaves in the morning and open them in the evening. One of the most singular cases of the action of light on plants is that of the *Lotus* of the Euphrates, as described by Theophrastus, and which he represents as rearing and expanding its blossom by day, closing and sinking beneath the surface of the water by

night, so as to be beyond the grasp of the hand, and again rising up in the morning to present its expanded blossom to the sun. The same phenomenon is also related by Pliny.

"Sheep Rot."

For some time a great mortality has prevailed among sheep, and the destruction reported is something appalling. The malady is popularly known by a very old Saxon name, "rot," and is in reality due to the presence in the liver and hepatic canals of numbers of the *Distoma hepaticum*, a trematode entozoon, as well as the *Distoma lanceolatum*, also a member of the same order. These entozoa, from their resemblance to the fish called "flukes," have received the same name, and have a particular predilection for the biliary apparatus, whose function they more or less destroy, and thus lead to the slow death of the sheep or other animals they may infest. After wet seasons, animals which have been pastured on tainted land are certain to suffer, from their having ingested with the herbage the ova of the *Distoma*. Pastures are tainted by "fluke" infested sheep, which pass the mature worms or their ova with the fæces, and these lodge on or are washed into the ground. The worms, of course, die, and the ova within them are liberated; and these, together with the free ova, appear to have not only a strong vital resistance to meteorological alternations, but also the good fortune to find a ready and acceptable intermediary host in the *Limnæus minutus*, a little mud snail common everywhere, and particularly on wet land. This snail becomes possessed of a number of ova in its interior, and during damp weather it crawls from its breeding place in the ground up the stalks of grass and herbage, and is swallowed by the sheep or other herbivorous animals when they are grazing. Received at first into the stomach, the ova undergo partial development, and then find their way into the biliary canals. If their number is considerable, when they have attained their full growth they dilate and obstruct these canals, the walls of which become considerably thickened. During their development the secretion of bile becomes gradually diminished, and that fluid is viscid, like mucus, and altered in color; at the same time the parenchyma of the liver becomes atrophied from the compression the "flukes" exercise upon it, and it may even become disorganized. Hence result icterus, disturbance in nutrition, anæmia, dropsy, and a general cachectic condition.

Sheep are not the only victims which suffer from the *Distoma*, for during the present mortality hares, rabbits, deer, and horses are said to have become infested, and died. The *Distoma hepaticum* has long been known to exist in the horse and ass, when they were allowed to pasture on unclean land during wet seasons.

Salt appears to be an excellent and well known prophylactic agent, and even a curative one when the disease has not made much progress. This beneficial action of sodium chloride has been known almost from time immemorial, and the freedom from "rot" of sheep which have been pastured on salt marshes has been also recognized for centuries.

The flesh of sheep which have been affected with this verminous disease cannot be said to be positively dangerous as food, though it must be greatly reduced in nutritive properties, as well as in quality. The human being may receive and harbor the *Distoma*, a fact worthy of remembrance. The present mortality is likely to render sheep scarce and expensive in this country for some time, and still further darken the prospects of our agriculturists.—*Lancet*.

A Deep Well.

The Continental Diamond Rock Boring Company, Limited, have lately completed for the Government of Mecklenburg-Schwerin a bore hole of exceptional depth, and the execution of which is of particular interest from the rapidity with which it has been completed. The boring, which was made for salt, is situated at Probst Jesar, near Lubtheen, and it was commenced on the 6th of July of last year, with an opening 12 inches in diameter. The first part of the bore had to be through a diluvial bed consisting mainly of drift sand and coarse gravel, and for sinking through this Kobrich's system was adopted, the diameter of the bore being maintained at 12 inches. The total depth sunk on this system was 98.05 meters, or 321 feet 8 inches, the sinking occupying 34 days of 24 hours each, of which 31 days were spent in actual boring and three days in sundry works. The average progress was thus at the rate of 3.163 meters per day, while the greatest depth bored in any one day was 7.496 meters, this being on August 11, 1879.

Below the diluvium the gypsum and rock were reached, and through this the boring was carried on with diamonds, the commencement being made on August 25, 1879, with a hole 10½ inches in diameter. Until a depth of 509 meters, or 1,670 feet, had been reached, however, no firm footing could be obtained on which to rest the tubing, and hence great annoyance was experienced from the falling in of masses of sand, the infalls being so great that sometimes when the boring rod was withdrawn the bore became filled up again to a depth of over 420 feet. The boring, however, was steadily proceeded with, and ultimately the final depth of 1207.25 meters, or 3,961 feet, was attained on the 6th of February last, the diameter of the bore at the bottom being 3 inches. The time spent in boring with diamonds was 163 days of 24 working hours.

The greatest progress made in any one day was on the 27th of January last, when a depth of 29 meters (95 feet 2 inches) was bored, this being nearly double the average progress. The total length of tube inserted was 1010.55

inches, or 3,315½ feet, the greatest length inserted in one piece being 456.424 meters, or 1,497½ feet, and this consisting of 7 inch and 8 inch tubes. Throughout the whole depth of the bore cores were drawn, some of these being salt cores over 2 feet long in one piece.

With the exception of a bore hole put down to the depth of 1,275 meters, or 4,183 feet, for the Prussian Government, a few years ago, and which took four years to accomplish, the bore of which we have been giving particulars is we believe the deepest yet sunk, and the fact that it was completed in less than six months speaks well for the skill and energy with which the work was carried out.

A Plan to Utilize Genesee Falls.

The Rochester *Democrat and Chronicle* of April 3 gives the following description of the Rochester Hydraulic Motor Company's plan for utilizing the water power of Genesee Falls:

The derrick, which is a miniature model of the one to be erected at the lower falls, stands in a room with the miniature machinery and airomotor. Water passes through small pipes and tubes into a flume at the upper part of the derrick, and has precisely the same effect, only in a smaller degree, as would the force of the falling waters of the Genesee exert in a proportionately gigantic flume. In the two perfectly gated compartments of the flume there are two metal siphons. By the time the gate has permitted sufficient flow of water to submerge the top of the siphon on either side the flow is stopped, and as soon as the water reaches the siphon's top the entire quantity within the reservoir discharges itself through the pipe of the siphon into another hydraulic process below. The two flume gates and siphons act alternately, and the double action progresses like clock-work. The water through the siphon pipe goes down into an air receptacle, the fall being five feet in the model, but twenty times as great in the motor itself, as designed to be erected, and as the five foot fall constitutes the amount of hydraulic pressure contained in the model, the proportionate force of the motor may be faintly imagined while noting the work of the small affair. Passing into the two air receptacles or cylinders (which lie in the water trough representing the river bed) the water surges down and compresses the air, which has already been admitted ahead of it into the cylinders. The water forces the volume of air forward into a drum, through another automatic closing valve. From the drum the air goes into the final air reservoir, where it remains compressed for use, and from whence it may be drawn off or distributed through the pipes to any desired point, for various uses. Even with this miniature model the air generated is very powerful, and will lift a heavy man right off the floor.

The original design of the inventor was to utilize the cataract of Niagara for running the machinery of Buffalo; but the falls and the city were too widely removed for this to be practicable at an expense of less than \$2,000,000, so that Rochester was chosen as the ground for the test, and the lower falls of the Genesee as the water power. The derrick for the motor will be erected on the east side of the falls, where there is a natural cove in the rock for the works below. The frame of the derrick will be 125 feet high, rising slightly above the edge of the falls and about 25 feet from it. The dam already placed across part of the falls directs the water to a 16 foot bulkhead, and is bolted to the solid rock with 5,000 pounds of bolts. The water going through the bulkhead enters the flume and the reservoirs and siphons in the derrick. The siphons will be nearly 100 feet long, and the air receptacles or cylinders in the river bed (four in number) will each be 500 feet long and 6 feet in diameter. The company intend to erect a suspension bridge running from the west side of the falls to the derrick. The dam was built last fall when the water was low, and work upon the rest of the machinery will be commenced as soon as the weather permits. To state it briefly, the objects to which the company propose to devote this enormous and exhaustless power are these: To supply the city of Rochester and vicinity with a motor (in lieu of steam) for mechanical and manufacturing purposes—a motor capable of working every and all portions of the machinery in the city, with force enough reserved to supply compressed air and run all our street cars, unaided by any other propelling power. Also, "to supply the city with a light (in lieu of gas) cheaper, brighter, softer, and safer than the Edison horseshoe light." In this connection mention may be made of the fact that the company already produces a light which meets the description given—and where it costs a dollar a foot to generate gas, this light can be generated for a cent a foot.

In conclusion it may be added that the Motor Company has already made partial arrangements with the street railway company, so that at the works of the former at the lower falls the air cylinders to be put upon each car can be filled, in a few seconds, with enough compressed air to run them sixteen miles. The tracks of the Rochester City and Brighton Railroad Company are already laid to the site of the company's works, so that the cars can be supplied without any additional expense in this respect. The new power can be supplied at less than one-tenth the present cost of horse power, and yet allow a very liberal margin of profit to the motor shareholders.

A CHEAP black varnish for polished iron and steel, and which is said to be very good, is made with ten parts of oil of tar and one part of sulphur. This mixture, of a deep brown color, is applied with a fine hair brush, and then let to dry at a gas flame until the varnish becomes quite black.

(16) J. M. asks (1) for the proportions for making rubber waterproof solution. How much rubber, how much bisulphide of carbon, and how much absolute alcohol? A. Caoutchouc (gum rubber) 1 oz., carbon disulphide, about 1/4 pint rubber, and vice versa. 2. If you drop coal oil on a hot plate it will vaporize. Is that the same as gas; if not, what is the difference between vapor and gas? Will the vapor condense back into liquid, or how will you keep it in a state of vapor? A. A gas is distinguishable from a vapor by the fact that, as in the case of atmospheric air, it can only be condensed by great cold and pressure. The vapor of coal oil or petroleum is not such a gas. If, however, this vapor be brought into contact with intensely heated surfaces a considerable portion of it is converted into a gas as permanent as that used for illuminating purposes. It is used by some of our gas companies for enriching common coal and "water gas." Alone it burns with a very smoky flame, owing to its richness in carbon.

(17) R. D. asks: What is peroxide of manganese composed of, and where can I obtain such as is used for filling the porous cup of a Leclanche battery? A. It is a compound of the metal manganese with oxygen. It occurs native as pyrolusite. It can be obtained through any druggist. 2. How is hard rubber moulded such as is used by electricians? I can get this rubber in sheets any thickness, and I want to know if I can melt it and run it into any form I wish. A. It cannot be melted or moulded as you propose. See pp. 48 and 105, Vol. 39, SCIENTIFIC AMERICAN.

(18) H. D. C. asks for a recipe of rubber cement that will cement together the edges or overlaps of thin sheet rubber. A. The rubber cement is prepared by dissolving finely cut pure gum caoutchouc in a sufficient quantity of naphtha. The naphtha is warmed by standing the vessel containing it in another containing hot water, away from fire.

(19) H. M. asks: What dye is strong enough and cheap enough to use as a test of suspected communication between a cesspool and a well? Can you suggest any better method than the use of a dye to learn if any communication does exist between the cesspool or well? A. The coal tar dyes magenta and fluoresceine have been employed successfully for similar purposes.

(20) G. W. H. asks how to make a good cement for wood with a light color. A. Dissolve best white glue in a sufficient quantity of strong hot acetic acid.

(21) J. H. F. asks: Do you know of any method whereby gray iron castings can be coated with brass to a thickness of one-sixteenth or more of an inch? A. We know of no better way than that of brazing on a shell of the requisite thickness.

(22) W. L. asks where to find information in regard to the distillation of turpentine and resin. A. Consult Knight's New Am. Mech. Dictionary, also Johnson's and Appleton's Encyclopedias. We know of no book on the subject.

(23) E. H. K. asks: What work on assaying could you recommend to me? Or is there anything in your paper that would give satisfactory information on metallurgy? A. Consult Percy's Metallurgy and Rickett's "Assaying and Assay Schemes."

(24) D. H. C. asks for the name or names of some complete and reliable book or work on assaying gold and silver, etc., from all kinds of quartz and rock and ore. I want some complete work on the above giving full details of the latest and best methods, giving materials, etc.; used; name of book, price, address where to be had. A. See reply to E. H. K., this page. You should address booksellers who advertise in this paper for their catalogues and price lists.

(25) F. B. W. asks if Richard Trevithick, of Merthyr Tydvil, South Wales, ran an engine on rails before an engine was run on the Stockton and Darlington road, England. A. Yes, in 1803, in South Wales.

(26) A. M. R. asks: What is the composition of the gelatine transfer pad? A. See p. 235, Vol. 41, SCIENTIFIC AMERICAN.

(27) A. D. writes: I am desirous of using vulcanized India rubber for moulding purposes. Will you tell me the best method of reducing rubber to the proper consistency for that purpose, and if anything is required to harden it again? A. Vulcanized rubber cannot be reworked in the way you propose. See pp. 48 and 105, Vol. 39, SCIENTIFIC AMERICAN.

(28) C. W. V. writes: In your issue for February 28, 1880, Vol. 42, page 133, you give a receipt for gutta-percha cement. What kind of pitch do you mean; that made from coal or that made from the pine tree? A. Pine pitch. The addition of shellac will harden it.

(29) S. L. H. asks for a receipt for making a solution to be used as sizing on white paper so as to prepare it for varnishing with alcohol varnish. A. Have you tried thin aqueous solution of glue?

(30) H. T. writes: 1. A piece of floor oil-cloth has been laid and in use several months and still remains sticky to such a degree that chairs, tables, etc., placed upon it will adhere to it more or less. What is the cause, and how can it be remedied? A. Try the application of a moderately strong wash of acetate of lead in hot water. 2. By what process can the polish of black marble, such as cases of French clocks are often made of, be restored after having become dull by age or handling? A. Use fine moist rouge and chamois skin. 3. I have a piano of excellent quality in every way except that it will not remain in tune longer than about one week after tuning, owing, as I believe, to the tuning pins being too small or thin for their sockets. Can I remedy this defect by the application of any such substance as glue or resin or anything of that nature to the pins or sockets; if so, which is the best, and how should it be applied to obtain the best result? A. Get a new set of tuning pins of large diameter. 4. In our climate the felt with which the dampers and hammers of pianos are covered is generally damaged, materially within a short time by moths. Could not this felt, before application, be impregnated with some chemical that would prevent the attack of the moths and that would not

at same time produce deleterious effects upon the glue with which the felt is fastened to the hammers, or upon the strings where they are struck or touched by it? A. A little camphor sprayed on in alcoholic (absolute) solution does very well.

(31) J. R. C. asks how to remove castor oil and balsam fir from a camel's hair brush. A. Use oil of turpentine or ether.

(32) H. B. G. writes: In the *Science Record* of 1874, page 20, is a recipe for destroying hair. One of the ingredients is sulphhydrate of sodium. Now, is there another or common name for it, for I have been to every druggist in this vicinity; some say that they do not know what it is; others say that there is no such thing. A. Use ordinary chemically pure sulphide of soda (sodium sulphide), sold by dealers in laboratory supplies.

(33) W. P. writes: I have spilled a lamp full of coal oil on a Brussels carpet. How can I remove the spot or stain? A. Spread over the spot, above and beneath, warm pipe clay, and allow it to remain 24 hours; then brush it off and beat out the adhering portions with a light switch.

(34) L. F. asks: 1. What advantage is it in the gravity battery to have the copper on the bottom instead of having it suspended from a yoke? A. It is so placed because the cuprous solution is strongest at that point, and as a matter of convenience. 2. If you silverplate first with a striking solution and strong battery, why do you not finish with the same also; or what advantage is there to use a richer solution and weaker battery? A. A weak bath and strong battery, because a strong bath or long exposure in a weak one is apt to act upon the uncoated metal and render the deposit uneven; a weak current and stronger bath, because such a current produces a more regular and "freer" coating, and such a bath has less resistance and requires a smaller exposure of anodes and less attention. 3. Your receipts for striking solutions have to 1 gallon of water from 1/4 oz. of AgCy, Vol. 40, page 124, 4; and 5 oz., Vol. 42, page 59, 4; and from 1 lb. of KCy, Vol. 46, page 124, 4; to 2 1/2 lb. of KCy, Vol. 42, page 59, 4. A. As a rule, the former gives the best results, especially with the more positive metals; the latter works more rapidly and quite satisfactorily with copper and German silver, if the battery is rapid enough and the work properly trussed.

(35) S. E. T. writes: I am using water from a well at the bottom of which there is quicksand. The suction pipe is two or three feet from the bottom—yet there seems to be a sort of fine mud or sand-like deposit around and on the water gauges. I blow out about a foot of water from the boiler every other day. The water which comes out is clear and free from a deposit. I do not see why there should be an apparent deposit around and from the water gauges and still the water seem so clear. Can you help the difficulty by any explanation? Do you think there is any great amount of deposit or scale-forming material collecting on the interior of the boiler? When we are running the planer the water in the boiler seems to rise up or foam. Is there any remedy for it? A. The water should be first pumped into a setting tank and drawn from that to deliver to the boiler; two setting tanks used alternately will be necessary, except one tank be large enough for a day's work, and is filled in the evening, and the water allowed to settle through the night. We can give no opinion about the scale forming, without knowing the character of the water. The foaming may proceed from bad water, bad circulation, or scant steam room. The residue consists chiefly of a very fine, light silicious clay and lime.

(36) A. F. O. writes: In pouring the composition for my gelatin printing pad I am troubled with little bubbles, which leave troublesome depressions. How can they be avoided? A. Warm the vessel in which the composition is to be poured, and skim the surface by drawing a sharp edged piece of metal or cardboard over it immediately after pouring.

MINERALS, ETC.—Specimens have been received from the following correspondents, and examined, with the results stated:

F. L. S.—It is micaceous hematite. Its precise value here could only be ascertained by an analysis. Distance from railroad or navigable route, etc., must also be taken into consideration.—H. W. B.—It is chalcopyrite, an ore of copper—iffound in sufficient quantity, of some value.—A. L. F.—1. Clay slate containing iron pyrites. 2 and 3. Porphyry. 4. Iron pyrites in altered dolerite.

COMMUNICATIONS RECEIVED.

- On Mercury in Vulcanite Plates. By T. H. C.
On Ice boats. By T. D.
On the Power Used in Driving a Foot Lathe. By M.
On Ice Boats. By J. P. C.
Astronomical Notes. By W. R. B.
On Water Supply for Washington. By C. L. F.
On Repairing Spiral Springs. By E. N. M.

[OFFICIAL.]

INDEX OF INVENTIONS

FOR WHICH

Letters Patent of the United States were Granted in the Week Ending

April 13, 1880.

AND EACH BEARING THAT DATE. [Those marked (r) are reissued patents.]

A printed copy of the specification and drawing of any patent in the annexed list, also of any patent issued since 1866, will be furnished from this office for one dollar. In ordering please state the number and date of the patent desired, and remit to Munn & Co., 37 Park Row, New York city. We also furnish copies of patents granted prior to 1866; but at increased cost, as the specifications not being printed, must be copied by hand.

- Adjustable chair, M. F. Bell..... 226,475
Anode frame, A. Van Winkle..... 226,576

- Arm rest for writers, H. H. McElroy..... 226,411
Artist's canvas stretcher, J. G. Fletcher..... 226,509
Auger, earth, D. P. Cudd..... 226,444
Automatic gate, J. P. Kelso..... 226,522
Axle box cover, car, A. R. Tiffany..... 226,463
Axle box, locomotive, J. J. Thomas..... 226,571
Axle, vehicle, W. C. Partlow..... 226,454
Bale tie, J. R. Cavett..... 226,388
Baling bran, etc., machine for, H. Kennedy..... 226,523
Barrel bodies, heating apparatus for, Wood & Wilkison..... 226,435
Barrel swing, P. W. Nelson..... 226,538
Belt fastener, W. L. Potter..... 226,546
Billiard table, J. Walsh..... 226,430
Boot and shoe, D. A. McDonald..... 226,532
Boot and shoe shank, Buren & Fenton..... 226,486
Boot and shoe, spring soled, T. Nuthmann..... 226,541
Boots, last or form for shaping rubber, I. W. Tufts..... 226,574
Box, D. Dunscomb..... 226,502
Brazelet, rubber, D. Stone..... 226,564
Brake lever, A. C. Fish..... 226,508
Brush, F. Sprower (r)..... 9,160
Brush holder, E. B. Randolph..... 226,551
Brush, muclage, J. B. Davids..... 226,500
Buckwheat hulling machine, T. Nelson (r)..... 9,161
Butter package, S. M. Kohr..... 226,524
Butter, preservation of, T. F. Wilkins..... 226,467
Button setting instrument, G. W. Prentice..... 226,549
Candlestick, W. Selkirk..... 226,556
Car coupling, R. F. Fairlie (r)..... 9,147
Car coupling, D. Frank..... 226,396
Car wheel, J. F. Kelly..... 226,453
Carbureter, M. S. Wright..... 226,581
Carpet sweeper, Gates & Potter..... 226,512
Carriage top, D. Conboy..... 226,389
Cheese cutter, W. R. Green..... 226,513
Chimney caps, etc., ventilator for, B. W. Felton..... 226,507
Cigars, putting up, J. Felbel..... 226,392
Clasp, C. C. Shelby..... 226,559
Clock, electric, J. Happersberger..... 226,401
Cloth, etc., machine for cutting, H. Stein..... 226,427
Clothes line adjuster, F. Bonaventure..... 226,384
Coffee pot, C. B. Veronee..... 226,465
Coin holding and delivering apparatus, A. S. Tyler..... 226,575
Coin holding and delivering device, J. O. Hands..... 226,514
Composition of matter, J. L. Pope..... 226,547
Compound engine, K. W. Jurisch et al..... 226,405
Compound engine, L. Perkins..... 226,416
Cornice, window, B. W. Kerfoot..... 226,406
Cracker machine, C. L. Vale (r)..... 9,151
Cradle and carriage, combined, H. S. Pruyne..... 226,458
Cultivator fender, L. Davis, Jr..... 226,501
Cultivator tooth, E. R. McCall..... 226,531
Cutter head, G. W. Amesbury..... 226,381
Dashes, device for making, Peters & Standish..... 226,417
Draught bar, vehicle, H. Livingston..... 226,407
Dredging apparatus, W. H. Seward..... 226,557
Drilling machine, temple roller, N. Chapman..... 226,491
Electric machine, dynamo, J. E. Braunsdorf..... 226,483
Elevator safety attachment, Bissell & Littlefield..... 226,478
Engines, automatic apparatus for stopping, Ripp & Mueller..... 226,553
Evaporator, A. L. & A. S. Folger..... 226,395
Exercising machine, J. Arnett..... 226,488
Fan, M. Rubin (r)..... 9,159
Fence and fence post, wire, Boyer & Kinsey..... 226,385
Fence, portable, M. Higbee..... 226,408
Fibers from textile plants, extracting, P. A. A. M. A. Favier..... 226,506
Filing and binding papers, device for, I. W. Hey-singer..... 226,402
Firearm, breech-loading, G. H. Fay..... 226,505
Firearm, magazine, N. King (r)..... 9,157
Firearm trigger, G. Schalck..... 226,555
Fire escape, H. Fuller..... 226,449
Fire kindlers, machine for making, A. F. Temple..... 226,569
Fish, preparing and preserving, D. W. Davis..... 226,390
Floors, walls, etc., covering for, G. P. Chiles..... 226,440
Flour bin and sifter, combined, J. M. Clark..... 226,441
Fluid motors, valve gear for, W. F. Class..... 226,494
Foul air trap for wash basins, J. L. Hutchinson..... 226,519
Fountain, J. Storer..... 226,428
Fulling mill, R. Eickemeyer (r)..... 9,146
Gas, generator for producing carbureted water, J. D. Averell..... 226,472
Gas governor, L. P. Blair..... 226,479
Gas, process and apparatus for manufacturing, M. S. Frost..... 226,397
Gem setting, V. Draper (r)..... 9,154
Glucose, manufacturing, C. Furbish..... 226,398
Glucose, manufacturing, J. F. Wolff..... 226,434
Grain, etc., apparatus for cleaning, J. Arbuckle..... 226,471
Grain drill fertilizing attachment, W. H. Young..... 226,469
Grain meter, G. A. Fry..... 226,511
Gum, chewing, T. Adams (r)..... 9,152
Harness, breast, C. M. Foulke..... 226,510
Harrow, F. P. Fuller..... 226,448
Harrow, D. L. Garver (r)..... 9,148
Harrow, G. Newton..... 226,414
Harrow, farm, A. O. Stiveson..... 226,563
Harvester brake, Jones & Pharis..... 226,451
Hat flanging machine, F. Law, Sr..... 226,525
Hat pounding machine, C. J. Sargent..... 226,554
Hat pressing machine, W. Foster..... 226,393
Hay unloader, F. Patrick..... 226,457
Hides and skins, softening, plumping, and depilating, J. Foley..... 226,447
Hoe, hand, R. L. Turner..... 226,573
Hoisting apparatus, C. E. Albro (r)..... 9,153
Horse detacher, C. B. Sibert..... 226,560
Horses, apparatus for cleaning, M. J. Sunderlin..... 226,565
Horseshoe, J. M. Rouchel..... 226,422
Horseshoe calk sharpener, J. Low..... 226,408
Incubators, heat regulating device for, H. B. Tatham, Jr..... 226,568
Interlocking switch and signal apparatus, A. G. Cummings..... 226,499
Iron, manufacture of, Hamilton & Griffith..... 226,400
Ironing board, G. H. Pearel..... 226,543
Label holder, H. Baker..... 226,474
Latch, automatic gate, Webb & Duncan..... 226,577
Lath bolter, Murray & Holt..... 226,537
Lawn rake, W. C. Quigley..... 226,419
Lightning rod coupling, E. C. Bacon (r)..... 9,145
Loom temples, burr roll for, Prouty & Sprague..... 226,548
Lubricator, T. M. Wilson..... 226,433
Magnet, electro, J. H. Bunnell..... 226,485
Magneto-electrical machine, A. E. Briggs..... 226,386
Measuring stick, shoemaker's, W. H. Varnum..... 226,429
Mechanical motor, J. G. Marcy..... 226,409
Mechanic's horse, J. F. Warner..... 226,431
Milk cooler, F. W. Moseley (r)..... 9,156
Nail forging machine, D. Armsstrong..... 226,437
Packing for steam or water pipes, J. W. Cameron..... 226,387
Paeking, piston rod, R. Shearer..... 226,558
Paper and cloth, coating, A. Sackett..... 226,459
Paper bag, W. Patterson..... 226,456
Paper bag machine, S. & M. Ruthenburg..... 226,423
Paper making machines, screen plate for, Pinder & Hardy..... 226,545
Papier mache, manufacturing articles in imitation of, K. Cunningham..... 226,497

DESIGNS.

- Clock case, G. Havell..... 11,730
Coffin handles, Bailey & Brainard..... 11,723
Gimp, J. Graham..... 11,737
Handkerchief, J. Grimshaw..... 11,723 to 11,726
Newel post, J. I. Healey..... 11,736
Ornamental pin, A. Vester..... 11,735
Pen and pencil cases, barrels for, J. C. Aikin..... 11,737
Spoon or fork handle, C. T. Grosjean..... 11,728
Stocking fabric, ornamental, J. E. Hanifen..... 11,729
Umbrella handle, F. J. Kaldenberg..... 11,731 to 11,734

TRADE-MARKS.

- Beer, lager, Schmitt & Koehne..... 7,876
Cigars, cigarettes, and smoking and chewing tobacco, C. G. Emery..... 7,870
Galloons, doubles, Prussian bindings, braids, shoe laces, etc., R. Thorp & Sons..... 7,877
Guanos, superphosphates, and fertilizing compositions, R. W. L. Rasin & Co..... 7,872, 7,873
Hats, felt, Crofut & Knapp..... 7,875
Scarfs for men's wears, made up, Fisk, Clark & Flagg..... 7,871
Soaps, S. W. Bell & Co..... 7,874

English Patents Issued to Americans.

From April 9 to April 13, 1880, inclusive.


- Boot nailing machinery, A. Knowlton, Boston, Mass.
Churn, W. Earle, Philadelphia, Pa.
Cocoon oil, refining of, A. P. Ashbourne, Boston, Mass.
Grinding mills for wood pulp, G. King, Oswego, N. Y.
Hat brushes, J. Peters et al., Philadelphia, Pa.
Heat, utilizing from furnaces, A. H. Hearington, Rochester, N. Y.
Organs and apparatus for playing, G. H. Chinnock et al., Brooklyn, N. Y.
Printing press, J. L. Firm et al., —, N. J.
Saw sharpening machinery, G. W. Dudley et al., Waynesborough, Va.
Screws threads, machinery for cutting, F. Armstrong, Bridgeport, Conn.
Telegraphic cables, manufacture of, M. M. Manly et al., Philadelphia, Pa.

Advertisements.

Inside Page, each insertion --- 75 cents a line. Back Page, each insertion --- \$1.00 a line. (About eight words to a line.) Engravings may head advertisements at the same rate per line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue. The publishers of this paper guarantee to advertisers a circulation of not less than 50,000 copies every weekly issue.

"BIG STORY—BUT TRUE."

NEWTONVILLE, MASS., April 2, 1880. Messrs. BAUDER & CO.: License and Sample (Bastlake Clothes Stick) received. Have sold 1,200 already—not all delivered yet. Biggest thing out. Sells like hot cakes. You can make any use of this you please. Big story—but true. Yours, etc., KARL THAXTER, County License and Sample sent, prepaid, for One Dollar. Circular Free. Address BAUDER & CO., Birmingham, Ohio.



CLUTE BROTHERS & CO., Schenectady, N. Y., High Speed Yacht Wheels, Yacht and Tug Engines a specialty. \$777 A YEAR and expenses to agents. Outfit Free. Address P. O. VICKERY, Augusta, Maine.

FOR SALE.

Mining Property in Georgia. One of Gold, \$15 per ton; Galena, 20 Silver, 10 Copper; Pyrolusite, 70; Black Wadd, 36; Asbestos; Kaolin; Mica and Soapstone. A. H. McLAWS, Georgia Land and Mining Agency, Augusta, Ga.

DRAWING INSTRUMENTS, SURVEYING INSTRUMENTS, ANEROID BAROMETERS, MICROSCOPES, TELESCOPES, FIELD GLASSES, MAGIC LANTERNS.

JAS. W. QUEEN & CO.,

924 Chestnut St., Philadelphia, Penn.

Catalogues sent on application. Part 1. Mathematical Instruments, 162 pages. Part 2. Optical Instruments, 188 pages. Part 3. Magic Lanterns, 150 pages. Part 4. Philosophical Apparatus, 183 pages.

PRIZE MEDAL, PARIS, 1878.



MAKE and SAVE MONEY

BY USING THE CELEBRATED MODEL PRINTING PRESS

Any smart boy can readily manage it and do hundreds of dollars worth of work every year. I will give BUSINESS MEN all their printing bills. Presses for Business Printing \$6 to \$22. Card Presses as low as \$3. Rotary foot and steam power presses \$100 to \$160. 7,000 now in use. Send 10 cents for handsome illustrated 124-page Instruction and Specimen Book, entitled

HOW TO PRINT

and copy of MODEL PRINTERS GUIDE, with all the particulars. J. W. DAUGHADAY & Co., Inventors and Manufacturers, 723 Chestnut Street, Philadelphia. "The Model Press surpasses anything we ever expected. It has about paid for itself in two weeks.—BENSON & MCGILL, Hartwell, Ga." "I would not take \$100 and be without the Model Press. It has netted me in less than three months over \$200.—J. H. STARR, Hartford, Conn." "No investment will pay as well as a Model Press. In my own business I have saved about \$300 a year by it.—B. J. BICKNELL, Memphis, Tenn."

GREAT LABOR SAVING TOOL.

Chase's Pipe Cutting and Threading Machine, for Steam, Gas, Fitters, and Machinists, for cutting and threading Pipes, Tubes, Round Iron, Bolts, and nuts, 1/4 to 2 inches. No pipe splitting. No bevel inside or outside. A boy with this machine can do more work than two men with old system. No other has automatic cut-off or makes nipples. Send for circular. Chase Machine Co., 120 Front St., N. Y.

A Patent for a Belt Stretcher For Sale. Address A. T. GREEN, 529 Washington Ave., S. Minneapolis, Minn.

WANTED.


In a large factory, a thoroughly competent mechanic to study present methods of handling and manufacturing, and devise means to economize in labor, etc., with ability to improve on machinery now in use, and invent new where such can be employed to advantage. Address, with references, giving full particulars of experience, etc., X. B., Box 773, New York City.

THE HOLLY SYSTEM OF STEAM HEATING CO. LIMITED, LOCKPORT N.Y. FOR CITIES AND VILLAGES HOLLY STEAM COMBINATION CO. LIMITED, LOCKPORT N.Y. SEE ILLUSTRATED AD. IN LAST NUMBER.

PROGRESS OF INDUSTRIAL CHEMISTRY.—By J. W. Mallet. The latest and most approved processes, and the latest experimental results in the manufacture of the following important commercial products: Niter, Potassium Chloride, Potassium Sulphate, Potassium Chlorate, Pyro-Chromate, Potassium Ferro-cyanide, Potassium Cyanide, Sodium Chloride, Sodium Nitrate, Sodium Sulphate, Borax, Ammonium Chloride, Calcium Chloride, Calcium Chlorate, and Magnesium Sulphate. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 214. Price 10 cents. To be had at this office and from all newsdealers.

FREE Illustrated CATALOGUE of 1-Ct. Chromos, Watches, Revolvers and Novelties—CHEAPEST & largest assortment in the U. S.—E. F. NASON, 111 Nassau St., N. Y.

PEERLESS



Damper Regulator. Superior in every respect to all other regulators. The great self-fuel-saving appliance ever invented. Insures safety from explosion. In ordering mention steam pressure. Illustration sent on application. We set it up and guarantee performance. Price, \$75.00. AMERICAN STEAM APPLIANCE CO., 18 & 15 Park Row, SOLE MANUFACTURERS, NEW YORK.

RUBBER BACK SQUARE PACKING.

BEST IN THE WORLD.


For Packing the Piston Rods and Valve Stems of Steam Engines and Pumps. B represents that part of the packing which, when in use, is in contact with the Piston Rod. A the elastic back, which keeps the part B against the rod with sufficient pressure to be steam-tight, and yet creates but little friction. This Packing is made in lengths of about 20 feet, and of all sizes from 1/4 to 2 inches square.

JOHN H. CHEEVER, Treas. NEW YORK BELTING & PACKING CO., 37 & 38 Park Row, New York.

PENNSYLVANIA LAWN MOWER.


Surpassing all others, and pronounced the best.

1880



ADVANTAGES. Lightness combined with strength. Requires less repairs. Cuts grass more smoothly. Less liable to obstruction. Will cut longer grass. Easily adjusted. Is more durable. No springs. Almost noiseless. Every Mower warranted.

LLOYD, SUPPLEE & WALTON, PHILADELPHIA.



IMPLEMENTS, MACHINERY, ETC. Catalogues, prices, and Agency terms solicited. Unexceptional references. OSKAR NETZLER, Agent in Brisbane, Queensland, Australia.

PHOSPHOR-BRONZE,

ACKNOWLEDGED TO BE THE BEST METAL for BEARINGS, COG WHEELS, HYDRAULIC SLIDES, CYLINDERS, VALVES, Pump Rods, Phosphor-Bronze BOLTS, ETC.

Pamphlets and particulars on application to The Phosphor-Bronze Smelting Co., Limited, 2038 Washington Ave., Phila., Pa. Sole Manufacturers of Phosphor-Bronze in the U.S.

ROCK BREAKERS & ORE CRUSHERS.

(THE "BLAKE" STYLE.) This machine has for twenty years stood the TEST, and found to be the best one made for breaking all kinds of hard and brittle substances, such as ORES, QUARTZ, EMERY, etc., etc. Mr. S. L. Marsden, for the past twenty years connected with the manufacture of this machine, superintends its manufacture. PARREL FOUNDRY AND MACHINE CO., Manufrs., Ansonia, Conn.

No Sawdust! No Planing!

Thin lumber, 1-16 to 1/4 inch thick, cut and seasoned by our recently patented machines, equal if not superior to the sawed and planed wood, being smooth, flat, and in all cases perfectly seasoned. Used by the largest manufacturers in the country, and giving entire satisfaction. In addition to our specialty, our usual complete stock of sawed Hardwood, Lumber, and Veneers, figured and plain, Burls, etc.

GEO. W. READ & CO., 186 to 200 Lewis Street, New York.

Bookwalter Engine. Compact, Substantial, Economical, and easily managed; guaranteed to work well and give full power claimed. Engine and Boiler complete, including Governor, Pump, etc., at the low price of \$240 00. HORSE POWER..... \$240 00 4 1/2 " " " " " 280 00 6 1/2 " " " " " 370 00 Put on cars at Springfield, O. JAMES LEFFEL & CO., Springfield, Ohio, or 110 Liberty St., New York.

AGENTS Catalogue free. \$7 per day made easy. J. F. GAGE & CO., Boston, Mass.

Wanted in every Family.

Splendid combination. Step ladder, height, 5 feet; clothes bars, 20 feet; best ironing or skirt board, all neatly combined in one compact, durable article. Can be carried in one hand. Weighs only 18 lb. Customers say, "Well pleased." Send for sample. Price \$2. Agents' terms a bonanza. Rights for sale. Address J. H. MARTIN, Hartford, N. Y. See illustration in SCIENTIFIC AMERICAN, March 20, 1880.

"RELIABLE" Engines a complete success. Prices still 40 per cent. below those of other makers. Unequaled for efficiency, simplicity, and durability. Prices from \$250 for 10 H. P., to \$400 for 30 H. P. All complete, with Governor, Pump, and Heater. Address, for circular, HEALD, SISCO & CO., Baldwinsville, N. Y.

PERFECT NEWSPAPER FILE

The Koch Patent File, for preserving newspapers, magazines, and pamphlets, has been recently improved and price reduced. Subscribers to the SCIENTIFIC AMERICAN and SCIENTIFIC AMERICAN SUPPLEMENT can be supplied for the low price of \$1.50 by mail, or \$1.25 at the office of this paper. Heavy board sides; inscription "SCIENTIFIC AMERICAN" in gilt. Necessary for every one who wishes to preserve the paper. Address MUNN & CO., Publishers SCIENTIFIC AMERICAN

Pulley Blocks. Iron Sheaves. Phosphor Bronze Self-Lubricating Bushings. PENFIELD BLOCK WORKS, Lock Box 99, Lockport, N. Y.

THE EAR.—BY CHAS. H. BURNETT, M.D. A valuable paper, giving a report of four cases, among many others, in which is shown the beneficial effect derived from the prolonged and uninterrupted wearing of cotton pellets as artificial drum-heads, and which the author claims are the only useful kind of artificial drum-heads that have ever yet been devised. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 217. Price 10 cents. To be had at this office and from all newsdealers.

Patent Steam Friction Crane

Will coal locomotive in three minutes. Two machines will load or unload 1,000 tons per day of coal or ore. The best and cheapest. NOBLE & HALL, ERIE, PA.

JOHN R. WHITLEY & CO. European Representatives of American Houses, with First-class Agents in the principal industrial and agricultural centers and cities in Europe. London, 7 Poultry, E. C. Paris 8 Place Vendôme. Terms on application. J. R. W. & Co. purchase Paris goods on commission at shippers' discounts.

To Electro-Platers.

BATTERIES, CHEMICALS, AND MATERIALS, in sets or single, with Book of Instruction for Gold, Silver, or Nickel Plating. PHOENIX ELECTRO MANUFACTURING ELECTRIC CO., 19 Bloomfield Street, Boston, Mass. Illustrated Catalogue sent free.



ELEVATORS. HAND POWER AND HYDRAULIC FREIGHT & PASSENGER. SHAFTING PULLEYS & HANGERS. L. S. GRAVES & SON ROCHESTER N.Y.


THE DINGEE & CONARD CO'S BEAUTIFUL EVER-BLOOMING ROSES

THE BEST IN THE WORLD. Our Great Specialty is growing and distributing these Beautiful Roses. We deliver Strong Pot Plants, suitable for immediate bloom, safely by mail at all post-offices. 5 Splendid Varieties, your choice, all labeled, for \$1; 12 for \$2; 19 for \$3; 26 for \$4; 33 for \$5; 40 for \$6; 47 for \$7; 54 for \$8; 61 for \$9; 68 for \$10; 75 for \$11; 82 for \$12. Send for our New Guide to Rose Culture—60 pages, elegantly illustrated—and choose from over Five Hundred Finest Sorts. Address THE DINGEE & CONARD CO., Rose Growers, West Grove, Chester Co., Pa.

TRIUMPH MIDDINGS MILL. Under Runner, Iron Frame. Mills changed from old to new process. WILCOX, SHINKLE & MILLER, Mill Furnishers, PITTSBURGH, PA. Established in 1848.


Gear Molding without Patterns. Scott's Gear Moulding Machines, AIR COMPRESSORS & ROCK DRILLS. DELAMATER IRON WORKS, Boiler Makers, Engine Builders, and Founders, FOOT OF W. 13th ST., North River, NEW YORK. ESTABLISHED 1841. POWER CIDER PRESS WITH DOUBLE PLATFORM. Send for circular. Boomer & Boschert Press Co., SYRACUSE, N. Y.

THE FRICTION CLUTCH CAPTAIN



can be applied to all classes of machinery that is driven by fly-wheels and are liable to be broken by power stored up in wheel, such as calender rolls, upsetting machines, presses, and wire drawing machines. It can be used to save gearing and all machinery from breaking by using our clutches. Starts gradual, stops quick. Any amount of power controlled. Friction Hoisting Engines and Hoisting Drums, for line shaft and safety elevators. Can be run faster and stop quicker than any other friction. D. FRISBIE & CO., New Haven, Ct.

ICE-HOUSE AND COLD ROOM.—BY R. G. Hatfield. With directions for construction. Four engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, 59. Price 10 cents. To be had at this office and of all newsdealers.



AIR COMPRESSORS.

THE NORWALK IRON WORKS CO., SOUTH NORWALK, CONN. TIGHT & SLACK BARREL MACHINERY A SPECIALTY JOHN GREENWOOD & CO. ROCHESTER N.Y.


THE CONSTRUCTION OF CANVAS Canoes.—By W. F. Stephens. Complete descriptions and working drawings of two handsome and durable boats, designed for the benefit of those who do not care to go to the expense of a wooden canoe, and who prefer to build and equip their own craft. The larger boat in model is similar to the famous Baltic Rob Rob, but is an improvement upon that. Dimensions: length, 14 ft.; beam, 26 in.; depth at bow, 12 1/2 in.; stern, 12 in.; amidship, 9 in.; draught, loaded, 5 in. The smaller boat is well suited for a boy, and will do for hunting, fishing, and cruising. It is very portable. Length, 12 1/2 ft.; beam, 26 in.; depth, 12 1/2 in., and 8 1/2 inches. By means of the detailed directions and drawings here given, any one with slight mechanical ingenuity, can construct for himself a boat which, with proper care, in use, will prove very durable, containing SCIENTIFIC AMERICAN SUPPLEMENT, No. 216. To be had at this office and from all newsdealers.

THE FORSTER-FIRM GOLD AND SILVER AMALGAMATING COMPANY of Norristown, Pa., will grant state rights or licenses on easy terms. This system works up to assay, and recovers the mercury rapidly. Apply as above.

MACHINERY FOR SALE. Three large lathes; also, one large planer. For particulars, address THE HARTFORD FOUNDRY AND MACHINE CO., J. S. HUNTER, Pres't., Hartford, Conn.

SALESMEN WANTED \$125 A Month and Expenses Selling to Dealers. SAMPLES FREE. Send 2c. STAMP to CIGARS. B. FOSTER & CO., Cincinnati, O.

BIG PAY to sell our Rubber Printing Stamps. Samples free. Taylor Bros. & Co., Cleveland, O.



MAGNETIC REACTIONS.—BY THEO. du Moncel. An interesting and instructive paper, by one of the most eminent of French electricians, demonstrating that the effects of magnetism, like those of electricity, are of two different natures, according as magnets act as currents or as charges in the static state. Static action and dynamic action defined. How static magnetism is distributed in a simple magnetic system shown by magnetic phantoms. The effects which result from reactions exchanged between a magnet and its armature. Apparatus for showing this. Magnetism, from a static point of view, shown to behave like electricity in a condenser. Magnetic condensation. Remanent Magnetism, and how it differs from Condensed Magnetism. Illustrated with 11 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 217. Price 10 cents. To be had at this office and from all newsdealers.

CORRUGATED AND CRIMPED IRON ROOFING AND SIDING, Iron Buildings, Roofs, Shutters, Doors, Cornices, Skylights, Etc. MOSELEY IRON BRIDGE AND ROOF CO., 5 Dey Street, New York.

AN EASILY MADE SMALL, STRONG, AND CHEAP BOILER, for little Steamboats. By H. K. Stroud. With an engraving. This excellent little boiler is made of wrought iron mercury flasks, which may be readily obtained, ready for use. Seven flasks are screwed together with ordinary gas fittings. This boiler has been used for a year past, with much success, in the steam Sharpie yacht Mannelita, Length of boat, 16 ft. 6 in.; beam, 4 ft. 6 in.; propeller, 16 inches diameter. For further description of boiler, boat, and engine, with method of securing the propeller shaft in stern post, see SCIENTIFIC AMERICAN SUPPLEMENT, No. 182. Price 10 cents. To be had at this office and of all newsdealers.

CARNEGIE BROS & CO UNION IRON MILLS PITTSBURGH PA. WROUGHT IRON BEAMS CHANNELS TEES & ANGLES

The attention of Architects, Engineers, and Builders is called to the great decline in prices of wrought STRUCTURAL IRON. It is believed that, were owners fully aware of the small difference in cost which now exists between iron and wood, the former, in many cases, would be adopted, thereby saving insurance and avoiding all risk of interruption to business in consequence of fire. Book of detailed information furnished to Architects, Engineers, and Builders, on application.

A New and Enlarged Edition.

Overman's Moulder and Founder.

JUST READY.

The Moulder's and Founder's Pocket Guide: A treatise on moulding and founding in green sand, dry sand, loam, and cement; the moulding of machine frames, mill-gear, hollow-ware, ornaments, trinkets, bells, and statues, description of moulds for iron, bronze, brass, and other metals; plaster of Paris, sulphur, wax, etc.; the construction of melting furnaces, the melting and founding of metals; the composition of alloys and their nature, etc. By Fred. Overman, M.E. A new edition, to which is added a supplement on statuary and ornamental moulding, ordnance, malleable iron, castings, etc. By A. A. Fesquet, Chemist and Engineer. Illustrated by Forty-four Engravings. In one volume, 12mo, 342 pages price \$2.00, by mail free of postage.

PREFACE.—The remarkable success which has steadily attended the publication of THE MOULDER'S AND FOUNDER'S POCKET GUIDE, by the late Frederick Overman, has induced the publishers to engage the services of Mr. A. A. Fesquet, in adding to it a supplement which shall bring it up to the best practice of the present day; more especially in some important particulars which are wanting in the original treatise. That gentleman has, therefore, after much conscientious and intelligent labor, and with special facilities which were extended to him, in the most courteous and liberal manner, by the heads of some of the first foundries in this city, produced the matter here presented, which appears under his name. A full Index is now also for the first time added. We believe that in its present form it must prove even more useful and popular in the future than it has done in the past; great as that popularity has been.

CONTENTS.—CHAPTER I. MOULDING.—Materials for Moulding; Tools; Moulding in Green Sand; Moulding in Open Sand; Mixed Sand Moulding; Dry Sand Moulding; Loam Moulding; Removing of the Core; Moulding without thickness; Irregular Forms; Moulding of Bronze Ornaments; Moulding partly of Loam and Sand, and partly of Metal; Impressions and Castings. CHAPTER II. MELTING OF METALS.—Iron; Qualities of Iron; No. 1 Iron; No. 2 Iron, No. 3 Iron; Characteristics of Foundry Pig; Mixing of Iron; Kind of Castings; Kind of Moulds; Melting of Cast-Iron; In the Blast Furnace; Melting Iron in Crucibles; Melting in Reverberatories; The Cupola, Description of; Operation in a Cupola; Pigs; Blast-machines; Fans; Hot Blast; Drying Stoves. General Remarks. Cleansing of Castings; Time of Casting; Cost of Moulding and Casting; Melting of Bronze Metal; Melting of Lead, Tin, Antimony, and Brass.


APPENDIX.—Receipts and Tables; Alloys of Iron; Alloys of Precious Metals; Alloys of Copper; Brass; Lead and its Alloys; Tin and its Alloys; Zinc and its Alloys; Bronzing, etc.; Glazing of Castings; Enamel; Tables.

SUPPLEMENT.—STATUARY, ORNAMENTAL MOULDING, ORDNANCE, ETC. BY A. A. FESQUET.—The Wax Process; Accidents; Finishing; Philadelphia Bronze Statuary; The New or French system; Practical Process; Separating the Parts of the Plaster Pattern; Tenons and Mortises; The Flasks; the Copes; the Moulding; The False Core; The Openings or Gates for the Entrance of the Metal; the Sands Used, etc.; Turning the Flasks Over; Removing the Pattern, etc.; Requirements for an Inside or Real Core; Air and Gas Passages; Finishing the True Core; To Remove the True Core; Fastening the False Cores with Wires; Interior Coating of the Mould; Dividing the Pattern; Drying the Moulds; Temperature of the Moulds; Pressure; Repairing Accidents; Melting the Metal; Mounting or Joining the Parts of the Statuary; The joints, separately. CHAPTER III. TOOLS REQUIRED; Patterns which may be Cast by this Process; Hardening the Plaster—Alum Plaster; Moulds for Castings of White Metals; Zinc Castings; Solders; Moulding in Wax; Plastic Clay for Deeply-cut Pattern; Brass and Bronze Ornamental Castings for Door Locks, Knobs, Hinges, etc.; Ornaments for Moulding; Small Articles; Difficulty of the Metal Reaching the Extremities in Small Castings; New Alloys, Aluminum-Bronze; Phosphor-Bronze; Spiegeleisen; Snap Flasks, Plate Moulding, etc.; Preparation of the Mould for Casting; Door Hinges and Swivels of Cast Iron; Uniting of Cast and Wrought Iron; Small Sand Irons; Lifting of the Core in the Flask; Moulding Iron Castings; Small Articles; Fonderie a Calibasse; Scaffolding; Ordnance; Bronze for Ordnance; Moulding; Melting and Pouring the Bronze; Shrinkage; Gen. Cebatius's Experiments upon increasing the Hardness and Elasticity of Bronze; Moulds for Bronze, Cast-Iron, and Steel Ordnance; Pig Metal used for Ordnance; Moulding Sand; Cast Steel Guns; Ordnance Cast Solid and with Core; Casting Cannon Balls; Hollow Projectiles; Hollowness in "Solid Shot" caused by Cooling; Crystallization of Metals in Cooling; Patterns should have no sharp Angles, etc.; Chilled Castings; A. Whitney & Son's Chilled Car Wheels; Stereotypes; Electrotypes; Flexible Moulds; Lottinoplast; Gutta-percha; Moulds for Electrotypes; Plasters; Gelatine for Moulds; Contraction on Shrinkage of Metals and Alloys; Table of the Shrinkages of Castings; Weights of Castings from Patterns; Miscellaneous Processes and Receipts; Malleable Iron Castings; Index.

The above or any of our books sent by mail, free of postage at the publication price. Our new and enlarged CATALOGUE OF PRACTICAL AND SCIENTIFIC BOOKS, 96 pages, 8vo.; a Catalogue of Books on DYING, CALICO PRINTING, WEAVING, COTTON and WOOLEN MANUFACTURE, 4to.; Catalogue of a choice collection of SCIENTIFIC BOOKS, 12mo.; Catalogue of SCIENTIFIC BOOKS, 4to.; List of Books on STEAM AND THE STEAM ENGINE, MECHANICS, MACHINERY, and ENGINEERING, 4to.; List of Important Books on METALLURGY, METALS, STRENGTH OF MATERIALS, CHEMICAL ANALYSIS, ASSAYING, etc.; 4to.; List of Books on MINING, MINING MACHINERY, COAL, etc.; 4to.; two Catalogues of Books and Pamphlets on SOCIAL SCIENCE, POLITICAL ECONOMY, BANKS, POPULATION, PAUPERISM, and kindred subjects; a Catalogue of recent additions to our stock of PRACTICAL SCIENTIFIC AND TECHNICAL BOOKS; as well as a List of LEADING BOOKS on METAL MINING, METALLURGY, MINERALOGY, ASSAYING, and CHEMICAL ANALYSIS, sent free to any one who will forward his address.

HENRY CAREY BAIRD & CO., Industrial Publishers, Booksellers, and Importers, 810 WALNUT STREET, PHILADELPHIA.


AHEAD OF ALL COMPETITION! 1880.



THE CHILADELPHIA LAWN MOWER. EIGHT SIZES FOR HAND USE. Weighing from 51 lbs. THREE SIZES FOR HORSE POWER. The very large increase in our sales last year prove that these machines fully sustain the awards "AS THE BEST" made to them at the great Centennial hundred day trial, in Philadelphia, in 1876, and their complete victory at the Paris Exposition in 1878. We offer for 1880, Machines from entirely new patterns and greatly improved in every respect. Examine our New Lawn Sweepers, Hand or Horse size.

GRAHAM, EMLEN & PASSMORE, Patentees and Manufacturers, 631 Market St., Philadelphia, Pa. Send for Descriptive Catalogue with prices.

THE No. 3 Eureka Band Saw



has advantages over any other manufactured. Is first-class in all respects, cheap, and durable. Also only Planers and Upright Shapers and Variety Moulding Machines, and a large variety of Wood Working Machinery. For particulars, address FRANK & CO., Buffalo, N. Y.

52 Gold, Crystal, Lace, Perfumed, and Chroma Cards, name in Gold & Jet 10c. Clinton Bros. Clintonville, Ct.

THE DRIVEN WELL.

Town and County privileges for making Driven Wells and selling Licenses under the established American Driven Well Patent, leased by the year to responsible parties, by WM. D. ANDREWS & BRO., 235 BROADWAY, NEW YORK.

THE MOSS ENGRAVING CO., (MOSS'S NEW PROCESS),

535 PEARL STREET, COR. ELM, ONE BLOCK FROM BROADWAY, JOHN C. MOSS, Supt. NEW YORK.

Mr. JOHN C. Moss, having disposed of all his interest in the PHOTO-ENGRAVING Co., 67 Park Place, has arranged with this Company to superintend its operations, which will be conducted on an extensive scale under the improved process recently invented by him, which is greatly superior to the old. The lines are much deeper, and the cost of production much less.

OUR MOTTO IS "THE BEST WORK AT LOW PRICES, ALWAYS ON TIME." Parties having engraving to do, will find it to their interest to give our NEW METHOD a trial.

THE SKINNER PORTABLE & STATIONARY ENGINES, BOILERS & GOVERNORS, FIRST CLASS & ECONOMICAL, SKINNER & WOOD, ERIE PA. SEE ILLUSTRATED ADVERTISEMENT.

TELEPHONE Works 1 mile. Circulars free. HOLCOMB & Co., Mallet Creek, Ohio.

SPARE THE CROTON AND SAVE THE COST. Driven or Tube Wells

furnished to large consumers of Croton and Ridgewood Water. WM. D. ANDREWS & BRO., 235 Broadway, N.Y., who control the patent for Green's American Driven Well.

SHEPARD'S CELEBRATED \$50 Screw Cutting Foot Lathe.

Foot and Power Lathes, Drill Presses, Scrolls, Circular and Band Saws, Saw Attachments, Chucks, Mandrels, Twist Drills, Dogs, Calipers, etc. Send for catalogue of outfits for amateurs or artisans.

H. I. SHEPARD & CO., 331, 333, 335, & 337 West Front Street, Cincinnati, Ohio.

ORGAN BEATTY PIANO

NEW ORGANS 25 Stops, 3 set Golden Tongue Reeds, 5 Oct. A, 3 Knee Swells, Walnut Case, warranted 4 years, Stool \$50. New France, \$125 to \$225. Newspaper Free. Address Daniel F. Beatty, Washington, New Jersey.

Lathes, Planers, Shapers

Drills, Bolt and Gear Cutters, Milling Machines, Special Machinery. E. GOULD & EBERHARDT, Newark, N. J.


ELEVATORS.

All kinds of Hoisting Machinery a specialty. Steam, Hydraulic, and Belt Power for Passengers and Freight. Iron Furnace lifts. Portable Hoists. STOKES & PARRISH, 30th and Chestnut St., Phila. Pa.

ACME STEAM PUMPS, FOR EVERY DUTY.

VALLEY MACHINE CO., EASTHAMPTON, MASS.

PROSPECTING MINERAL LANDS: SPECIALTY.



CYLINDRICAL SECTIONS OR CORES OBTAINED THE WHOLE DISTANCE BORED ARTESIAN WELLS BORED ROUND AND SQUARE. PROCESS, ESTIMATES GIVEN AND CONTRACTS MADE BY THE PENNSYLVANIA DIAMOND DRILL CO. BOX #23 POTTSVILLE PA. MANUFACTURERS OF DIAMOND DRILLS FOR ALL KINDS OF ROCK BORING.

Pond's Tools, Engine Lathes, Planers, Drills, &c. DAVID W. POND, Worcester, Mass.

Grain Speculation

in large or small amounts. \$25 or \$25,000. Write W. T. SOULE & CO., Commission Merchants, 180 La Salle St., CHICAGO, ILL., for Circulars.

THE NEW OTTO SILENT GAS ENGINE.

Useful for all sizes of small stationary steam engine. Built in sizes of 2, 4, and 7 H. P. by SCHLEICHER, SCHUMM & CO., 303 Chestnut Street, Phila., Pa. H. S. Manning & Co., 111 Liberty St., N. Y., Agents.

"BLAKE'S CHALLENGE" ROCK BREAKER.

Patented November 15, 1879. For Macadam Road making, Ballasting of Railroads, Crushing Ores, use of Iron Furnaces, etc. Rapidly superseding our older styles of Blake Crusher on account of its superior strength, efficiency, and simplicity. Adopted by important Railway and Mining Corporations, Cities, and Towns. First Class Medal of Superiority awarded by American Institute. BLAKE CRUSHER CO., Sole Makers, New Haven, Conn.

STEAM PUMPS.

HENRY R. WORTHINGTON, 239 Broadway, N. Y., 83 Water St., Boston, 709 Market St., St. Louis, Mo. THE WORTHINGTON PUMPING ENGINES FOR WATER WORKS—Compound, Condensing or Non-Condensing. Used in over 100 Water-Works Stations. WORTHINGTON STEAM PUMPS of all sizes and for all purposes.

Prices below those of any other steam pump in the market. WATER METERS. OIL METERS.



J. A. FAY & CO. CINCINNATI, O. U.S.A.

The George Place Machinery Agency

Machinery of Every Description, 121 Chambers and 103 Reade Streets, New York.

PATENTS

CAVEATS, COPYRIGHTS, LABEL REGISTRATION, ETC.

Messrs. Munn & Co., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine Improvements, and to act as Solicitors of Patents for Inventors. In this line of business they have had OVER THIRTY YEARS' EXPERIENCE, and now have unequalled facilities for the Preparation of Patent Drawings, Specifications, and the Prosecution of Applications for Patents in the United States, Canada, and Foreign Countries. Messrs. Munn & Co. also attend to the preparation of Caveats, Registration of Labels, Copyrights for Books, Labels, Reissues, Assignments, and Reports on Infringements of Patents. All business entrusted to them is done with special care and promptness, on very moderate terms.

We send free of charge, on application, a pamphlet containing further information about Patents and how to procure them; directions concerning Labels, Copyrights, Designs, Patents, Appeals, Reissues, Infringements, Assignments, Rejected Cases, Hints on the Sale of Patents, etc.

Foreign Patents.—We also send, free of charge, a Synopsis of Foreign Patent Laws, showing the cost and method of securing patents in all the principal countries of the world. American inventors should bear in mind that, as a general rule, any invention that is valuable to the patentee in this country is worth equally as much in England and some other foreign countries. Five patents—embracing Canadian, English, German, French, and Belgian—will secure to an inventor the exclusive monopoly to his discovery among about ONE HUNDRED AND FIFTY MILLIONS of the most intelligent people in the world. The facilities of business and steam communication are such that patents can be obtained abroad by our citizens almost as easily as at home. The expense to apply for an English patent is \$75; German, \$100; French, \$100; Belgian, \$100; Canadian, \$50.

Copies of Patents.—Persons desiring any patent issued from 1836 to November 20, 1866, can be supplied with official copies at reasonable cost, the price depending upon the extent of drawings and length of specifications.

Any patent issued since November 20, 1866, at which time the Patent Office commenced printing the drawings and specifications, may be had by remitting to this office \$1.

A copy of the claims of any patent issued since 1866 will be furnished for \$1.

When ordering copies, please to remit for the same as above, and state name of patentee, title of invention, and date of patent.

A pamphlet, containing full directions for obtaining United States patents sent free. A handsomely bound Reference Book, gilt edges, contains 140 pages and many engravings and tables important to every patentee and mechanic, and is a useful hand book of reference for everybody. Price 25 cents, mailed free.

Address MUNN & CO., Publishers SCIENTIFIC AMERICAN, 37 Park Row, New York. BRANCH OFFICE—Corner of F and 7th Streets, Washington, D. C.

ROOTS' NEW IRON BLOWER.



POSITIVE BLAST. IRON REVOLVERS, PERFECTLY BALANCED IS SIMPLER, AND HAS FEWER PARTS THAN ANY OTHER BLOWER.

P. H. & F. M. ROOTS, Manufacturers, CONNERSVILLE, IND.

S. S. TOWNSEND, Gen. Agt., 6 Cortlandt St., 8 Dey Street, NEW YORK. WM. COOKE, Selling Agt., 6 Cortlandt Street, JAS. BEGGS & CO., Selling Agts., 8 Dey Street. SEND FOR PRICED CATALOGUE.

Advertisements.

Inside Page, each insertion --- 75 cents a line. Back Page, each insertion --- \$1.00 a line.

Engravings may head advertisements at the same rate per line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

The publishers of this paper guarantee to advertisers a circulation of not less than 50,000 copies every weekly issue.

The Rue Manufacturing Co.

523 CHERRY ST., PHILADELPHIA, PA.,

having settled in full for all infringements of Patents, now sell

A New Lifting Injector with One Lever, the best in the market.

"BUCKEY" LAWN MOWER.

The lightest and easiest running MOWER ever made. STRICTLY FIRST CLASS. MAST, FOOS & CO., Springfield, Ohio.

The Klinkerfues Patent Hygrometer

or Weather Prophet, has been acknowledged by all scientific authorities as the best. Various forms of the instrument are for sale by HENRY GUTH, 245 Bowery, New York, Sole Agent for U. S. and Canada.

SECOND-HAND BLAKE CRUSHER for sale cheap. New pattern. 12x16. Address P. O. Box 231, Baltimore, Md.

A PLANING MILL OUTFIT FOR SALE very low for cash. Will sell all together or each machine separate. All first-class machines, good order. J. H. KERRICK & CO., Indianapolis, Ind.

Established 1844. JOSEPH C. TODD, Successor to TODD & RAFFERTY, PATERSON, N. J., Engineer and Machinist.

Flax, Hemp, Jute, Rope, Oakum, and Bagging Machinery. Steam Engines, Boilers, etc. Sole Agent for Mayher's New Patent Acme Steam Engine and Force Pumps combined. Also owner and exclusive manufacturer of

THE NEW Baxter Patent Portable Steam Engine.

These engines are admirably adapted to all kinds of light power for driving printing presses, pumping water, sawing wood, grinding coffee, ginning cotton, and all kinds of agricultural and mechanical purposes, and are furnished at the following low prices:

1 Horse Power, \$150 1 1/2 Horse Power, \$190 2 Horse Power, 245 2 1/2 Horse Power, 275 3 Horse Power, 290 4 Horse Power, 350

Send for descriptive circular. Address J. C. TODD, PATERSON, N. J. Or No. 10 Barclay St., New York.

PERFECT SECURITY AGAINST The Rubber-covered Carriage Step is the safest and handsomest Step made, and is fast superseding the old iron Step on fine carriages. Durability warranted. Carriage builders will be sure to please their patrons by adopting this improved Step. For sale by dealers in Carriage Goods. RUBBER STEP MFG CO., Boston, Mass.

ACCIDENTS FROM SLIPPING. ANHYDROUS LIQUID AMMONIA, FOR ICE MACHINES. Applied direct to coil. No residue. No air or moisture in apparatus. Complete volatilization. No danger. LARKIN & SCHEFFER, Manufacturing Chemists, St. Louis, Mo.

RAIL ROAD DEPOTS IRON BUILDINGS WHARF SHEDS SUGAR HOUSES SELF-FILLING COTTON STORES PUBLIC MARKETS (CATALOGUES GRATIS) RETORT HOUSES WALTER C. BERGIUS & CO - GLASGOW - SCOTLAND.

BOILER PRESSES. STILES & PARKER PRESS CO., Middletown, Ct.

H.W. JOHNS' ASBESTOS LIQUID PAINTS

are strictly pure linseed-oil paints of a higher grade than have ever before been manufactured for structural purposes.

A saving of 25 to 33 per cent. of customary outlays can be effected by the use of these paints. Samples of sixteen newest shades for dwellings sent free by mail. Be sure and get the genuine, which are manufactured only by

H. W. JOHNS M'FG CO., 87 Maiden Lane, New York.

Sole Manufacturers of Genuine Asbestos Roofing, Boiler Coverings, Steam Packing, Sheathings, Cements, Coatings, &c. Descriptive Price Lists free by mail.

MACHINE KNIVES FOR PAPERMILLS, BOOK-BINDERS, WOOD WORKING AND AGRICULTURAL MACHINERY. ALSO PARALLEL VISES FOR MACHINISTS, PIPE FITTERS, BLACKSMITHS, WHEELWRIGHTS, PATTERN MAKERS & C. MANUFACTURED BY TAYLOR STILES & CO. REIDSVILLE, WARREN CO., N. J.

Mill Stones and Corn Mills.

We make Burr Millstones, Portable Mills, Smut Machines, Packers, Mill Picks, Water Wheels, Pulleys, and Gearing specially adapted to Flour Mills. Send for catalogue. J. T. NOYE & SONS, Buffalo, N. Y.

THE MACKINNON PEN OR FLUID PENCIL.



Particulars mailed Free. MACKINNON PEN CO., 200 Broadway, near Fulton St., N. Y.

The New York Ice Machine Company, Low Pressure Binary Absorption System.

Advantages over other Machines. Makes 25 per cent. more ice. Uses only 1/4 water of condensation. No Pressure at rest. Pressure in running, 14 pounds. Self-lubricating. No Leaks, non-inflammable. No action on Metals. Easy Attendance.

COLUMBIA BICYCLE.

A practical road machine. Indorsed by the medical profession as the most healthful of outdoor sports. Send 3 cent stamp for 24 page catalogue, with price list and full information, or 10 cents for catalogue and copy of The Bicycling World.

WM. A. HARRIS, PROVIDENCE, R. I. (PARK STREET), Six minutes walk West from station. Original and Only builder of the HARRIS-CORLISS ENGINE

With Harris' Patented Improvements, from 10 to 1,000 H. P.

BOILER COVERINGS. Plastic Cement and Hair Ties, with or without the Patent "AIR SPACE" Method.

ASBESTOS MATERIALS, Made from pure Italian Asbestos, in fiber, mill board, and round packing. THE CHALMERS-SPENCE CO., 40 John Street, and Foot of E. 9th Street, New York.

GENUINE BABBITT METAL, Fine Brass and Composition Castings, E. STEBBINS M'FG CO., SPRINGFIELD, MASS.


ILLUSTRATIONS OF ALL KINDS MADE QUICKLY AND CHEAPLY.



FIRST GRAND MILLERS' Exhibition, TO BE HELD IN EXPOSITION BUILDINGS, IN CINCINNATI, FROM May 31st to June 26th inclusive.

Six Automatic Cut-off Engines to be Tested. Ten Complete Flour Mills in Operation. A Complete Vienna Bakery. Mill Machinery from all Quarters of the Globe. Reduced Railroad Rates. Ample Hotel Accommodations.

XX COT (not painted), White Duck \$2.



Makes a perfect bed. No mattress or pillows required. Better than a hammock, as it fits the body as pleasantly, and lies straight. Folded or opened instantly. Self-fastening. It is just the thing for hotels, offices, cottages, camp-meetings, sportsmen, etc. Good for the lawn, piazza, or "coolest place in the house." Splendid for invalids or children. Sent on receipt of price, or C. O. D. For 50 cts. extra, with order, I will prepay expressage to any railroad station east of Mississippi River and north of Mason, and Dixon's line. For 75 cents, in Minnesota, Missouri, and Iowa.

HERMON W. LADD, 108 Fulton St., Boston; 207 Canal St., New York; 165 North Second St., Philadelphia. Send for Circulars.

BI-SULPHIDE OF CARBON. E. R. TAYLOR, Providence, R. I.

PATENT Galvanized Iron Tackle Blocks

For all Hoisting Purposes. Light, Easy Running, Durable. Superior to all Wood Blocks. Cheaper than all other Iron Blocks. PROVIDENCE TOOL CO., Providence, R. I.

THE PICTET ARTIFICIAL ICE COMPANY, Limited, Ice Machines to make from 20 pounds per hour to 50 tons per day, at 36 Cortlandt St., New York. P. O. Box 3083.

WIRE ROPE

Address JOHN A. ROEBLING'S SONS, Manufacturers, Trenton, N. J., or 117 Liberty Street, New York. Wheels and Rope for conveying power long distances. Send for circular.

THE TANITE CO., STROUDSBURG, PA. EMERY WHEELS AND GRINDERS. LONDON-9 St. Andrews St., Holborn Viaduct, E. C. LIVERPOOL-42 The Temple, Dale St.

ROCK DRILLING MACHINES AND AIR COMPRESSORS. MANUFACTURED BY BURLICH ROCK DRILL CO. FITCHBURG, MASS. SEND FOR PAMPHLET.

Pyrometers. For showing heat of Boiler Flues, Superheated Steam, Oil Stills, etc. HENRY W. BULKLEY, Sole Manufacturer, 149 Broadway, N. Y.

PORTLAND CEMENT, From the best London Manufacturers. K. B. & S. AND BURHAM CEMENTS. For sale by JAMES BRAND, 85 Beekman St., New York.

ROOFING. For steep or flat roofs. Applied by ordinary workmen at one-third the cost of tin. Circulars and samples free. Agents Wanted. T. NEW, 32 John Street, New York.

Working Models And Experimental Machinery, Metal or Wood, made to order by J. F. WERNER, 62 Centre St., N. Y.

THE ACME CUBE PIPE TONGS. VARIOUS SIZES FROM 3/4" TO 4" INCH. MOST EFFICIENT MADE. NOBLE HALL, 135 N. 4TH ST., PHILA. PA.

The Asbestos Packing Co., Miners and Manufacturers of Asbestos, BOSTON, MASS., OFFER FOR SALE: PATENTED ASBESTOS ROPE PACKING,

- LOOSE "
JOURNAL "
WICK "
MILL BOARD,
SHEATHING PAPER,
FLOORING FELT,
CLOTH.

BROWN'S PAT. SPLIT PULLEYS Shafts, Hangers, PULLEYS

At low prices. Largest assortment. A. & F. BROWN, 37, 59, & 61 Lewis St., New York.

PROSPECTUS

OF THE Scientific American FOR 1880.

The Most Popular Scientific Paper in the World. VOLUME XLII. NEW SERIES. Only \$3.20 a Year, including postage. Weekly. 52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information, and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelties in Mechanics, Manufactures, Chemistry, Electricity, Telegraphy, Photography, Architecture, Agriculture, Horticulture, Natural History, etc.

All Classes of Readers find in THE SCIENTIFIC AMERICAN a popular resume of the best scientific information of the day; and it is the aim of the publishers to present it in an attractive form, avoiding as much as possible abstruse terms. To every intelligent mind, this journal affords a constant supply of instructive reading. It is promotive of knowledge and progress in every community where it circulates.

Terms of Subscription.—One copy of THE SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States or Canada, on receipt of three dollars and twenty cents by the publishers; six months, \$1.60; three months, \$1.00.

Clubs.—One extra copy of THE SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.20 each; additional copies at same proportionate rate. Postage prepaid.

One copy of THE SCIENTIFIC AMERICAN and one copy of THE SCIENTIFIC AMERICAN SUPPLEMENT will be sent for one year, postage prepaid, to any subscriber in the United States or Canada, on receipt of seven dollars by the publishers.

The safest way to remit is by Postal Order, Draft, or Express. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to

MUNN & CO., 37 Park Row, New York.

To Foreign Subscribers.—Under the facilities of the Postal Union, the SCIENTIFIC AMERICAN is now sent by post direct from New York, with regularity, to subscribers in Great Britain, India, Australia, and all other British colonies; to France, Austria, Belgium, Germany, Russia, and all other European States; Japan, Brazil, Mexico, and all States of Central and South America. Terms, when sent to foreign countries, Canada excepted, \$4, gold, for SCIENTIFIC AMERICAN, 1 year; \$9, gold, for both SCIENTIFIC AMERICAN and SUPPLEMENT for 1 year. This includes postage, which we pay. Remit by postal order or draft to order of Munn & Co., 37 Park Row, New York.

THE "Scientific American" is printed with CHAS. F. NEU JOHNSON & CO.'S INK. Tenth and Lombard Sts., Philadelphia, and 50 Gold St., New York.