ENGINEERING INVENTIONS

by Messrs. Henry Dods and Frank Hindes, of Virginia City, Nev. It has a compensating spring device to relieve the shocks of gripping the cable, and prevent the slipping of the grip on the cable; also a specially devised frame, bed plate, and slide, enabling the clutch to be so worked as not to injure the cable.

A car coupling has been patented by Mr. Timothy C. O'Donovan, of Walker's Mills, Pa. It consists in a combination with a drawhead having a flattened cross rod of a coupling link with a transverse groove, and an enlargement for receiving the cross rod of the drawhead, which link can be swung so that its hook can catch on the cross rod of the opposite drawhead, whereby the cars will be coupled.

A mine railroad has been patented by Mr. John G. Thompson, of Cuba, Ill. In an inclined or sloping road for working cars in opposite directions at the same time by a rope doubled around a drum at the upper end of the road, the road being single track with a turnout, the rope is so arranged within the single track, and branching into and along the turnouts. that the switches work automatically, and the cars cross the rope whout obstruction or delay.

An improved gauge cock has been patented by Mr. Micbael J. Fitzgerald, of Fort Wingate, N. M. In combination with the stock and main and transof its passages are so made as to be entirely shnt off from the passages of the stock in its closed position; the weightedlevercan always be relied upon for keeping the cock closed except when purposely opened to test the water in the boiler.

MECHANICAL INVENTIONS.

'An insertible saw tooth of improved form has been patented by Mr. William B. Risdon, of Trenton, N. J. The tooth is made with a toe, a perforation, and a slit at its heel to adapt it to be secured in a saw plate with a shoulder and a recess at the rear end by a rivet wholly within the tooth, thus putting no strain upon the plate, and in no way affecting its truenes

A bolt header has been patented by Mr. Benjamin McKillen, of Verona Mills, Mich. It is a tool with handled and pivoted die jaws, having rabbet grooves in the lower side to be secured between and on the jaws of a vise. The tool affords great facility for making well defined angles to square shanks, and may also serve as a holder for rods of different kinds of work for setting and truing the parts.

An improved mechanical movement has been patented by Mr. Francis W. Goodyear, of Spring field, Mass. It is intended to make reciprocating motion more readily convertible into rotary, and is applied in a simple manner to various hand and foot power machines. There is a ratchet action in which no springs are used, and the whole movement is practically noise-

An improved piano pedal stool has been patented by Mr. William Winter, of Albany, N. Y. The invention consists in a stool provided with foot levers connected by connecting rods and elbow levers pivoted on a bar of the stool and adapted to operate the pedal levers of a piano or like instrument. The stool is provided with devices foreasy and rapid attachment to the instrument or pedal lyre. The angle levers are provided with pads to protect the pedal levers from be

An apparatus for dyeing with hydrocar bons has been patented by Mr. Engen Rau, of Hartford, Conn. It is a dry dyeing machine with an appacolor dissolved in benzine and oil; it has a wringer for taking out snrplus color, and a drying chamber, from whence the fabric is conveyed between endless blankets through a highly heated finishing chamber where it s subjected to steam pressure, the whole in one continuous operation, and with no waste of color.

patented by Mr. Richard Thoens, of New Orleans, La. It is designed for the minute regulation of the flow of of different widths, so as to form a rough inner surface. gas, being especially intended for use in connection with ice machines in which ammonia gas is used. The valve stem is packed by rubber washers, between which is a metal washer, and these washers are clamped bewashers spreading to close tightly against the stem and the inner surface of the valve body.

An improvement in saw mills has been shorten the time and lessen the labor of washing. patented by Mr. Walter P. Scoffeld, of Hawthorn, Fla. It consists in a contrivance of belt shifting devices, whereby a trip block on the log carriage will automatically shift the belt from the loose to the tight pulley of ings, and there is a locking device for the connecting which can be secured in any position to adjust the feed the paper, and so each quire will receive just the rods of the oppositely acting friction wheels of the set measure to weighing regularly any desired quantity. wheels, out of contact with the set works drive wheel.

AGRICULTURAL INVENTIONS.

A cultivator has been patented by Mr. Charles D. Reed, of Polo, Ill. According to this invention, as the standards and plows are moved laterally a bar keeps the couplings parallel, so that the shovels the blade upward, the whole to prevent the razor from will always be held at the desired angle with the line cutting the person using it. of draught, thus always doing good work, however they may be moved laterally.

A corn planting attachment for plows has been patented by Mr. Philip Dougherty, of Fort Dodge, Iowa. A jointed spout can be so adjusted to the depth of the intended furrow and the width of the furrow slice that the seed may be dropped in the outer part of the previous furrow and will be covered by the furrow the seed being dropped as the plow is drawn forward.

A corn planter bas been patented by Mr. and are so arranged and held in place that they will drop more or less seed as required. A pawl carrying wheel provided with a sliding rod, a connecting bar, and a perforated plate.

ers are forced down to mark the soil by the revolution by raised and lowered.

The fender is constructed in combination with the plow beam, with its forward end pointed and curved slightly inward and its rear end curved outward and npward, so that as the plow is drawn forward the fender raises the leaves of the plants.

Mr. Obadiah Wilson, of Plainville, N. Y., has obtained a patent for an improved method of conveying tobacco from the field and depositing it in the drying house. The invention consists in a truck with four wheels and provided with a removable rack upon which the plants are placed after they have been cut. They are then transferred to the drying house and the and lower parts of the fifth wheel is greatly reduced, rack is removed bodily from the truck, which obviates the necessity of rehanding the plants, saving time and labor, and lessening injury to the crop from handling.

MISCELLANEOUS INVENTIONS.

An improved suspender end has been pais composed of colored braid with a lining of chamois verse passage, the plug has a weighted lever, and both leather and an interposed piece of cloth, the ends being thus made more durable and less liable to stretch out of the hee can enter the hive of shape, while the braid is kept out of contact with the shirt of the wearer.

> An improved fire escape bas been patented by Mr. John Schmittknecht, of New York city. It provides for a shaft let into the wall of a building, or goes into the water, and is so arranged that, when the placedagainst the same, the shaft having ladder rounds, and being provided at its upper end with a skylight, so protected with bars or grating as to prevent clandestine entrance.

> A combined register and ventilator has been patented by Mr. William H. Maxfield, of Maysville, Ind. It consists in a special construction and combination of parts whereby the whole is made to present an ornamental appearance, great facility is afford. of the required shape of the roll of goods to be repreed for removing and cleaning the interior, and it may be readily operated from opposite ends of its air box.

An automatic vehicle brake bas been patented by Mr. Richard R. Pace, of Lineville, Ala. The invention consists in levers pivoted on thills held to the front axle by shackles, the levers carrying brake shoes at the outer ends, and having the outer ends connected with the thills by extensible braces. The brake can be so locked as to be made inoperative when desired.

An improved window cornice, that is convenient and readily adjustable, has been patented by Mr. Micbael Leuz, of New York city. The center piece has grooves and stop blocks, and there are sliding end pieces with end T-bars and set screws, the combination being such that the whole is strongly made and readily fitted to the place desired. 2

William A. Whitney, of Hudson, Mich., for an improved wheel barrow in which the legs and braces are. by a combination of bolts and metal devices, connected rigidly and closely to the handles, so that the wheel barrowframe will be very strong, and can easily be taken apart and put together again.

A vegetable grinder and slicker has been patented by Mr. Edward Schmitz, of Winsted, Conn. A grating cylinder, which may be changed for a cutting cylinder, is devised so as to be suitably revolved in a sort of hopper, whereby the grinding, grating, or cutratus for saturating the previously dried fabric in a ting of cabbages, potatoes, and other vegetables may be readily accomplished, for domestic use or for feeding

An improved hot blast stove for blast furnaces has been patented by Mr. Charles Alger, of Hudson, N. Y. The invention consists in the peculiar construction of the air heating pipes, which can be A gas valve for ice machines has been made of wrought iron if desired, and are faced inside and outside with firebricks, those inside being made fract, of Pittsburg, Pa. The heat is applied from di-

A washing machine or improved washboard hasbeen patented by Mr. A. E. Kiel, of Montrose, Iowa. The board has three roll sets, each set consisting of a ribbed, a smooth, and a corrugated roll, tween metal rings with beveled surfaces, the rubber the rollers not to be in contact but as close as possible without touching, and the grooved rollers being of greater diameter than the plain ones, the whole to

An improved grain weigher and measure has been patented by Mr. James E. Kemble, of Vicksburg, Mich. By a combination of valves in a circular case, inside of which is another circular case, suitably the feed shaft, to rotate the latter only when the log pivoted and divided by partitions, one loaded side falls setting apparatus is to be operated; the driving shaft to discharge a weighed load, while the light side rises is supported steadily its whole length by pivoted bear- to be filled, the weigh bar being provided with a weight

A razor guard has been patented by Mr. James P. Tryner, of Denver, Colo. It is formed of a strip with a forked arm at each end, in the ends of the patented by Mr. E. W. Bush. of Armstrong, Mo. The prongs of which rollers are journaled, one being slight object of the invention is to produce such a combination ly above and the other slightly below the cutting edge of the blade; one of the prongs has a check plate, and on the upper surface of the strip is a spring for pressing

An improved measure for measuring grain, vegetables, etc., has been patented by Mr. William A. Carpenter, of Bankers, Mich. In a metal cylinder having its top and bottom edges turned over wire rings, a wooden ring surrounds the upper part of the cylinder, and a wooden bottom rests upon a bottom flange made strong and durable.

A combined vault cover and ventilator has

has adjustable slides and arms to engage with crank lever, whereby the water received upon the cover will A cable grip apparatus has been patented arms of markers, and held up by springs, so that mark- flow into the channel plate, and the cover can be readi-

> An improved bottling device has been pa-A cotton, corn, and tobacco fender for tented by Mr. Alfred Rigny, of New York city. In a raising the leaves of plants while soil is being thrown tube open at both ends, the upper part carries a lateral around the stalks by the plow, has been patented by supply pipe, and there is a valve at the lower end, ope-Messrs, M. F. Duncan and R. E. Coyle, of May's Lick, rated by a rod through the tube. The tube is calcurated by a rod through the tube. The tube is calculated to occupy the exact space required to be left empty for corking the bottle, and it can be readily moved from one bottle to another without any waste of liquid.

An improved fifth wheel for wagons has peen Patented by Mr. Thomas Evans, of Gravesend, N. Y. It is formed of two circular channel plates with interlapping flanges and corresponding central depression and wearing surface, in combination with a circular skeleton frame with conical rollers journaled in its rims. By this means the friction between the upper and the turning of the wagon is made much easier.

A bee hive of new and improved construction has oeen patented by Mr. Edward Meyer, of Halletsville, Texas. The bees can, in this hive, be fed and watered very conveniently, a peculiarly made water tank being attached; the honey can be removed without tented by Mr. Jacob Katzenberg, of New York city. It permitting the bees to escape, and there is no danger of being injured by the bees while removing the combs, while the arrangement is such that none of the enemies

> A rotary leader link for fishing lines forms the subject of a patent which has been issued to Mr. Earl Ludwig Bollermann, of New York city. It is for hand lines, with a weight or sinker at the end which fisherman throws out his line, the snells with their hooks will not become tangled up with or wrapped about the line, but will fall in their proper places, no matter how much the line may be twisted.

> Mr. Morris H. Marcus, of Edenburg, Pa., nas patented an improved sample dummy. The invention consists in a dummy for cloth or rolled goods, made of wood or other suitable material, with its body sented, and having reduced ends, on which are secured and mounted pieces of selvage till a bulk is obtained equal tothat of the body of the dummy. This is covered a piece of the goods, thus representing a solid roll of cloth which is specially adapted for window show.

> A folding cot of improved construction for use in hotels and hospitals has been patented by Emily F. Vance, of Gallipolis, Ohio. Two pairs of legs are united at the upper ends by longitudinal rails, the legs being crossed and pivoted in the usual way. A quilted bottom or sheet is lined and partly stuffed with cotton batting, and a pillow is provided at each end. which can be removed very easily and readily. The cot requires no mattress, and can be folded compactly.

A cap for receiving the fulminate for firdves in blasting rock, etc., has been natented Letters patent have been granted to Mr. by Mr. George Freund, of Durango, Colo. A metal tube is threaded internally and externally to within a short distance from the lower end, where a suitable fulminate is placed and the lower end closed by a cap. A threaded cap with a conducting wire is screwed on the upper end, or a fuse is then inserted. The tube can be screwed in a giant candle of explosive material. the flange fitting on the upper end of the candle.

A feed governor for cotton gins has been patented by Mr. Henry P. Schaefer, of Schulenberg, Tex. Most gin saws now suck or draw in the cotton fastest at the central part of the saw shaft, drawing the cotton from the edges of the feed board toward the center. By this improvement a thinner layer of cotton is fed at the center, the suction of the central saws drawing in from the thicker edges such portion as will make the whole supply to the gin saws even and regular and prevent all choking.

A new process of and apparatus for distillation has been patented by Mr. James G. Ponterect fire, steam jacket, or steam coil, and the fermented mash, beer, etc., are agitated during the distilling process in such manner as to prevent lees or solid particles from adhering to the side or bottom of the still and thus burning or scorching, this being accomplished by causing a stream of the liquid being distilled to be constantly withdrawn and forcibly injected back into the still while in operation.

A machine for wetting paper has been patented by Mr. John W. Morrison, of Omaha, Neb. The quires are fed to feed rollers, from whence they are taken by fingers so adjusted that only the under side of the paper may be wetted in a water tank, or the whole may be submerged, as desired, and thence the naper is conveyed out through other rolls to a receiving table, the whole being done as tast as the operator can

An improved washing machine has been of parts as will facilitate the application of rubbing devices to an ordinary wash tub. There is a false bottom, below which the dirty water collects, and the false bottom being provided with radial ribs, the clothes to he washed are spread on the false bottom, and a disk is recked to and fro over them in a horizontal plane by means of a suitable handle. The machine can be feadily adapted to or easily removed from any tub.

A tobacco moistening tray has been patented by Mr. Charles N. Swift, of New York city. A shallow tray with perforated cover carries a sheet of bibulous by turning the edge of the cylinder over a wire, the material in such a way that a single supply of water whole making a measure simple in construction yet will last considerable time, and the tray requires but little attention, so being well adapted to place in show cases, etc., where the cigar boxesmay be arrangedupon been patented by Mr. T. W. Langill, of New York city. it. The same inventor has also obtained a patent for a William P. Lanham, of Star, Mo. The seed dropping. The casing has a grate at its upper end and a water moistening pad of some bibulous substance covered slides are operated by the revolution of the drive wheels, receiving channel plate at the lower end, the cover by a perforated plate, and supported on a plate folded resting upon the inner flange of the channel plate, and at the edges over both the bibulous substance and the

Business and Personal.

The Charge for Insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office asearly as Thursday morning to appear in next issue.

The tobacco of the club room ought to be of the purest kind and most delicate fragrance. Where many enjoy their pipes and cigarettes together, the air soon ecomes heavy and offensive unless they are very par ticularabout their choice of brands. Gentlemen of refined tastessecure Blackwell's Durham Long Cut.

The Universal Calculator solves all problems in arithmetic and trigonometry, instantly by a mechanical process. Indorsed by leading mathematicians and the scientific press. Price \$1.00 by mail. W. H. Wythe, Ocean Grove, N. J.

Jenkius Standard Packing and Jenkins Patent Valves. Price list free, Jenkins Bros., 71 John Street, New York.

Thread Cutter.-Something new and useful adapted to all kinds of sewing machines. Patent for sale. Address. Gavino Gutierrez & Co., 192 Front St., New York.

Irido-Copper, manufactured by the American Iridium Co., Pearl and Plum Sts., Cincinnati, Ohio, is superior to bronze metal for journal hearings of accurate and high running machinery, being hard and slightly porous.

Pumps-Hand & Power, Boiler Pumps. The Goulds Mfg. Co., Seneca Falls, N. Y., & 15 Park Place, New York. Fox's Corrugated Boiler Furnace, illus, p. 354. Hartmann, Le Doux & Maecker, sole agents, 134 Pearl St., N. Y.

One 12 inch Weston Dynamo Electric Machine in good order, for sale at one-half price. Address P. O. Box 433, Hartford, Conn.

Corliss Steam Engines at a bargain. One $12'' \times 42''$; one $16'' \times 36''$; one $20'' \times 42''$.

All in first-class running order. Henry I. Snell, 135 North 3d St., Philadelphia, Pa.

Steam Pipe and Boiler Covering, Roofing Paints, Preared Roofing, and general line of Asbestos materials, Phil Carey & Co., 127 Central Avenue, Cincinnati, O.

For Freight and Passenger Elevators send to L. S. Graves & Son, Rochester, N. Y.

Best Squaring Shears, Tinners', and Canners' Tools Ningara Stamping and Tool Company, Buffalo, N. Y.

Lathes 14 in. swing, with and without back gears and screw. J. Birkenhead, Mansfield, Mass.

The Best.-The Dueber Watch Case.

If an invention has not been patented in the United States for more than one year, it may still be patented in Canada. Cost for Canadian putest, \$40. Various other foreign patents may also be obtained. For instructions address Munn & Co., SCIENTIFIC AMERICAN Patent Agency, 261 Broadway, New York.

Guild & Garrison's Steam Pump Works, Brooklyn. N. Y. Steam Pumping Machinery of every description. Send for catalogue.

Nickel Plating .- Sole manufacturers cast nickel andes, pure nickel salts, polishing compositions, etc. Complete outfit for plating, etc. Hanson & Van Winkle. Newark, N. J., und Stand W. Broerty St., New York.

Lists 29, 30 & 31, describing 4,000 new and 2d-hand Machines, ready for distribution. State just what machines wanted. Forsaith & Co., Manchester, N. H., & N. Y. city. For Power & Economy, Alcout's Turbine, Mt.Holly, N. J.

"Abbe" Bolt Forging Machines and "Palmer" Power ners a specialty. Forsaith & Co., Manchester, N.H. Railway and Machine Shop Equipment.

Send for Monthly Machinery List to the George Place Machinery Company, 121 Chambers and 103 Reade Streets, New York. "How to Keep Boilers Clean." Book sent free by James F. Hotchkiss, 84 John St., New York.

Wanted .- Patented articles or machinery to make and introduce. Gaynor & Fitzgerald, New Haven. Conn. Water purified for all purposes, from household supplies to those of largest cities, by the improved filters manufactured by the Newark Filtering Co., 177 Commerce St.. Newark, N. J.

Improved Skinner Portable Engines. Erie, Pa.

Presses & Dies, Ferracute Mach, Co., Bridgeton, N.J. Split Pulleys at low prices, and of same strength and sppearance as Whole Pulleys. Vocom & Son's Shafting Works. Drinker St., Philadelphia. Pa.

Supplement Catalogue.-Persons in pursuit of information on any special engineering, mechanical, or scientific subject, can have catalogue of contents of the Sci-ENTIFIC AMERICAN SUPPLEMENT sent to them free. The SUPPLEMENT contains lengthy articles embracing the whole range of engineering, mechanics, and physical science, Address Munn & Co. Publishers, New York. Machinery for Light Manufacturing, on hand and built to order. R. E. Garvin & Co., 139 Center St., N. Y.

Fossil Meal Composition, the leading non-conducting covering for boilers, pipes, etc. See adv., p. 414.

Straight Line Engine Co., Syracuse, N. Y. Best in coign, materials, working governing; no packing. Curtis Pressure Regulator and Steam Trap. See p.349. C. B. Rogers & Co., Norwich, Conn., Wood Working

Machinery of every kind. See adv., page 350. LightningScrew Plates, Labor-saving Tools, p. 348.

Woodwork'g Mach'y, Rollstone Mach. Co. Adv., p. 366 Steam Pumps. See adv. Smith, Vaile & Co., p. 382.

AjaxMetal Company, Phila. Clamer's AjaxMetals for railroad, rolling mill, engine bearings, cocks, and valves. Fire Brick. Tile, and Clay Retorts, all shapes. Borgner

& O'Brien, M'f'rs, 23d St., above Race, Phila., Pa Peck's Patent Drop Press. See adv. page 396.

Drop Forgings, Billings & Spencer Co. See adv., p. 398. Bradley's Road Cart, Syracuse, N. Y. See p. 398.

Diamond Planers. J. Dickinson, 64 Nassau St. N. Y. Steam Hammers, Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Emerson's 1884 Book of Saws, New matter. 75,000. Free. Address Emerson, Smith & Co., Beaver Falls, Pa. Hoisting Engines. Friction Clutch Pulleys, Cut-off Couplings. D. Frisbie & Co., Philadelphia, Pa.

Gould & Eberhardt's Machinists' Tools. See adv.,p. 396. Barrel, Keg, Hogshead, Stave Mach'y. See ad., p. 398. For Mill Macb'y & Mill Furnishing, see illus, adv. p.396.

Renshaw's Ratchet for Square and Taper Shank Drills. The Pratt & Whitney Co., Hartford, Conn.

© 1883 SCIENTIFIC AMERICAN, INC