ENGINEERING INVENTIONS.

A car coupling has been patented by Mr. William T. Quinley, of Golden Lake, Ark. It consists of combined pin and link holders, which may be set independently of each other, for coupling cars automatically, the ordinary pin and link being used.

A steam throttle valve has been patented by Mr. Augustus H. Morrison, of Mechanicsville, N. Y It is for automatically regulating the flow of steam where, in a given operation or need, a varying amount is required, and the amount required controlling the operation of the valve, for which novel devices are provided.

A steam whistle has been patented by Mr. John Einig, of Jacksonville, Fla. The improvement consists of an extension contrivance of the lower end of the bell, to enable it to be shifted nearer to or farther from the nozzle to adapt it to high or low steam in the adjusting of the whistle for producing sounds most agreeable to the ear.

A car coupling has been patented by Mr. George J. Selleck, Jr., of Beetown, Wis. A lever is pivoted in the slot of the drawhead, a coupling pin being pivoted to the free end of the lever, and a lever is pivoted in the bottom of the drawhead, baving its inner end weighted, the outer or front end being slotted, so that when the link is in the drawhead the coupling pin passes through the link and through the slotted end of the weighted lever, and is thus held in place.

A steam engine has been patented by Mr. Anthony Bollinger, of Zanesville, O. It has special constructions of piston, with separate steam and exhaust chambers, communicating with the steam inlet and exhaust pipes, the pipes or tubes being arranged to move with the piston and telescope the steam supply pipe; there is also a special arrangement of the valves and means for tripping them, the object being to make a simple and durable engine, which may be readily reversed, is easily operated, and economical in the use of steam.

MECHANICAL INVENTIONS.

A journal bearing has been patented by Mr. James M. Elliott, of Winnsborough, S. C. The cap of the journal box has an adjustable bearing block, and is provided with adjusting screws for setting it down on the journal; also with an adjusting screw and bear ing faces for controlling the block laterally, the cap being permanently bolted down on the box.

A shingle machine has been patented by Mr. Charles A. Tarragon, of Portland, Oregon. It is made with sills having rails carrying rack bars with wheels, connected by a crossbar with each other, and engaging with gear wheels fixed to a shaft, so the rack bars are made to move forward and back evenly, spring pressed knives tapering the shingles according to tapered gauge bars, with other novel features.

A regulator for paper drying machines has been natented by Mr. Augustus H. Morrison, of Mechanicsville, N. Y. The invention consists in journaling one of the top rollers in one arm of a three armed lever, to another arm of which is attached a rod and tension spring, while to the opposite arm is connected the handle of a steam valve for regulating the supply of steam to the drying cylinders; there is also a bell for giving alarm if the web of paper breaks, with other novel features.

AGRICULTURAL INVENTIONS.

A harrow attachment for plows has been patented by Mr. Enoch C. Calvin, of Pinckneyville, Ill. An obtuse angled bar carrying teeth on its outer arm is so combined with a turn plow, another bar bent at both ends having teeth adapted to work rearwardly, as to form a harrow rigidly attached to the plow beam to pulverize and level the soil, cutting down the high parts of the furrow slice and filling the low places.

A combined roller and seed planter has been patented by Mr. Julius F. Muenchow, of Plainview, Iowa. The rollers have their axles connected with the platform of the machine by a king bolt, the opening plows have standards with screw threads, and attached to the platform of the machine are seed boxes with discharge spouts, closed at their lower ends hy valves operated by springs.

A fleece binder has been patented by Mr. Theodore C. H. Krueger, of Brady, Texas. It is constructed with a box attached to a supporting frame, and having inclined flanges upon its side edges, with hinged press boards and fingers operated by push bars, a cord, and a treadle, so the fleece can be compressed and held while being tied, a knife being so attached that all the twines of the bundle can be cut at a time

MISCELLANEOUS INVENTIONS.

A jar and fastening therefor has been pa-Mr. Herman Pietsch, of Flatbush, N. Y. The

Business and Personal.

The Charge for Insertion under this head is One Dollar a line for each insertion ; about eight words to a line. Advertisements must be received at publication office asearly as Thursday norning to appear in next issue

For Sale .- Two new, first class engine lathes; each back-g'd, sc.-cut., rod-f'd, power cross f'd, compound rest, full counter, friction pullers, center rest, face plates, etc. One $16' \ge 26'', $625;$ one $16' \ge 20'', $416. E.$ Cornish, Manchester, N. H.

121% in. Reflg. Telescope, \$300. Tydeman, 835 Linden Street, Camden, N. J.

Wanted.-A competent head draughtsman thoroughly conversant with the construction of injectors, who can assume superintendency of factory; salary no object. Address "Injector," P. O. Box 3562, New York city.

A gentleman don't want tobacco that will foul the air bite the tongue, or unstring the nerves. He wants only nature's exquisite flavors and delicate tonic. These are found nowhere in such perfect combination as in the leaf of the Golden Belt of North Carolina. of which Blackweil's Durham Long Cut, for pipe and cigarette smoking, is made.

Required .- Cash capital of \$5,000 to advertise and introduce a valuable patented invention for saving power and economy of space in all kinds of Belt Driving machinery. This patent has already been adopted by one of the principal electric light companies of this country, and is in use in England and France. Attention of a manufacturer with the above amount to invest is especially solicited to this splendid opportunity for a good investment. For full particulars apply to S. Samper & Co., No. 134 Pearl Street, New York.

To introduce our "Patent Socket Screwdriver" we will send one to any address for 35 cents. Stamps taken. George S. Allen, Plantsville, Conn.

The Cyclone Steam Flue Cleaner on 30 days' trial to reliable parties. Crescent Mfg. Co., Cleveland, O.

For Steam and Power Pumping Machinery of Single and Duplex Pattern, embracing boiler feed, fire and low pressure pumps, independent condensing outfits, vac-uum, hydraulic, artesian, and deep well pumps, air compressors. address Geo. F. Blake Mfg. Co., 44 Washington St., Boston; 97 Liberty St., N Y. Send for Catalogue. Quinn's device for stopping leaks in boiler tubes Address S. M. Co., South Newmarket, N. H.

Mills, Engines, and Boilers for all purposes and of every description. Send for circulars. Newell Universal Mill Co., 10 Barclay Street, N. Y.

Wanted -- Patented articles or machinery to manufactureandintroduce. Lexington Mfg. Co., Lexington, Ky. Brush Electric Arc Lights and Storage Batteries. Twenty thousand Arc Lights already sold. Our largest machine gives 65 Arc Lights with 45 horse power. Our Storage Battery is the only practical one in the market. Brush Electric Co., Cleveland, O.

For Freight and Passenger Elevators send to L. S. Graves & Son, Rochester, N.Y., or 46 Cortlandt St., N. Y. "How to Keep Boilers Clean." Book sent free by James F. Hotchkiss, 86 John St., New York.

Stationary, Marine, Portable, and Locomotive Boilers specialty. Lake Erie Boiler Works, Buffalo, N.Y.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J. The Hyatt filters and methods guaranteed to render all kinds of turbid water pure and sparkling, at economi-cal cost. The Newark Filtering Co., Newark, N. J.

Send for Monthly Machinery List to the George Place Machinery Company,

121 Chambers and 103 Reade Streets, New York.

Steam Boilers, Rotary Bleachers, Wrought Iron Turn Tables, Plate Iron Work. Tippett & Wood, Easton, Pa. Iron Planer, Lathe, Drill, and other machine tools of modern design. New Haven Mfg. Co., New Haven, Conn. For Power & Economy, Alcott's Turbine, Mt.Holly, N. J. If an invention has not been patented in the United States for more than one year, it may still be patented in Canada. Cost for Canadian patent, \$40. Yarious other foreign patents may also be obtained. For instructions address Munn & Co., SCIENTIFIC AMERICAN Patent agency, 361 Broadway, New York.

Guild & Garrison's Steam Pump Works, Brooklyn, N. Y. Steam Pumping Machinery of every description. Send for catalogue.

Nickel Plating .- Sole manufacturers cast nickel anodes, pure nickel salts, polishing compositions. etc. Complete outfit for plating, etc. Hanson & Van Winkle, Newark, N. J., and 92 and 94 Liberty St., New York.

Supplement Catalogue.-Persons in pursuit of information on any special engineering mechanical, or scientific subject, can have catalogue of contents of the Sci-ENTLFIC AMERICAN SUPPLEMENT sent to them free. The STPPLEMENT contains lengthy articles embracing the whole range of engineering, mechanics, and physical science. Address Munn & Co., Publishers, New York.

Machinery for Light Manufacturing, on hand and built to order. E. E. Garvin & Co., 139 Center St., N. Y. Mineral Lands Prospected, Artesian Wells Bored, by

Iron and steel wire of all kinds. Extra qualities straightened and cut to lengths a specialty. Trenton Iron Co., Trenton, N. J., and 17 Burling Slip, New York. Split Pulleys at low prices, and of same strength and

appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.



HINTS TO CORRESPONDENTS.

Initial To Contribution (NDERTIS).
Name and Address must accompany all letters, or uo attention will be paid thereto. This is for our information, and not for publication.
References to former articles or answers should give date of paper and page or number of question.
Inquiries not answered in reasonable time should repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all, either by letter or mail, each must take his turn.

or mail, each must take his turn. Special Information requests on matters of personal rather than general interest, and requests for PromptAnswers by Letter, should be accompanied with remittance of \$1 to \$5, according to the subject, as we cannot be expected to perform such service without remuneration.

Scientific American Supplements referred to may be had at the office. Frice 10 cents each. Minerals sent for examination should be distinctly marked or labeled,

(1) W. H. S. H. asks (1) how Thorley's food is made. A. We do not know the composition of Thorley's food. It is a medicinal preparation, and in order to determine its constituents, it will be necessary to have it analyzed by some competent chemist or pharmacist. 2. How to make bluing? A. For bluing take 1 ounce of soft Prussian blue, powder it and put in a bottle with 1 quart of clear rain water, and add a quarter of an ounce of oxalic acid. A teaspoonful is ufficient for a large washing. 3. How to soften water. A. Hard water contains more or less calcium carbonate. The addition of lime will make it soft: See description of the process used in England on page 4306 of Scientific American Supplement, No. 270. 4. How the different kinds of ink are made. A. SCIEN-TIFIC AMERICAN SUPPLEMENT, No. 157, gives numerous receipts for all kinds of ink.

(2) J. W. asks: 1. What would be the effect on coal gas to heat it just before it came to the burner? A. The effect of heating on the gas alone with an ordinary burner would not be beneficial for illumination? 2. Do you know of a flat flame tip that has been patented that does it ? A. No.

(3) A. H. asks how to take smoke stains out of marble caused by the building being partially burned. A. We recommend the following . Take 1 oz. of ox gall, 1 gill of lye, 11/2 tablespoonfuls of turpentine; mix, and make into a paste with pipe clay. Apply the paste to the spots, and allow it to remain over them for several days. Or take 2 parts of common soda, 1 part of pumice stone, and 1 part of finely powdered chalk, sift it through a fine sieve, and mix it with water, then rub it well over the marble and then wash the marble off with soap and water.

(4) F. H. S. says: My boy 20 months old is beginning to talk, and stutters terribly. What remedy can I use? A. No medicines will be of any service, but you should have the child examined by some good physician. Stuttering in children is often caused by something abnormal in the mouth or throat; cleft palate for instance, elongated or diseased uvula, a tumor at some point, etc. It is also caused by hearing some one else stutter; the remedy for this is of course to keep him away from the influence. If neither of these causes exist, you must wait; nothing can be really done to break the habit before the child is six to seven years old.

(5) J. F. B. asks: What parts of glue and glycerine mixed together will give me a thin substance that, after drying, can be bent or doubled without cracking or breaking? A. You will have to use a composition similar to printers' rollers. An average composition consists of Cooper's best glue, 81/2 lb.; extra sirup, 2 gal.; glycerine, 1 pint; Venice turpentine, 2 Steep the glue in rain water until pliant, and then drain it well. Next melt it over a moderate fire, but do not "cook" it. This will take from 15 to 25 minutes. Then put in the sirup or molasses and boil three-quarters of an hour, stirring it occasionally and skimming off impurities rising to the surface. Addthe glycerive and turpentine a few minutes before removing from the fire, and pour slowly. Slightly reduce or increase the glue as the weather becomes colder or warmer.

(6) L. W. asks 1. For the process for cleaning and curing tripe from the slaughter house to the market. A. In New York it is partially parboiled, but in some other places only washed with cold water

To prepare wax for polishing floors, 121/2 pounds of yellow wax rasped are stirred into a hot solution of 6 pounds of good pearl ash in rain water. Keeping the mixture well stirred while boiling, it is first quiet, but soon commences to froth: and when the effervescence ceases heat is stopped, and there are added to the mixture while stirring 6 pounds of dry yellow ocher. It may then be poured into tin cans or boxes, and hardens on cooling; when wanted for use a pound of it is diffused in 5 pints of boiling hot water, and the mixture, well stirred, is applied while still hot to the floor by means of a paint brush; it dries in a few hours, after which the floor is to be polished with a large floor brush, and afterward wiped with a coarse woolen cloth. It is said that a coat will last six months.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

September 2, 1884,

AND EACH BEARING THAT DATE.

l	[See note at end of list about copies of these pate	ents.]
	Air cooling apparatus, E. H. Lynch Alabastinue, etc., mixing and proportioning granular or plastic materials for, M. B.	
l	Church Ash pan. J. H. Hart	
1	Ax, Martin & Humbert	304.538
•	Axle lubricator, Rosensteel & Shallenberger Axle lubricator, J. T. Young	
r	Axle lubricator, car. Hitchcock & Greasby	304,324
t	Bag. See Paper bag. Ball trap, J. J. King	304 654
ı	Basins and sewers, connection between, C. I.	
3	Kane Bed bottom, spring, S. D. Tuttle	
	Beehive, O. M. Foltz	304,419
-	Bicycle, W. Clemson Bicycle saddle, G. W. Marble	
3	Bit brace, J. S. Fray	
	Board. See Sign board. Boiler for heating buildings, W. H. Byram	304,609
3	Boiler furnace, W. Lowe	304,332
	Bolting reel frame, W. E. Gorton Boot and shoe uppers, machine for moulding, G.	304.082
	H. Clark Boot or shoe crimping machine, Fifield & Holt	304,502
9	Boots or shoes, seat beater for, G. Wunderlich	304,517 304,482
r t	Bottle and jar stopper, W. W. Guptill Box. See Camera box. Journal box. Paper	304,312
	box.	
3	Box fastener, J. R. Sprague Boxes, wire band for, H. Frank	304,369 304,308
	Brace. See Bit brace.	-
	Brake. See ▼ehicle brake. Bread cutter, M. Schneider	304,459
	Bridle overdraw loop, N. B. Le Blond	304,381
-	Brine, purification of, E. A. Mebus Broom handle, whisk, T. P. Watkins	
,	Brush, paraffine, H. C. Thomas Buckle, trace, W. J. Butler	304,470
t	Buggy cover, E. Bradley	
1	Burber. See Vapor burner. Button attaching implement, M. H. McNair	304.541
ı	Buzz, whistling, F. R. Hunt	304,648
t	Calendar, J. W. McIndoe Camera. See Photographic camera.	
	Camera box, T. H. Blair Can. See Oil can. Paint can.	304.406
1	Candy rolling table, J. W. & W. P. Kirchhoff	304,655
;	Car and freight transfer apparatus, R. H. Ram- sey	304.563
1	Car buffer, R. E. Ricker	304,668
2	Car coupling, J. W. Davis Car conpling, D. L. Hays	
f	Car coupling, W. Henry	304,429
1	Car coupling, J. B. Parent Car coupling, W. T. Quinley	
1	Car coupling, D. M. Reynolds Car coupling, G. J. Selleck, Jr	304,452
1	Car coupling, C. B. Spencer	304,467
e	Car coupling and brake, J. II. Duffins Car door mechanism for freight cars, grain, J: A.	304,628
-	Hagan Car draw bar, street, W. P. Hudson	
1	Car draw bars, manufacture of railway, D. S.	
2	Wineland Car replacer. R. H. Watterson	
•	Car starter, J. C. Wood	304,393
	Carriage step, J. Pendergast Carrier. See Cash and parcel carrier. Trace car-	003,000
	rier. Cash and parcel carrier, W. P. Bigelow	304.491
	Casting steel, F. K. Haffey	304,314
	Chain, drive, H. H. Doubleday Chain, drive, E. L. Howe	
1	Chair. See Railway chair. Chairs, attachable rocker for, W. Malick	
•	Chandelier, oil and gas, S. Horowitz	304,645
)	Cigar and cigarette, J. McGovern Cigar mould, H. Hilde	
,	Cigars, apparatus for manufacturing, Moeller &	
	Sierk Cigars, manufacture of, H. Thoss	304,582
	Circuits, apparatus for automatically opening closed, J. P. Tirrell	\$04.876
	Clasp. See Snap clasp.	
	Cleaner. See Cotton cleaner. Cotton gin saw cleaner.	
	Cleat, F. M. Munroe Clock, secondary electric, C. E. Barschig	804,349 304 595
·	Clock striking mechanism, S. M. Terry	
	Cloth, machine for chinchilla-finishing, C. H. Baush	304,402
l	Cock, hydraulic, A. Hallowell	304,316
·	Cock, relief and gauge, M. S. Cabell Coils, rings. and similar articles, device for mak-	a04,610
	ing. Crimmett & Cook	
	Combination lubricator, A. E. Barthel Compound engine, M. Coryell.	
	Concrete and other plastics and cements, appara- tus for mixing ingredients of, C. Sooysmith	
	Copperas, apparatus for recovering, J. Lyons	304,333
	Corkscrew, W. Crabb Cotton cleaner and condenser, W. Jarrell	304.527
	Cotton gin saw cleaner. R. M. Dorsey	304,304
	Coupling. See Car coupling. Pipe coupling. Crank pitman, shaft, M. W. Clay	994,410
	Cravat holder, J. N. Proeschel Cream from milk, apparatus for separating, W.	304,663
•	Horner	
1	Creamery or refrigerator, F. W. Moseley Cultivator, M. O. Morehouse	

jar has flanges near its mouth, and the cover has grooves and a clamp, with hooks, a lug projecting outward on one hook for being grasped to spring that end of the clamp free in opening the jar.

A rubber spring has been patented by Mr. Frank E. Flagg, of New York city. It is made of rubber cord, with the ends wound and metallic ferrules placed thereon, the latter provided with connecting devices for holding the spring in place, making a simple and durable spring for icemen's rubber aprons, door bands, cage hangers, etc.

A water tight glove has been patented by Pauline W. A. Petersen, of Brooklyn, N. Y. It is made of waterproof canvas, leather, or rubber, with the tips of the fingers, the thumb, and palm provided with projections or ribs, so the thickness and strength of these parts are increased, and the friction surface of the glove enlarged.

A railway ticket has been patented by Mr. Charles J. Knapp, of Deposit, N. Y. This invention provides a specially devised coupon book for " thourailway tickets, to promote convenience in their taking up or punching, and to enable the holder to easily verify the mileage punched out by the conductor.

Munson's Improved Portable Mills, Utica, N. Y. C. B. Rogers & Co., Norwich, Conn., Wood Working Machinery of every kind. See adv., page 142.

Curtis Pressure Regulator and Steam Trap. See p. 78. Woodwork'g Mach'y, Rollstone Mach. Co. Adv., p. 77. Drop Forgings. Billings & Spencer Co., Hartford, Conn. We are sole manufacturers of the Fibrous Asbestos

Removable Pipe and Boiler Coverings. We make pure asbestos goods of all kinds. The Chalmers-Spence Co., 419 East 8th Street, New York.

SteamHammers. Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York, Emerson's 1884 Book of Saws. New matter. 75,000. Free. Emerson, Smith & Co., Limited, Beaver Falls, Pa Hoisting Engines, Friction Clutch Pulleys, Cut-off Couplings. D. Frisbie & Co., Philadelphia, Pa.

Barrel, Keg, Hogshead, Stave Mach'y. See adv. p. 173. Blacksmith Drilling Machines for 1/4 to 3/4 inch diameter, \$22.50. Pratt & whitney Co., Hartford, Ct.

For best low price Planer and Matcher. and lates improved Sash, Door, and Blind Machinery, Send for catalogue to Rowley & Hermance, Williamsport, Pa. The Porter-Allen High Speed Steam Engine. Southwark Foundry & Mach. Co., 430 Washington Ave., Phil. Pa. 1 tum. 2. Also how to polish floors with beeswax? A.

Pa. Diamond Drill Co. Box 423. Pottsville. Pa. See p. 141. Munson's Improved Portable Mills. Utica. N. Y. Hunson's Improved Portable Mills. Utica. N. Y. is bay rummade? A. A cheap bay rum can be prepared by saturating a quarter pound block of magnesium carbonate with oil of bay; pulverize the magnesia, place it in a filter, and pour water through it until the desired quantity is obtained, then add alcohol. The quantity of water and of alcohol depends on the des ired strength and quantity of bay rum. 3. What are a few of the best muscle and blood producing kinds of food? A. The question of nutritive foods is discussed elaborately in SCIENTIFIC AMERICAN SUPPLEMENT 186. under the title of "Food Physiology and Force." and " Cost in Scientific American Supplement 124, as and Nutritive Value of Foods." 4. Are wild meat and game better than domestic? A. Not necessarily (7) F. A. N. asks: 1. How would you go to work to put a good finish on a piece of black walnut

wood with white wax or paraffine to take the place of varnish or shellac? What would you use to cut the wax to get it in a liquid state, and what proportion to mix it. Also what to color it with, so it would not show white in the pores of the wood? A. Wax and paraffine are both soluble in benzine or naphtha. You can make it of any desired thickness by using more or less naphtha. You can color with burnt umber or with asphal-