ENGINEERING INVENTIONS

The propelling of marine vessels forms the subject of a patent issued to Mr. William O. Robbins, of New York city. Compressed air pipes lead from the stern of a vessel close to the propeller blades which are made to revolve by the force of air at a high pressure, whereby only short propeller shafts are need ed, and friction and danger of breakage is removed.

A car coupling has been patented by Mr. Ernest M. Brown, of New Boston, Ill. The draw bar has a head, from one side of the face of which two longitudinal slotted prongs project, and which has a coupling pin, in combination with a coupling link of an opposite drawhead, so the cars are at all times coupled by two links, and the pins have considerable play in the links.

A car brake and starter has been patented by Mr. Evvind Lee Heidenreich, of Chicago, Ill. Combined with the axle is a sliding sleeve having clutch cups at its ends which can be engaged with clutches mounted loosely on the axle and engaging with a wheel in which a spiral spring is coiled, so the energy of the car's motion while being stopped is stored to be given out in helping to start the car again.

A car coupling has been patented by Mr. Joseph McCov. of Independence. Mo. Combined with the drawhead is a V-shaped link lifter pivoted on the bottom and connected with a swinging piece arranged at one side of the drawhead, while on the opposite side is a horizontal bar with a beveled head projecting beyond the end of the drawhead, the device being intended to both raise the link and couple automatically.

A railroad gate has been patented by Mr. Albert M. Woodruff, of Athens, Mich. It is made with a shaft having a staple and rigid arms carrying suspended weights, with a push bar and springs so arranged and connected with supports attached to the track that the gate will be opened by the wheels of an approaching train, held open while the train is passing, and then automatically closed.

A valve gear has been patented by Mr. John R. Deering, of Emporia, Mo. The construction is such that the valve will be fully moved by an eccentric during an eighth of a revolution of the shaft, and will remain still until the eccentric reaches the opposite side, so the exhaust will be open for three-quarters of the time of revolution, thus giving an exceptionally free exhaust and reducing the back pressure on the piston to a minimum

A car coupling has been patented by Mr. John O'Brien, of Austin, Minn. A shaft is jour-naled in the top part of the drawhead in front of the coupling pin, carrying a plate whose free edge projects toward the rear of the drawhead, adapted to lift the outer end of the link when the shaft is turned, with which are other novel features, the device being calculated to facilitate the coupling of cars having drawheads of unequal heights.

A railway and tramway chair has been patented by Mr. John Poyser, of Sherwood Rise, Mansfield, Nottingham County, England. It is made with three jaws formed in one piece with or rigidly attached to an ordinary base, one jaw being shaped to receive one side of the rail in the usual way, and the two jaws on the other side leaving sufficient space to allow of the easy admission and extraction of the rail, a wooden or metal key being driven in this space to fix the rail firmly in position.

..... AGRICULTURAL INVENTIONS.

A corn planter has been patented by Messrs. Edwin M. Calef and Truman L. Tracy, of Missouri Valley, Iowa. This invention covers a novel construction and arrangement of parts intended to facilitate the planting of corn in accurate check row, and promote convenience in adjusting the seed dropping mechanism to keep the cross rows in line.

A mower has been patented by Mr. Benjamin Saunders, of Claverack, N.Y. The axle and main gear wheel are connected by a ratchet wheel, and spring pressed pawls are pivoted to the radial arms of a hub, so arranged that the main gear wheel can be driven at a fast or slow speed, and the sickle bar thus be made to vibrate more or less quickly, as the character of the grass may require, without stopping the machine.

A cotton chopper has been patented by Mr. James F. Barringer, of Bennettsville, S. C. It is made with wheels and an axle, runners connected by a shaft, pivoted bars, standards, and chopping hoes attached to a swinging extension bar vibrated by a crank shaft driven from the wheels and axle, making a machine to facilitate the chopping of cotton to a stand, and one which can be conveniently adjusted, operated, and controlled.

MISCELLANEOUS INVENTIONS.

with wires that radiate from a central point, so that the wires will be held very firmly at the center of the frame, and the frame will be cheap and strong.

A convertible chair has been patented by Mr. Edward H. Lewis, of Nashville, Tenn. It is a folding chair of novel design, readily convertible into a tented by Mr. Josiah Fowler, of St. John, N. B., Canasettee, bed, or cot, a lounge, a child's crib, or a carpet da. The outer end of the axle has no screw or nut to or wall paper exhibiting frame; it is composed of three hold the wheel in place, but instead there is a screw cap main bent sections, which may be put together without slipped over the bed of the axle, which is screwed by an tenons or mortising, glued angles, or ordinary framing.

A backing for books has been patented by Mr. Gustav A. Shurmann, of New York city. It consists of wood or other suitable material provided with removable attaching strips for holding the leaves, furnishing a device for binding in a firm and substantial manner, and in such way that the leaves or body of the book can be removed from the covers.

A carriage seat has been patented by Mr. Charles Morgan, of Bridgewater, Nova Scotia, Canada. The frame of the seat is so arranged, in connection with the use of springs, that it is adapted to slide back a little when the carriage receives a sudden shock or jerk, and then again return to its place, thus easing the back of the person occupying the seat

A composition of matter for facing brownstone and for making artificial stone has been patented by Mr. Benjamin E. Ratcliffe, of New York marks are impressed upon paper, upon which the city. It consists of linseed oil, sand, and litharge, in specified proportions, with any desired pigment for coloring, and if a finer grained mixture is required, ground impressions of the figures of the struck up or impressed pumice stone is added.

A grindstone frame has been patented by Mr. Julius B. Johnson, of Johnson, Neb. It is a knockdown frame which can be readily put together, formed of two sides and two end pieces, each having at the sides of the frame having oppositely arranged grooves down their inner faces, near each end, with which, by reason of the construction and fit of the legs, cross end pieces to keep the sides at their proper dis- | rails of the side pieces, making a child's crib that can tances apart are dispensed with.

A stair rod-has been patented by Mr. Thomas Worley, of New York city. It is made with interior screw threads in each end, the screws to fit and other substances has been patented by Mr. Charles therein having radial perforations in their shanks, with caps having flanged outer ends and transverse slots to inclose the screws and the ends of the rod, so that such is another vertically adjustable shaft with feed roller. rods may be readily applied and removed, and will hold and a knife held adjacent to the outer sides of the rollthe carpet firmly.

A disinfecting compound has been patented by Mr. Ferdinand Jossa, of Boston, Mass. It consists of definite mixtures of sulphate of iron, borax, chloride of sodium, and bicarbonate of soda, dissolved in warm water and mixed with dry sulphate of lime, the compound being suitable for use as a powder, in hard cakes, or dissolved in water according to the strength required.

Luther C. Baldwin, of Manchester, N. H. A U-shaped support, made of gas pipe or other suitable material, is attached to the side of a building or to the ground, supported from the bowed portion, the arms holding a rollef which has a crank for being fixed near a faucet or hydrant, to facilitate the use of small hose in sprinkling, washing, etc

Saddle bags form the subject of a patent issued to Mr. Joseph J. Stephens of Coalesburg, Mo. I'he bag is made open at the top, with a low front wall, in which is a cover opening on links as a tray, the whole affording a convenient receptacle for vials and other articles, while there is a flap cover which swings over the top and front of the tray and fastens to the front of the body.

A safety lamp has been patented by Mr. John L. Williams, of Shenandoah, Pa. This invention the draught attachments, with other novel features, covers novel attachments arranged outside of the wire gauze cylinder of the lamp, with adjustable sleeve on the wick tube to afford safety against a rush of gas, also an extension of the gauze cylinder below the burner, an additional wire gauze protector at the top of the lamp, with other novel features.

A combined wire stretcher and staple puller has been patented by Ela Moore, of Walla Walla, Washington Ter. The handle has teeth and a clamping lever, in combination with a fulcrum plate or head made on a curve, having at one end a hook and at the under side of the opposite end a depending pawl, making an especially useful device for building and repairing

patented by Mr. HenryC. Dyer, of St. Louis, Mo. There is a chamber with means for agitating the feathers, and for registering the distance traveled, and will register a blower for making a current of air which carries off the distance either forward or backward, up to tens or the lighter feathers and allows the heavier ones to drop hundreds of thousands of miles if required, without reinto a pit, there being rollers and belts with pins over which the feathers are conducted, the larger ones catching on the pins and dropping down.

patented by Mr. Joseph R. Kennedy, of Philadelphia, Middlesex County, England. The lens is so supported C. B. Rogers & Co., Norwich, Conn., Woo Pa. The ruler is formed with a straighttube and spring as to swing both on a horizontal and on a vertical axis, Machinery of every kind. See adv., page 348. tongues, the latter adapted to enter a slot in the edge of with vertical and horizontal adjustments, whereby the A belt clasp has been patented by Mr. tongues, the latter adapted to enter a slot in the cage of while vertical and not more than a boundary of the slate frame, the device being such as not to inter-same results may be obtained as by the combined use of fere with the ordinary use of a slate, while adapted to sliding fronts and swing backs, the bellows body of the ly made slide is so combined with the buckle that the hold a pencil and sharpener. and also for use as a ruler camera readily lending itself to any desired adjustment and measuring implement.

hoisting rope so contrived to run that the bucketcan be controlled by a single rope or chain, and will be opened and closed automatically, the apparatus being inexpen sive to manufacture and its working easily controlled.

A carriage axle and box have been paexternal thread into the hub of the wheel and by an in-ternal thread into the inner and larger end of the axle box, with other novel features, to promote durability and noiseless running.

A sweat pad for horse collars has been patented by Mr. Edward L. McClain, of Greenfield, O. A corrugated strap, preferably of rubber, is attached to a sweat pad, the strp being adapted to be brought around the inner roll of the collar and passed under the hames, so as to be held between the hames and the collar, the attachment being thickest at its outer or free end, so it will have a wedging action between the hame and collar.

The marking of chocolate cream drops and other confectionery forms the subject of a patent issued to Messrs. John S. Hawley, of Brick Church, N. J., and Herman W. Hoops, of New York city. The cream drops or other confectionery are laid while warm and plastic, and upon cooling and hardening preserve paper on which they have been laid.

A folding crib has been patented by Mary E. Woodward, of Parker, Dakota Ter. It is each end a corner piece with triangular cross section, the corner pieces hinged together in pairs, and bottom boards being hinged to swing upward to the bottom be folded compactly, quickly set up, and will then stand firmly.

Goettler. of New York city. Combined with a horizontal shaft mounted in fixed bearings, with a feed roller, ers, with other novel features, so the material will be cut smoothly as it is drawn against the edge of the knife by the feed rollers.

A magazine spring gun has been patented by Mr. Stephen D. Engle, of Hazleton, Pa. The magazine, to contain balls or projectiles, may be a simple longitudinally bored extension of the stock, connecting with the barrel at the breech, and allows one ball at a time to pass into the bore on suitably elevating A hose reel has been patented by Mr. the muzzle, when the follower or driver is in position, the propelling springs, which act in unison, giving an extended and powerful throw.

> A stove has been patented by Messrs. Burt A. Brigden and Edwin Cannon, Jr., of Moravia, T. Around the life par, and low down, is noted a horizontal partition, cutting off all passage of gases from the coal to the smoke flue except through the fire pot and grate. the smoke flue being below the line of the partition, the stove being intended to economize fuel by consuming the gases, while being simple in construction.

> A horse collar has been patented by Mr. Ebenezer Fisher, of Philadelphia, Pa. This invention covers a steel horse collar of two sections, each forged from a sheet of steel to form thin side flanges, whereby a greater degree of spring action is provided for embodying improvements on a collar which has been the subject of several former patents by the same inventor.

> A windmill has been patented by Mr. Oren Stoddard, of Busti, N. Y. By this invention it is designed to utilize the ornamental towers of buildings to locate wheels, vanes being suitably pivoted to arms to swing edgewise to the wind on the returning side, with two doors for each side closing to the center plane of the wheel, and so that only the ordinary form of the tower will appear when the doors are closed and the wheel not in use

An odometer has been patented by Mr. Benjamin F. Hutches, Jr., of Galveston, Texas. It is A machine for sorting feathers has been a simple, compact instrument, with geared wheels and dials, for attachment to bicycles, carriages, cars, etc., quiring special adjustment of the registering mechan ism

A photographic camera has been pa-A ruler attachment for slates has been tented by Mr. Thomas Samuels, of Hadley-Monken, of the lens.

Business and Personal.

The charge for Insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday mornin to appear in next iss e.

For Sale .- At a low price, a full set of Patent Office Reports, excepting the year 1843; all but 5 volumes bound in Half Russia. Address C. H. P., P.O. box No. 653, New

York city. Specula for Reflecting Telescopes. Finest quality. 5 inch, \$25; 6 inch, \$30. Prof. Brooks, Phelps, N. Y.

"Wrinkles in Electric Lighting," by V. Stephen; with illustrations. Price, \$1,00. E. & F. N. Spon, New York.

For Sale.-Scientific American, 47 volumes; Jan uary, 1862, to July, 1885. Bound or unbound. Wm. W. Stepler, Wilmington, Del.

Wanted.-A second-hand Vacuum Pan, from 3 to 4 feet, with pump complete. Address P. O. box 86, Detroit. Mich

Wanted.-Patented articles or hardware specialties to manufacture on contract or to manufacture and place on the market. First-class facilities. Correspondence solicited. Address Hull Vapor Stove Co., Cleveland, Ohio.

Volney W. Mason & Co., of Providence, R. I., have sent a number of their Friction Pulleys and Clutches for use in mines in Colorado and Montana.

Forging and Trimming Dies. Drop Forgings of all kinds. Beecher & Peck, New Haven, Conn.

Billings' Double-acting Ratchet Drills. Drop Forgings all kinds. Billings & Spencer Co., Hartford, Conr

Astronomical Telescopes, from 6'' to largest size. •bservatory Domes, all sizes. Warner & Swasey, Cleveland, O.

Peerless Leather Belting. Best in the world for swift running and electric machines. Arny & Son, Phila

"How to Keep Boilers Clean." Send your address A machine for cutting cloth, leather, for free 88 page book. Jas. C. Hotchkiss, 86 John St., N. Y. The most complete catalogue of Scientific and Mechanical Books ever published will be sent free on ap-plication to Munn & Co., 361 Broadway, N. Y.

Shafting, Couplings, Hangers, Pulleys. Edison Shafting Mfg. Co.,86 Goerck St., N.Y. Send for catalogue and prices. Air Compressors, Rock Drills. Jas. Clayton, B'klyn, N.Y.

Iron Planer, Lathe, Drill, and other machine tools of odern design. New Haven Mfg. Co., New Haven, Conn. Every variety of Rubber Belting, Hose, Packing, Gaskets, Springs, Tubing, Rubber Covered Rollers, Deckle Straps, Printers' Blankets, manufactured by Boston Belting Co., 226 Devonshire St., Boston, and 70 Reade St.,

New York. Write to Munn & Co., 361 Broadway, N. Y., for catalogue of Scientific Books for sale by them

Wanted.-Patented articles or machinery to manufacare and introduce. Lexington Mfg. Co., Lexington, Ky. Mills, Engines, and Boilers for all purposes and of every description. Send for circulars. Newell Universal Mill Co., 16 Darchay Street, N. 7.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J. For Power & Economy, Alcott's Turbine, Mt. Holly, N.J.

Send for Monthly Machinery List

to the George Place Machinery Company

121 Chambers and 103 Reade Streets, New York.

If an invention has not been patented in the United States for more than one year, it may still be patented in Canada. Cost for Canadian patent, \$40. Various other oreign patents may also be obtained. For instructions address Munn & Co., SCIENTIFIC AMERICAN patent agency, 361 Broadway, New York.

Guild & Garrison's Steam Pump Works, Brooklyn, N. Y. Steam Pumping Machinery of every description. Send for catalogue.

Machinery for Light Manufacturing, on hand and built to order. E. E. Garvin & Co., 139 Center St., N. Y. Nickel Plating.-Sole manufacturers cast nickel anodes, pure nickel salts, polishing compositions, etc. Complete outfit for plating, etc. Hanson, Van Winkle & Co., Newark, N. J., and 92 and 94 Liberty, St., New York.

For Steam and Power Pumping Machinery of Single and Duplex Pattern, embracing boiler feed, fire and low pressure pumps, independent condensing outfits, vacuum, hydraulic, artesian, and deep well pumps, air compressers, address Geo. F. Blake Mfg. Co., 44 Washington, St., Boston; 97 Liberty St., N. Y. Secul for catalogue.

Supplement Catalogue .- Persons in pursuit of information of any special engineering, mechanical, or scien-tific subject, can have catalogue of contents of the Sci-ENTIFIC AMERICAN SUPPLEMENT sent to them free. The SUPPLEMENT contains lengthy articles embracing the whole range of engmeering, mechanics, and physical science. Address Munn & Co., Publishers, New York.

Knots, Ties, and Splices. By J. T. Burgess. A Handbook for Seafarers and all who use Cordage. 12mo., cloth, illustrated. London, 1884. Sent, postage prepaid, on receipt of 50 cts. by Munn & Co., New York.

C. B. Rogers & Co., Norwich, Conn., Wood Working Stephens' Patent Bench Vises are the best. S e adv.,

George E. Zeltmacher, of Brooklyn, N. Y. A peculiarclasp can be readily adjusted to lengthen and shorten the belt, which will remain as fixed when adjusted, and the belt will not be disfigured or otherwise injured.

A hasp lock has been patented by Mr. Charles P. Pond, of Camden, N. Y. Combined with a hasp, a lock is formed in the swinging end of the same, no key being required to lock the hasp, and the improvement covering a lock which is simple in construction, strong and durable, and one which can be used on numerous objects.

A nail extractor has been patented by Mr. Lewis Howard, of Watkins, N. Y. Combined with making an improved device for extracting nails and spikes easily and rapidly.

A wire frame has been patented by Mr. tion consists principally in holding the ends of the wires A revolving chair has been patented by

with side rack teeth upon the pivot bar, passing through vided with a power accumulating balance wheel, one or the bar will be securely supported and can be readily loose balls carrying reciprocating tapering pockets conraised and lowered, and the chain will remain at the desired height.

James E. Goodhue, of St. Charles, Ill. It is a self. regulating mill of the class known as "solid wheel" a claw bar, with a spring bit secured to its under side, a mills, and its construction is such that the mill may be clevis is pivoted to the bit, and a pin unites the shank of promptly stopped during heavy or light winds, while the clevis between the bit and the under side of the bar, the vane maintains its position in line with the wind, with various other novel features to improve the construction and promote the efficiency of windmills.

Henry F. Fordham, of Greenport, N. Y. This inven- by Mr. William G. Thompson, of Brooklyn, N. Y. Itis and an arm or rake being held above its floor, while the made with a foot block carrying the bucket arms, a hopper may be revolved around a shaft, with other with a tube and wedge, key, or rivet, in making frames head block-carrying connecting bars and pulleys, and a 'novel features.

An apparatus for transmitting power Mr. C. Arnold Graef, of Bay Ridge, N. Y. A lever pawl has been patented by Mr. Louis G. C. y Saenz, of Pue-is pivoted to the socket attached to the legs, and engages bla, Mex. This invention combines a rotatable shaft prothe socket and carrying a pivoted seat spider, whereby more disks being fast on the shaft, and one or more structed to receive the disks partly within them and between the balls in the pockets, with other novel features A windmill has been patented by Mr. to promote the accumulating and transmission of power.

An ore separating and concentrating machine has been patented by Mr. Henry Landrin, of Anglet, Basses-Pyrenees, France. It works on the gravity principle, a hollow vessel being held in an upright position in a frame, the upper third of the vessel being cylindrical, and the lower two-thirds tapered toward the bottom, a hopper being in the upper part, the A grappling bucket has been patented bottom of the hopper formed of sector-shaped wings,

Curtis Pressure Regulator and Steam Trap. See p. 365. Send for catalogue of Scientific Books for sale by Munn & Co., 361 Broadway, N. Y. Free on application.

Rest Automatic Planer Knife Grinders, Pat. Face Plate hucks. Am. Twist Drill Co., Meredith, N. H.

Cushman's Chucks can be found in stock in all large cities. Send for catalogue. A. F. Cushman, Hartford, Conn.

Crescent Steel Tube Scrapers are made on scientific rinciples. Crescent Mfg. Co., Cleveland, Ohio.

The Improved Hydraulic Jacks, Punches, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York. Hoisting Engines. D. Frisbie & Co., Philadelphia, Pa. Tight and Slack Barrel Machinery a specialty. John Greenwood & Co., Rochester, N.Y. See illus. adv., p. 3.

"To Mechanics."-When needing Twist Drills, ask 'Standard," or send for catalogue to Standard Tool Co., Cleveland, O. See page xi., Export Edition.

The best Steam Pumps for Boiler Feeding. Valley Machine Works, Easthampton, Mass.

Wood Working Machinery. Full line. Williamsport Machine Co., "Limited," 110 W. 3d St., Williamsport, Pa.