

Supplement Catalogue.—Persons in pursuit of information of any special engineering, mechanical, or scientific subject, can have catalogue of contents of the SCIENTIFIC AMERICAN SUPPLEMENT sent to them free. The SUPPLEMENT contains lengthy articles embracing the whole range of engineering, mechanics, and physical science. Address Munn & Co., Publishers, New York.

Crescent Steel Tube Scrapers are made on scientific principles. Crescent Mfg. Co., Cleveland, Ohio.

Curtis Pressure Regulator for Steam Heating Apparatus, Waterworks, etc. Curtis Regulator Works, Boston, Mass.

The Improved Hydraulic Jacks, Punches, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Friction Clutch Pulleys. D. Frisbie & Co., Phila.

Tight and Slack Barrel Machinery a specialty. John Greenwood & Co., Rochester, N.Y. See illus. adv., p. 158.

Garden Hose, Linen Hose, Lawn Sprinklers, Hose Reels, Hose Pipes. Greene, Tweed & Co., 118 Chambers St., N. Y.

Manufacture of Soaps, Candles, Lubricants, and Glycerine. Illustrated. Price, \$4.00. E. & F. N. Spon, New York.

New Portable & Stationary Centering Chucks for rapid centering. Price list free. Cushman Chuck Co., Hartford, Conn.

Astronomical Telescopes, from 6" to largest size. Observatory Domes, all sizes. Warner & Swasey, Cleveland, O.

English tanned Walrus Leather, Sea Lion, Oak, and Bull Neck Leather for Polishing. Greene, Tweed & Co., New York.

## Notes & Queries

### HINTS TO CORRESPONDENTS.

**Names and Address** must accompany all letters, or no attention will be paid thereto. This is for our information, and not for publication.

**References** to former articles or answers should give date of paper and page or number of question. **Inquiries** not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all, either by letter or in this department, each must take his turn.

**Special Written Information** on matters of personal rather than general interest cannot be expected without remuneration.

**Scientific American Supplements** referred to may be had at the office. Price 10 cents each.

**Books** referred to promptly supplied on receipt of price.

**Minerals** sent for examination should be distinctly marked or labeled.

(1) H. C. S. writes: To make a dynamo machine like that described in SUPPLEMENT, No. 161, larger, do you make the iron part larger in proportion and work with more layers of wire? A. Enlarge the different parts of the dynamo proportionately.

(2) H. L. B. asks how to connect wires in a battery telephone of three stations using ordinary electric call bells. A. Arrange your line so as to cut out all the telephones, leaving the bells normally in circuit. Any ordinary switch which will cut out your telephone and leave the bells in the circuit will answer your purpose.

(3) J. P. L. asks how the zincs and carbons in a bichromate battery for a small incandescent electric lamp are made. A. The zincs are generally cut from sheets of rolled zinc, but they may be made of zinc cast in moulds. The carbon plates cannot readily be made by a tyro. It is both better and cheaper to purchase them; however, if you desire to try the experiment of making your own carbon, you may select clean pieces of coke, finely pulverize them, mix with a small quantity of sirup or molasses into a thick paste, force the paste into a suitable mould, close the mould, leaving vents for the escape of moisture and gas, place the mould in a muffle or crucible, and cover it with powdered carbon. Heat it till the moisture is driven off and the sirup is carbonized, allow the mould to cool, then remove the plate from the mould, dip it in very thin sirup, dry, recarbonize, and repeat the operation until the plate is sufficiently dense for use.

(4) W. K. D. asks: Please inform me in correspondence column of SCIENTIFIC AMERICAN as follows: 1. The best method of rendering a magic lantern screen transparent, or as much so as white thin cotton fabric can be rendered? A. Coat your screen with a varnish made of Venice turpentine dissolved in a good quality of spirits of turpentine. A sizing of the best white glue with a little glycerine added renders a screen quite translucent. 2. Can I use a 1 inch diameter lens of  $3\frac{1}{4}$  inches focus to any advantage in a small photographic apparatus to make transparencies for magic lantern slides, about one inch wide, i. e., the picture on the slide to be that width? What size stop, if any, should I need, and how far from lens should it be placed? Could I make a battery to run Guiscom's electric motor as efficiently as to buy it ready made by them? Also, please say if you know what difference in running power there is between the double induction motor and the V motor made by the Electro Dynamic Company, of Philadelphia. A. Your lens, if of good quality, may be used for photographic purposes in the manner suggested. You should employ different sized stops; a small stop will make a camera work deep and sharp, but slow. You can make your own battery for running your motor. Consult SUPPLEMENT, Nos. 157, 159.—We do not know as to the relative merits of the two motors referred to.

(5) R. B. L. asks (1) how to construct a dry kiln to hold about 5,000 feet of lumber. A. The cost in a drying room for lumber depends upon the method used. If you have exhaust steam, that should be used in preference to live steam. In either case, coils of iron pipe are to be placed near the floor with an open platform above for piling the lumber in a proper sized room for the amount of lumber to a charge. See SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 375 and 479, for illustrations of drying apparatus. 2. The power of an average man compared with the horse power? A. The power of man at best performance is from  $\frac{1}{4}$  to  $\frac{1}{2}$  horse power. Average men, one-sixth

horse power. 3. What is the best means of transmitting power by pulleys from a horizontal line shaft to one running at right angles? A. A right angle belt is much in use, and gives as good results as any of the special angle couplers in the market. The right angle belt has a quarter twist passing around idlers on a vertical shaft. 4. The best way of constructing a "rumble" for smoothing chair legs and rounds by friction, as is done in a hollow drum, and how full should such drum be filled to give best results? A. A good "rumble" may be made from a large, strong cask by mounting it on a shaft with flanges to bolt to the heads with suitable door. Charge half full with material, and add sawdust or bran sufficient to accomplish the work.

(6) V. E. N.—Choke bore is a slight narrowing of the muzzle of shotguns to prevent the charge from excessive scatter. To be done well, a gun should be choked in boring. A good gunsmith should be able to make a fair job. Barrels are brazed together.

(7) W. S. C. writes: 1. We use shavings for fuel. When we fill up the furnace, sometimes there is a puff, and the smoke will come out round the doors. What is the reason of this? A. Gas is formed, which, mixed with the air, is explosive. 2. What is a suction chamber connected to a suction pipe designed for? A. To ease the motion of the water in the suction pipe and prevent hammering.

(8) G.—The ear drums you ask about sell for \$3 per pair, silver mounted. For mending band saws, scarf the ends with a file to make a lap of three-eighths of an inch. Grind a piece of borax on a piece of slate or roughened earthenware, with water, to a paste. Take a piece of charcoal, grind one side flat on a stone, and hollow out a place in the middle a little larger than the width of the saw, so as to let the blowpipe flame go under the saw. Fasten the scarfed ends of the saw (after dipping in the borax) together with small binding wire, such as is used by jewelers. Then fasten the scarfed part of the blade over the recess in the charcoal with wire pins, seeing that the saw is straight. Lay a small piece of coin silver on the top at the edge of the scarf, and with the blowpipe throw the flame under the blade, heating until the silver melts, when it will flow through the scarf and appear on the under side, and your work is done.

(9) J. A. T. asks amount of pressure per square foot with the wind blowing at 20, 30, 40, 50, 60, 70, and 80 miles an hour. A. 2,  $4\frac{1}{2}$ , 8,  $12\frac{1}{2}$ , 18, 25, and  $32\frac{1}{2}$  pounds.

(10) K. G. McL. asks (1) how to temper clay that is used in making cast iron water pipe joints? A. By thoroughly working with water and fine sand. 2. How to tell tempered clay? A. By its soft, tenacious feel.

(11) F. P.—Valves should have the full area of the suction pipe, and should lift  $\frac{1}{2}$  of their diameter.

(12) F. D. W.—In the vicinity of New York, tin waste is utilized by the chemical manufacturing companies, for the production of tin salts and polishing powders. The tin scrap is boiled in hydrochloric acid, or sodium hydrates, from which are reduced the salts and pigments used in the arts. Do not know of any patents on these processes.

(13) W. T. F.—The difference in pressure between the top and bottom of a boiler is due to the weight of the water, which is about 0.43 pound per inch for each foot in height of solid water. This should make no difference in choice of the place for the entrance of the feed water.

(14) P. L. asks: 1. Will an eight horse power boiler, using steam at 65 or 70 pounds per square inch, run an engine of four horse power (really a six horse engine, but speeded down to four) and heat a room 45x80 feet and room about 25x80 feet, using the exhaust while engine is running, but having pipe connections, so that live steam can be turned in when engine is shut down? The boiler is a first class upright tubular one, having heating surface equal to over eight horse power, and with inspirator. If boiler will not heat rooms and run engine, how large a boiler will it need? A. It requires one-half the power of your boiler to heat the rooms. If you use the exhaust steam for heating, adding a small jet of live steam when required, you may accomplish considerable economy in fuel. For this purpose, better consult with some steam heating engineer as to details. 2. A plumber in this town claims that there is no more heating capacity in steam at 60 than at 8 pounds per square inch. Is he right? A. He is wrong.

(15) W. T. F.—Multiplying the square of the diameter by 0.7854 gives the area of the piston; multiply the area by the pressure for the whole pressure on the piston. To get the mean engine pressure when a cut-off is used requires a special computation, which you may find in Haswell's Engineer's Pocket Book. A steam gauge will not be harmed at 2 or 3 inches from the boiler, provided there is a siphon below it to keep the steam from heating the interior of the gauge. The firm from whom you purchased the gauge will have it tested.

(16) L. J. S.—Cold cellars, as arranged in New York on the plan you state, have a uniform temperature of 33 to 34 degrees Fah. Such cellars have a pipe surface of one square foot to each 10 cubic feet of space, or 1 lineal foot of inch pipe to  $3\frac{1}{2}$  cubic feet of space. The manner of circulating is of importance. It is desirable that the individual circuit or travel of the brine should not be over 200 feet in length, and that the coils should be so arranged that every pipe shall have an equal circulation. The brine should be kept at near the point of saturation. The ice need not be crushed fine, but rather in lumps, keeping the tank full of ice, with an overflow for the waste brine. The return stream should pour on top of the ice, and the outflow from near the bottom of the tank, with an ample strainer, the salt being fed with the ice. The "tank pumps" are also preferred as a circulating power, as they move nearly twice the quantity of brine with the same size steam cylinder that the power pumps do. Rapidity of circulation is important.

The circulating pipes should be covered with frost when the conditions are right. There is no better or cheaper process with chemicals, except with a refrigerating machine.

(17) W. F. B.—A locomotive built by the Baldwin Locomotive Works, for the Central Railroad of New Jersey, has made 75 miles per hour on straight track, with 5 passenger cars. There are other locomotives in England and the United States that can do as well or possibly a little better for short drives. See SCIENTIFIC AMERICAN SUPPLEMENT, No. 231, for a description of the Baldwin locomotive.

**MINERALS, ETC.**—Specimens have been received from the following correspondents, and examined with the results stated.

G. B. C.—Nothing definite can be said concerning the specimen unless it was analyzed. It appears, however, to be graphite. Its value depends upon the extent and availability of the deposit.

### TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. In addition to our facilities for preparing drawings and specifications quickly, the applicant can rest assured that his case will be filed in the Patent Office without delay. Every application, in which the fees have been paid, is sent usually to the Patent Office the same day the papers are signed at our office, or received by mail, so there is no delay in filing the case, a complaint we often hear from other sources. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, N. Y.

## INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

March 23, 1886,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Acid compounds, manufacture of salicylic, B. Schmitt.....	338,365
Acid, etc., apparatus for the manufacture of sulphurous, Ritter & Kellner.....	338,557
Alarm. See Burglar alarm. Fire alarm. Locomotive whistle alarm.....	
Alloy, O. M. Thowless.....	338,317
Animal catching device, C. F. Morley.....	338,606
Atomizer, A. M. Shurtleff.....	338,367
Auger, post hole, G. W. Smith.....	338,648
Axes, making, C. W. Hubbard.....	338,270
Axle lubricator, B. M. Freiligh.....	338,661
Axle lubricator, J. C. Nichol.....	338,287
Axle, roller and extension, A. L. Adams.....	338,459
Bag. See Hand bag.....	
Bail fastening or clutch, H. W. Eames.....	338,342
Bail, kettle, J. E. Gaitley.....	338,506
Banjo, B. E. Boyden.....	338,335
Bannerette, G. R. Osborn.....	338,356
Barium, manufacture of anhydrous oxide of, L. Q. & A. Brin.....	338,628
Barrel head, J. R. Allgire.....	338,379
Bearing, anti-friction, G. D. Burton.....	338,657
Beehive, W. M. Myers.....	338,285
Beehive, J. M. Shuck.....	338,647
Beer, compound for purifying, B. Mueller.....	338,284
Belt, electric, J. H. Woodward.....	338,683
Belt fastener, E. C. Smith.....	338,565
Billiard table leveler, E. A. Hornbostel.....	338,667
Binder for music, periodicals, etc., J. C. Koch.....	338,350
Blackboard, school, J. Frey.....	338,397
Boat. See Sectional and folding boat.....	
Boiler. See Steam boiler. Steam heater boiler. Water tube boiler.....	
Boiler furnace, A. Backus, Jr.....	338,462
Boilers, water heating apparatus for, Welch & Crooks.....	338,453
Bolt. See Door bolt. Indicator bolt.....	
Bolts, machine for making thimbles for, J. T. Smith.....	338,567
Boiling reel cloths, cleaner for, G. S. Burnap.....	338,430
Boot-tree, E. W. Whitmore.....	338,575
Bottle stopper, C. K. Hamilton, Jr.....	338,348
Bottles, etc., apparatus for rinsing or washing, F. Cuntz.....	338,587
Bottles, valve stopper for, A. B. Vanes.....	338,571
Box. See Safety collecting box.....	
Brake. See Car brake.....	
Brick, concrete block, etc., H. C. Cowan.....	338,490
Broom support, F. S. Capron.....	338,248
Brush, blacking, B. G. Fitzhugh.....	338,504
Brush handle and holder combined, C. Buck.....	338,476
Brushes, etc., rack and holder for tooth, N. W. Griswold.....	338,402
Buckle, J. F. Winter.....	338,327
Buckle and trace loop, combined pad, A. Hartz.....	338,408
Buildings, construction of wooden, C. C. Gilman.....	338,509
Buildings, outer wall of, C. C. Gilman.....	338,514
Burglar alarm, J. E. Church.....	338,388
Burglar alarm, A. C. Tonner.....	338,319
Butter and other materials, treatment of rancid, C. Marchand.....	338,538
Button, H. R. Heath.....	338,409
Button, J. S. Hovey.....	338,269
Button and fastening, E. P. Whitney.....	338,377
Button fastener setting instrument, F. H. Richards.....	338,554
Button fly-scalloping machine, C. B. Hatfield.....	338,665
Buttons, making, J. F. Thayer.....	338,373
Cable tension device, T. W. Burt.....	338,357
Can, D. C. Mory, Jr.....	338,432
Candle holder, barbed, A. Grafke.....	338,594
Candy, etc., mixing and heating and cooling kettle for, T. Burkhard.....	338,583
Car brake, M. J. Moriarty.....	338,283
Car coupling, J. C. Fowler.....	338,635
Car coupling, J. T. Hammick.....	338,405
Car coupling, C. E. Mark (r).....	10,702
Car coupling, W. Powell.....	338,297
Car door fastener, F. P. Hanchett.....	338,519
Car motor and brake, Morell & Goff.....	338,642
Carbon from hydrocarbon vapor, apparatus for producing, hard, J. J. McTighe.....	338,605
Carbon, manufacture of hard, J. J. McTighe.....	338,542
Carpet sweeper, J. Hinkley (r).....	10,701
Carriage seats, detachable back for, H. Mankel, Jr.....	338,537
Carriage standard, H. Biggs.....	338,655
Carriage top prop, L. E. McKinnon.....	338,281
Carrier. See Trace carrier.....	
Case. See Measuro case. Watch case.....	
Cash and parcel transfer system, electric, G. F. Green.....	338,663
Cash and parcel transmitting apparatus for store service, Stearns & Grant, Jr.....	338,369
Caster, A. C. Frankel.....	338,636
Centrifugal power, continuous apparatus operated by, A. J. A. Dumoulin.....	338,393
Centrifugal reel, H. E. Beerling.....	338,466
Chair. See Invalid chair. Rail chair.....	
Cheese cutter, E. L. Liedke.....	338,533
Chimney top, C. W. Carll.....	338,249
Churn, T. E. Macy.....	338,280
Cigarette machine, pocket, L. L. Arnold.....	338,590
Clamp. See Keying clamp.....	
Clarifying extracts, A. Morand.....	338,431
Clasp. See Spring clasp.....	
Clip apparatus for transporting loads by means of ropes or cables, Roe & Bedlington.....	338,615
Clothes drier, H. Normandy.....	338,288
Clothes hook, N. Rubenstein.....	338,677
Coffin, B. Morris.....	338,547
Combination lock, J. C. Culmer.....	338,586
Comminuted substances, method of and apparatus for manipulating, A. Morand.....	338,430
Composing stick, C. Frecker.....	338,259
Cooking vessel, C. J. Parker.....	338,547
Copying press, G. W. Williams.....	338,625
Cords in the seams of textile and other fabrics, method of inserting, J. Pusey.....	338,613
Cotton chopper, J. C. Farley.....	338,255
Coupling. See Car coupling. Thill coupling.....	
Creamery, N. Yingt.....	338,577
Cultivator, Peters & Skinner.....	338,234
Cutter. See Cheese cutter. Rod cutter. Vegetable cutter.....	
Damper regulator, automatic, J. E. Spencer.....	338,636
Desk and seat, school, I. Osgood.....	338,745
Desk, cabinet, F. A. Coffin.....	338,632
Desk, school, J. F. Bigger.....	338,468
Desks, foot rest for school, W. P. Conner.....	338,487
Ditching machine, tile, H. Sullivan.....	338,678
Door bolt, S. A. Kintner.....	338,640
Drier. See Clothes drier. Grain drier. Lumber drier.....	
Drill frame anchor, E. Bittenbender.....	338,469
Dust collector, N. W. Holt.....	338,639
Dyeing and washing wool and cotton, machine for, W. & M. Pollard.....	338,438
Easel, Osborn & Gregory.....	338,555
Electric coupler, automatic, J. S. Raworth.....	338,350
Electric generator, dynamo, C. J. Van Depoele.....	338,320
Electric machine, dynamo, C. Batchelor.....	338,333
Electric machine regulator, dynamo, R. E. Ball.....	338,333
Electric meter, J. S. Raworth.....	338,549
Electric meter, S. Z. de Ferranti.....	338,588
Electric motor, G. H. Stout.....	338,622
Electrical currents, system of generating, C. J. Van Depoele.....	338,321
Electrical subway, C. C. Gilman.....	338,514
Electro-magnetic poise adjuster, C. W. Hastings.....	338,522
Electro-magnetic reciprocating engine, C. J. Van Depoele.....	338,375
Elevator. See Water elevator.....	
Embroidering machine, E. Cornely.....	338,438
End gate, wagon, Noyes & Gardner.....	338,545
Engine. See Electro-magnetic reciprocating engine. Motive power engine.....	
Eraser, J. Pusey.....	338,299
Eye bars, apparatus for rolling, C. L. Strobel.....	338,623
Fan, automatic, Smith & Caldwell.....	338,511
Fare register, J. W. Meaker.....	338,426
Faucet, D. & T. Morris.....	338,563
Fence, N. E. Weisell.....	338,573
Fence wire, tension apparatus for, J. M. Overpeck et al.....	338,610
Ferments, manufacture of pure non-organized, M. Blumenthal.....	338,471
Fiber and fibrous matter, treatment of, F. B. Greene.....	338,595
Fifth wheel, E. M. Simmons.....	338,562
Fifth wheel gear for vehicles, J. G. Ebken.....	338,594
File and binder for pamphlets, bills, etc., J. R. Pitt.....	338,675
File cabinet for papers, etc., C. H. Moulton.....	338,643
File, newspaper, W. F. Winship.....	338,682
Files, cabinet for holding paper, H. W. Reade.....	338,300
Filter, J. C. Higgins.....	338,411
Filter, J. W. Hyatt.....	338,414
Filter press, Remmers & Williamson.....	338,568
Finger nail polisher, G. H. Broadhurst.....	338,245
Fire alarm, A. C. Gordon.....	338,593
Firearm, breech-loading, J. C. Broyles.....	338,247
Firearm, safety lock, H. C. Waldecker.....	338,541
Fire extinguisher, chemical, R. A. Ballou.....	338,242
Fire extinguisher, hand, W. M. Harrison.....	338,520
Fireproof post and column, C. C. Gilman.....	338,512
Floor and ceiling, fireproof, C. C. Gilman.....	338,513
Floor arch, C. C. Gilman.....	338,516
Floor, fireproof, C. C. Gilman.....	338,510
Floors and ceilings, construction of, fireproof, C. C. Gilman.....	338,517
Foot power machine, W. L. Perry.....	338,437
Forceps, digital, S. R. Wilcox.....	338,324
Fruit gatherer, J. N. Rudd.....	338,303
Fuel apparatus, vapor, A. I. Ambler.....	338,461
Furnace. See Boiler furnace.....	
Furnace door, J. A. Roney.....	338,616
Furnace for precious metals, C. L. Hartsfeld.....	338,365
Furnaces, shaking grate for, C. Scheef.....	338,305
Gas conveying conduit, J. Schinneller.....	338,559
Gas regulator, E. C. McCloy.....	338,422
Gate. See Railway safety gate. Wagon end gate.....	
Gate, M. B. & W. Y. Gordon.....	338,401
Gate, K. H. C. Preston.....	338,298
Generator. See Electric generator. Steam generator.....	
Glue, manufacturing, K. Upton.....	338,374
Grain binder, E. M. Kellogg.....	338,417
Grain drier, M. L. Mowrer.....	338,673
Grain for fermentation, preparing whole, Andersen & Woolner, Jr.....	338,579
Grinding mill, L. B. Joy.....	338,416
Hammer, G. F. Hall.....	338,404
Hand bag, C. H. Buchanan.....	338,475
Hand grenade extinguisher, W. W. Luyster.....	338,604
Handle. See Knife handle. Rein handle. Stove door handle. Tool handle.....	
Harness ring, J. F. Smith.....	338,568
Harrow, W. J. Lane.....	338,531
Harvesters, main wheel for, W. N. Whiteley.....	338,376
Harvesting and binding machine, S. Johnston.....	338,273
Hat, F. H. Crafts.....	338,584