

America's cup, for which the British cutter Galatea is now the avowed competitor. Whether the Atlantic will fulfill her mission, and win the honorable office of defending the cup, will be determined by the preliminary races between the four competitive American clippers, the Puritan, Priscilla, Mayflower, and Atlantic. Each boat has its champions, but they are all so admirable that the most experienced yachtsmen hesitate to express any opinion about the result of the forthcoming trials. The success of the Puritan has made the superiority of the centerboard over the cutter a foregone conclusion in the minds of nearly all American yacht owners. This confidence has made the interest in the national contest much more lively at present than in the real contest between the American champion and the British challenger. Apparently, everything possible has been done to make the successful clipper, whichever she may be, a worthy representative of the most advanced principles of American yacht building.

Iron Foundations for Heavy Guns.

In case of a war with foreign powers, we should be forced to the rapid construction of temporary fortifications behind earthen parapets. One of the great difficulties in the way of such construction is the time required for building properly the heavy, massive masonry foundations up to this day regarded as necessary under heavy guns. This difficulty may be now avoided (according to Captain W. H. Bixby, Corps of Engineers, U. S. Army) by the use of wrought iron instead of masonry for these foundations.

Captain Bixby proposes to replace the present slowly built, difficultly moved, difficultly leveled masonry foundations for heavy guns behind earthen parapets by rapidly constructed, easily moved, easily leveled wrought iron foundations, to rest on cross girders or sleepers, embedded in the earth of the terre-plein, and provided with a front parapet anchorage sufficient to resist all direct recoil.

The holding power of anchorages embedded in mere earth is well known by the experiments of our Q. M. Department on suspension bridge anchorages during the war of 1861-65, and it is also well shown by the Shoeburyness experiments of 1881 (see p. 41, Part 2, of Captain Bixby's report on "Sea Coast Fortifications in Europe").

A 40-foot earthen parapet and suitable iron rod and cross girder anchorage may well be trusted to resist and absorb all the direct horizontal recoil of even a 100-ton gun, leaving to the foundation alone the lighter duty of supporting the carriage and gun and the comparatively small vertical component of the recoil.

An iron girder foundation, resting on sleepers and earthen bed, may be fairly well trusted to serve as an efficient support to the vertical weights and blows of our heavy guns, after the first few rounds have been fired. A little unequal settlement may naturally be expected, but such settlement is of minor account today, for two reasons: first, heavy guns of the present and future must be traversed by machinery, and such machinery will overpower the slight extra resistances due to unequal settlement of the gun's platform; second, whenever an unequal settlement becomes marked and objectionable (probably not oftener than once in a month during action), the iron girder foundation can be jacked up and earth tamped in underneath it (exactly as is currently done to remedy similar unequal settlements of railroad tracks).

It seems now quite probable that future fortification in the United States (when it does come) will demand economy of time rather than economy of money. In any case the advantages which may arise from rapidity of original construction, rapidity of construction in place, facility of repair, facility of change of position if necessary to allow of other angles of fire, facility of replacement if necessary to allow of guns of greater weight and size—all these advantages appear sufficient to authorize at least the trial of such a foundation under one of our heaviest guns.

Captain Bixby's suggestions are now being considered by the War Department, and will undoubtedly lead to some change in the present slow methods of gun foundation construction.

The Tongue in Disease.

One of our medical contemporaries states that different complaints are indicated by the condition of the tongue, as follows:

A white-coated tongue indicates febrile disturbance; a brown moist tongue indicates disordered digestion or overloaded primæ viæ; a brown dry tongue indicates depressed vitality, as in typhoid conditions and blood-poisoning; a red moist tongue indicates debility, as from exhausting discharges; a red dry tongue indicates pyrexia, or any inflammatory fever; a "strawberry" tongue with prominent papillæ indicates scarlet fever or rotheln; a red glazed tongue indicates debility, with want of assimilative power of digestion; a tremulous, flabby tongue indicates delirium tremens; hesitancy in protruding the tongue indicates concussion of the brain; protrusion at one side indicates paralysis of the muscles of that side.

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors. PUBLISHED WEEKLY AT No. 361 BROADWAY, NEW YORK.

O. D. MUNN. A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year, postage included. \$3 20 One copy, six months, postage included. 1 60

Clubs.—One extra copy of THE SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.20 each; additional copies at same proportionate rate. Postage prepaid.

Remit by postal or express money order. Address MUNN & CO., 361 Broadway, corner of Franklin Street, New York.

The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, postage paid, to subscribers. Single copies, 10 cents. Sold by all newsdealers throughout the country.

Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, postage free, on receipt of seven dollars. Both papers to one address or different addresses as desired.

The safest way to remit is by draft, postal order, express money order, or registered letter. Address MUNN & CO., 361 Broadway, corner of Franklin Street, New York.

Scientific American Export Edition.

The SCIENTIFIC AMERICAN Export Edition is a large and splendid periodical, issued once a month. Each number contains about one hundred large quarto pages, profusely illustrated, embracing: (1.) Most of the plates and pages of the four preceding weekly issues of the SCIENTIFIC AMERICAN, with its splendid engravings and valuable information; (2.) Commercial, trade, and manufacturing announcements of leading houses. Terms for Export Edition, \$5.00 a year, sent prepaid to any part of the world. Single copies, 50 cents. Manufacturers and others who desire to secure foreign trade may have large and handsomely displayed announcements published in this edition at a very moderate cost.

The SCIENTIFIC AMERICAN Export Edition has a large guaranteed circulation in all commercial places throughout the world. Address MUNN & CO., 361 Broadway, corner of Franklin Street, New York.

NEW YORK, SATURDAY, MAY 22, 1886.

Contents.

(Illustrated articles are marked with an asterisk.)

Table listing various articles such as 'Art in the garden', 'Inventions, index of', 'Belts, a carrier through a mill', 'Inventions, mechanical', etc., with corresponding page numbers.

TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT No. 542.

For the Week Ending May 22, 1886.

Price 10 cents. For sale by all newsdealers.

Detailed table of contents for the supplement, including sections like 'I. CHEMISTRY', 'II. ELECTRICITY', 'III. ENGINEERING AND MECHANICS', 'IV. GEOLOGY', 'V. HYGIENE AND MEDICINE', 'VI. MILITARY ENGINEERING', 'VII. NATURAL HISTORY', 'VIII. PHYSICS', 'IX. SANITARY ENGINEERING', 'X. SOCIAL SCIENCE'.

AN UNDERGROUND RAILWAY FOR NEW YORK CITY.

In March, 1870, the SCIENTIFIC AMERICAN published illustrations of an underground railway which had then been built, for a distance of one block, under Broadway, New York. It was known as the Beach pneumatic tunnel road, the cars to be propelled by compressed air, but was never completed, except for a distance of about two hundred feet. From that day to this, the project of an underground Broadway railroad has come up at almost every session of the State Legislature, until a bill for this purpose has at last been passed, and received the Governor's signature. There are said to be grave doubts about the constitutionality of the act, which will have to be settled before the work of building is actually begun, but the names of the eminent capitalists and business men connected with the enterprise afford an assurance that this great undertaking will now be prosecuted in earnest.

By the plan adopted, the company is allowed forty-four feet under the surface, the least width between the sidewalks on Broadway being, for a short distance, thirty-nine feet, and the average width being about forty-nine feet. The sewers, water, gas, and steam pipes, with tubes for wires, etc., are to be carried in vaults and subways of brick or iron, to be built and kept in repair by the company; they are to be open for entrance at every quarter of a mile distance, and it is estimated will cost \$400,000 a mile. This will, of itself, be a great saving to the city, and obviate the necessity of the frequent tearing up of the pavement, at present so great a source of public inconvenience. The kind of power to be used is not specified; it may be electricity or any motor not emitting smoke, gas, or cinders.

During construction, a temporary bridge is to be maintained over all places where the work is going on, so that travel will not be interfered with during the progress of the work. The road is to extend under Broadway from the Battery to Fifty-ninth Street, a distance of about four and a half miles, with a branch at Madison Square to Forty-second Street, but both of these lines to be further continued, if found desirable, in the future. The sections named are to be completed within five years, and the city is to receive for the privileges granted three per cent. of the gross revenue. The capital stock of the company is fixed at \$25,000,000, and the cost of building is variously estimated at from \$3,000,000 to \$6,000,000 per mile.

The only work in the world at all similar to this proposed arcade subway under Broadway is the underground railway system of London, by which that city is belted by a nearly complete double circle of subterranean roadway, though with many open cuttings within high walls. These underground roads cost from two and a half to four million dollars per mile, and pay from three to four per cent. interest on the capital invested. Although the total population of London is more than four millions, while that of New York should not be placed higher than probably one-third of this, the rapid growth of the latter city, and its peculiar configuration, determining most of its travel in main north and south lines, seem to indicate that the new road is likely to have as large a business, in proportion to its mileage, as its London predecessor. Let us hope that it will, also, be as well and solidly built, for the London road is, both in its building and operating, a most creditable example of a high order of engineering skill.

PROGRESS OF INDUSTRIAL ELECTRICITY.

"How was that made?"

This question was asked of a prominent metal merchant as a vessel was handed him, made in the shape of a head-light reflector. It was composed of copper about one sixty-fourth inch thick, tough, pliable, and very smooth on the inner surface. Examining the edges of the flange, the merchant noticed that the thickness of the metal did not vary in the least around the entire rim.

"It was spun."

"No."

"Stamped."

"No."

"Pressed."

"No."

"Cast? Impossible."

"No, it was not cast."

"Then it must have grown."

It had grown, but it was with the rapidity that only electricity can give to growth.

The process by which the above casting or vessel was made is as follows:

A rigid male form is made of the approximate shape and less in size than the article wished to be reproduced. This form is then immersed in a kettle of refined wax, paraffine, or similar substance.

The shape of form will decide in what position the form is to be held; in the case of a reflector, the form is held with small end up. The wax must be pure, and free from dirt or water to get best results. The wax is heated so that it will run nicely. By immersing form in kettle and withdrawing vertically, the wax will run smoothly, and as it cools in a few seconds leaves a smooth, true surface. This surface is now rendered