

vanized wire sieves distributed between the coils of steam pipes. Air for drying is admitted at the bottom of this shaft along the floor by slide doors. And to carry off the moist air I now use natural draught, by a wooden stack, 4 feet square and 20 feet high; at one-third of the distance from each end of the shaft, two more moist air draughts, each 4 feet square, connect with the 20 foot high stack from the top of the center of the shaft or evaporator. When I run this evaporator up to its full capacity, it puffs up and sweats the fruit with only 150° of heat. If I should put an exhaust fan in the center of the moist air stack, would it stop this sweating and cooking process of the fruit that I am now troubled with? If it would, what kind and size of fan would it require to give the best results for this sized evaporator? A. It appears from your description that the ventilation of the evaporator is not equally distributed, or is weak at the ends. This should be tested by thermometers at points out of the direct current of air through the evaporator, to ascertain inequality of temperature, and if found, should be regulated by increasing the number of vents and lessening the size. The wire sieves should not be too close to the steam pipes, as the strong radiant heat would cook the fruit, when a thermometer hung up in the moving air would only indicate 150°. If you had only one row of steam pipe with the fruit above it, or in other words, spread the plant over a larger area with less height, the cumulative heat of air circulating through 5 rows of coils would be avoided. We apprehend (although you failed to state it) that the trouble is on the upper shelves at points of least circulation. A common fan blower of 2 feet diameter, blowing the air into a chamber under and along the bottom of the evaporator, with perforations to equally distribute the air, might prevent cooking in the hot parts, but would make the lower tier too cool for effective service. The most effective driers for fruit have all the heat below, so that air of the same temperature pervades the whole chamber. This arrangement is largely used in New York and other places for drying fruit.

(549) H. L. asks: 1. Would it cost any more to run the dynamo after it was set up and ready to run than it would cost to run oil lamps for the same amount of light? A. Oil lamps are more economical than incandescent electric lights. 2. In what SUPPLEMENT can I find it described in full? A. SUPPLEMENT, No. 600. 3. How are the magnet arms secured to the base and top, and of what kind of iron are all the castings made? A. This information is given in the SUPPLEMENT referred to. 4. What do you mean by the polar extremities? A. The extremities in which the magnetic poles are developed. 5. Would not copper bars do instead of the bronze bars of the commutator? A. Yes. 6. Where can I get copper or bronze? A. Consult our advertising columns. 7. Can I melt copper or bronze in a blacksmith's forge, and in what? A. You can melt it in a Hessian crucible. Heat the crucible and its contents gradually at first. 8. How can I mould the metal for the commutator cylinder. A. Use ordinary moulding sand. 9. Would it not do as well to solder the ends of the armature wire to the commutator cylinder as to screw them? A. Solder is apt to fail in such a place. 10. With what size wire shall I wrap the armature and magnet of a twelve-light machine, made on the same principle as the eight-light machine? A. Wrap the armature with No. 18 wire. Apply four extra layers of wire to the magnet, and increase the speed.

(550) A. V. asks: Would you be so kind as to let me know how many layers and how many turns in each layer of No. 10 copper wire will bring a magnet to its maximum point, the core of which is soft iron, being 1 1/2 inches in diameter, 10 inches long, being in circuit with 250 1/2-candle power lamps connected in multiple arc, from a dynamo having 72 volts? A. We presume that your lamps are 70 volt; if so, their resistance is very slight, and you cannot afford to introduce more than a fraction of such resistance in series with them. Thus No. 4 wire would introduce a resistance of about one-tenth ohm, or nearly one-third that of your lamps, reducing their illuminating power seriously. Your proper method is to use heavy wire, and if necessary increase the size of the core, and as a last resource use lamps of lower voltage.

(551) O. T. H. writes: 1. In the SCIENTIFIC AMERICAN SUPPLEMENT, April 14, 1888, No. 641, page 10240, on the 31st line, about how to make a simple electric motor, it reads: "The size of the iron wire of the core is No. 18 American wire gauge," and on the next page, the 7th line from the last, it reads: "Size of wire on armature, Am. W. G. No. 16." Please tell me which one is right? A. Both. No. 18 iron wire is right for the core, and No. 16 is right for the coils of the conductor wound upon the core. 2. What is meant by a disk of vulcanized fiber? A. Vulcanized fiber is an insulating material used largely in electrical work. 3. How much will it cost to run the simple electric motor for eight hours? A. Seventy-five or eighty cents. 4. Which is the easiest way to make a cell of plunging bichromate battery, having one zinc plate 5x7 inches and two carbon plates of the same size? A. Place the zinc plate between two paraffined quarter inch bars of wood. Place the carbon plates outside of the strips, and clamp the carbon plates and the zinc plates together by means of a pair of paraffined bars of wood three-quarters of an inch thick, and extending beyond the edges of the plate.

(552) F. G. W., Denver, writes: On Sunday, February 3, there were three groups of spots on the sun in the form of a triangle. These groups seemed to be composed of minute spots. On Monday afternoon, February 4, we had a violent dust and wind storm. It continued through the night. On Tuesday afternoon, February 5, I observed the sun. The spots had disappeared. With my strongest eye piece, giving a power of 100, I could not detect a trace of the spots. I am almost certain that there was some connection between the storm and the spots. Would a solar cyclone, or something like it, produce such a storm? A. The past season has been a period of minimum sun spots, and any sudden outburst of spots upon the sun at such periods indicates abnormal conditions of activity at the solar surface, which at times heretofore have caused coincident magnetic storms upon the earth. These magnetic storms have been followed by wind storms. It seems to be pretty well established that there is an almost

instantaneous coincidence of magnetic effect upon the earth derived from solar disturbance. This may also resolve itself into its electrical equivalent and become observant in corresponding meteorological phenomena.

(553) R. A. W., "Adams Co."—In the SCIENTIFIC AMERICAN SUPPLEMENT, No. 182, and in others you will find many forms of electro-magnets described. In general terms the larger you make the magnet, the greater will be the power. You might try a one inch bar of iron, two feet long, bent into U shape, and wound with 1,000 feet of No. 15 wire. This with from five to fifteen cells of Fuller battery would give an excellent effect.

(554) G. E. T.—White military belts can be made to look as good as new by the following: Dissolve 1 ounce white tallow soap in 3/4 pint of warm water and mix well therewith white of one egg and 3 ounces fine Paris white. Wipe in and rub down with a rag. White Castile soap may be used where the white tallow soap cannot be had.

(555) R. S. asks: 1. What size should I make the iron wire armature core of simple motor, March 17, 1887, if the whole armature was to be 5 inches diameter? What size iron wire would I have to use for the core, and how many layers of it would I have to wind? A. Use 12 layers of No. 18 wire. Make the core 3 inches wide. 2. What size wire would I have to use on armature, and how many layers on armature? A. Wind the core with No. 16 wire disposed in 20 coils of six layers each.

(556) J. S. S. writes: 1. I can get almost unlimited gravity battery power (nearly 300 cells), and would like to run a simple electric motor as described by you. How can I do it by this battery? A. If you wish to use all the cells, place 16 in series and as many as you wish in parallel, the more the better. A. Gravity battery, owing to its high resistance, is ill adapted to this work. 2. In the storage battery does the current decompose the water? A. Not unless the current is continued after the battery is fully charged. 3. (a) What is the amount of the dangerous alternating current? (b) Of the continuous? A. (a) 600 to 700 volts. (b) About the same.

(557) W. A. R. asks: Can you change the center of gravity of a dish by filling it with water, or in other words, can you make a hollow vessel or dish of such a shape that it will tip over by filling it with water? A. To a pipe inclined at an angle of 45° attach a small base of sufficient weight to support the pipe while empty. Such a vessel when filled with water will tip over.

(558) C. E. B. asks: 1. If five Leclanche cells were to be set up in one common solution without the glass jars, would such a battery be equal in power to one of the usual form of separate jars? A. No; its power will be scarcely more than that of a single cell. 2. How many electric light carbons six inches long should I use to each zinc in a sal-ammoniac battery to get the best results? A. 9 or 10. 3. For electric gas lighting should the zincs and carbons be connected one to the other, or should they be connected separately? A. For a single lamp the zinc of one cell should be connected with the carbon of the next, and so on. For a number of lamps the elements would have to be connected according to the voltage of the lamps. 4. Would such a battery as described above or a Leclanche battery work with a solution of salt (chloride of sodium)? A. You can get a current from a Leclanche battery charged with a solution of common salt, but it is not equal to sal-ammoniac, and it evolves chlorine, which is disagreeable. A Leclanche battery is very quickly polarized in active service, and takes time to recover.

(559) H. D. H. asks: Have ice boats been known ever to make 100 miles an hour, and about what rate of wind would be necessary for that speed under the most favorable circumstances? A. We have no record of so high a speed as 100 miles per hour for an ice boat. A 60 mile gale might produce the speed if the boat could preserve its leeway, or hold up to the wind, which is very doubtful. Probably from 50 to 60 is the highest speed ever attained. See SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 54, 61, 214, and 220, for sailing faster than the wind.

(560) W. F. P. writes: 1. I find the battery described in the SCIENTIFIC AMERICAN for December 17, 1887, soon becomes polarized. Will you kindly inform me through your Notes and Queries how I may remedy this? Is it necessary to amalgamate the zincs off? A. All single-fluid bichromate batteries are unsatisfactory as regards constancy of current. You cannot remedy it. 2. Is there any hand dynamo described in your paper that may be constructed without castings? Is the simple electric motor suited for this purpose? A. The trouble with a dynamo having soft iron laminated magnet cores, such as used in the motor named, is that it is hard to start the current for want of residual magnetism. We advise you to adhere to cast iron cores for small machines.

(561) A. A. writes: With regard to the simple electric motor in the SCIENTIFIC AMERICAN SUPPLEMENT, No. 641, of April 4, 1888, page 10240, will you be kind enough to inform me if a field magnet with the body made of cast iron would be as efficient as one made of strips of Russia iron, such as described in the article? A. The difference is slightly in favor of the Russia iron or wrought iron magnet, but if you use very soft gray cast iron, the difference will not be perceptible.

(562) Motor.—Any device which will keep the bars of the commutator smooth and clean would be worthy of a patent, and could be patented if new.

(563) A. P. asks for the value of coal gas for cooking purposes. Is it to be preferred to coal, and is it more economical than coal? Could you give me the address of a good maker of gas stoves? A. Coal gas for cooking saves the annoyance of ashes and dust, and if properly used, is in many cases not more expensive than coal, as it can be extinguished as soon as the cooking is over. For gas stoves apply to your gas company, or consult our advertising columns.

(564) W. J. H. asks: 1. Will the dynamo described in SCIENTIFIC AMERICAN SUPPLEMENT, No. 600, run lights enough to light a room 20x40x12? A. The dynamo will run eight to twelve 16 candle power lamps—hardly enough for room you mention. 2. What kind of lamps are the best to use with it? A. Use Edison or other incandescent lamp, 60 volt, arranged in parallel. 3. How much power does it require to run the dynamo, and what would be the running expense of the lamp per hour, when run from 4 to 6 hours a day? A. About one horse power. A lamp will last about 400 hours. From these data you can make your own calculations, based on expense of fuel, etc., in your locality.

(565) A. H. asks: 1. What is paraffine wax made from? A. It is made largely from distillation of coal at low temperatures. Ozocerite, a natural mineral, is also an extensive source. 2. At what temperature does it run best (to mould)? A. Different samples melt at different temperatures; such as requires 112° Fah. or more is adapted for casting. When well fused, you can pour it into the moulds. 3. Is oil proper to use? A. No. Generally you will require nothing on the mould. 4. How do you cleanse it? A. Melt it and keep in fusion until impurities either settle or rise to the top, when they can be removed. You can wash it with hot water or filter while hot through flannel. Chemical treatment involves heating with strong acids or alkali, according to the nature of the impurities, followed by washing.

(566) H. S. C.—For description and tests of the modern great guns see SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 230, 256, 450, 510, 583, 600, 617, 615. For the great battles of the world, see Fisher's "Outlines of Universal History," which we can mail for \$3.50. We know of no successful attempts at aerial navigation without balloons.

(567) F. V. B. asks how to temper drills to drill surface rocks and bowlders, some of the hardest granite, others more like flint, and what steel is best to make the drills of? A. Use what is called "drill steel" in the hardware trade. Make the cutting edge rather thick, and do not draw the temper. Any blacksmith can forge and harden such drills at the lowest heat without drawing the temper.

(568) H. W. G.—Belts that slip from overwork are benefited by lagging the pulleys. It is true that two cylinder engines at right angles have no dead center without a balance wheel.

Enquiries to be Answered.

The following enquiries have been sent in by some of our subscribers, and doubtless others of our readers will take pleasure in answering them. The number of the enquiry should head the reply.

(569) C. P. T. writes: The months of January and March of this year have each two new moons on the first and thirty-first days, while February has none. Can you tell me how long it will be until another such event occurs?

Replies to Enquiries.

The following replies relate to enquiries recently published in SCIENTIFIC AMERICAN, and to the numbers therein given:

(404) H. R.—Water Power, etc.—For estimating the value of a water power, multiply the water flowing in the stream in cubic feet per minute by 62.4 (the weight per cubic foot) and by the fall in feet. Divide this product by 33,000 for the horsepower. See SCIENTIFIC AMERICAN SUPPLEMENT, No. 616, on water power. 2. Set posts butt down. 3. Bark on, wet or dry as convenient. 4. Charred posts last 50 per cent longer than uncharred. 5. Winter is the best time to cut posts.

(405) C. A. A.—Roofs.—Water from a galvanized iron roof is not safe. The roof should be painted with iron oxide paint. Galvanized iron pipe is largely used for conveying water, and is considered safe if water is allowed to run constantly. Tin makes the best roof, all things considered. Water is safe to drink from a roof painted with oxide of iron paint.

Books or other publications referred to above can, in most cases, be promptly obtained through the SCIENTIFIC AMERICAN office, Munn & Co., 361 Broadway, New York.

TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted March 12, 1889, AND EACH BEARING THAT DATE. [See note at end of list about copies of these patents.]

Acid, alizarine-blue sulpho, R. Bohn	399,480
Acid, alizarine-blue sulphuric, R. Bohn	399,481
Aerial railway or wire tramway and appliance therefor, J. Prittie	399,383
Air brake, J. B. Lapsch	399,420
Alarm for doors, etc., N. J. Busby	399,242
Album, O. J. Griffiths	399,324, 399,325
Alizarine indigo blue, R. Bohn	399,482
Alizarine green, R. Bohn	399,479
Amalgamator, centrifugal, W. White	399,590
Armature, dynamo, J. A. Hayes	399,328
Atomizer, R. S. Knode	399,539
Auger bit, F. T. Wyckoff	399,595
Axle box, car, W. S. G. Baker	399,467
Axle lubricator, car, T. B. Bishop	399,369
Axle lubricator, car, G. W. Parker	399,627
Axles, toughening steel, J. Coffin	399,360
Bag holder, Bradshaw & Meek	399,373
Baling press, E. Beadle	399,472
Baling press, power, W. W. Seely	399,568
Baling machine, twine, I. P. Miner	399,339
Balloon, C. A. Kunzel	399,271
Barrel head, J. A. Campbell	399,494
Battery. See Secondary battery.	
Bearing, roller, R. W. Hent	399,615
Bed, cot, E. J. Foster	399,154
Bed pan, rubber, A. C. Eggers	399,508
Bed, spring, D. H. Gall	399,257
Beehive, H. Penoyer	399,281
Beit fastener, E. L. Budlong	399,489
Belt shifting mechanism, J. J. Daley	399,501
Bicycle, A. G. Rose	399,285
Bicycle, G. T. Warwick	399,454
Bicycle, safety, G. T. Warwick	399,455
Bit. See Auger bit.	
Blast apparatus for blast furnaces, J. M. Hartman	399,262
Board. See Bookbinder's press board. Switch board.	
Boat. See Torpedo and gunboat.	
Bobbin, J. H. Wells	399,599
Boiler. See Range boiler. Steam boiler. Wash boiler.	
Boiler, G. F. Spencer	399,443
Boiler feeder, F. E. & M. E. Vaughn	399,586
Book, G. D. Barnard	399,469
Bookbinder's press board, J. H. Shaw	399,573
Bookcase, folding, P. Kaffenberger	399,415
Book mark, indexing, J. Lane	399,417
Book or album, N. J. Dobbins	399,249
Book stapling machine, C. E. Preusse	399,565
Books, leaf holder for, J. Hyland	399,411
Bottle cleaning machine, B. Binnington	399,477
Bottle stopper, J. J. Sands	399,440
Bottle washer, G. S. Slocum	399,576
Box. See Axle box.	
Braiding machine, W. Mundt	399,623
Brake. See Air brake. Car brake. Sled brake. Vehicle brake. Wagon brake.	
Brake, J. Fulton	399,515
Brick drying apparatus, G. B. Merrill	399,276
Bridge, swing, M. A. Redding	399,347
Burner. See Gas burner. Oil burner.	
Butter fat from milk, extracting, C. A. Johnson	399,415
Button strip for garments, H. W. Lyon	399,335
Calcing rock, G. E. Carleton	399,490
Calcing stone, etc., kiln for, G. E. Carleton	399,495
Camera adjuster, H. E. Poehlman	399,345
Can opener, J. H. Fisher	399,252
Car brake, H. W. Howell, Jr.	399,408
Car coupling, G. W. Decker	399,316
Car coupling, A. Heron	399,532
Car coupling, F. Johnson	399,333
Car coupling, D. C. McCoy	399,278
Car heater, Ruprecht & Bates	399,633
Car motor, railway, E. E. Sentman	399,572
Car, stock, J. F. Elder	399,605
Car, stock, W. H. H. Sissum	399,574
Cars, system of and apparatus for heating, R. J. Wilson	399,592
Carding engine flats, apparatus for controlling the grinding of, J. M. Hetherington	399,533
Carriage, baby, W. H. & H. N. Dunn	399,380
Carriages, fan attachment for baby, Van Nohuys & Downes	399,565
Carrier. See Trace carrier.	
Case. See Book case. Lock case. Jewelry case. Watch case.	
Cash carrier apparatus, C. W. McCormick	399,428
Cash carrier apparatus, N. Weeks, Jr.	399,457
Chair. See Rocking chair.	
Chimney cap and protector, W. W. Wright	399,594
Chimney cap or ventilator, E. P. Ryder	399,566
Clasp. See Shoe clasp.	
Cleaner. See Gun cleaner. Railway track cleaner. Sink cleaner.	
Clutch, friction, D. T. Denton	399,385
Coal, machine for cutting, T. Bower et al.	399,485
Coat and vest, combined, S. E. Reinhard	399,436
Cock, pressure regulating stop, E. Rueff	399,565
Coffee pot, E. T. Newlin	399,431
Coin-operated device, automatic, B. S. Molyneux	399,643
Coke oven, M. Sandford	399,634
Coking furnace, G. A. Clark	399,378, 399,379
Compound cabinet engine, E. W. Hemlin	399,524
Condenser for charcoal kilns, J. Fredrich	399,255
Confessional, folding, J. J. Dunn	399,388
Copy holder and register, J. C. A. Dean	399,503
Copying press, letter, C. A. Thompson	399,583
Corking and wiring corks to bottles, Wile & La Casse	399,303
Cotton presses, trumper attachment for, A. Schkade	399,441
Coupling. See Car coupling. Electric circuit coupling. Pipe coupling. Wire coupling.	
Crusher. See Ore crusher.	
Cultivator, J. A. Pearce	399,628
Cultivator, A. C. & J. D. Tower	399,296
Cultivator, hand, K. Voigt	399,300
Curtain roller, A. Sweetland	399,448
Cutter. See Weed cutter.	
Dental disk holder, H. H. Sisson	399,350
Dentist's lathe, N. W. Holt	399,406
Desk, school, W. Lippincott	399,272
Die. See Heel cutting die. Screw cutting die.	
Digger. See Potato digger.	
Dish washer, W. D. Miller	399,426
Drainage trap, J. Shaw, Sr.	399,442
Drawer, furniture, D. C. Clapp	399,598
Dredging machine, J. Edwards	399,251
Dress form, inflatable, A. M. Gelwicks	399,322
Dress shields, apparatus for manufacturing seamless, F. W. Smith, Jr.	399,637
Drill. See Seed drill.	
Drums, snare strainer for, E. E. Fry	399,336
Dye, making a brown, J. Strasburger	399,581
Dynamo machine, G. L. Du Laney	399,320
Egg poacher, W. H. Littleton	399,422
Electric circuit, J. J. Carly	399,377
Electric circuit coupling, A. C. Griggs	399,326
Electric circuit protector, W. B. Harvey	399,400
Electric generators and motors. Prevention of sparking in, D. Higham	399,402
Electric machine, dynamo, D. Higham	399,403, 399,404
Electric machines and electric motors, commutator for dynamo, B. Heywood	399,329
Electric machines and electric motors, prevention of sparking in dynamo, D. Higham	399,401
Electric meter, E. F. H. H. Laueker	399,336
Electric motor, etc., A. H. Eddy	399,507
Electric switch, H. T. Paiste	399,560
Electric wire conduit, underground, Penney & Little	399,343
Electrical distribution and conversion, system of, T. H. Hicks	399,534
Electrical distribution, system of, G. Westinghouse, Jr.	399,639