

## RECENTLY PATENTED INVENTIONS. Engineering.

**HEAT AND MECHANICAL ENERGY.**—Hermann Mehner, Hackettstown, N. J. This invention is for a method of transforming heat into mechanical energy analogous to the theory of Sadi Carnot relative to a thermo-dynamical cycle of operations, in which a substance is finally brought to the same state in all respects as it had at the beginning. The method is stated to consist principally in changing the heat form of energy into a physico-chemical form and *vice versa*, the additional heat which may be stored in water in which salt-peter is dissolved being used to illustrate the application of the invention. "By exhausting hot steam into the hot salt a full condensation takes place without the help of any cool substance or body, no heat being carried off, and the entire amount being locked up in the molten mixture, to be transferred into a suitable boiler and transformed into steam at a somewhat higher temperature, whereby steam of higher pressure is made, and at the same time salt-peter in a dry state is again obtained and also the absorbed heat, heating being done with crystallizing salt, and the steam after doing its work being again condensed by the salt." The use of other solvents or volatile solutions and combinations of salts is provided for, admitting of a large number of modifications of the process in its practical application, the end being in each case to use mixtures by which the heat now lost in operating motors may be recovered and returned to the cycle of operations of the motor, proceeding in reverse order as regards the reactions by which the "heat binding" substances employed are affected. Twelve claims are embraced in this patent, and the final claim, which is very comprehensive, is for "a method for actuating a thermo-dynamical machine by first binding the waste heat of the machine by dissolving solid substances in the vapors or their products of condensation to form a liquid, and then desiccating the liquid at a high temperature to recover the solid substance and the vapor containing the waste heat and the additional new heat of a high temperature introduced by the desiccation to form power to drive the machine."

## Railway Appliances.

**CAR COUPLING.**—Charles E. Seabury, Stony Brook, N. Y. This is an improvement on a former patented invention of the same inventor providing means for automatically coupling cars, the improvement specially providing means for holding the coupling link in a perfectly straight position, so that it will be sure to enter the drawhead of an opposing coupling. For this purpose the drawhead is made with a concave recess in the top, and attached to the link is an upwardly curved spring to fit the recess. The spring also allows the link to be moved to one side or the other or to be moved vertically, so that it may be made to enter a higher or lower drawhead.

**CAR BODY.**—John Turner, New York City. This invention covers a novel construction, especially adapted for horse, cable, and electric cars, and designed to give greater air space and more head room than is usual in the cars at present in use, while the car will not be higher, will be very strong, and can be built at the minimum cost. The construction also provides for the perfect ventilation of the car, and the arrangement is such that the ventilating apparatus may remain open in inclement weather without admitting rain or snow to the interior of the car.

**SIGNALING DEVICE.**—William Newcomb, Johnsonville, N. Y. A semaphore blade attachable at different points on a pivotally supported sectional hub has interior springs to counterbalance the weight of the blade, and is arranged for operation in connection with batteries and circuit wires and devices on a locomotive and at stations to set signals automatically by the action of electricity and gravity, to protect the moving train in front and rear. The mechanism is so constructed that a visual signal is exposed which may also be seen in the dark, thus protecting the train by night as well as in the daytime.

**RAILWAY.**—William S. Herrington, San Francisco, Cal. This invention provides for a construction especially designed for use in cities, in which the track is underground while the body of the car is above ground. A tunnel of uprights, bases, ties and braces, is constructed just below the pavement, and the casing of this tunnel is formed with a continuous central slot at the top, widened at curves, the trucks riding on their wheels on the tracks laid in the base of the casing, having each an upwardly extending hollow extension supporting a disk with a hub, on which the car body is swiveled. The roadbed will thus be formed independent of ordinary roughness of the surface, the track will not interfere with travel and cannot be obstructed by snow, and the danger from runaway accidents is greatly reduced.

**CAR AND BRAKE FOR LOGGING RAILWAYS.**—John N. Valley, Jersey City, N. J. Two patents have been granted this inventor, in addition to one for a logging railway heretofore granted the same inventor, the construction of the road, carriages and brake being also applicable for general use in transporting passenger cars, freight, etc., in situations where a quickly made and inexpensive structure is called for. The railway structure is elevated, and consists of a longitudinal log stringer supported by laterally diverging posts hangers from the stringer supporting the track. The frame of the carriage is U-shape, its upwardly ranging sides or legs carrying the car wheels to ride on each side of the suspended track. From the bottom of the carriage depend hooks for supporting the load. The drawbar is bolted to the yokes forming the carriage frame, and extends beyond both ends, forming buffers, several cars being thus conveniently coupled together. The brake for this carriage is of novel form, and the brake shoes, instead of being applied to the wheels, are adapted to be brought to bear with great force against the sides and bottom of the track, giving a power of braking that is especially desirable in mountainous regions where steep grades are frequent. The brake is of simple and strong construction, and the brake lever is in convenient reach of the car or train operator.

## Mechanical Appliances.

**TOOTHED GEARING.**—Matthew P. Campbell, Glasgow, Scotland. This invention provides a wheel having angular pivoted teeth with enlarged roots adapted to bear against each other, the teeth being free to oscillate on their pivots, the distance of the teeth from center to center being constant, while their inclination may be varied to accord with screws or worms of varying pitch. The pivot pins may be passed through a row of holes in a circle around the wheel rim, or two rows of staggered holes may be formed in the rim, alternate teeth being pivoted in the outer circle of holes and the others in the inner circle. This gearing is especially adapted for the transmission of great power, and is particularly designed for use on wormwheels and worms.

**MACHINE WRENCH.**—Marshall Martin, Walla Walla, Washington. This is a combination wrench and bolt holder, in which the cog die and its toothed driving gear and shaft are contained in a housing composed of separate plates hinged together, and united by a fastening adapted to admit of the housing being opened as required. The device is especially adapted for use on the rims of vehicle wheels, to hold and fasten the screw bolts and nuts which assist in securing the tires on the wheels, and for unscrewing the bolts when required to remove the tire.

**SANDPAPERING MACHINE.**—Herbert Spoor, Berlin, Wis. In this machine the sandpaper is secured about the face of a horizontal cylinder, and the material to be operated upon is fed over the cylinder by means of feeding rollers, the invention providing for the uniform adjustment of the cylinder and of the feed rollers, while a reciprocating as well as a rotating motion is imparted to the sandpaper cylinder. The construction of the machine is such as to facilitate the ready adjustment of its several parts to the work in hand, and insure the regular feed of the material operated upon.

**AX HANDLE FASTENER.**—Joseph M. Didero, Lorain, Ohio. The end of the handle adapted to enter the eye of the blade has a transverse central slot crossed by a longitudinal slot. A wedge having a head fits in the central slot, and side wedges are introduced into the longitudinal slot, one at each side of the central wedge, the side wedges having heads with one side rabbeted on the under surface to adapt them to fit over the head of the central wedge. As an additional security, each of the side wedges has an aperture adapted to register with corresponding apertures in the blade at each side of the eye, and when the handle and wedges are in proper position a screw or bolt is passed through the registering apertures and through the handle.

**NIPPLE HOLDER.**—Henry B. Spencer, Catskill, N. Y. This device consists of a hollow body having one end internally screw-threaded and a plug adjacent to the threaded portion through which extends a squared hole, there being mounted in the threaded portion of the body a tapering head with cutting edges and having a shank extending through the hole in the plug, while a screw mechanism moves the shank and head. This improvement forms a simple and convenient device to efficiently hold the nipple while a thread is being cut on it.

**CHUCK JAW.**—William J. C. Rowe, New York City. This invention relates to extension jaws for chucks, providing a simple, economical and durable device stepped to receive articles of different diameters and capable of being readily attached to the jaws of any chuck to increase its capacity. For this purpose reversible auxiliary jaws are employed, which, when turned upon one face, will receive large objects, and when turned upon the opposite face, will clamp small articles. The auxiliary jaw may be a casting or a forging with central opening to receive and neatly fit the chuck jaws forming a portion of the ordinary chuck, the slotted portion being flat and smooth and adapted to fit closely to the face of the chuck.

**CONCENTRATOR AND AMALGAMATOR.**—Jacob Rodermond, New York City. Combined with a receiving pan having horizontal rotating arms and teeth on their lower faces, with perforated upright blades on their upper faces, a bottomless cup encircling their central portion, is a lower pan containing mercury, an apertured disk being in the pan and perforated plates attached to its upper face, while combined agitating and gathering devices are secured to its lower face. These devices consist of a horizontal body from which depends a spiral blade having its ends laterally curved in opposite directions, while there is a tubular connection between the upper portion of the upper pan and the lower portion of the lower pan, the improvement being designed to afford a simple and durable machine for treating ores, in which any number of pans may be employed.

## Miscellaneous.

**ANNUNCIATOR.**—William C. Dillman, Brooklyn, N. Y. A swiveling leaf carrying a mouth piece is arranged at the mouth of a speaking tube, a catch holding the leaf in raised position, while electrically operated means are employed for releasing the catch, and an electric bell is arranged in a circuit which is closed by the dropping of the leaf. When speaking tubes from several points all center at a common point, this improvement enables a speaker in a distant room to indicate positively at the central point the tube through which he is calling, as the leaf carrying its mouthpiece will be dropped and a bell rung by pressure on a push button, the bell continuing to ring until the leaf is again thrown up.

**WASHING SUGAR.**—Ramon F. Cordero, Rubio, Venezuela. This invention relates to the washing of sugar by alcohol, providing therefor a special form of apparatus whereby the same alcohol may be retained and used to wash successive charges. Combined with the sugar-receiving cone is an alcohol supply receptacle having a valved connection with the upper end of the cone, an outlet at the lower end of which has a glass section, below which and connected therewith is a boiler. There is an alcohol-condensing apparatus above the boiler, a trapped vapor pipe lead-

ing from the boiler to the condenser, and a valved pipe connecting the latter with the alcohol supply receptacle. The operation of washing the sugar and condensing the alcohol may be kept up in rapid succession, while one charge is being washed the alcohol of the preceding charge being separated from the molasses.

**FABRIC TURFING TOOL.**—Vicente Fernandez, Guanajuato, Mexico. This is an embroidering implement that may be readily carried in the pocket and used on a great variety of work. Its handle carries a hollow sleeve, and a spring-pressed rod having one end formed into a sleeve is adapted to slide in the handle sleeve, the opposite end being slotted and bent to form a presser foot. A rod extends through the handle sleeve to one end of which a needle is attached so as to project through the presser foot, the position of which is regulated by a brake. The tool is easily threaded, and may be readily changed to carry a great variety of thread, and it may be conveniently operated by a single hand.

**HORSE DETACHER AND BRAKE.**—Annie H. Chilton, Baltimore, Md. Arranged to slip on the ends of the shafts are cuff-like sections, to which are connected the traces, the singletree, and locking arms to hold the traces in place, the arms being connected with a spring-actuated locking device, by operating which the cuff-like sections may be pulled off the shafts. The invention also provides effective means whereby, when the horse is released from the vehicle, the shafts will be held up from the ground and the vehicle will be braked, thus avoiding the danger of an upset or of the breaking of the shafts after the horse is released.

**INCUBATOR.**—Archer H. Burr, Omaha, Neb. A double-walled case holds the egg trays, above which are located double tanks with their upper compartments open, an outside double tank provided with means for heating being connected with the inside tanks. The invention is an improvement in that class of incubators adapted for automatically supplying the egg chamber with the right amount of moisture and air, maintaining an even temperature therein if sufficient heat is supplied to the heating tank.

**TYPE WRITING MACHINE.**—Eugene A. Ford, New York City. This typewriter is designed to print a large number of characters or letters without the necessity of multiplying keys, while the ink ribbon is automatically moved to unwind from the full reel and wind upon the empty one. The finger key is specially adapted to rapid work, being so formed as to allow the finger to readily slip from its edge after the key is depressed. A series of tubular type arms in the machine carry spindles having on their free ends heads with different type and different sides, and on the opposite ends segmental pinions engaged by a circular rack in any position in which they may be placed, a locking and releasing mechanism controlling the rack, which is moved by a double-acting key and a series of levers.

**DOOR TRACK AND HANGER.**—Charles O. Parsons, Milwaukee, Wis. The door track is, according to this invention, supported from the studding of a partition wall by end brackets, and intermediate brackets, there being preferably three of the latter, one at the center and one at each side of the doorway or frame. Adjusting screws are provided to elevate or lower either end of the track to compensate for any settling of the building, and cause the doors to hang plumb at all times, and this can be done without the aid of a mechanic, as the adjusting devices are within easy reach without removing parts of the door frame or partition. The improvement is specially designed for use in connection with division doors of living rooms.

**TRUSS.**—George V. House, Jr., New York City. This invention provides a trussing having improved means for altering the size, form, and relative position of the pad, to adapt it for service in all varieties of hernia. This truss has a pad bulb, made of partly elastic material, such as India rubber, etc., adjustable by means of a pivotal shank, entering a carrier plate after passing through a slotted base plate, and engaged by a binding screw passing through one of a series of holes arranged in rows radiating from the pivot shank in a cap plate and in the truss band between the cap plate and base plate.

**TRUSS PAD.**—An additional patent has been granted the above inventor for an improvement, whereby the production is cheapened and a more convenient, lighter device is afforded. In such cheaper grades it is found that good results can be secured by using a rigid pad bulb and dispensing with the carrier plate, the bulb having on its inner face a nut in which works a threaded hub with fixed headed shank, the base plate having a slot enlarged at one end to permit the head to enter and admit the shank in the slot the pad and base plate being adapted for disconnection without removing the hub shank, and the position of the pad being readily adjustable.

**LAMP EXTINGUISHER.**—John B. Greenhaigh, Blackstone, Mass. This is a simple attachment designed to be readily applied to any ordinary lamp burner, by which the flame of the wick may be extinguished, and which will operate automatically to put out the light when the lamp is overturned. Two hoods having depending shanks are pivoted on the wick tube, a spring-pressed lever having a cup at one end and engaging the shanks by its other end, normally holding the hoods closed, while a weight resting in the cup of the lever holds the hoods open.

**PUZZLE.**—Elmer E. Jenne, Iliou, N. Y. This device consists of a closed receptacle containing a series of circular spaced ribs provided with non-aligning apertures, the cover having an inlet opening over a space inclosed by one of the ribs, and a second opening showing solid portions of the ribs. The puzzle is for the player or operator to so manipulate the board or receptacle that concealed balls may be made to travel from the innermost to the outermost circular space and back to the starting point.

**NOTE.**—Copies of any of the above patents will be furnished by Munn & Co., for 25 cents each. Please send name of the patentee, title of invention, and date of this paper.

## Business and Personal.

*The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in the following week's issue.*

For Sale—New and second hand lathes, planers, drills, shapers, engines, and boilers, belting, pulleys, and shafting. List sent free. W. P. Davis, Rochester, N. Y.

Barrel, Keg and Hogshead Machinery. See adv., p. 83.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J.

For best hoisting engine. J. S. Mundy, Newark, N. J.

Most rapid low-priced, manifolding typewriter. Patent for sale or on royalty. J. J. Green, Boonton, N. J.

Best Ice and Refrigerating Machines made by David Boyle, Chicago, Ill. 170 machines in satisfactory use.

The Improved Hydraulic Jacks, Punches, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Screw machines, milling machines, and drill presses. The Garvin Mach. Co., Laight and Canal Sts., New York.

C. E. Billings' Patent Surface Gauge. Drop Forgings. Bronze Forgings. Billings & Spencer Co., Hartford, Conn.

"How to Keep Boilers Clean." Send your address for free 96 p. book. Jas. C. Hotchkiss, 112 Liberty St., N. Y.

Wanted—Capital to take out and sell European patents on a first class invention. Address H. E. J., 207 4½ St., N. W., Washington, D. C.

Guild & Garrison, Brooklyn, N. Y., manufacture steam pumps, vacuum pumps, vacuum apparatus, air pumps, acid blowers, filter press pumps, etc.

Rubber Belting, all sizes, 7½ per cent from regular list. All kinds of rubber goods at low prices. John W. Buckley, 156 South Street, New York.

Split Pulleys at Low Prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.

The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4; Munn & Co., publishers, 361 Broadway, N. Y.

Wanted—A civil engineer, who is also experienced in city engineering. Permanent position. Give full references and state salary expected. Address F. W. Matthiessen, La Salle, Ill.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.

## Notes & Queries

### HINTS TO CORRESPONDENTS.

**Names and Address** must accompany all letters, or no attention will be paid thereto. This is for our information and not for publication.

**References** to former articles or answers should give date of paper and page or number of question.

**Inquiries** not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.

**Special Written Information** on matters of personal rather than general interest cannot be expected without remuneration.

**Scientific American Supplements** referred to may be had at the office. Price 10 cents each.

**Books** referred to promptly supplied on receipt of price.

**Minerals** sent for examination should be distinctly marked or labeled.

(3229) F. & L. ask for some information in regard to staining cigar box lumber. A Cigar box lumber is prepared by veneering. Whitewood is often used as the basis, veneered with Spanish cedar. On soaking a piece in water, the thin layer will come off.

(3230) E. C. A. writes: In our saw mill we are running a 54 inch circular saw at 700 revolutions per minute and another 34 inch saw at 1,200 revolutions per minute, which runs at a right angle with the big saw. The smaller saw is placed about 20 feet from the large one and about 8 feet to one side, and runs in the same direction. It has a ring of holes 9 inches from its center running all around the saw, and when in motion everything in the mill can be seen by looking through this ring of light as plain as looking through common window glass, and everything looks just as natural except the large circular saw, which appears to be revolving slowly backward, so slow that every tooth in the saw can be seen as plain as when standing still. When stopping the mill, the large saw appears to stop long before it really does. What is the cause of this strange delusion? A. The effect described is similar to that produced in the stroboscope or zoetrope. It is due to intermittent vision and the persistence of the retinal image. The rate of rotation of the small saw was related to that of the large saw in such a way as to permit of seeing the teeth of the latter only when the teeth were in certain positions, thus causing them to appear nearly stationary. The revolving saw viewed through an instantaneous photographic shutter would appear stationary. If viewed through a shutter opened and closed once during each revolution of the saw, the eye would receive a succession of images which would be retained by the persistence of vision and then blended into one continuous image. The small saw acted as a shutter in producing this effect. It is not necessary that the shutter should be limited to one exposure per revolution of the saw. There may be a number of exposures, but to make the saw appear stationary, the number should be an aliquot part of the number of teeth in the saw.

(3231) C. A. B. wishes the formula for the preparation of the platinum paper used by photographers. A. The sensitizing bath is made by dissolving dry ferric hydrate in a concentrated hot solution of oxalic acid. The acid is poured on to the ferric hydrate until it is just dissolved. Then 12 parts of sodium chloro-platinate are added to the hot solution. The whole is filtered and the solution thickened slightly by evaporation. The paper well sized is laid or floated