

Vol. LXVIII.-No. 17. Established 1845.

NEW YORK, APRIL 29, 1893.

\$3.00 A YEAR. WEEKLY.

Weekly explains the methods adopted with sufficient it was not until the buildings were nearly ready for clearness; and the accompanying sketch shows the their decoration that the subject was again taken up. general arrangement of the apparatus:

In the painting of the buildings, the necessity for some method of covering their great areas which would Exposition to accomplish so vast'a work by hand. Some be more rapid and less expensive than the brush was realized almost from the beginning of construction. Millet, Director of Decoration, and his assistant, Mr. Where such extensive wooden construction is used it is impracticable to dress all surfaces, and there exist | Meanwhile, the painting of the buildings then near many spaces inaccessible to the brush; while the rough or "whiskered" lumber makes the life of the brushes exceedingly short.

As soon as the placing of foundations had been com-

THE PAINTING MACHINES AT THE WORLD'S FAIR. and efforts made to perfect a painting machine, but The following abstract of an article in *Harper's* the earlier experiments were far from successful, and Additional impetus was given by the fact that there weeks were occupied in further experiments, Mr. F. D. C. Y. Turner, giving much attention to the problem. completion progressed as rapidly as possible by hand in the usual manner. Finally, a machine which successfully sprayed color upon the surfaces to be covered, on menced, careful consideration was given this subject, produced and immediately set to work In this first

successful apparatus, the color (in nearly all cases kalsomine) was passed directly through the rotary engine used for compressing air; but, because of its gritty nature, the wear was so great as to become a serious objection, and to render a more satisfactory remained insufficient time before the opening of the method of introducing the color necessary, and further improvements were made, with successful results.

A rotary engine invented by Mr. T. G. Turner, of New York, driven by a five horse power electric motor, provides the compressed air in cases where the pneumatic system of the Exposition is not available. This engine furnishes the required pressure in a uniform manner, without the air chamber necessary to overcome pulsation in compressors operated upon the reciprothe same general principle as the "atomizer," was cating principle. The engine, electric motor, color (Continued on page 262.)



THE WORLD'S COLUMBIAN EXPOSITION-THE PAINTING MACHINE.

© 1893 SCIENTIFIC AMERICAN, INC.

ESTABLISHED 1845.

A. E. BEACH.

MUNN & CO., Editors and Proprietors. PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy one year to any foreign country belonging to Postal Union. 4 00 by postal or express money order, or by bank draft or chec

MUNN & CO., 361 Broadway, corner of Franklin , treet, New York,

The Scientific American Supplement

The Scientific American Supplement is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for the U. S., Canada or Mexico, \$6.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country. See prospectus, last page. Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to one address in U. S., Canada or Mexico, on receipt of seren dollars. To foreign countries within Postal Union, *cight* dollars and fifty cents a year. . THE SUPPLEMENT o pages, uniform in size tion for SUPPLEMENT, o vear to foreign conts. Sold

Building Edition.

Building Edition. THE ARCHITECTS AND BUILDERS EDITION OF THE SCIENTIFIC AMERI-CAN is a large and splendid illustrated periodical, issued monthly, con-taining floor plans, perspective views, and sheets of constructive details, pertaining to modern architecture. Each number is illustrated with beautiful plates, showing desirable dwellings, public buildings and archi-tectural work is invaluable. Has the largest circulation of any architec-tural publication in the world. Single copies 25 cents. By mail, to any part of the United States, Canada or Mexico, 82.06 a year. To foreign Postal Union countries, \$3.00 a year. Combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN, to one address, \$5.00 a year. To foreign Postal Union countries, \$10.00 a year. PLEMENT, \$0.00 a year. To foreign Postal Union countries, \$10.00 a year.

Spanish Edition of the Scientific American.

LA AMERICA CIENTIFICA E INDUSTRIAL (Spanish tradeedition of the SCIENTIFIC AMERICAN) is published monthly, uniform in size and typo-graphy with the SCIENTIFICA AMERICAN. Every number of La America is profusely illustrated, It is the finest scientific, industrial trade paper printed in the Spanish language. It circulates throughout Cuba, the West Indies, Mexico Central and South America, Spain and Spanish posses-sions—wherever the Spanish language is spoken. \$3.00 a year, post paid to any part of the world. Single copies 25 cents. See prospectus.

MUNN & CO., Publishers, 361 Broadway, New York.

The safest way to remit is by postal order, express money order, draft or bank check. Make all remittances payable to order of MUNN & CO. Readers are specially requested to notify the publishers in case of any failure delay, or irregularity in receipt of papers.

NEW YORK, SATURDAY, APRIL 29, 1893.

Contents.

(Illustrated articles are marked with an asterisk.)

SCIENTIFIC AMERICAN SUPPLEMENT No. 904.

TABLE OF CONTENTS OF

For the Week Ending April 29, 1893. Price 10 cents. For sale by all newsdealers.

PAGE BIOGRAPHY.—M. Taine.—A graphic sketch of the great French author, with portrait.—1 illustration 14450 II. BOTANY.-Kangra Buckwheat.-The Himalayan buckwheat compared with the ordinary buckwheat..... 14451 III. CHEMISTRY.—The Chemistry of Osmium.—An important paper on this rare metal.

14453 IV. CIVIL ENGINEERING.-Jetty Harbors of the Pacific Coast.-How harbors are formed on the Western coast of the United How haroors are formed on the second 14447

..... 14448 V. EDUCATION,-Shall We Examine?-By CLARENCE M. BOU-TELE,-A plea for the abolishment of school examinations...... 14439

VIII. MINING ENGINEERING.-The Lease or Tribute System of Mining.-The Colorado system of working mines, and its ad-

. 14448

THE WORLD'S COLUMBIAN EXPOSITION.

on the opening day, it should be laid on exhibitors and and telegrams have been frequently sent out to exhibitors at different times calling their attention to exhibits if they wished to escape the rush of the last few days and be ready with their displays on the opening day. Everything possible seems to have been done by the Exposition to force matters, so that there should be no excuse for not being ready on time. The facilities for handling exhibits have been more than ample, although on a few occasions they have been pretty well tested. One serious drawback during the month of April has been the difficulty of securing sufficient skilled labor, especially carpenters, and also of getting teams enough to haul lumber and other supplies. A fair illustration of the embarrassments that have been met in this latter particular is that of an exhibitor who after a good deal of effort secured carpenters enough to do his work, and engaged a drayman to haul his lumber at seven dollars a load. The drayman hauled part of the lumber, and as he was waiting his turn at the Sixty-fourth Street entrance to get passage for his team into the grounds to discharge his load, another exhibitor who was looking for a man to haul lumber offered ten dollars a load. This offer was promptly accepted without completing the agreement with the first exhibitor, and so the carpenters who had been engaged to prepare the exhibit were without lumber to work with, and the exhibitor had to hunt up other means of getting his lumber.

The Exposition has done much less night work than it was expected would be necessary. In the mechanical department three shifts of men have been employed during April, because of the fact that this department was much behind in the work of installing the engines and boilers of the great power plant and of completing the steam and other connections. More ordinary labor has been at hand than could be employed. Every day for the last six weeks from a dozen or two to a hundred or more men have haunted the gate adjoining the service building seeking employment. With such an abundance of labor the Exposition has been able to push work with the greatest vigor by daylight.

Some idea of the manner in which work was rushed toward the last can be gained from the way in which Stony Island Avenue, which runs along the western boundary of the Exposition grounds, was macadamized. April 10 this avenue was full of deep ruts and sinkholes almost its entire length. On the 15th it was a finely macadamized road for a distance of about a mile. At the same time that this work was being carried on, provision had to be made for the passage of teams and drays which were bringing exhibits and supplies into the Exposition grounds.

The work of turfing lawns adjoining the State and other buildings in the northern part of the grounds was begun on the 10th, and by the close of the week was completed so far as building operations would permit. Work was begun on the promenades and walks about the same time, so that all that remained for the landscape department to do during the last week of the month was to complete the work of turing the lawns adjoining those buildings where this work had been delayed and finish the work of hardening the more active arteries of travel. Temporary buildings and structures which had been necessary during the period of construction, but which had outgrown their usefulness, disappeared almost in a night.

When the middle of April arrived, a comparatively evaporating water for generating steam. There will small percentage of the exhibits was installed, and also be a great variety of tests of the engines and electhe Exposition management found it imperative to let trical machines. All these tests will be as exhaustive as up somewhat on some of its stringent regulations, es it is possible to make them, and they will be carried pecially in regard to the driveways and narrow-tired out on a much larger and more comprehensive scale vehicles. A very large number of exhibits enter the than has ever before been possible. The results of grounds on vehicles instead of arriving in cars, and up these tests will be of great scientific value to the to the middle of the month it was imperative that mechanical and industrial world. these vehicles have extra width of tires, or they would The work of hanging pictures in the gallery of fine not be permitted more than to enter the grounds, and all such exhibits had to be transferred to vehicles arts was begun the second week in the month and has which were properly provided with the requisite width been carried on energetically ever since. Each nation of tire. The number of exhibitors who had exhibits has pushed its own department, so that altogether this which could be installed with very little trouble inside building will be nearer a state of completeness than most of the others. One of the interesting exhibits in of a few days was very large, and they did not make any effort toward preparing their exhibits until the latthis building is that which has been installed in the east wing by the French. This is what is called the ter part of the month. This brought in such a rush that, as a general rule, the original vehicles conveying Trocadero collection, and comprises a very large the exhibits were permitted to drive into the grounds number of plaster reproductions of some famous and buildings, thus furthering the work of the Expo-French works. This collection is to remain permansition vehicles, and at the same time doing away with ently in this country, arrangements having been perconsiderable delay in transferring. The more importfected to that end. ant driveways had been covered with planking since The elevated road which enters the grounds, and winter, so that no damage worth mentioning was done which will carry passengers from the heart of the city, to the driveways by the narrow tires. has completed its commodious station immediately In addition to furthering the work in this way, over the annex to the Transportation building. The the installing force was increased to as many men station is so arranged that visitors can go from it to the as could possibly be used, and an abundance of adjoining station of the Intramural Railway without labor was held in reserve and at the service of the necessity of going down one flight of stairs and up

the exhibitors who were in need of assistance. The If there is any blame to be placed because the lighting equipment to the buildings has been in-World's Columbian Exposition is not fully completed stalled for several weeks and ready for use, and with the extra rush that began at the middle of the not on the Exposition management. Urgent letters month, considerable night work became necessary. Quite an incredible amount of work has been done since the 17th of April, and as a result it is probable that the necessity of their being prompt in installing their most of the buildings will be practically ready on the opening day. Among these buildings in which exhibits will be practically complete are the Agricultural building, Mining building, Transportation building, United States government building, Fine Arts building, Fisheries building, and Transportation building.

> April 10 was originally set as the last day upon which exhibits would be received, but there has been so much delay and such a comparatively small part of the exhibits had arrived up to this date that Director General Davis extended the time to April 30.

> The telephone service at the Exposition grounds has been completed, and some days ago connection was made with the long distance wires, so that during the holding of the Exposition visitors will have every facility for talking with New York, Boston, Philadelphia, and other cities.

> Although it became necessary to close to visitors the buildings in which exhibits were being installed during the month of April, other attractions were held out by the Exposition management, making it well worth while for visitors to go to the grounds to see these attractions themselves, in addition to the Exposition buildings and other sights. The leading attraction has been the flowers, and these have drawn many visitors, especially on Sundays. As soon as the display of cyclamens or "Persian violets" began to fade, other elaborate and very complete displays were made-among these pansies, cinerarias and English primroses. A great treat to lovers of flowers is promised soon, when the rhododendrons blossom. France and Germany have each contributed a splendid collection of these, which have arrived in most excellent condition. The French display will be made largely in the grounds adjoining the Woman's building. In addition to all these flowers there is also a very attractive show of early Blossoming bulbs on the terraces in front of the Manufactures and Liberal Arts building and the Agricultural building. The greatest display of flowers when the Exposition is opened will be on the Wooded Island, which gives promise of being equal in its way to many of the other large displays of exhibits.

> The opening ceremonies on May 1 will not be quite so select and exclusive as was at first proposed. The Council of Administration has decided that they shall be held outdoors and in the Grand Plaza in front of the Administration building. A temporary platform will be constructed from which the exercises will be carried out, and where seats will be provided for the 1,500 invited guests. There is such ample space in this Grand Plaza that it is believed that from 75,000 to 100,000 people can witness the ceremonies

> The heaviest piece of material that was handled in the Palace of Mechanic Arts was the shaft of the Allis two thousand horse power quadruple expansion engine. This shaft weighed thirty-three tons, or three tons more than the largest cylinder of this engine. No difficulty was experienced in handling and placing it in its bearings, but a good deal of time was consumed in the operation.

> The engineering department of the Exposition has been at work during the past month outlining and arranging the work for making every preparation for a large number of tests. These tests include everything, from burning fuel oil with efficiency and economy to

IX. MINERALOGYAsbestosThe qualities of different kinds of	I
Manufacture of the Diamond.—Moissan's success in making diamonds artificially.—2 illustrations	ì
X. MISCELLANEOUS.—The Christopher Columbus Festival.— Initial features of the journey of the caravels from Spain.—Pro- posed monument to Columbus.—Z illustrations	(
XI. NATURAL HISTORYA Breed of Tailless CatsThe Manx and the Japanese cats1 illustration	() {
X11. NAVAL ENGINEERING. – Progress of Navai Architecture. – Four new types of vessels now in hand by shipyards	1
XIII. PHOTOGRAPHY.—Glycin.—A new developer.—With formula and directions for its use	1
XIV. SANITARY ENGINEERINGUse of Marine Saltfor the Re- moval of Snow-Electrolytic Processes of DisinfectionStreet cleaning processesA suggestive presesutment	5
XV. TECHNOLOGY.—A New Theory of Dyeing.—Witt's theory of mordanting	(
ing cloth and recording its length on the margin2 illustrations 14442 Machine for Manufacturing CordageGlover's machine for	
making rope of proper twist.—2 illustratious	1
F. NURSEY A valuable contribution The manufacture of in- nocuous white paint	1
unuation of this important paper on engraving processesVari- ous photogravure methods	ł
oily substances from distillation residues]

another. The elevated road has accomplished an immense amount of work during the month of April, and will have no difficulty in running its trains into the Exposition grounds in time for the opening ceremonies

Exhibitors seem to have the staff mania, although in a somewhat milder form than the Exposition management. Nearly all of the larger and more pretentions booths and pavilions throughout the various buildings use staff to a greater or less extent for the purpose of ornamentation. In fact, there are very few booths outside of the smaller ones which are constructed without using it. In the Manufactures and Liberal Arts building is an especially elaborate display of staff ornamentation. In the midst of all this mass of staff it is a relief to look at the German section, which has quite a display of structural and fancy iron ornamentation. In the Mining building staff is not used quite so extensively, yet there are several pavilions which combine building stone or terra cotta and use staff ornamentation.

A national bank, established under the auspices of the Chemical National Bank of Chicago, has opened for business in one of the wings of the Administra-



THE AGRICULTURAL BUILDING.

The Agricultural building, next to the Administration building, is probably more conspicuous than any other building at the World's Columbian Exposition in the amount of statuary and other ornamentation. The architecture of the building is of the Classic Renaissance style. It fronts on the Basin and is directly opposite the south end of the Manufactures and Liberal Arts building. At the west of it is the South Canal, which separates it from the Palace of Mechanic Arts,

dome of the central pavilion. This is the figure of Diana that was formerly on the tower of the Madison Square Garden in New York City. Immediately over the main entrance is a winged figure illustrative of the "Victory of Ceres." This is a female figure with outstretched hands, holding a laurel wreath. On each side of this figure is the Ceres group. This group comprises two female figures holding between them a large shield on which is the word "Ceres," and underneath this is a garland of fruit. Cupids stand on either side of each of the figures, holding in their hands cornucopias which are running over with abundance.

On each corner pavilion are two reproductions of what is called the Four Seasons, making altogether eight of these groups. This group consists of four female figures representing the four seasons of the year, spring, summer, autumn, and winter. They are set back to back with their arms outstretched for sheaves of wheat extended above their heads.

Besides these groups of figures, which are decidedly Grecian in design, there are two other groups which are eminently rural and illustrative of agricultural pursuits. One of these is a horse group, the other cattle. There are four of the horse groups, two on tion building, and will do a banking business during while in the rear, or east of it, is what is called the the front of the building, one on the east end of the



THE WORLD'S COLUMBIAN EXPOSITION-CATTLE GROUP, AGRICULTURAL BUILDING.

the six months that the Fair is in operation. This South Pond. This building, like all the other Exposi-building facing the pier at which steamboats will bank is established both for the convenience of visitors and exhibitors, and special arrangements have been made so that there shall be as little red tape as possible in cashing checks or making drafts. The its surrounding conditions, and will be well worth a visit of banking men.

from east to west, and 500 feet wide from north to south. The cornice line, like all the other buildings ing on a slightly raised elevation holding the handle surrounding the Basin, is 65 feet above grade. The of an ancient stone plow; two spirited horses are bank has been fitted up in a manner in keeping with main entrance is on the north face of the building, and attached to the plow, yet held in check by a firm on either side of it are mammoth Corinthian pillars, 50 hand. feet high and 5 feet in diameter. Pavilions are reared Soda water fountains are among the most con- at each corner and from the center of the building, the center one being 144 feet square. Curtains connect pedestal holding a garland of flowers which encircles the corner pavilions, forming a continuous arcade the necks of the cows. Standing on the right side of the group is the figure of a goat, and on the left is that of a calf. The number and positions of these vilion is surmounted by a dome 96 feet high, and on each of these domes is a group of maidens of heroic groups are relatively the same as those of the horses. size, called the Horoscope Group. These figures are We give an engraving of this group. represented as holding aloft a globe about which is a zone with signs of the zodiac. The figures are made lief, are fifty-four single figures of the Angel of Abunof staff, while the globes are of sheet copper. Each dance holding a cornucopia which is overflowing with group represents a distinct race, one the Caucasian, the fruits of the harvest. These figures are clothed in another the Mongolian, another the Ethiopian, and loose flowing robes and are classical like the others. Between the springs of the arches of the north, east, The main entrance leads through an opening sixty and west sides of the building are twenty-two more four feet wide into a vestibule, and from this vestisingle figures in relief representing a female classically bule into the rotunda, which is one hundred feet in clothed, holding in her hands the signs of the zodiac. diameter. This rotunda is surmounted by a mammoth On the east front there are two spandrels, also two on the west and one on the north side. Four of these are glass dome one hundred and thirty feet high.

tion buildings, is covered with staff. It is 800 feet long land passengers, and one on the west front. The group comprises a figure of a Grecian plowman stand-

In the cattle group, which is likewise strongly Grecian, is a woman standing on a slightly raised

On the exterior walls of the building, in strong re-

spicuous structures in several of the larger buildings, and, judging by their size and capacity, the Exposition management expects a very thirsty crowd of around the top of the building. Each corner pavisitors

The railway terminal station at which passengers will arrive in the Exposition grounds by all the railroads, except the Illinois Central, was practically completed by the middle of April. It is a very fine appearing structure, and is especially convenient in its interior arrangements. The railway tracks entering it have been down for some months, and have been considerably used for the storage of freight cars, but the fourth the American Indian. have now been mostly cleared away to be ready to receive passenger trains. The switching plant which is to control the vast network of tracks is not quite completed, and there is some doubt as to whether it will be fully finished on the opening day, but it will be near enough completion to fully answer all the requirements.

Perhaps the most conspicuous figure on the buildthe same. The two on the west side are immediately ing is that of Diana the huntress mounted on the under the Horoscope Group and represent a pastoral

on the right with two ewes and a lamb. The other framework, a sprocket wheel on this shaft being conspandrel represents the triumph of Ceres, and is on nected with a similar wheel on the treadle shaft, by the north front. Ceres, the central figure, is represented | the operation of which the large gear wheel is rotated as standing erect, holding a sheaf of wheat in her left hand and a shepherd's crook in her right. Further brake lever pivoted on the steering lever, a brake may down on the pediment are other reliefs. On the left is be applied to the shaft of the large gear wheel to stop a reproduction of Flora, Bacchus, and other mythological deities seated in a chariot drawn by two tigers. Over against this relief on the right hand is a figure of Mercury and pastoral deities in a car drawn by two dragons. The statuary is all the work of William Philip Martini of New York, with the exception of Diana, which is the work of Mr. Augustus St. Gaudens.

In addition to these decorations and ornamentations in staff, there are six mural paintings on the exterior walls, four on the west face and two on the east. These paintings consist of female figures gracefully draped, with flowers and fruit in their hands typifying the fruitfulness of nature. These paintings were executed by Mr. George W. Maynard. In the main entranceway are four mural paintings similar to the others in style and effect. One of these, representing "Fertility," carries a sheaf of wheat and a basket of fruit. The other figure, "Abundance," carries a shock of grain in one hand, while in the other there is an overturned horn of plenty, from which fruit and flowers are flowing out in abundance. Two other figures painted on the side walls of the entranceway represent mythological beings. One is a male figure driving a chariot drawn by dragons, the other a female figure in a chariot drawn by lionesses. The ornamental painting in connection with these figures was done by Charles Schladermaundt.

Thirty-seven States in this country and thirty-five foreign nations and states have exhibits in this building. The interior arrangement is such as to provide over fourteen acres of desirable space for purposes of rim, the roller coming in contact with one edge of the exhibiting.

AN IMPROVED UNICYCLE.

A wheel which can be easily steered and propelled, and which is designed to enable a rider to attain a high rate of speed, is shown in the accompanying engraving, and forms the subject of a patent issued to Mr. James Imlah, of Barre, Vt. This wheel has an inner wheel supporting a suitable framework and having a double rim, the two parts of which engage ball bearings of inner annular flanges connected by spokes with the tire of the outer wheel, so that as the latter in the spring, beginning in the month of March and travels on the ground the inner wheel rolls off on the flanges, and the rider in his seat holds the framework in normal position, the inner wheel not revolving.

Scientific American.

[APRIL 29, 1893.

scene of a shepherd with a crook in his hand, sitting gear in mesh with a gear wheel on a shaft in the with cotton and a sponge dipped in oil fastened to one to give motion to the exterior wheel. By means of a the machine. The steering lever is arranged in front of the rider's seat, and by means of the mechanism connected therewith friction rollers may be brought into engagement with opposite edges of the double



IMLAH'S UNICYCLE.

rim, turning the wheel in the opposite direction, and when engaging the other edge moving the wheel in the reverse direction. One can easily get into the machine by turning the framework half way around, allowing the saddle to come back into place after stepping in.

THE PEARL BUTTON INDUSTRY.

The pearl oyster shells from which pearl buttons are made come principally from the coast of Australia and the South Pacific islands. The oysters are gathered ending in May. Fully 200,000 persons are employed in gathering the oyster during the season. When the end of a small wooden chuck, rubs a little rouge made boats arrive at the grounds, the divers are stripped of a mixture of tripoli, flour and tallow, and presses it Between the two ball bearings in the rim is an internal 'naked and well oiled; their noses and ears are stuffed up against the muslin wheels, which give it a beauti-

of their arms. Armed with knives, they and their baskets are then lowered to the bottom of the sea by means of large 40 or 50 lb. stones attached to ropes. The divers remain under water from 50 to 80 seconds. As soon as a basket is filled it is drawn up and the diver comes up to the surface. After resting a few moments he again descends, filling the basket again, and so on until he becomes exhausted, when another man takes his place.

The fishing is done in about 8 to 10 fathoms of water. The shells are imported into this country. There are two varieties. the white and the black or smoked pearl. They run from 2×3 inches to 6×8 inches in diameter, the largest of the shells being about a half inch in thickness near the joint. The shells are very brittle when they arrive in this country, and have to be soaked in water before they can be worked. This soaking brings them back more to their natural state. After soaking in tubs they are taken to the cutting lathe.

The operator, taking the shell in one hand, by means of a lever forces a hollow saw-edged tool against the shell, which cuts its way through, the circular piece dropping out of the hollow tool when drawn back by the lever. This operation is continued until the entire shell is perforated. The teeth of this sawing tool are 1-32 part of an inch in length.

These circular pieces are then taken to another lathe to be trimmed and formed. The circular piece of pearl is placed in the end of a slotted dogwood chuck which is hollowed out the same shape as the button. The attendant, by the use of sharp-pointed tools made of saw files, trims and forms the button as it revolves. Fancy designs on the faces of the buttons are made with ball and circular saw-shaped tools, which are placed in lathes, the operator holding the button in his hands and pressing it against the tool as it revolves. The drilling of the eyes is also done on a lathe, the button being placed in a chuck similar to that on the forming machine. The attendant by means of a lever forces the drill against the button, which cuts out the eyes.

For smoothing off ridges the buttons are put into a revolving barrel with a mixture of powdered pumice stone and water. The polishing wheels are 6 and 14 inches in diameter and made of 54 separate pieces of unbleached muslin clamped together at the center on the shaft of the machine. The revolving of the shaft causes the circular pieces to stick together, forming a perfect wheel. The attendant puts a button in the



THE PEARL BUTTON INDUSTRY.

© 1893 SCIENTIFIC AMERICAN, INC

ful polish. These wheels make 3,000 revolutions per minute.

After polishing the buttons are placed on cards and ready for sale. Fifty hands can turn out about 150 gross per day of buttons. The shells cost from 40 to 50 cents per pound. The buttons when finished cost from 40 cents to \$25 per gross wholesale. The annual consumption of pearl buttons in the United States amounts to about \$3,500,000.

The sketches of this subject were taken from the plant of E. Huebner & Son, Newark, N. J.

AN IMPROVED SADDLE ATTACHMENT.

A combined loop and hook, for quickly and easily forming the connection between the saddle straps and



belly girths, and secure ly fastening them in position, is shown in the accompanying illustration, Fig. 1 showing the loop and hook in use on a saddle, Fig. 3 being a side view, and Fig. 2 showing the attachment to a girth ring. This improvement has been patented by Mr. John F. Kohler, No. 906 Columbus Avenue, New York City. The elongated metallic loop is slightly larger at its upper end, so that a strap may be passed through it several times if desired, and at the lower end it is doubled upon itself to form a

hook adapted to engage

MENT.

the girth ring, a portion of the hook surface being flattened and having an outwardly extending stud to engage perforations in the saddle strap. The tension of the girth and straps is designed to hold the saddle in place so that it cannot accidentally get loose, and the strap is easily and quickly fastened to the stud.

A TOOL TO DRILL CONICAL RECESSES.

Fig. 1 shows a perspective and Fig. 2 a sectional view of an improved tool, patented by Mr. Charles A. Cutting, of Middletown, Va., and which may be used to conveniently drill conical recesses to receive posts, dowels, etc., as indicated in Fig. 3. At the lower end of the bit, between the twists, is held a removable cutter, an offset on its upper end fitting into a recess in the upper end of the bit and forming a pivot for the cutter to swing outward on, so that it will stand at angles to the axis of the bit. A shell or sleeve, slightly enlarged at its lower end, fits loosely over the cutter



The Wire Gun.

The first public test of the Brown segmental wire wound gun was made at Birdsboro, Pa., April 15, and was attended with much success. Government exprts, representatives of foreign powers and a number of invited guests from New York, Philadelphia, and other cities were present. Three shots were fired, and the gun successfully withstood a pressure which the experts declared would blow any other gun in the world to atoms. The tests broke all records, and one of the enthusiasts declared they placed the United States in the van in gun making.

On the third and final test the charge was thirty pounds of powder, the projectile sixty pounds weight. The gun recoiled about 15 feet, and a section of the stone quarry rose in the air as the projectile struck.

The test gauges were set to show a pressure of between 40,000 and 60,000 pounds; it was found that the pressure had gone beyond the larger figure and exceeded the means at hand for measurement. The pressure was declared by experts to be something above 70,000 pounds. The standard army requirements are only 37,000 pounds.

The gun has just been finished as a sample for the United States government. It was built at the Diamond Drill Works at Birdsboro, under the personal supervision of John Hamilton Brown, the inventor. It is built on a new system, which is the winding of a steel wire around a segmental core of steel. The core is made of twelve pieces of steel 19 feet long, and with a cross section like the key of an arch. The core is 3 inches in thickness at the breech, and three-quarters of an inch at the muzzle.

This is wound with thirty three layers of steel wire seven one-hundredths of an inch in thickness. The gun is about 15 inches in diameter at the breech and 10 inches at the muzzle. The gun is 19 feet in length and weighs three and one-third tons.

Venetian Mosaics for the Fair.

The British vice-consul at Venice says that the splendid mosaics now produced there continue to take the first place in the artistic markets of the world. Among the important works recently executed by the Venice and Murano Company, a well-known mosaic manufactory, is a large mosaic panel representing Columbus being received by Queen Isabella and King Ferdinand of Spain. after his return from America. This panel, measuring about 200 square feet, shows Columbus when kneeling before the sovereigns, presenting to them the natives of the newly discovered land and some products of the soil. The persons represented are about thirty-eight in number, many of them of the natural size, formed in three principal groups. In the most important is Columbus, having at his side the Crown Prince, and the sovereigns surrounded by the dignitaries of the court, ladies and nobles, and pages holding the standards. In the middle group, but more to the left, are the native Indians, and near the entrance of the hall other Spanish nobles, and the companions of Columbus. The gorgeous and various attires of all the figures, their warlike implements, the splendid stuffs of all sorts and tints, the rich decoration of the hall, the pageantry of the court, the strange costumes of the natives in full contrast with the others, and the various attitudes of all these personages, form a whole in perfect harmony with the details of the scene, owing to the excellent distribution of the figures and the perfect fusion of tints. The work is so delicately executed, says the vice-consul, by the clamp com- that no one can believe that the panel is not painted ing in contact until on touching it he discovers that it is entirely composed of small enamel cubes, put together without end of the sleeve, any aid of color or cement, and worked according to The space formed the mode of the old Venetian mosaic school. This panel is to form the pendant of another, representing Columbus landing in America, and which will shortly be executed by the Venice and Murano Company. These mosaic works are executed for Mr. H. Furber, of Chicago, who is now building a palace near the Exhibivolving the tool tion, which is to be called Columbus Palace, and will, the shell revolves it is said, be the largest in America. The two panels with it, while the are to be placed in the entrance hall. The author of the

the valve extending below the body and having on its lower end a disk-like turbine water sprinkler, shown in Fig. 3. It may have any number of spray perforations, and is adapted to rotate freely, the perforations being so inclined that the water pressure causes its rapid rotary movement. Within two pendent links supported from lugs on opposite sides of the body of the sprinkler is held a saddle bar, on which the head of the valve stem rests, and this bar rests upon a coupling bar, shown in Fig. 4, whose outer ends have lips which lock over the lower edges of the pendent links. This coupling bar may be made entirely of fusible metal, but preferably consists of two pieces of brass or other metal, lap-folded and united, as shown, by a solder which will fuse at a temperature below that of boiling water. The fusing of this solder, when a fire starts in the vicinity of the sprinkler, causes the two pieces of the coupling bar to be



HOLMES' AUTOMATIC SPRINKLER.

separated, lets down the saddle bar, pushing the pendent links outwardly, and allows the valve with its turbine disk to drop, the force of the escaping water then causing its widespread spraying distribution. Further information relative to this improvement may be obtained of Mr. C. H. Matthiessen, P. O. box 655, Chicago, Ill.

AN IMPROVED FEED-WATER REGULATOR.

An automatically operating regulator of the feeding of water to a steam boiler, designed to hold the water in the boiler at all times at about its normal level, is shown in the picture, and forms the subject of a patent issued to Mr. Emory M. Carr, of New Castle, Ind. A slightly inclined pipe arranged alongside the boiler, with its upper end at about the normal water level, is connected by a pipe at its lower end with the water space of the boiler, and a pipe connects its other end with the steam space. Both ends of the longitudinal pipe are secured in heads, and on the head on its higher end is fulcrumed a lever, the lower end of which is connected by a longitudinal rod with the other head, while its upper end is connected by a rod with



CUTTING'S RECESS BORING TOOL.

terial being bored. A lug in the upper end of the shell prevents the bit from being accidentally withdrawn therefrom. In operation, as the tool cuts into the material, and its lower end moves out of the shell, the point of the cutter is pushed outward to assume an conical recesses, as shown in Fig. 3. A wedge set in its sides in contact with the walls of the recess.

+ + +

tool is free to move | cartoons is Prof. Chev E. Paoletti, an artist well known downward in the in Venice, and affirmed to be one of the best painters shell as the latter who still maintain the traditions of the great Venetian school. As a work of art, the mosaic is said to be the rests on the mamost remarkable modern specimen ever exhibited. a valve in the steam pipe connecting the boiler with

AN AUTOMATIC SPRINKLER TO PUT OUT FIRES.

spring, normally holding the valve to its seat. With the water at its normal height, it fills the longitudinal Many of the insurance companies now stipulate for pipe, and the feed pump is still, but as the water falls the employment of automatic sprinklers in manuangular position relative to the bit, thus forming facturing establishments which they underwrite, or, the pipe becomes filled with steam, the heat of which in the absence of such sprinklers, charge a higher causes an expansion of the pipe and an outward movethe bottom of this recess is adapted to engage the rate for insurance. A sprinkler of this kind, which ment of the lever fulcrumed on its upper end, thus bottom of a post or dowel, splitting it and wedging has been patented by Mr. Thomas Holmes, of Chicago, pulling the rod connected with the valve in the steam Ill., is shown in the accompanying picture, Fig. 1 pipe leading to the feed pump, and setting the latter representing the operation of these sprinklers in a in motion. As the boiler is filled by the incoming wa-PITCH pine beams will shrink in thickness from 18% room, and Fig. 2 being a larger perspective view of ter the longitudinal pipe is also filled, and by its coninches to $18\frac{1}{4}$; spruce from $8\frac{1}{2}$ to $8\frac{1}{4}$; white pine, the device attached to a pipe by which water is suptraction as it cools the lever fulcrumed at one end from 12 inches to 11%; yellow pine, a trifle less. Cedar plied under pressure. Within the body of the sprinkler is moved to close the value in the steam pipe leading beams will shrink from a width of 14 inches to 13¼; a valve is held to close the water supply opening, and to the feed pump, the spring on the rod also assisting elm from 11¾ to 10¾; and oak from 12 to 11¾ inches. to have a limited fall as the valve opens, the stem of to close the valve.

the feed-water pump. On the latter rod also is a coiled

THE PAINTING MACHINES AT THE WORLD'S FAIR. (Continued from first page.)

reservoir, etc., are mounted upon a truck which is readily moved from place to place. Into the reservoir atmospheric conditions on the day of the eclipse were At both these stations photographs were taken in adthe kalsomine is poured after having been properly all that could have been wished for, and that the remixed, and through it, from the bottom, there is sults will be satisfactory to the highest degree. He forced a jet of air at a pressure of 18 to 20 pounds per says, in a dispatch printed in the New York Herald square inch. In this manner the contents are kept on the morning of April 17: "The corona seen, gen-astronomical world from his association with Dr. agitated, and any deposit of sediment prevented. From the top of the reservoir the air is then conducted ically portraved by Captain Tupman, and complex. through a pipe to a point on the outside near the base, like that observed by Liais in 1857, which extended and here, by means of a half inch regulating valve, the color passes into the main air pipe, where it unites with the compressed air, forming a spray which passes into an ordinary three-quarter inch gardenhose of any desired length. At the end of this hose is attached a nozzle, consisting of a brass pipe, flattened out so as to corona. Filaments were numerous about both the leave an aperture one-sixteenth inch wide and about 1½ inches long. One machine furnishes spray for two nozzles, each being operated by a skilled painter, who During the total eclipse several flaming solar promiapplies the color as one would handle a lawn-sprinkling hose. While trained painters are not absolutely necessary to the proper operation of the appliance, it served, but the impression of the scene was rather one has been found that better results are obtained by their employment. From ordinary scaffolding the extended at the base, but not very long. The moon color is sprayed upon the woodwork in sections, the appeared of almost inky darkness, with only enough machine being moved as the work progresses.

In many cases in the main buildings the use of a tundity conspicuous, while from behind the orb separate compressor has been unnecessary, the Expo-streamed out on all sides the radiant filaments, beams sition having in operation throughout the grounds and sheets of pearly light, which formed an irregular underground pipes supplying compressed air for the operation of the ejectors in connection with the its center. The inner corona was of dazzling brightsewerage system. Where this power is available, the ness, but still more dazzling were the eruptive promiprocess is the same, except that the compressed air is nences, which blazed through it—to use the words of heated by means of a coil adjusted in a salamander containing a coke fire. This secures the proper temperature, and enables the machine to work in very cold weather, when hand painting is impossible. Heating is not required where individual compressors are used, because the friction of the machine raises the temperature of the air to the required point.

There are now at work within the grounds fourteen machines, each with a force of three men, working eight hours a day.

A' comparative test recently made showed that one painter could cover with a brush a daily average of about eight squares, while a machine upon similar work accomplished with equally satisfactory results nearly twenty times this amount, there being, however, two nozzlemen for each machine. As high as 304 squares have been done by one machine in eight hours, but this was an exceptional case, where all conditions were favorable for rapid work. On December 8, 1892, a number of machines began work upon the interior of the Manufactures building. At the end of three weeks, with a daily average of about 30 men. 1,332,669 square feet, half of the entire surface to be covered, had been finished. One of the advantages of this system is that in the coldest weather, when brushes are frozen solidly in transit from pail to wall, the machine work goes actively ahead.

The only comparison between machine and brush whereby the former suffers is in the amount of material used. Where 20 barrels of kalsomine are required for hand work, the machine will use 21. With lowest reading of the thermometer occurred several a saving, however, in time and labor of about 20 to 1, minutes after totality. Upon review of all the obserthe small amount of waste in material is scarcely worthy of consideration.

Luminous Air.

Dr. Philip Lenard, of Bonn, assistant to Professor Hertz, has recently exhibited a novel light produced contact, when the edge of the moon began to touch by electric oscillations, and a paper has been read on the subject before the Royal Prussian Academy of Sciences, at Berlin. Hertz has shown that the rays was at 8h. 19m. 9s. The third contact, marking the proceeding from the cathode of a Geissler tube, which are capable of exciting phosphorescence, will pass 59s.; and the final contact, at which the moon left the through thin metal. If it were practicable to find a sun's disk, at 9h. 30m. 10s. sheet of metal foil thick enough to be airtight and opaque, yet thin enough to be permeable by this dissage into the open air by closing an opening in a disapparatus in question a shutter which Dr. Lenard calls the "window," because while quite impermeable to air and light, it allows the rays from a cathode at a distance of 12 centimeters to penetrate it freely. These rays render the air faintly luminous. A halo of bluish light surrounds the "window," and is moderately bright only on its surface. At the same time a strong odor of ozone is recognizable. Substances capable of phosphorescence, if held near the "window," shine with their peculiar light on the side nearest to it. All the phenomena of phosphorescence cease if a magnet is so applied to the discharge tube as to repel the cathode rays from the inner side of the "window." The atmosphere is a dull medium for the cathode rays to penetrate, coal gas is more permeable, and so is hydrogen, while oxygen and carbonic acid are less permeable than air.-Elec. Engineer, London.

THE TOTAL SOLAR ECLIPSE OF APRIL 16. Professor Pickering, of the Harvard College station at Mina Aris, in the Chilean Andes, reports that the erally speaking, resembled the corona of 1871, as graphsome 700,000 miles from the sun. There were four streamers, two of which had a length exceeding the sun's radius, or stretching out more than 435,000 miles. Several dark rifts were visible, extending directly outward from the moon's limb to the utmost limit of the solar poles. Compared with the corona of January 1. 1889, the corona just observed was more brilliant. nences attained great distinctness and brilliancy. Within the streamers no rapid movements were obof calm and tranquillity. The streamers were widely illumination at the edge of the disk to make its ro-'star-like decoration,' with the black lunar globe in Professor Young-'like carbuncles.' "The spectroscopic observations secured are very

promising. As the eclipse progressed the temperature



PATH OF THE ECLIPSE OF THE SUN, APRIL 16

of the air fell considerably below its normal. The vations, it may be said the corona was a combination of that of 1871 and that of 1857, as drawn by Liais. The photographs obtained were very numerous and highly satisfactory."

In a subsequent dispatch it is stated that the first the edge of the sun, occurred at 7h. 17m. 6s. A. M. cessation of the total phase, was registered at 8h. 21m.

Professor Pickering says the results of photographs obtained with the differential spectroscope give twenty charge, it would be possible to allow these rays a pas- lines in the "reversing layer" of the solar atmosphere -the shallow stratum of gas lying just above the pho- He has also shown that the tint of the light is altered charge tube with such a piece of foil. This idea has to sphere and known to contain the vapors of many been realized by Dr. Lenard by means of an ingen-elements commonly found on our globe. Twelve of thanum, thorium, and zirconium all give a white light, iously arranged apparatus and a hammered aluminum these brilliant-colored spectral lines were seen through the oxides of cerium, didymium, and niobium, even in plate 0 003 millimeter thick. This plate forms in the the telescope. This is said to be the first time that small amount, give a yellow tint to the light, while these lines have been successfully photographed. Seven prominences were observed, estimated to have attained a height of 80,000 miles. The integrating spectroscope showed red and yellow lines, two green lines and one blue in the corona. A dispatch received by Director Holden, of the Lick Observatory, from Professor Schaeberle, states that the expedition sent to Chile from that institution to observe the eclipse was also signally successful, and are able to put it on the market at the price stated is a that fifty photographs were obtained. There were eight expeditions stationed along the line of totality for the observation of this eclipse, of which the United States observers selected locations try. upon the Andes, in Chile, where the atmospheric conditions were most promising. The expedition of the firm is likewise a gem in respect to mechanical perfec-Harvard College Observatory, under Mr. Bailey, Professor Albrech, of Valparaiso, co-operating with him, one dollar.

took their position at an altitude of 3,700 feet. Professor Schaeberle, from the Lick Observatory, went a few miles further north, to an altitude of 6,600 feet. dition to the visual observations. Next in order comes the expedition of the Argentine Republic, upon their own territory, under Mr. Thome, long known in the Gould in the production of the great catalogues of southern stars, which complement Argelander's catalogues of the stars of the northern heavens. In Brazil, upon the Atlantic coast, are three parties-an English expedition under the direction of Mr. Taylor, forty miles from Ceara; a French party in the same neighborhood, and a Brazilian party under the well known M. Cruls. On the coast of Africa there are two expeditions—an English expedition located sixty miles northerly from Bathurst, under the direction of Professor Thorpe, and a French expedition a few miles further to the southward.

When the photographs and full details from all these sources come to hand it is expected that they will form an important addition to our knowledge of solar physics, and possibly afford material aids in lines of investigation whose connection therewith has not heretofore been seen.

The Italian Torpedo Cruiser Arethusa.

The Arethusa is another of those ships of high velocity and great offensive powers which are soon to be added to the Royal Naval Squadron. Her principal dimensions are the following: Length, 70 m.; width, 8.20 m.; depth, 5.43 m.; tonnage displacement, 846.44 t. The armament is composed of six torpedo-launching tubes, five rotating on the deck and one fixed on the bow, of one cannon of 125 millimeters, of six cannons of 57 millimeters. Her defense consists of a deflective deck and coal bunkers super-added to it. The machinery, according to the contract, should be of 4,000 H.P., but the builders of the Arethusa, Orlando Bros., have been able to obtain the showing of 4,422 H. P. They consist of two vertical triple expansion engines supplied from four locomotive boilers with forced ash pit draught. Allowing for the great increase of horse power obtained, the speed has reached 21 knots as a maximum, and 20.7 knots as a mean of three hours trial, that is to say, about a mile in excess of the other ships of this type existing in our navy. The Arethusa with natural ventilation makes 18 knots, so under both natural and artificial draught she is the fastest ship in our navy next to the Piedmont. The plans of the ship are due to the lamented Commander Vigna, those of the engines to the engineer Salvatore Orlando. The guns come from the Armstrong establishment of Pozzuoli.—Revista Nautica.

Incandescent Lights.

The chemical composition of the mantle in the new Auer incandescent lights has lately been discussed in the Journal fur Gasbeleuchtung. The substance deposited on the cotton web consists of the oxides of metals of the cerium and zirconium groups, which exist in various minerals, for the most part in combination with silicic acid. The oxides are extracted from the minerals, and dissolved in nitric acid. This solution forms the bath in which the cotton web is dipped, and impregnates the latter so thoroughly that, on drying and burning, a finely meshed mantle of the oxides remains. It is necessary that the oxides employed in the manufacture should be free from iron, as that metal exercises a marked deleterious influence on the radiating power. Few experiments have been made to test the durability of mantles made from different oxides, but those of complex composition appear to last best. M'Kean has demonstrated that thorium oxide develops the highest illuminating power from the gas, while oxide of lanthanum ranks next, followed in order by the oxides of yttrium, zirconium, and cerium. A mixture of two-thirds oxide of thorium and one-third oxide of yttrium is recommended for obtaining the highest lighting efficiency. by the constitution of the mantle. The oxides of lan-

cerium oxide in large proportion gives a red light, and oxide of erbium a green one.

A Good Watch for One Dollar and a Half.

In another column will be found the advertisement of Messrs. R. H. Ingersoll & Bro. of their \$1.50 watches. We can say of this article it is an excellent time keeper, and fully answers to all they claim for it The fact they remarkable evidence of American ingenuity, while it also indicates the wonderful perfection to which clock and watch mechanism have been brought in this coun.

The little electric engine advertised by the same tion and operation, yet they sell it at the low price of

POSITION OF THE PLANETS IN MAY. VENUS

is morning star until the 2d, then evening star. She is in superior conjunction with the sun on the 2d. at 4 h. 15 m. A. M., passing from his western to his eastern side, and becoming evening star. She will be invisible for about six weeks on account of being so close to the sun, and will then emerge from her seclusion and gradually increase in size and brilliancy, until she stands highest on the celestial roll call, the sun and moon alone excepted. Observers will welcome her presence during the summer evenings, and rejoice in the light of her radiant luster as the months roll on. Her reign continues during autumn and winter, for she only reaches her greatest eastern elongation from the sun on December 6, her period of greatest brilliancy on January 12, 1894, and her inferior conjunction on February 16, 1894. The queen of the stars until that time will be most conveniently situated for observation.

Venus is in conjunction with Neptune on the 25th at 1 h. 35 m. P. M., being 1° 36' north. It will be noted that the inferior planets at superior conjunction seem to pass from the sun's western side to his eastern, while the superior planets at conjunction pass from the sun's eastern side to his western. The result is that the number of planetary conjunctions is increased, as in this case, where Neptune moving westward toward the sun meets Venus moving eastward from the sun, and their conjunction necessarily occurs.

The moon, when one day old, is in conjunction with Venus on the 16th, at 1 h. 6 m. A. M., being 3° 4' north.

The right ascension of Venus on the 1st is 2 h. 37 m. her declination is 14° 28' north, her diameter is 9".8 and she is in the constellation Aries.

Venus rises on the 1st at 5 h. 2 m. A. M. On the 31st, she sets at 7 h. 54 m. P. M.

SATURN

is evening star. He continues to hold his place as the only large visible planet and is finely situated for observation, with the brilliant Spica on the southeast, and with Gamma Virginis on the east, the beautiful double star that has been his companion for months. The planet is still retrograding or moving westward, is evening star. He is very near the sun, and almost and observers will note that the distance between him and the double star increases during the month. Saturn makes his transit on the 1st at 9 h. 50 m. P. M., and is plainly visible in the southeast, as soon as it is dark enough for the stars to come out. He cannot fail to be recognized, from the description given, and this excellent opportunity for the telescopic study of the ring-girdled planet and the noted double star should be improved.

The moon, three days after the first quarter, is in conjunction with Saturn on the 25th, at 3 h. 48 m. A. M., being 43' south. The conjunction is invisible, occurring when moon and planet are below the horizon. The moon occults Saturn and Gamma Virginis for observers in the southern hemisphere who are rightly located.

The right ascension of Saturn on the 1st is 12 h. 31 m., his declination is 0° 23' south, his diameter is 17'.9, and he is in the constellation Virgo.

Saturn sets on the 1st at 3 h. 48 m. A. M. On the 31st, he sets at 1 h. 47 m. A. M.

JUPITER

is morning star. He makes rapid progress westward from the immediate vicinity of the sun, rising on the 31st 1 h. 8 m. before the sun, when he becomes visible as morning star to sharp-sighted observers. Jupiter's diameter when farthest from the earth is 31".4. while the diameter of Venus under the same conditions is 9".8. The former became morning star four days before the latter became evening star, and makes his appearance in the morning several weeks before his rival graces the west with her visible presence.

Jupiter is in conjunction with Mercury on the 20th at 2 h. 6 m. P. M., being 56' north. The former a superior planet, and the latter an inferior planet, traveling in opposite directions, must meet on the celestial road when within certain limits. If one had eyes to pierce within the solar rays, an assemblage of planets would be found in near proximity to the great day star.. Jupiter and Mercury near together on his western, and Neptune and Venus on his eastern side. The moon, the day before her change, is in conjunction with Jupiter on the 14th, at 9 h. 52 m. P. M., being 2° 20′ south.

erful telescopes will be turned upon his disk, with the possibility of learning something of this strange world, where clouds are few and sunshine reigns.

The moon, when three days old, is in conjunction with Mars on the 18th, at 5 h. 15 m. A. M., bing 3° 32' north.

The right ascension of Mars on the 1st is 5 h. 25 m., his declination is 24° 20' north, his diameter is 4".5, and he is in the constellation Taurus.

Mars sets on the 1st at 10 h. 14 m. P.M. On the 31st, he sets at 9 h. 39 m. P. M.

MERCURY

is morning star. There is nothing of note in his course, as he makes his way from western elongation to superior conjunction, excepting his conjunction with Jupiter, already alluded to.

The moon, on the day before her change, is in conjunction with Mercury on the 14th, at 6 h. 56 m. A. M., being 3° 12' north.

The right ascension of Mercury on the 1st is 0 h. 59 m. his declination is 3° 7' north, his diameter is 7".6, and he is in the constellation Pisces.

Mercury rises on the 1st at 4 h. 5 m. A. M. He rises on the 31st at 4 h. 12 m. A. M.

URANUS

is evening star. He is still in excellent position for observation as he retrogrades or moves westward. Observers who have located the seemingly small planet will find it an enjoyable study to follow his course and keep track of the slow-motioned wanderer until he disappears from view. He is in a region almost destitute of visible stars, Alpha Librae on the east being his nearest neighbor of any size. At the close of the month, he has retrograded into his old quarters in Virgo.

The moon is in conjunction with Uranus three days before the full, on the 27th, at 6 h. 44 m. P. M., being I used about \$3,000 of Northern capital in prospecting, 1° 24′ south.

The right ascension of Uranus on the 1st is 14 h. 26 m., his declination is 13° 56' south, his diameter is 3".8, and he is in the constellation Libra.

31st, he sets at 2 h. 54 m. A. M.

NEPTUNE

at his greatest distance from the earth. His conjunction with Venus has been described.

The moon, the day after her change, is in conjunction with Neptune on the 16th, at 6 h. 50 m. P. M., being 5° 5′ north.

The right ascension of Neptune on the 1st is 4 h. 34 m., his declination is 20° 28' north, his diameter is 2".6, and he is in the constellation Taurus.

Neptune sets on the 1st at 9 h. 5 m. P. M. On the 31st, he sets at 7 h. 17 m. P. M.

Venus, Mars, Saturn, Uranus and Neptune are even ing stars at the close of the month. Jupiter and Mercury are morning stars.

Volcanic Activity at the Sandwich Islands. Mr. S. D. Macdonald, F.G.S., of Halifax, N. S., who is wintering on those islands, writes as follows:

"The somewhat abrupt termination of what promised to be a violent eruption from the summit crater of Mauna Loa, after its usual period of quiet, places the people of Hawaii in a state of awful suspense, fearing, as they have every reason to from past experience, that an underground lava flow is in progress, and may, at any moment, burst forth beneath them. Several sharp earthquake shocks accompanied the eruption, which is always considered to be a premonition of a flow. There can be little doubt but that an outburst from somewhere along the dome of the mountain is impending."

This summit crater, known as Mokua-weo-weo, has an elevation of 14,000 feet, and from it have come most of the lava flows that have wrought such destruction on that island. Its gently rounded top or dome, viewed at short distance, affords not the faintest indication of the fires which slumber within, and which, when they do awaken, cause such terrible earthquakes and lava

pit or lake of fire on the flank of Mauna Loa, has been unusually active for some months past. This vast pit or caldron is nine miles in circumference, with vertical walls, and a depth of from 400 to 1,100 feet, according to the rise and fall of its molten tide. At present intense action is confined to its western portion. Visitors and tourists who have witnessed it in magnificent action of late are enthusiastic in their description of its fiery fountains tossing their red-hot spray high in air. Its gory surges sometimes rolling in low, curling waves, and again dashing like wind-driven surf against lava cliffs, which fall, remelt, and form new waves, to be borne onward again in its blood-red tide, while dreadful detonations and earth tremors add sublime terror to the awful scene. In extent, grandeur and intensity of action, Kilauea is unrivaled among volcances. is allowed free.

Gorrespondence.

A Liquid Road Hardener Wanted.

To the Editor of the Scientific American:

I have an abiding faith in the inventors of America. Our State has just voted the amendment, good roads. Now we want the inventor to help us out, and he can own the earth.

We want a liquid that can be sprinkled on the roadbed from a tank, that will petrify the ground to a depth of four inches or more, that will not cost to exceed \$5 per rod. The ingredients would have to vary, as the soil varies. You can see the possibility of such a thing, and it may be possible.

Union City, Mich., April 6, 1893. D. L. MERRILL.

Progress of Mineral Industries in Virginia.

To the Editor of the Scientific American: For us it is a matter of glad tidings to see the flow of

Northern and foreign capital continuing with increased vigor toward the development of Virginia minerals.

About new year I began prospecting on the Irwin farm, Goochland County, for mica and discovered very valuable deposits of "lepidolite" (silicate of aluminum, potassium, and lithium) and "phlogopite" (silicate of aluminum, potassium, and magnesium) in kaolin and quartz, the former closely resembling the ores of Zinnwald, in Saxony, and especially those of Moravia and some sections of the Presidency of Bengal, in Hindostan; while the latter is equal in size and far superior in quality to the famous specimens extracted in such vast profusion from the Laurentian limestones of North Burgess, England, and reach the unusual size of $20'' \times 30''$.

To demonstrate the wealth of these new discoveries, under an optional right to purchase between January 1 and March 25, 1893, and during that time produced from within sixty feet of the surface, in open cut, over \$10,000 worth of lepidolite, phlogopite, and biotite. Uranus sets on the 1st at 4 h. 55 m. A. M. On the A Northern syndicate have purchased a tract of 1,500 acres near Irwin, at a cost of \$120,000, and are now preparing to work it on an extensive scale with \$250,000 capital, which is all fully subscribed, and to which I am consulting engineer.

Further up the James River, near West View, on the R. & A. R.R., on the Jayne & Case farm, I am bringing "to bank," from a depth of less than fifty feet, peculiarly fine specimens of "fuchsite" (silicate of aluminum, potassium, and about 6 per cent of chromic oxide), a bright green mica, such as is famous to Schwarzenstein in the Tyrol, and peculiarly adapted for grinding up for the manufacture of wall papers and other glittering decorations, such as Christmas cards, shop signs, theatrical purposes, and enormously demanded as a lubricant for rapidly revolving machinerv.

Here also land has jumped in price from the wearisome old agricultural value of not more than \$10 per acre up to \$100, and in one case I know of \$250 per acre.

Still further up the James and backward from it the use of hundreds of thousands of imported dollars is located, and the employment of vast sums of money, such as even the days of land booms in this country never paralleled, is going on with daily increasing strength, the money earning fabulous profits and dividends.

Mica, however, is not by any means the sole attraction and impetus to draw capital into mining here; for gold, cobalt, lead, graphite, and the generous family of hydrated silicates of magnesia are each and all taking a prominent part in our State's mineral pro-JOHN N. ADAMS. gress.

Civil and Mining Engineer.

Irwin and Richmond, Va.

Transportation of Frozen Fish.

Mr. John Wallace, a prominent fish shipper at Kalama, Wash., gives, in Ice and Refrigeration, some interesting facts in relation to the rail shipment of frozen flows, the like of which are unknown elsewhere. fish, which may be of general value. As our readers The crater of Kilauea or, more properly speaking, the well know, a large quantity of frozen salmon finds its way from the freezing plants at the fisheries to the East. In shipping the trade recognizes the fact that fish frozen solid will in part refrigerate themselves. They therefore pack them tightly in boxes and load into refrigerator cars. These cars are first reduced to as low a temperature as practicable, and then the floor is covered with several inches of chilled sawdust. The boxes of fish are then loaded in, leaving a space of several inches between the sides, ends, and top of the car, which also is filled with cold sawdust. Then the car is closed and sealed. No ice is placed in the tanks of the car, but it has been found by quite extensive experience that fish so packed for shipment reach their destination in perfect condition in reasonably warm weather without ice, and that, too, after a passage of fifteen to eighteen days. The saving effected is the first cost of the ice; then cost of freight on the ice, and also a gain of 1,500 pounds of fish in lieu of that much weight of ice, which by the practice of the N. P. road

The right ascension of Jupiter on the 1st is 2 h. 26 m., his declination is 13° 28' north, his diameter is 31".4, and he is in the constellation Aries.

Jupiter rises on the 1st at 4 h. 56 m. A. M. On the 31st, he rises at 3 h. 17 m. A. M.

MARS

is evening star. There is one thing to be said in his favor, and this is his high northern declination, always desirable in a planet's course. This would be more highly appreciated if he were in a different portion of his orbit. As he is practically invisible, his long stay above the horizon is of little avail, but, as in many terrestrial events, his time will come, when the most pow-

THE COLUMBUS CELEBRATION, NEW YORK.

scene of unusual and interesting festivities. In celebration of the four hundredth anniversary of the landing of Columbus in the new world, and as a fitting guests. The following ships of war will take part in prelude to the opening of the World's Columbian Ex- the great naval demonstration :

cession, the line of march being from the Columbian The harbor of New York will, this week, be the statue, at Central Park, down Fifth Avenue, Washington Square and Broadway to the City Hall, where the Governor of the State will receive the distinguished

THE SQUADRON OF COLUMBUS.

Three vessels have been constructed, the exact counterparts of those which formed the original squadron of Columbus. One of these, representing the Santa Maria, Columbus' ship, was built by the Spanish government; the other two, the Nina and position, at Chicago, a grand naval parade will here | FOREIGN.-English.-Blake, Magicienne, Tartar, Pinta, were constructed in Spain, at the expense of



THE ARGENTINE WAR SHIP EL NUEVE DE JULIO.

being worthily represented.

The magnificent waters of the Hudson River, which cover the heart of the great city on the west, form the anchorage for the great fleet, and here the ships, including the representative squadron of Columbus, deployed in two lines, will be reviewed by the President of the United States. This grand affair is appointed for the 27th inst. On the day following, the 28th, another most interesting festival takes place on | nington, Bancroft, San Francisco, Atlanta, Chicago, shore. Detachments of marines and sailors from the various war ships will land and join in a grand pro-¹ Dolphin, and the monitor Miantonomoh.

take place, the leading naval powers of the world | Australia; Spanish.-Reina Regenta, Infanta Isabel, | the United States. From Huelva these vessels, con-Nueva Espana; Russian.—Dimitri Donskoi, General Admiral, Rynda; German.-Kaiserin Augusta, Seeadler; French.-Arethuse, Jean Bart, Hussard; Italian.-Etna, Dogali, Giovanni Bausan; Netherlands. -Van Speyk ; Argentine Republic.-Nueve de Julio : Brazil.—Aquidaban, Tiradenta, and Republica. A few other representative vessels were also expected. AMERICAN.-Philadelphia, Newark, Baltimore, Ben-Yorktown, Vesuvius, Charleston, Concord, Cushing,

voyed by American war vessels, sailed over the original route taken by Columbus, to Havana, thence to Hampton Roads, and from there to New York, with the combined fleet of American and foreign ships, to take part in the naval festivities.

The Revue Maritime Autrichienne, of Pola, has recently published a very interesting article giving the result of all the investigations that have lately been made, particularly in Spain, for the purpose of ascertaining what was the exact type and maritime value of the three ships. The first of these, the Santa Maria,



THE GERMAN WAR SHIP KURFURST FRIEDRICH WILHELM.

© 1893 SCIENTIFIC AMERICAN, INC.

between perpendiculars, 75 feet; greatest width, 23 feet; the progress made in naval construction during the depth, 14³/₄ feet; burden, from 120 to 130 tons. As the four centuries that have elapsed, we give plates of some crew never exceeded ninety men, the ship was capable of the modern war vessels. Three centuries elapsed of carrying quite a large supply of food and water.

small three masted vessel, with five sails only; a jib,

foresail, mainsail, topsail, and a lateen. The general form of the hull was that of the round ships of the period. There was a large poop and a small forecastle. The freeboard was very low amidships, and the deck was here open.

The nautical qualities of the Santa Maria were excellent, as the admiral's log proves: "This ship behaved very well in bad weather, and had the speed of a good sailer."

The dimensions of the two other ships commanded by Columbus are not indicated. The sketches and the picture represent them as much smaller. The Nina resembled the Santa Maria. The Pinta carried lateen sails on her three masts, at least at the beginning of the voyage; but the admiral's log tells us that at the first stop (at the Canaries) this set of sails was replaced by square ones, in order that the ship might be placed in the same conditions as the These three two others.

the mainmast and that of the admiral at the mizzen. The first was divided into four squares, two red others a castle. These were the arms of Castile. Those of Aragon were excluded by the orders of Queen Isabella, the government of that country having refused to participate in the expenses of the expedition. The admiral's flag was a white pennant with a green cross between two crowned letters F and I-the initials of the names of Ferdinand and Isabella, who had given these arms to Columbus. A cross was painted on the sails of the ships, according to the custom adopted by the Spanish and Portuguese, in order

had the following dimensions: Length of keel, 62 feet; In contrast to the ships of Columbus, and as showing 18 knots; she is ship-rigged, Russia still regarding after the discovery of the new world by Columbus be-The suit of sails of the Santa Maria was that of a fore the discovery of steam navigation was made.

sails with favor. She has a 9 inch belt, but no horizontal armor; which the Russian naval authorities seem to have held in small account until last year. The Pamyat Azova was launched in 1887; she is 377 feet long by 50 feet beam, and is wood-sheathed over the

The very latest and probably the most perfect exam- armor belt. She mounts two 8 inch 13½ ton breech-



FURST FRIEDRICH WIL-HELM.

Another of our engravings, which is from Illustrirte Zeitung, represents the Kurfurst Friedrich Wilhelm, which was launched at Wilhelmshafen, June 30, 1891. The following are the chief dimensions of this vessel: length, 396 feet; breadth, 64 feet; depth, 36 feet; displacement, with medium draught of 24 feet 6 inches, 10,000 tons. Two screws, having a diameter of 16 feet 8 inches, are driven by two three-cylinder compound engines, giving a speed of between fifteen and sixteen knots.

The Heathen Chinee.

THE SQUADRON OF COLUMBUS-THE SANTA MARIA NINA AND PINTA.

ships, sailing as consorts, flew the flag of Castile at | ple of modern steam naval architecture is realized in | from California, who is on a visit to the Eastern the new Argentine war ship El Nueve de Julio, which cities, declines to commit himself on the Chinese figures to-day in the harbor of New York. We give an and two white. The latter each bore a lion and the engraving from Engineering. She is regarded as the fastest war vessel afloat, and is one of the most powerful. She is 350 feet long, 44 feet broad, 161/2 feet mean draught, displacement 3,500 tons, 14,500 indicated horse power; speed, 22 knots on 6 hours' run, 22.74 knots on mile run, being over 25 miles per hour.

Her machinery and magazines are below water line. She has sloping sides protected with steel $4\frac{1}{2}$ inches thick.

THE RUSSIAN CRUISER PAMYAT AZOVA.

to distinguish their vessels from those of the infidels. I illustration, is a vessel of 6,000 tons, with a speed of Chinese."

A well-to-do wine grower question-if there is a question. He says: "My personal dislike to the Chinese is as strong as anybody's, but that doesn't blind me to the fact that we Westerners would be nearly helpless without them.

"They have built our railroads, laid out our streets, hewn our wood, and drawn our water for us, and today we depend on them to run our farms and gardens. do our housework, and cook our food. They do for us what women servants do for you in the East. Besides, as between the Chinese and the men who direct hos-This ship, of which we give from the Engineer an tilities against them in San Francisco, I prefer the





THE RUSSIAN BELTED CRUISER PAMYAT AZOVA.

© 1893 SCIENTIFIC AMERICAN. INC

[APRIL 29, 1893.

EXPERIMENTS WITH SOAP BUBBLES. T. O'CONOR SLOANE, PH.D.

Soap bubbles afford so fascinating a subject for experiment that any notes on the subject are sure to prove of interest to many. In the experiments illustrated several properties of the film are shown. Its permanency and strength enable it to make the material for the sails or vanes of a wind mill. The mill wheel is constructed very readily with a bonnet pin as axle and a thin piece of wire fastened thereto, as shown, to determine the outline of the sails. This wire gives two loops, one on each side of the axle, which are then loop may be used, and the standard experiments with little gullies, or along the ridges of little hills, with no bent into a helical shape, as shown. A little stand is thread loops may be performed with a film inside of provided for it, as shown; the interior of the notches in soap bubbles. which the pin rests may be smoothed by being touched with a hot wire. This carbonizes the wood and forms dipped into a cup of soap bubble solution and removed therefrom; this leaves the vanes filled with the film,

drop is touched off with a piece of paper and the wheel is placed in its journals. To make it rotate, the experimenter blows through a paper tube, a foot long and one or two inches in diameter, standing about six feet from the wheel and holding the tube about six inches from the mouth and pointing at the face of the wheel. If held directly against the mouth, the blast of air will not reach. If the wheel is being projected in a lantern, it should be placed with its plane of rotation oblique with the plane of con-

may thus be made to spin with very high velocity.

The fact that a film tends to be as small, as possible is very elegantly shown by the use of a conical glass tube. By dipping its larger end deeply into fectly horizontal. the solution so as to wet the interior and withdrawing it, a film forms across its mouth. The film, tending to contract, travels toward the small end of the tube. A second film is picked up this time by a slight immer-|soda is dissolved in 320 parts of water; either rain

sion of the end, and it also proceeds on its journey. In this way a number of films can be formed in the tube, all traveling from the large to the small end at the same

If a large and a small soap bubble are placed in communication with each other, the small one will always empty into the large one. This may be shown by a more or less complicated apparatus, involving the use of a bifurcated glass tube or its equiva-

will completely disappear, and a single one containing the contents of both will be left. This is an exceedprinciple involved of breaking films within bubbles admits of many other experiments. Thus the entire film may be broken at once, producing a very rapid action. Three or four bubbles may be blown and stuck together and the films between them may be broken singly so as to aggregate all the bubbles into one. It is obvious that instead of the wire a thread

For blowing the bubbles nothing is better than a simple bottle with doubly perforated cork fitted with rider. The result (on rough roads or on any side slope) a better journal. To prepare it for use, the wheel is two glass tubes. The tubes may be from one-eighth is a constant nervous fear which makes the use of to one-quarter inch in internal diameter. Their shape these machines anything but joyous. The difficulty and arrangement are clearly shown in the cut. The in question would be very much increased with a narwhich is forced to take a helical form. The pendent bottle catches the condensed moisture of the breath row machine with the "two rear wheels about five or



densers, so as to receive a good breeze. The wheel which otherwise would interfere with the success of the tricycle there is a decided sensation in the rider's

the experiments. One great point to be observed in blowing a bubble is to start it with the mouth or opening of the pipe on which the bubble is formed per-

Many formulæ more or less complicated have been published for soap bubble solutions. The following I have found to be very satisfactory: 1 part of caustic

small the loop is, in a few seconds the small bubble rut while the other is upon a hummock several inches higher, the tricycle is one of the most uncomfortable and "tricky" machines imaginable, and in the case of ingly effective experiment, and it will be seen that the the country roads mentioned is not safe against upsetting sidewise—unless it is made very low and with the rear wheels three or four feet apart.

The beauty of a bicycle is that when the rider has once learned to keep it upright, this vertical position may be easily maintained, regardless of the side slope of the road, and, furthermore, the machine may pick its way in narrow and devious side paths, or along more difficulty than upon level ground. The tricycle, upon the contrary, immediately begins to tip sidewise, under the conditions named, much to the alarm of the

six inches apart," as proposed by the correspondent, "J." In such case a very slight difference of level sidewise would tip the machine at a considerable angle, so that it would be extremely difficult to prevent tipping over, while a bicycle under the same circumstances would stay perfectly upright.

When a "cycle" turns a rather sharp curve, even if the ground is level, the difference in favor of the bicycle is again very marked, as it can lean inward naturally to counteract its centrifugal force, while with

speed.

To sum up the

question, and assuming that the

road to be run up-

on is reasonably

flat and smooth, a

tricycle is a useful

and pleasant vehi-

cle for old people,

invalids, and oth-

ers who do not wish to learn or

practice anything

like acrobatic

work. It also has

the considerable

advantage that it

may be run very

slowly or stopped

entirely without

mind that he is about to be thrown over outwardly. One of the principles involved in the vertical position which the bicycle maintains (except upon curves) is that the combined center of gravity of the machine and of the rider keeps its path in a vertical plane, while with the tricycle this is impossible, unless the roadway is exactly horizontal sidewise, or unless one of the wheels leaves the ground entirely. As, however, both wheels are supposed to stay upon the ground, the consequence is that the center of gravity travels in a line which is wavy in a sidewise direction, the result being anything but pleasant for the rider or conducive to safety and high

SIMPLE DEVICE FOR BLOWING BUBBLES.

even under the roadway circumstances mentioned, is of course the extra weight which has to be transported -as for carrying a given load it is not possible to make a tricycle as light as a bicycle. Furthermore, considering the fact that our available roads are only reasonably flat and smooth, and the further fact that curves must sometimes be followed, all tricycles should have their centers of gravity as low as possible, and their wheels wide apart sidewise. Under conditions varying from those just given, a bicycle is by far the most practicable and pleasant vehicle, not only on account of its comparative cheapness, lightness, and high speed, but on account of its superior adaptability

Ec. Un

lent. In the cut a method of doing the same thing, water or distilled water should be used. To this is the rider leaving his seat. Its principal disadvantage, added 7 parts of pure oleic acid; the whole is agitated strongly until full combination has taken place. All the above parts are parts by weight. To 3 volumes of the above solution 1 volume of the purest glycerine is added and the whole thoroughly mixed by shaking. After standing a day or two, solid impurities float to the top; the clear solution may be siphoned from under them and is ready for use. It has sometimes seemed to the writer that it improves with time.

Bicycles versus Tricycles. BY OBERLIN SMITH.

Pertinent to certain communications by "J." in the February 25th and "A. G." in the March 25th issues of to all kinds and conditions of roads. bubble solution. To bring the interiors of the bubble in communicathe SCIENTIFIC AMERICAN, I wish to call attention to tion with each other, the film within the small loop on a very prevalent error in regard to the stability of the transverse wire must be broken. A short glass tricycles when comparing them with bicycles. This tube and a straight piece of wire are required for this error the writer once indulged in himself before he had purpose. One end of the wire is heated in a candle or learned to ride a bicycle and had found out with what lamp flame. The glass tube, which has previously perfect ease one of these machines will stay upright, been moistened with the soap bubble solution, is then apparently without a voluntary effort—that is when thrust right through the lower bubble in about the running. At first sight it seems ridiculous that a position shown in the cut. As it goes through the thing should stand upon two points instead of the bubble it picks up a film which closes it, and prevents proverbial three which we learned about in our the bubble from entering, although the film slowly school geometry. This, however, is not a case o travels toward the open end of the tube. The wire is standing, but of a combination of delicate motions. now thrust through the glass tube and with it the film The theory of the three points resting upon a plane, within the loop is touched, and the wire is at once as applied to a tricycle, is all right, provided the ma withdrawn. The hot wire breaks the little film the chine is running upon a horizontal plane, as upon the instant it touches it. As quickly as possible the tube floor of a rink or the center of an asphalt street. is also withdrawn or its open end is closed by the When, however, the conditions of the environment finger. Communication thus being established bechange, as, for instance, when one has to run upon the tween the interiors of the bubble by the breaking of sloping part of a street near the curb, or upon a slopthe film within the loop, at once the smaller bubble ing sidewalk, or, what is very much worse, upon counbegins to empty itself into the large one, and, however' try roads where the wheel upon one side may be in a 'far higher speed.

rate.

A SMALL BUBBLE EMPTYING INTO A LARGER ONE.

far more elegant because simpler, is given. A closed ring of wire with a handle is supported on a stand; the ring should be about an inch and a half in diameter. Across its center a thin wire is stretched, with a very small loop made at its center, which loop should lie in the plane of the large ring. A soap bubble is blown, about 2 inches in diameter, and placed upon the previously moistened ring. The ring is then inverted and a second soap bubble, as nearly as possible of the same size as the other one, is placed upon the ring. The condition of things thus brought about is that there is a soap bubble above and one below the ring, while the ring itself is closed with a flat disk of soap

WINDMILL SAILS OF SOAP BUBBLE FILM.

The Connelly Car Motor in England.

For the past two months a portion of the traffic on the London and Greenwich tramway system has been regularly worked by a small locomotive driven by oil vapor. This is the Connelly motor, which has had successful use on tramways in the United States for some time. The portion of line assigned to it on the Greenwich route is five-eighths of a mile in length, beginning just beyond the South Bermondsey Railway Station. The engine is fixed in a small car, and is capable of developing 12 horse power on the brake. From a return of seven days working-14 hours a day -it appears that 350 trips were made, covering 507.85 miles and carrying 4,182 passengers, with a total consumption of 70 gallons of oil. The engine works most satisfactorily, taking gradients and sharp curves well, maintaining the Board of Trade regulation speed of 8 miles an hour easily, and being evidently capable of a

RECENTLY PATENTED INVENTIONS. Engineering.

ROTARY ENGINE. -James C. Walker, Waco, Tex. This engine has a steam drum rotated by steam passing out through arms discharging into annular chambers rotating about the drum in a reverse direction, the arms carrying pistons which travel in the annular chambers, valves and steam spaces being arranged to deflect the steam and impart a rotary motion to the annular charges, as the steam is discharged from the drum. Two distinct rotary motions in reverse directions are obtained, and peculiarly arranged cut-off devices are provided, the discharge of the steam being automatically controlled.

Railway Appliances.

SLEEPER BLOCK.—Reuben D. Culver, Veedersburg, Ind. Sleeper blocks, preferably made of terra cotta, and with a broad, flat base and tapering sides. have side shoulders in which extend longitudinal rods connected by securing bolts to the base of the rail. The bases of the rails are shaped to conform to the beveled tops of the sleeper blocks, and the blocks and the rails are connected by cross tie rods. The blocks are arranged in trenches and rest upon a solid foundation, to afford a permanent and level seat.

RAILROAD GATE.-Wm. J. O'Beirne, Brooklyn, N.Y. This invention is especially for elevated railroads, the gate provided being designed to close the platform to the track and train until the latter is at a standstill. One long gate, moving easily on friction rollers, is held on the edge of the station platform, and this gate has openings at distances apart adapted to register with the platforms of the several cars, these openings being closed by auxiliary gates. By turning one hand wheel the operator moves the several gate openings to the proper place when the train stops, and by turning another hand wheel the several gate openings are simultaneously opened and closed.

Electrical

ALARM CLOCK.-Thomas P. Adams, Rico, Cal. An attachment for an ordinary alarm clock is provided by this invention, by means of which an alarm may be given by an electric battery and bell, the alarm to continue until the circuit is broken. A case contairing the battery has on its upper side two contact plates and an insulating piece, upon which rests an ordinary metallic clock, the alarm being connected with the plates. A circuit maker is adapted to be held elevated by the winding arbor of the alarm, and when released it descends upon the other contact plate and electrically connects the two plates through the medium of the clock case

Mechanical.

MORTISING MACHINE.—Christian Loetscher, Dubuque, Iowa. A tilting frame is mounted to turn on the bed plate frame, a bed plate being held laterally adjustable on [the tilting frame, while a clamping plate sliding on the bed plate has a rod, the axis of which forms the center of the tilting frame. The invention is an improvement in chain tool mortising machines. After the machine is once started no further attention is required, the several mechanisms being actuated automatically and the operator only needing to remove the material to be treated or shift it on the bed plate to bring it in proper position for the mortising tool.

FLOOR CLAMP.-Geo. O. Woolcocks, Brooklyn, N. Y. The head of this tool has slotted arms between which fits a toe piece having parallel arms and spurs, there being a cam lever between the arms of the toe piece, while a pin passing through the arms of the toe piece and cam lever projects into the slots of the arms of the head. This clamp is light, strong, and inexpensive, takes up but little room, and may be quickly applied to the boards of a floor, wall, or ceiling, to force them firmly together and hold them in position until they are thoroughly fastened.

STAIR BEVELING INSTRUMENT.-John A. Caldwell, Vancouver, Canada. 'This is an improvement on a former patented invention of the same inventor, for an instrument for describing stair curves. The invention consists of blades having slotted transverse guideways, sleeves engaging the compass legs being held transversely adjustable in the guideways, the sleeves being also mounted to turn in the guideways. The improved instrument is simple and durable in construction, and adapted to be readily and conveniently adjusted and manipulated for drawing the desired lines.

Agricultural.

WHEEL PLOW.-Abraham Dalke and Gustav Wiens, Henderson, Neb. This invention provides an improvement in gang plows whose frames are the gate. The post is strong and readily set up, permits adjustable vertically by means of cranked axles, that the full opening of the gate, and allows for its adjustplows may be made to run at different depths in the soil, mentat any desired height from the ground. or readily moved from place to place. Three plows are rigidly secured to the frame, on a line diagonal to the line of draught, and the rear one only has a landside, a forward wheel on a front laterally bent axle rendering landsides unnecessary on the two front plows. The main axle is rocked, and the plows raised or lowered by a hand lever within convenient reach of the driver, and having a spring-pressed dog for locking it to a notched fixed segment TRANSPLANTER.-Daniel Clow, Janesville, Wis. This invention relates more particularly to an improved tobacco transplanting device, providing an apparatus adapted to carry a supply of water, and means for intermittently discharging a definite quantity upon each plant as it is placed in the ground. A vertically adjustable frame regulates the depth of the furrow, the discharge of water upon the plant is controlled by a regulating valve, and an adjustable feeder's seat carries the rollers which press the dirt with the desired pressure around the plant.

method of charging water with lime, the latter being de livered to an upwardly flowing column of water below its outlet, the charged liquid being decanted at a point above while the undissolved lime gravitates toward the inflowing water, and is prevented from flowing out with the charged liquid, affording a continuous production of milk of lime. A saturating apparatus based on the same principle is employed for preparing solutions of soda, barium, or other readily soluble reagents.

TREATING GOLD AND SILVER ORES. George W. McGee, 531 Sacramento Avenue, Chicago, Ill. According to the process provided by this invention, the crushed ore is submerged in a solution of caustic soda or potash, the mixture is heated and to it are added salts of oxalic acid and sulphate of copper or bluestone, the liquid being then evaporated from the mixture. The process is simple and comparatively inexpensive, and is designed to render refractory and other ores free milling, preventing the gold or silver from volatilizing during the process of reduction.

PARACHUTE PROPELLER.-Elijah Nyswanger, Hanford, Cal. Two scoop-shaped paddles are pivoted oppositely on a reciprocating frame or carrier, and arranged with their concave sides inward, with means for throwing the paddles alternately into operative position inclined to each other to form a conical pocket, and into inoperative position or parallel to each other, there being a crank connection between the hinged paddles and crosshead rods. The hinged paddles or wings open to offer resistence to the air or water when pulled in one direction, and when pulled in the opposite direction, they tilt into position to move with little resistance. The propeller is adapted for use on vessels in the water or on air ships.

SPRING HINGE.—Herman Reichwein, Villa Park, N. J. An improvement simplifying the construction of double-acting hinges has been made by this inventor, the new hinge having but few parts, and designed to be perfect in action, durable, and quickly applied. It has a stationary and a swinging section, the latter having a rocking movement upon the other at their inner faces, while a pintle with two transversely connected vertical members is mounted in the sections, and a spring between one hinge section and its vertical mem ber, the spring being in a suitable barrel or casing

UMBRELLA NOTCH AND RIB.-Harry L. Heck and William S. Kellogg, Little Rock, Ark. The body of the notch has a flange with rib sockets, and a recess above the flange adjacent to which is a spring, a cap having an aperture to receive the spring when the cap is forced upon the body, the two sections being readily disconnected by forcing the springs inward. A device is also provided for attaching the cover to the ribs at a point intermediate of their lengths, and it consists of a wire bent upon itself to form an eye or loop at the top of the rib, to which the cover is stitched. The wire is carried down on opposite sides of the rib, and bent up-ward into its hollow U-shaped portion, where it is extended longitudinally.

MATCH BOX.—Housatonic Brass Company, Wallingford, Conn. The hinged cover of this box is adapted to receive and hold by frictional engagement a removable cap or casing constituting a separate chamber for the reception of dice, etc., the cup or casing being adapted for use as a dice box when taken out of the cover.

HORSE DETACHING DEVICE.-Charles E. Harris, Brandon, Cal. A lever pivoted on the breas collar is connected with the traces, a casing supported from the harness saddle being also connected with the traces, the casings being fastened to the shafts or poles by a locking device in which the locking latches are engaged by tripping levers upon the pulling of a wire by the occupants of the vehicle, the casings then sliding over the thills on the further forward motion of the animal. The animal is very quickly attached to the vehicle where this improvement is employed, and may be instantly released from the vehicle in case of accident or a runaway.

BIT BRACE. - John E. Hitch, Wilmington, Ohio. This brace has an adjustable sweep, that the brace may be readily adapted to a large or small boring bit, or for boring in contracted spaces. The horizontal portions of the sweep are in two sections, the outer sec tion, on which is the handle, being so jointed to the inner arms that it may be extended out at full length from the bit, or adjusted so that the handle will be nearly up to the vertical line of the bit.

GATE POST.-Joseph W. Barnes, Mauzv. Ind. This gate has a base consisting of two parallel beams and connecting braces, the metal post passing through one of the beams, and having at its lower end a foot packed by the ground. Brace rods connect the upper end of the post with the outer beam, and collars vertically adjustable on the post form seats for the eyes of

FAN ATTACHMENT FOR CHAIRS.-Anton Flierboom, Elizabeth, N. J. A foot rest adapted to serve as a treadle is held in arms pivoted near the bottom of the front legs of the chair, and there is a crank and pitman connection between the treadle foot rest and a shaft journaled under the seat, this shaft being connected by a belt with a vertical shaft at the chair back, on the upper end of which is held a fan wheel. A pitman from the crank is also connected with a bellows, so arranged that when the fan wheel is rotated the bellows will direct a current of air upon the feet and legs of one rocking in the chair. WASHING MACHINE.-Ernest W. Gerbracht, Brooklyn, N. Y. This is a machine for scouring or cleaning filter press cloth, blankets, bags, etc., and the that no index is contained, an omission which is very cleansing material is held in a sluiceway over which passes a carrier with the fabrics, the scouring devices acting in the presence of the cleaning compound, and the material during the process being made to travel in a direction to carry the cleansed portion away from the cleansing material. The operation of the brushes is automatic, and the adjustable and traveling carriers have automatic WATER PURIFYING PROCESS .- Alfred clamps to hold blankets or cloths of different thick-

WASHING MACHINE.-Frank J. and Mead C. Coon, Walla Walla, Washington. Mounted centrally on spiral springs, so as to be easily rocked, is a suds box having a flat bottom and straight sides and ends, and inclined end shelves extend toward the center and bottom of the box to form pockets with contracted mouths. As the box is rocked, and the water and clothes thrown alternately from one side to the other, the air in the pockets is compressed and released, and the air and water are forced through the clothes in alternately opposite directions

CLOTHES DRIER .- Thomas Fry, Calgary, Canada. This is an improvement in clothes horses or racks, and consists of a suspensory device which may be readily attached to or detached from a socket secured to the ceiling or other overhead support. It is of simple construction, the rack being readily lengthened or shortened and revolved in its socket as desired, while the arms which receive the clothes may be easily disconnected from the body of the rack, enabling the device when not in use to be placed in a small compass

FLAT-IRON HOLDER.—Carl C. Moritz nd Stephen D. Greenwood, Salt Lake City, Utah Ter. This holder is made in two hinged sections, adapted to be quickly closed upon the handle of a flat iron, no matwhat the diameter of the handle may be. The fingers of the hand are also protected from the heat of the iron by a fender or guard held beneath the handle, both the holder and the guard having an asbestos-coated surface where they come in contact with the heated iron.

JAR CLOSURE. - Frank. H. Palmer, Brooklyn, N. Y. This improvement provides for securely fastening a jar cover in place to prevent leakage, and also to prevent fruit or other solid contents from being exposed to the air above the liquid in the jar. The solid contents are held down by a cover plate having projections extending into the upper end of the jar, and the latter is formed with an exterior flange having a double bevel, while the cover has a bail with downwardly extending arms having inwardly bent lugs abutting on the lower bevel, and adapted to engage the bottom of the flange when the bail is pressed.

Designs.

BRUSH OR MIRROR BACK.-Austin F. Jackson, Taunton, Mass. This design embodies floral sprays introduced inside of beads around the edges, in combination with convoluted scrolls and ribbon-like repentations

MEDAL.-Cesar Orsini, Rome, Italy. The obverse side of this medal has medallions represent ing Columbus and Washington, with an eagle spreading its wings above and holding an olive branch in its talons beneath. The reverse has a heroic figure of Liberty gazing at a cross apparently displayed in the sky over the grounds of the Columbian Exposition.

NOTE.-Copies of any of the above patents will be furnished by Munn & Co., for 25 cents each. Please send name of the patentee, title of invention, and date of this paper.

NEW BOOKS AND PUBLICATIONS.

A MANUAL OF MACHINE DRAWING AND DESIGN. By David Allan Low and Alfred William Bevis. London : Longmans, Green & Co. 1893. All rights reserved. Pp. vii, 375. Price \$2.50.

The title of this work explains very fully its scope. It overs the mechanical drawing of all kinds of machinery, including boilers. A large number of illustrations, all in line work, are given to elucidate more thoroughly the subject. Some general principles of mechanics and notes on mechanical drawing precede the main volume of the work. It will be found a thoroughly meritorious contribution to the literature of the draughtsman's art.

THE MANUFACTURERS OF THE UNITED STATES. A classified and complete reference book for buyers and sellers for domestic and foreign trade. 1892. New York: The Manufacturers' Publishing Co. Pp. 1,500. Price \$10.

This work may be divided into three parts. The first is an index of articles. This is most exhaustive, covering about eighty three-column pages of fine print. These pages are numbered. After them comes the second and principal part of the work. This is the list of manufacturers of and dealers in the articles named. It is arranged in alphabetical order, referred to the articles. Under each one are given the names of the firms or houses handling the article. To this part pages 1 to 991 are devoted. The third part is devoted to the larger industries, some eightythree heads being given and pages 1500 to 1817 being given to them, From page 991 to 1500 there is a break in the numbering, the design being to allow for the insertion of extra pages. The exceedingly systematic arrangement of parts and the exhaustive indexing make this a very

merous tables relating to the determination of curves for railroad lines. The work is bound in a cover adapted to the pocket and its whole aspect is one of a field book which will be in constant use by the practical engineer.

CONTRIBUTIONS FROM THE LICK OB-SERVATORY. No. 3. Terrestrial atmo-spheric absorption of the photo-graphic rays of light. By J. M. Schaeberle. Sacramento: State Office, A. J. Johnstone, Superin-tendent State Printing. 1893. Pp. 89. 89.

 $From the Lick\ Observatory\ this\ monograph\ is\ sent\ us.$ It will be found of special value in these days of photographic astronomy, and its technical value will be certainly very widely recognized by astronomers.

- INDIANA. DEPARTMENT OF GEOLOGY AND NATURAL RESOURCES. Seven-teenth annual report. S. S. Corby, State Geologist. 1891. Indianapolis: W. B. Burford, contractor for State printing and binding. 1892. Pp. 705. 22 plates.
- THE COSMIC ETHER AND ITS PROBLEMS. A scientific sketch. By B. B. Lewis. Bridgeport, Conn.: The *Evening Post* Print. 1893. Pp. vii, 159. Price \$1.
- ANNALS OF BRITISH GEOLOGY. 1891. By J. F. Blake. With six plates. London: Dulau & Co. 1892. Pp. x, 404.

'I'his excellent work will be seen from its title to be a tine qua non for working geologists. It contains an abstract of a very large number of papers on geology, mineralogy, lithology, and allied topics.

FIRST REPORT OF THE STATE ZOOLOGIST, ACCOMPANIED WITH NOTES ON THE BIRDS OF MINNESOTA. By Dr. P. L. Hatch. Henry F. Nachtrieb, State Geologist. Minneapolis: Har-rison & Smith, printers. 1892. Pp. 487

Any of the above books may be purchased through this office. Send for new book catalogue just published. MUNN & Co., 361 Broadway, New York.

SCIENTIFIC AMERICAN

BUILDING EDITION.

APRIL, 1893, NUMBER.-(No. 90.)

TABLE OF CONTENTS.

- 1. Elegant plate in colors, showing an attractive cottage at Villa Park, Mt. Vernon, N. Y. Floor plans and perspective elevations. Cost \$4,500 complete. Mr. Walter Stickels, architect, Mt. Vernon, N. Y.
- 2. Plate in colors showing the handsome Queen Anne residence of the Hon. Craig A. March. at Plainfield. N. J. Two perspective views and floor plans. Mr. Chas. H. Smith, architect, New York. An excellent design.
- 3. A dwelling near Longwood, Mass., erected at a cost of \$5,200 complete. Perspective views and floor plans. A model design.
- 4. A dwelling at Chester Hill, Mt. Vernon, N. Y., erected at a cost of \$4,750 complete. Floor plans, perspective view, etc. Mr. W. H. Symonds, architect, New York.
- 5. Engraving and floor plans of a residence at Oak-wood, Staten Island; N. Y., erected at a cost of \$3,540 complete. Mr. W. H. Mersereau, architect, New York.
- 6. A stable erected at Bridgeport, Conn. A unique design.
- 7. A residence at Wayne, Pa. A very picturesque design, treated in the Queen Anne and Colonial styles. perspective elevation and floor plans. Cost, \$6,250 complete. Messrs. F. L. & W. L. Price, architects, Philadelphia.
- 8. Engraving and floor plans of a Queen Anne residence at Newton Highlands, Mass. Cost. \$6.000. Messrs. Rand & Taylor, architects, Boston.
- 9. A square-rigged house, recently erected at Allston, Mass. Cost, \$2,600. Plans and perspective elevation. Mr. A. W. Pease, architect, Boston, Mass.
- 10. The Fifth Avenue Theater, New York. View of the main front, showing the terra cotta decorations; also view showing the iron framework, erected by the Riverside Bridge and Iron Co., and a view showing the fireproof arching, erected by the Guastavino Fireproof Construction Co.

11. Sketch of a dining-room fireplace.

Miscellaneous.

Dervaux, Brussels, Belgium. This invention provides a nesses.

valuable and acceptable book

TELEPHONE LINES AND THEIR PROPER-

TIES. By William J. Hopkins. New York : Longmans, Green & Co. 1893. Pp. xvi, 258. Price \$1.50. No index.

The extension of telephony is well shown in the publishing of this work, devoted entirety to what may be termed telephone engineering. Underground and overground work, long-distance lines, properties of wire, insulators, exchanges, switchboards, interferences from outside sources and similar topics form the body of the work. It will be found an excellent contribution to the literature of electricity. It is very greatly to be regretted severely felt, especially in scientific books

SWITCH LAYOUTS. By Augustus Torrey New York: Published by the Railroad Gazette. 1893. Pp. 191. Price \$1.

This pocket book contains over a hundred representa tions of methods of laying frogs and switches on railroad tracks. The numerous plates are all put together and followed by the subject of curve easements, with nu-

12. Miscellaneous contents : An improved woodworking machine, illustrated.-A new edge moulding or shaping machine, illustrated .- The box industry .-Natural gas at Geneva, N. Y .- Plaster of Paris floors.-Inside sliding window blinds and screens. illustrated .- City pavements -- The Alberene laundry tub, illustrated.-The "Murray" phaeton, illustrated. -An elegant bath tub, illustrated.-To thaw out frozen pipes .-- Improved plane irons, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITEC-TURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural Publication in the world. Sold by all newsdealers. MUNN & CO., PUBLISHERS, 361 Broadway, New York.

Business and Personal.

The charge for Insertion under this head is One Dollar a line for each insertion ; about eight words to a line. Adver tisements must be received at publication office as early as Thursday morning to appear in the following week's issue

Acme engine, 1 to 5 H. P. See adv. next issue

"U. S." metal polish. Indianapolis. Samples free Improved iron planers. W. A. Wilson, Rochester, N.Y. Wood pulp machinery. Trevor Mfg. Co., Lockport, N.Y Chain Belting & Grain Dryers, F. H. C. Mey, Buffalo, N.Y. Microbe Killer Water Filter, McConnell Filter Co.

Buffalo, N. Y. Patent Open-Side Planing and Shaping Machines

Pedrick & Ayer, Philadelphia, Pa.

Steam Hammers, 1mproved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York. Screw machines, milling machines, and drill presses

The Garvin Mach. Co., Laight and Canal Sts., New York Centrifugal Pumps. Capacity, 100 to 40,000 gals. per

minute. All sizes in stock. Irvin Van Wie, Syracuse, N.Y To Let-First floor. Wide entrance and space for ex perimental work. Light, power, etc. 521 West 30th St.

Manufacturers' illustrated truck and wagon catalogue mailed on application. Boston & Lockport Block Co. Lockport, N. Y.

Portable engines and boilers. Yacht engines and boilers. B.W. Payne & Sons, Elmira, N. Y., and 41 Dey Street, New York.

To Let-A suite of desirable offices, adjacent to the American offices, to let at moderate terms Apply to Munn & Co., 361 Broadway, New York.

Fine Castings in Brass, Bronze, Composition (Gun Metal), German Silver. Unequaled facilities. Jas McKenna & Bro., 424 and 426 East 23d St., New York. Jas. J

Hydrocarbon Burner (Meyer's patent) for burning crude petroleum under low pressure. See adv. pag 381. Standard Oil Fuel Burner Co., Fort Plain, N. Y.

For Sale or on Royalty—The simplest, most economi-cal, and practical reel for winding barbed wire by horse nower, No. 467,498, R. S. Dickinson, Columbus, Neb.

For the original Bogardus Universal Eccentric Mill. Foot and Power Presses, Drills, Shears, etc., address pure ammonium carbonate. Fuse the precipitated car-J. S. & G. F. Simpson, 26 to 36 Rodney St., Brooklyn, N. Y. | bonate with potassium cyanide, and fuse the metal thus

The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4; Munn & Co., publishers, 361 Broadway, N.Y.

Competent persons who desire agencies for a new popular book, of ready sale, with handsome profit, may apply to Munn & Co., Scientific American office, 361 Broadway, New York.

Any Manufacturer

of hardware or machinist's specialties, desiring to be represented in New York City and vicinity, will find it to his interest to address E.J. Hussey & Co., 80 John Street. New York. We are centrally located, active workers, and can furnish best of references.

IF Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.



HINTS TO CORRESPONDENTS.

Initials To conflicts on DELFIG.
Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information and not for publication.
References to former articles or answers should give date of paper and page or number of question.
Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.

Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.

Scientific American Supplements referred to may be had at the office. Price 10 cents each. Books referred to promptly supplied on receipt of

Minerals sent for examination should be distinctly marked or labeled.

(4940) H. L. L.-We would not advise you to try the experiment of driving your boat with a primary battery. You might do it with storage batteries, but we think you would get more satisfaction out of steam than from anything else. For 2 horse power you will want 16 large cells of plunge battery. These would be very troublesome and somewhat expensive to maintain. It will cost you probably not less than \$3 a day in addition to the labor required to take care of them

(4941) A. C. F., Cal., writes · With a water pressure of 20 pounds per square inch, what is the horse power of a water wheel whose diameter is 12 inches, two jets being used whose outlets measure three-six- into steam in a tube or boiler containing 5 cubic feet of teenths inch respectively? Please give rule for finding horse power of this wheel. If above wheel were 18 inches about 5,000 pounds per square inch and temperature of hundred feet, water supply unlimited? A. Rams work in diameter, would it have more power? Will above wheel, with pressure named, run hand dynamo illustrated in SCIENTIFIC AMERICAN SUPPLEMENT, No. 161, at the rate of 2,400 revolutions per minute (I mean 12 inch wheel) ? A. The 12 inch wheel with good buckets, like the Pelton wheel, with the pressure named, should run 500 revolutions per minute and be equal to four-tenths of a horse power, consuming 6 cubic feet of water per minute, and will run the dynamo. The 18 inch wheel will run 340 revolutions per minute and give you three-fourths horse power, using 10 cubic feet of water per minute. The 18 inch wheel will have no more power than the 12 inch with the same amount of water. Address the Pelton Water Wheel Company, San Francisco, for their catalogue of water wheels, from which you may obtain the power value under the varying conditions. The rule requires more explanation than we can give in Notes and Queries.

(4943) M. B. B. asks: If a ball be dropped into a hole that passes clear through the earth, vould it stop when it reaches the center or pass by it? I hold that the ball would stop, and I wish to settle an argument. A. The ball would have a hard rub in getting down to the center at all. Its circumferential velocity. derived from the earth's motion on its axis, would keep it against the east side of the hole, unless the hole was through the polar axis of the earth, when it might bob back and forth for a time until friction settled it at the

(4944) F. S. asks: 1. Is there any heat produced by the friction or motion of water? Is the temperature the same at the foot of Niagara Falls as in the river above? A. The agitation of water produces heat by friction, as demonstrated by Rumford and by experiments with screw propellers in a tank of water. Theoretically, the water in the pool should be slightly warmer than above the falls by friction, probably not within the means of observation. 2. Is there a reasonable probability that aluminum, in the near future, can be produced so cheaply as to come into practical use for roofing and other building purposes ? A. There is no easonable probability of aluminum becoming as cheap as tinned iron, zinc, or even copper for ordinary uses for some time yet, although its lightness now makes it about twice the price of copper per bulk.

(4945) W. B. H. asks: Will you please give me the processes for preparing chemically pure zinc and lead from the ordinary commercial metals? A. Zinc can be purified by simple distillation. This will remove most of the impurities. For the production of chemically pure lead the following process is given. As it is very complicated, probably your best plan will be to buy test lead as provided for assayers. This is almost chemically pure. Heat solution of lead acetate in a lead vessel with sheet lead at from 40° to 50° C. Filter and precipitate with dilute sulphuric acid. Treat the lead sulphate with a solution of ammonium carbonate and ammonia; this gives lead carbonate. A portion of the carbonate is heated in a platinum vessel just enough to give lead oxide. To the rest add dilute nitric acid, enough to dissolve part of the carbonate. To the boiling solution of lead nitrate thus produced the oxide is added, and the filtered solution is poured into a solution of produced again with potassium cyanide.

(4946) M. V. C. writes: Please inform how and what I will use to recast (scrap) Britannia metal so that it will have the same qualities as it has originally. That is its color and other properties. A. There is considerable variation in the composition of Britannia for various uses, and for the various parts of the same article. The alloy mostly used is composed of tin 15 pounds, antimony 1 pound, copper 3-10 of a pound. The solder on the work may be pure tin or a mixture of tin, lead or bismuth. Melt the metal in a kettle covered with pulverized charcoal. Add from 5 to 10 per cent of tin to make the metal cast clear.

(4947) G. S. asks how are guitars finished or varnished ? What kind of varnish is used ? A. The wood of guitars is finished as finely as possible with the finest sand paper; then rubbed with varnish on a piece of white woolen cloth, to fill the pores, leaving as little varnish on the surface as possible. When dry, rub down the surface to smoothness with the old sand paper that had been used ; then varnish with a thin coat, using a flat camel's hair brush. Make the varnish with gum mastic 1 ounce, gum sandarac 1/2 ounce, gum camphor 1/4 ounce, 95 per cent alcohol 2 fluid ounces; place in a clean bottle and dissolve, occasionally shaking up, then let it settle and decant for use. See next query also

(4948) L. C. R. says: Please give me a recipe for varnish used on violins. A. The famous Italian violin makers used, it is said, the following sort of varnish on their instruments : Rectified alcohol 1/2 gallon, 6 ounces gum sandarac, 3 ounces gum mastic and 1/2 pint turpentine varnish. The above ingredients are put into a tin can by the stove and frequently shaken until the whole is well dissolved. It is finally strained and kept for use. If upon application it is seen to be too thick, thin with an addition of more turpentine varnish. The wood should be stained before applying the varnish. For a red stain use camwood, logwood, or aniline.

(4949) W. T. M. asks: What is the H. P. of the electric motors used on street cars? And how can you figure the pressure of a boiler with common arithmetic? E. g. you put 1 cubic foot of water in a tube and evaporate it; the volume of the tube being 5 cubic feet, what will be the pressure of the steam in the tube; and if the volume of the cylinder of the engine is 30 cubic inches, 200 revolutions, how many additional cubic inches of water must be evaporated per hour to sustain this pres-

sure? A. Street cars require from 7 to 10 horse power for driving them. The volume of a cubic foot of water at 39° converted into vapor is 1641 cubic feet at atmospheric pressure. One cubic foot of water converted

located close by the banks of a tidal river. There is an bundance of excellent water from the well for ordinary daily domestic consumption. We desire to have an auxiliary supply in case of fire, by running a pipe direct to the river and pumping therefrom. We have consulted hydraulic engineers, and they differ in opinion. Now I would like to ask you, if we run this pipe from the bottom of the well to low water mark in the river, will the water flow into the well from the river, or will the reverse be the result and we lose our present supply by the ing of power in two cases as follows ? 1. Belting, a chopwater flowing from the well into the river? It is upon this point that the engineers differ. A. If the water in the well at ordinary height is higher than the water in the river, it will flow to the river; if lower, the river will flow to the well. It requires but little engineering to ascertain the exact conditions. Better make a direct connection from the river to the pump, with valves to control the suction from both directions

(4953) W. H. H. asks: How is the beautiful polish produced on the stocks of high grade guns ? A. The stocks after finishing with the finest sand paper are varnished with pure shellac dissolved in 95 per cent alcohol, dried, and rubbed down fine with the old sand paper. Another coat of shellac is given. Then rub with French polish or shellac and mastic equal parts in alcohol with woolen cloth until the desired polish is obtained.

(4954) H. M. asks: Can you inform me through your valuable paper how to make a hard black cement or filling, something that will bake or dry hard, and not be affected by the heat generated in polishing the metal in which it is used? A. Use fine iron borings and sulphur, made into a putty, hot. Press it hard into the hole. 2. What substitute is there for nitric acid in the process of dipping brass work that will produce the same effect without raising fumes? I know there is something, and would like to find out what it is. A. Oxalic acid acts similarly to nitric acid, but is not as active

(4955) H. B. asks: How many horse power would a constant stream of water of 2,000 gallons per minute produce with 40 feet fall through standpipe by means of a horizontal (or later style) turbine? A. The total value of the power as stated is 20 horse power, from which a net 17 horse power may be utilized

(4956) W. F. B. writes : I desire to make inquiry of you as to the best method of restoring the tone of a large bell which is cracked. The dimensions of the bell are as follows : Height 2 feet, diameter at base 2 feet 11 inches, thickness 21/2 inches. The bell is hung in the first Methodist church of this place, and was cracked by a crowbar or some other instrument falling on it from above. The crack is about 11 inches long, beginning 41/2 inches from the base and one inch from place where clapper strikes, running diagonally up the side, upper end of crack being 13 inches from base of bell. I wish to know the best method of sawing out the crack and what width the edges of it would have to be separated to prevent their coming in contact by the vibration. A. Drill a half inch hole at each end of the crack and saw out the crack between the holes with a narrow stiff hack saw three thirty-seconds of an inch thick. A frame may be made of iron spanning the bottom of the bell, to hold the hack saw and keep it from kinking. The position of clapper stroke should be changed as far as possible away from the crack. If a swinging bell, it should be turned around. The clapper should also be made lighter to save an extension of the crack by excessive vibration

(4957) J. S. T. asks: 1. What are the liquid products of oak wood and what is the best method of extracting them ? What are they used for and what are their market values ? What is the condition of the wood when the liquids are removed ? Is it susceptible of receiving other liquids by boiling or pressure, if so, what is the best process ? A. The products of oak wood are acetic acid, wood naphtha and charcoal. All the liquid products are marketed through the chemical trade. Char-coal finds a home market. Cannot quote price. The wood may be saturated with tar products for preservation. See Spon's "Encyclopedia," parts 1, 2, 3, on the distillation of wood, 75 cents each, mailed.

(4958) J. A. G., Quebec, writes : In your Notes and Queries, No. 4760, it is asked if aluminum could be tempered. A Canadian named F. Allard, of Levis, has discovered a process to temper that metal like steel

(4959) S. D. L. writes: I am using for a sciopticon an oxygen gas bag made of rubber and canvas; the gas is made from chlorate of potash and black oxide of manganese. Suppose I fill the bag full and use only a portion of it. Is there any objection in any way to leaving the remaining gas in the bag, to be used at some future time ? Does it injure the bag, or does the gas deteriorate ? A. The gas bag is not liable to deteriorate to any appreciable extent, and the gas will keep well in the bag with a very small percentage of loss

(4960) A. F. writes: Will you kindly inform me what head or fall of water is required to raise

[APRIL 29, 1893.

cal fuel. 6. What is your opinion of an upright boiler and fast and slow speed engines ? A. For small powers a vertical is preferred, with a medium speed engine. 7. What are the advantages of having a large boiler capacity? A. Easy firing and economy in fuel. 8. Has it any disadvantages in the matter of fuel, etc. ? A. None. 9. Which is more economical of power, belting or gearing? A. There is very little difference; if any, in favor of belting. 10. What would be the difference in the savping bar directly to an engine. 2. Belting to a line of shafting 75 feet long, and then to an engine. A. Power is saved with the least running gear, i. e., directly from the motive power. 11. What would be the best method of communicating power from an engine, say 10 horse power, with perpendicular band wheel? If you would advise a belt, would there be any loss of power or other disadvantage as compared with both wheels in the same plane? A. We recommend belts for small power in all cases unless absolutely necessary to use gearing by short distances of centers. The use of a secondary shaft may be made for transmitting power to a distance to advan-

(4962) Mason writes: Please state the ost practical manner of removing a white incrustation which has formed on the surfaces of hard red brick used in the front of a building. Can it be rubbed off with a soft brick ? Can an acid be used ? What would be the effect of painting? The owners of the building wish this incrustation removed, supposing that, if once removed, it would not appear again; would it ? And if it would, about what length of time before it would be seen again? A. The white substance encrusting the face of brick walls may be either carbonate of soda or sulphate of magnesia. They are derived from the lime containing soda salts or magnesia salts; pure lime makes no incrustating efflorescence. The usual method is to scrub the surface with a steel brush, then rub the surface with a soft brick; dry and oil with linseed oil. Weak hydrochloric acid will remove some stains. We do not recommend it, as it is very inconvenient to handle and care for on building fronts. When once cleaned as above describ ed it will not give trouble for some time. After the oiling, a coat of paint will stop the effiorescence.

(4963) J. W. R. writes : I have built the eight-light dynamo which you illustrated and gave detailed drawings and specifications of some years ago. And I can say that I am only too proud of it, as it is a "dandy." It neither gets warm nor sparks, and gives a nice, fine, steady, brilliant light. And as this was my first experience in constructing dynamo-electric machinery, and I had such good success. I feel that I can construct a storage battery if I had a few more pointers in regard to the one you gave a cut of last month. What I propose to do is this: Charge the battery with my surplus current from 7 P. M. until 10 P. M.; then my machine shuts down and I want to run about 15 or 20 16-candle power lamps 110 volts the remainder of the night. My machine is a United States Weston system 300 ampere 110 volt continuous current shunt-wound dynamo. Now what I want to know is this: 1. What thickness should the sheet lead be, also the dimensions of same for 15 or 20 lamps? A. 'The thickness of the lead plates should not be less than one-sixteenth of an inch. 2. How many lead sheets shall I need ? A. You should use about 15 plates per cell. For 50 volt lamps you will require 25 cells, for 110 volt lamps you will require 56 cells. The 50 volt lamps are generally used in connection with storage batteries. 3. How shall I connect in circuit in series, or same as my lamps are in parallel ? A. Connect your cells in series and your lamps in parallel. 4. What can I substitute for glass for the cells ? Something I could mould or cast myself, also how many shall I need ? A. We know of no perfect substitute for a glass cell, but sometimes wooden cells coated with pitch are used. Such cells thoroughly soaked in paraffine have also been used. 5. If I charge from 110 volt current, could I use 50 volt lamps? Would the battery charge last longer for the same number of hours than if I used 110 volt lamps ? A. The battery charge undoubtedly lasts longer when used in connection with high voltage lamps. 6. Could I charge the battery with my little eight-light dynamo 50 volts, provided I ran it long enough through the daytime? A Yes.

(4964) A. B. C. asks how to make court plaster. A. Isinglass (best, genuine), 1 ounce; water, 1/2 pint. Dissolve by heating them together in a covered vessel, strain the solution, and when only lukewarm add to itgradually, but quickly, a mixture formed of rectified alcohol 2 fluid ounces, tincture of benzoin 2 fluid ounces. Apply this composition (still warm) by means of a flat camel hair brush, or any appropriate "spreader," to the surface of silk, or sarcenet, stretched in a frame, repeating the application as soon as the preceding coating is dry, and again as often as necessary (six to twelve times). Lastly, when quite dry and hard, give the prepared sur-face a "finishing coat" with a solution of Chio turpentine, 1 ounce; dissolved in tincture of benzoin, 2 fluid ounces. Tincture of balsam of Peru, or of styrax, may be substituted for the tincture of benzoin, and a few drops of essence of ambergris or of musk may be added crease the fragrance of the compound. Some partie simply employ one or other of the above tinctures for the finishing coat, and others apply it to the unprepared side of the silk, by which the plaster is rendered partially waterproof, but the appearance of its exposed surface injured. Care should be taken that the first two or three applications of the gelatine composition do not sink into the silk, so as to appear on the right side, which will not be the case if it be only sufficiently warm to remain liquid, and be applied very thinly and rapidly, and with a light stroke of the brush or spreader. Use various colored silks, if desired. From the "Scientific American Cyclopedia of Receipts, Notes and Queries." (4965) W. M. says: 1. Suppose a quantity of air be compressed to obtain a pressure of 1,000 pounds per square inch; what amount of heat will be generated also at 2,000 pounds ? A. Air suddenly compressed to a thousand pounds pressure becomes red hot and sets fire to combustibles within the cylinder. This is the principle of the compressed air igniter. The ordinary method of compression to 1,000 to 2,000 pounds is by stages, with cool devices between the stages to keep

(4942) C. W. M. asks: Can you tell me how I can drill holes in glass, common window glass § A. The drilling of glass can be done with a hard drill and spirits of turpentine. A diamond drill is much better and cheaper, if there are many holes to drill.

about 750° or a low red heat. The water required to run at any fall from two to eight feet. They give the best rethe engine under the condition stated will be 1,440,000 sults at the latter height. cubic inches per hour.

(4950) F. N. A. asks: 1. To what distance will the Bell telephone serve as a transmitter ? A. Four or five miles on a good clear line. 2. Will a telephone work enough, better to pay for using two wires ? A. Yes. 3. What good transmitters are on the market now, for long distance, and where attainable ? A. None are for sale so far as we know.

(4951) L. J. asks: 1. Can you tell me the composition used in making the wax cylinders of the Edison phonograph? How many threads to the inch is used as a feed for same? What is the diameter of the brass drum for holding cylinders ? A. The composition of the wax cylinders of the phonograph is a secret. We know of no way to procure the formula for you. We believe the number of threads to the inch on the Edison phonograph is 100. The brass drum is about 2 inches in

ply for a village is obtained from an "infiltration well" | economical fuel. A. Coal is the safest and most economi- | per will be necessary to safely confine the air at such

(4961) D. E., Jr., writes: 1. Is there a telephone that can be bought outright which would be reliable for 1 or 2 miles? A. The electric telephone is not sold, but rented. 2. Would it be practicable to support a light wire for a vibrating telephone, from a heavier wire over it, by loops of light wire at proper distances? I had a very satisfactory vibrating telephone, but used a light iron wire, which when rusted would not bear the strain of taking the sag out. A traveling man put it up and put the poles too far apart. I thought I might run a heavier steel wire, and hang a light copper wire under it. A. Yes; with loops of elastic material. 3. What size wire would you suggest ? A. Use galvanized telegraph wire for the main wire. 4. What is the best type of steam engine for use in a creamery where there will be no regular engineer ? A. A vertical engine and vertical boiler on separate foundations. If not used constantly, a gasoline or petroleum engine will be perfectly safe and easy of management. See advertisements (4952) E. H. O. writes : The water sup- in SCIENTIFIC AMERICAN. 5. Also, the safest and most down the heat. 2. What thickness of cast iron or cop-

269

pressure ? A. The thickness of cylinder depends upon its size and the material. For cast iron a thickness of shell equal to one-sixth of the diameter. For bronze or copper one-eighth for moderate sizes. 3. Will the amount of heat generated be the same, whether the air be suddenly or gradually compressed ? Where and at what cost could I obtain an air pump for such pressure ? A. The heat generated will be the same, but will be partially absorbed by the cylinder in slow compression. (4966) S. A. B. asks how to make a so-Co Cra Cra lution of Prussian blue that may be applied to unsized

paper, so that it will not rub off, but will immediately be dissolved by water. A. Precipitate ferric chloride with excess of potassium sulphate. Filter the precipitate out and pour hot water through the filter paper. This will dissolve and give a solution of soluble Prussian blue. Applied to paper, it will probably be somewhat mordanted, so as to dissolve out with some difficulty.

TO INVENTORS,

An experience of forty-four years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequaled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

April 18, 1893,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

 Advertising, circulating system of, E. H. Hoff-mann.
 495,736

 Annealing, M. Coppinger, 2d.
 435,930

 Atomizer, C. Herscher.
 435,736

 Axle lubricator, J. A. Wyman.
 495,877

 Bag holder, R. Elliott.
 495,736

 Bar, Strawberry shortcake, F. J. Ball.
 495,877

 Baling press, M. B. Jones.
 495,872

 Baling press, M. B. Jones.
 495,872

 Baling press, M. B. Jones.
 495,872

 Baling press, W. S. Livengood et al.
 495,892

 Battery.
 See Secondary battery.

 Beam and girder support, F. Cavallaro.
 495,891

 Bedstead, sofa, I. A. Sturtevant.
 495,891

 Belt, electrica, H. B. Porter.
 495,691

 Belt, electric, G. F. Webb.
 495,683

 Bett, electric, G. F. Webb.
 495,683

 Bett, electric, G. F. Webb.
 495,683

 Bench. See Tube drawing bench.
 495,622

 Bitycle support, A. Liebrecht.
 495,623

 Bench. See Collapsite and folding boat.
 495,627

 Bisnuth gallate, basc, A. Liebrecht.
 495,627

 Bisnuth gallate, basc, A. Liebrecht.
 495,627

 Bisnath gelacon, basc, A. Liebrecht.
 495, Fit Fu Fu

Coin shooting machine, Haydon & Vail Collapsible and folding boat, Gamble & Allen Combination lock L Bingen	495,734 495,549 495,911	L
Comminuter, hollow roll, J. M.Cooper	495,665 495,546	L
Cooking apparatus, w. T. Martin.	495,561 495,821	M
Copying book, manifold, H. Scheckelhoff 495,521, Corn popper, W. D. Winfield	495,522 495,864	M
Cotton scoop, W. C. Brown Coupling. See Car coupling. Car and air brake	495,579	M
Thill coupling. Five coupling. Five coupling. Cover for household utensils, A. Schott	495,684	M
Crane, trave ling, J. B. Anderson Crank shafts, machine for bending, F. Hart Crate, egg, C. T. Belt	495,574 495,631 495,773	M M M
Cultivator and planter, J. W. Mullins	495,794 495,901	M M M
Curring tool, B. Westervelt Current wheel, W. F. Buckmann Currycomb, M. J. Bagley	495,765 495,780 495,871	M M
Cutter. See Thread cutter. Cycle, C. E. Hadley Dam, flexible, L. Debarle	495,732 495,788	M M M
Dandy roll, Young & Davis Disinfecting apparatus, S. G. Plumb Display box, F. Fear	495,573 495,563 495,949	N N N
Draught regulator, M. F. Campbell Dress shield, E. Pickhardt Drill. See Grain drill.	495,473 495,512	0
Drums or pulleys, means for supporting, B. W. Grist	495,738 495,885	000
Egg beater, A. C. Albrecht Egg poacher, C. T. Gott Elastic woven fa bric, Stokes & Hudson	495,925 495,796 495,762	0 0 P
Electric lighting system, H. Edmunds, Jr Electric machine, dynamo, T. L. Willson Electric motor and driven machine, combined, R.	495,932 495,538	P P P
Fuller Electric motor or generator, W. Koedding Electricity, ground generator of, M. Emme	495,547 495,941 495,582	P P P
Electrolytic apparatus, G. O. Rennertelt Elevator. See Grain elevator. Hod elevator. Passenger and freight elevator. Tobacco	495,600	P P
elevator. Elevator, W. H. Kern. Elevator, A. Larsen.	495,554 495,813	P P P
Elevator, O. R. Olsen. Elevator or conveyer, M. M. Shellaberger Engine. See Steam engine.	495,598 495,685	P P
Excelsior knife, H. C. Cloyd.	495,791 495,879 495,723	P P
Fan, W. H. Youngs. Fan, rotary, J. M. Seymour.	495,619 495, 525	P
Fastening device, T. Westerman Faucet and vent bung and bushing, D. Beebe	495,537 495,719	P P P
D. Beebe. Feed trough, G. W. Dunks.	495,718 495,666	P
Fence machines, electric welder for wire, J. D. Curtis.	495,626	
Fence post driving machine, E. Mohn Fence wire, machine for stretching and remov-	495,747	г Р
Fibrous substances, evening mechanism for ma- chines for opening, carding, and drawing, H.	495,610	P P
A. Davis A. Plecker	495,833 495,504 495,504	P P P
Firearms, breech bolt for, K. Krnka. Fireplace, W. R. Dawson.	495,741 495,786 495,827	P P P
Floors, hanger for laying fireproof, H. Graham Flower pot and stan d, Holt & Kooy Flue for buildings A Zerban	495,672 495,808 495,648	P P R
Fluid distribution apparatus, J. McNaughton Fluih tank for closets, P. Falkinburg Folding apparatus sheat S. G. Goss	495,904 495,611 495,482	Ř R
Fruit pitter, E. W. Weare Funnel and strainer, combined, W. J. Kayser Fur from pelts, machine for cutting. E. Beesley	495,860 495,635	R R
Sr. et al. Furnace. See Blast furnace Ore roasting and calcining furnace. Ultramarine furnace.	495,470	R
Gauge. See Micrometer gauge. Surface gauge. Water gauge. Game apparatus, C. Neilson	495,509	R R R
Game apparatus, H. C. Smith Garment hanger, W. O. Bement Garment supporter, F. Kern	495,527 495,926 495,893	R R
Gas apparatus, L. & L. Stevens, Jr Gas generator and burner, hydrocarbon, E. A. Edwards	495,917 495,726	R R R
Gas lighter and extinguisher, time, F. A. Lang- with	495,556 495,900	R
Generator. See Gas generator. Girder bracing tie bar, J. M. Cornell	495,866 495,785	R
Grain elevator, Flagg & Guymon Grain mixing device, F. Kaucher	495,670 495,698 495,590	R
Guns, discharging valve adapted to air, T. J. Winans	495,767	S
Guta-percha from the leaves and twigs of the guta-percha tree, process of and apparatus for the avtraction of D. Ricola	400,014	Sa
Hair drying apparatus, J. Machado	495, 558 495, 560	
bined, V. P. Travers	495,532	00000
Harrow, W. Williams. Harvester, corn, J. Simser	495,924 495,526 495 862	and and
Harvester reel mechanism, A. Stark Hat pouncing machines, pouncing head for, J. B. Howe	495,846 495,491	00000
Hay carrier, J. W. & J. W. Provan Hay press, McNeill & Huck Hay stacker, U. H. Palmer	495,756 495,826 495,831	S
Heater. See Lamp heater. Heating and ventilating rooms, apparatus for, W.S. Stuyvesant	495,528	s s
Heating and ventilation system, J. Scherfflus Hemmer, S. Laskey Hermetically closing receptacles, means for, L.	495,567 495,814	SSS
A. Bonnamy Hinge seats, device for marking and gauging, W. R. Shepard	495,775 495,761	s
Hod elevator, C. Carlson Honeycomb, device for casting bilateral artificial, P. Warnstorf	495,781 495,572	SSS
Honey shipping case, T. McManus Hook. See Check hook. Horseshoe nail machine, C. H. Yarington	495,597 495,606	0.000
Hose coupling, A. W. Jackson Hose reel, E. M. Birdsall. Hub, vehicle, P. F. Rachal.	495,890 495,720 495,707	and and
Huner and scourer, combined, A. F. Hinz. Hydrant, A. Scheid. Injector, F. Brunbauer	495,803 495,711 495,778	0000

 Spinoidian
 Spinoidian

 Spinoidian
 S

Car safety attachment, Bustin & McMackin 495,928	Insulator, L. Hills	Steam boiler and firebox therefor. C. W. Hullings 495,939	& F Poors 99 9/2
Car side bearing, W. W. Wooll 495,688	Ironing table, J. Mooers 495,680	Steam engine, G. De Laval 495,742	Toilet nowder Reliance Manufacturing Company 22.845
Car starter and brake, H. Duys, Jr 495,725	Joint. See Insulated pipe joint.	Steam engine, S. H. Rathburn 495,516	Watches Hampden Watch Company 22,06
Car, stock, B. C. Hicks 495,586	Journal bearing, A. C. Stiles 495,919	Steering mechanism, J. Christensen 495.622	Water wheels, Tamper Loffel & Company 99 857
Car, stock, A. P. Powell 495,909	Keyhole guard, E. Riley 495.517	Stencil apparatus, H. Sorg 495,604	water wheels, sames here a company
Cars, system of distributing steam for heating	Knife. See Excelsior knife.	Stocking and knitting same, E. R. Branson, 495,660	
railway, C. B. Grim 495,612	Knife, M. L. Hawks 495.699	Stop and waste device, H. C. Apel 495.575	· · · · · · · · · · · · · · · · · · ·
Card clothing, M. Duesberg-Delrez 495,694	Knitting machine varn feeding device, E. Bux-	Stopper. See Bottle stopper.	
Carpet fastener, H. Solt 495,844	torf	Store service apparatus, C. W. McCormick. 495.902	D TOTO NO
Carriage, baby, Dietrich & Habicht 495,476	Ladder, T. A. Strohm	Stove, J. Lamb	DESIGNS.
Cart, Butts & O'Marra 495,722	Lamp, bicycle, Bown & Hughes	Stove and attachment therefor, lamp, F. Highie 495 802	
Case. See Honey shipping case.	Lamp, electric, T. Hudson	Stove, railway car, M. E. Cook 495 880	Barrel scrubbing machine frame II Florbardt 99.921
Cash drawer and record sheet holder, C. F. Gol-	Lamp, electric arc, C. F. Adams	Stoves or furnaces, air supplying device for, C. J.	Bottle T C Wheeton 99.254
ler	Lamp, electric arc, E, E, & L, C, Beauvalet 495.772	Kille	Brush back toilet C C Wientro 22,004
Cash register and recorder, C. W. Weiss 495,764	Lamp, electric arc, F. T. Schmidt,	Striking and strength testing machine, coin-con-	Cake back of S U Leavenmenth 99 259
Cash register money drawer, E. N. Foote 495,934	Lamp, electric arc, W. A. Turbayne 495.643	trolled, G. Troxler, Jr. 495 571	Fonce panel I W Dwigging 99 250 99 250
Cash registering machine, Range & Foote	Lamp heater, W. Masters	Sugar, refining, E. Langen 495.614	Flugh tauk onging () E Vorgo
Caster, J. H. Russell 495,519	Lamp holder, incandescent electric, L. C. Whit-	Surface gauge, P. A. Benko. 495 565	Cimp C F Hortloin
Casting machine, type, J. G. Payyer 495,704	nev. Jr	Swing, W. R. Wilcox, 495 923	Glass surface ememoriation of sheet Brosen b
Ceiling, metallic, A. Friedley 495,935	Lamp, incandescent electric, E. W. Applegate 495 620	Swing, lever, W. R. Wilcox, 495,922	Malloch 99 250
Chain gear, drive, H. Guthrie 495,584	Land roller, E. W. Farr	Table. See Extension table. Ironing table.	Match safe Bernard & Frank 99/252
Check hook, W. Eckert 495,627	Land roller and harrow, C. Storia	Table leg fastening, J. Volz	Oilor bievelo H O Hall 99 357
Chimney attachment, S. R. Heberling 495,887	Lantern, railway, L. R. Thomas 495,530	Tack or nail machine feeder, E. O. Benson 495,774	oner, bicycle, 11. 0. Han
Christmas tree candle holder, H. Schlueter 495,641	Latch, J. M. Coffield 495.624	Talking machine, J. L. Atkins	
Churn, H. Drymon 495,478	Latch, gravity, F. O. Miller	Tanning agents, making solid extracts of sumac	
Cigar lighter, electric, Carter & Willey 495,929	Lath, sheathing, M. C. Nichols. 495,906	hemlock, and other, P. T. Austen 495 768	A printed conv of the specification and drawing of
Cigarette machine, R. Hardie 495,613	Lathe, polyhedral, M. Rul 495,839	Telegraphic messages, indicating, J. Levi 495,744	any patent in the foregoing list, or any patent in print
Clamp. See Saw brazing clamp.	Lathe tool holder, Barraclough & Rhodes, 495,576	Thill coupling, H. P. Faris	issued since 1863, will be furnished from this office for
Clothes pin, J. H. Russell 495,518	Lead, manufacturing white, Honman & Vulliez. 495,490	Thill coupling, W. H. Tydeman. 495.855	25 cents. In ordering please state the name and number
Clutch, E. Shaw 495,602	Leather turning machine, Q. W. Booth 495,776	Thimble, R. M. Durham	of the patent desired, and remit to Munn & Co., 361
Clutch, S. Trethewey	Life-saving device or fender, W. E. Holmes, 495,632	Thread cutter and holder, E. B. Look. 495,500	Broadway, New York.
Clutch, H. Wyman 495,540	Lightning arrester, E. Thomson	Tin cans, blank for the manufacture of. W. J.	
Clutch, hub friction, H.L. Moulton 495,748	Lock. See Combination lock.	Phelps	Canadian patents may now be obtained by the in-
Coal briquets, composition of matter for. J. N.	Locomotives, apparatus for supplying purified	Tin plate, apparatus for the manufacture of. D.	ventors for any of the inventions named in the fore.
Moerath 495,679	water to, R. Learmonth 495,496	Edwards	going list, provided they are simple, at a cost of \$40 each.
Coffee pot, J. K. Cummings 495,693	Log roller, W. A. Wilkinson 495,716	Tire, pneumatic, P. Bouery 495.777	If complicated the cost will be a little more. For full
Coffee pot, J. Green 495,997	Loom let-off motion, R. Wilby 495,766	Tire tightener, A. B. Bowen	instructions address Munn & Co. 361 Broadway New
Coin controlled machine, W. T. Lewis	Loom picker-staff check. J. Turner. 495 644	Tobacco elevator, B. F. Vanlandingham. 495 763	Work Other forder and and the birth of the best of

270

Advertisements.

ORDINARY RATES.

Inside Page, each insertion - - 75 cents a line Back Page, each insertion - - - - \$1.00 a line For some classes of Advertisements, Special and Higher rates are required.

The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head adver-tisements at the same rate per agate line, by measure-ment, as the letter press. Advertisements must be redeived at Publication Office as early as Thursday morning to appear in the following week's issue.



Canada, and Mexico, \$5.00 a year; or one copy of the SCIENTIFIC AMERICAN and one copy of the SUPPLE-MENT, both mailed for one year to one address for \$7.00. Single copies, 10 cents. Address and remit by postal order, express money order, or check,

NEW YORK

18

S.

X

P ŧ7-KEUFFEL&ESSER CO.

a diffe



KEROSENE OIL FUEL.

NO SKILLED ENGINEER.

THE SHIPMAN AUTOMATIC STEAM ENGINE.

No extra Insurance. Efficient, Economical, Durable.

SHIPMAN ENGINE COMPANY,

1, 2, 4, 6 and 8 HORSE POWER



Steel Type for Writing Machines

J. D. MALLONEE, M'f'r, STOCKTON, N. Y.

GATES ROCK & ORE BREAKER

THE COPYING PAD.-HOW TO MAKE and how to use; with an engraving. Practical directions how to prepare the gelatine pad, and also the aniline ink by which the copies are made, how to apply the written letter to the pad, how to take off copies of the letter. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, NO. **438.** Price 10 cents. For sale at this office and by all newsdealers in all parts of the country.



chines a specialty. Send stamp for catalogue. Amer. Vending Mach. Co., 29 Murray Street, New York.

MODEL 🐠 👁 🚽 WORK.



SCIENTIFIC AMERICAN SUPPLE-MENT. Any desired back number of the SCIENTIFIC AMERICAN SUPPLEMENT can be had at this office for 10 cents. Also to be had of newsdealers in all parts of the country.

J. Delaney & Co. Mfrs. rd & Fowler Sts., Milwaukee, Wis,



CROWNS OF GLORY ought to be given to the man who invented such a labor-saving tool as the original Howard-Allard Spiral Screw Driver. It would not be so good, if it was not made of the very best mate-rial, and by the most skilled me-ohanics. Just



н.

most skilled me-chanics. Just think of it, you only have to hold Just irop us a card and find out all about it. You "need it in your business." Sample A1, \$1.50; A2, \$1.25, postage paid. THE ALFORD & BERKELE CO., 77 Chambers Street, NEW YORK.

STEEL, IRON, COPPER, ZINC, BRASS, TIN, And all other Metals Perforated as Kegnired for Grain Cleaning and Min-ing Machinery, Woolen, Cotton, Paper and Pulp Mills, Kice, Flour and Oil Mills, Sugar and Matt Houses, Distilleries, Fliter Presses, Stone, Coal and Ore Screens, Byr Sc et The Works, Fliters, Spark Arresters, Gass and Water Works, Oil, Gas, and Vapor Stoves, Ooffee Machinery, etc., etc. Standard Sizes Perforated Thi and Brass always in Stock. THE HARRINGTON & KING PERFORATING CO., Chicago, And 284 Pearl Street, New York.

MUNN & CO., 361 Broadway, New York,



THE SCIENTIFIC AMERICAN ARCHITECTS' AND BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equa to about two hundred ordinary book pages; forming a large and splendid Magazine of Architecture, richly adorned with elegant plates in colors, and with other fine engravings; illustrating the most interesting examples of modern architectural construction and allied subjects. A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Sheets of Details, Estimates, etc. The elegance and cheapness of this magnificent work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers. \$2.50 a year. Remit to MUNN & CO., Publishers.

361 Broadway, New York.

BEATTY Organs, 27 stops \$22. Pianos, \$150 Catal. free. Dan'l F. Beatty, Wash'ton, N.J

Founded by Mathew Carey, 1785 HENRY CAREY BAIRD & CO. Industrial Publishers, Booksellers, and Importers.

SIO Walnut St., Philadelphia, Pa., U. S. A. SOUR new and Revised Catalogue of Practical and Scientific Books. SS pages, Svo, and our other Catalogues and Circulars, the whole covering every branch of Sci-ence applied to the Arts. sent free and free of postage to any one in any part of the world who will furnish his address.







Sport, Travel.

Recreation. and Fiction \$3.00 per year. 25c. a copy.





MECHANICS' TOOLS.

If you are interested in Tools as a manufacturer or amateur, you should have a copy of our new cata-logue. Our 1832 edition is a very elaborate and com-plete book of 704 pages, handsomely bound in eloth. The book will be sent to any part of the world, pre-paid, on receipt of \$1.00, and the money thus paid will be refunded with the first purchase amounting to \$10.00 or over. Every manufacturer and amateur should have this catalogue, even if they do not in-tend buying their Tools and Supplies of us. MONTGOMERY & CO., Fine Tools, 105 Fulton Street, New York City, N.Y.



 Σ

Þ

If you want the best Lathe and Drill



FUELS AND THEIR USE-A PRESIdential address before the Society of Chemical Industry, by J. Emerson Reynolds, M.D. discussing the modern developments of the fuels coal, peat and petroleum. Gasification of coal. Natural gas. Gasified petroleum. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. S68. Price 10 cents. To be had at this office and from all newsdealers.





ELECTRO MOTOR. SIMPLE, HOW TO



ELECTRO MOTOR. SIMPLE, HOW TO make. By G. M. Hopkins.—Description of a small electro motor devised and constructed with a view to assisting amateurs to make a motor wnich might be driven with advantage by a current derived from a battery, and which would have sufficient power to operate a foot lathe or any machine requiring not over one man power. with 11 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT. No. 641. Price 10 cents. Tobe had at this office and from all newsdealers. WOODEN TANKS FOR RAILE







MESSRS. MUNN & CO., in connection, where the united is a construction of the solution of the s

They are highly sensitive, and repeated tests show that they retain this sensitiveness as well as glass plates. No other films are so free from imperfections; none so uniform; none so reliable. Our film doesn't frill.

Our New Films are giving perfect satisfaction.



tent No. 463,569, granted to Emile Berliner, November 17, 1891, for a Combined Telegraph and Telephone; and controls Letters Patent No. 474,231, granted to Thomas A. Edison, May 3, 1892, for a Speaking Telegraph, which cover fundamental inventions and embrace all forms of microphone transmitters and of carbon telephones.





The SCIENTIFIC AMERICAN is printed with CHAS. ENEU JOHNSON & CO.'S INK, Tenth and Lombard Sts., Philadelphia, and 47 Rose St., opp. Duane, New York

© 1893 SCIENTIFIC AMERICAN, INC