

RECENTLY PATENTED INVENTIONS.
Engineering.

VALVE OPERATING MECHANISM.—Jacob J. Moore, Chambersburg, Pa. This inventor has designed novel means whereby the engine may be reversed or throttled by the use of a single lever and eccentric. The construction is such that when the lever is adjusted to its central position the eccentric will be adjusted to set the valve to shut off steam, and if the lever be moved either forward or back it will so throw the eccentric as to move the valve to open the port to admit steam to one or the other side of the piston to properly move it, to drive the engine forward or back. Duplicate eccentrics, one for each side, will be needed in locomotives.

Railway Appliances.

CAR COUPLING.—Edward J. Lahan, Quincy, Ill. In this coupler the drawhead has the usual flaring mouth, but with its sides, top and bottom, solid, whereby the interior coupling members are protected from the weather and the head rendered more stable and compact. The coupling is effected by means of a gravity latch, working automatically when the drawheads come together, obviating the need of going between the cars, and the uncoupling may be effected from either the sides or the bottom of the cars. The device is extremely simple and inexpensive.

SWITCH LOCK.—Samuel E. Bartlett, Red Bank, N. J. This invention relates to interlocking switch systems for railroads, where the switch, signal, and switch lock are all operated from a tower. The new device consists of a switch or bolt under the control of the operator and adapted to engage the switch bar to lock the same in position by an ingenious system of sliding plates which are engaged by the bolt. By this mechanism the operator is prevented from locking the switch unless it is in the proper position, and he cannot display the proper signal controlling such switch unless it is properly set and properly locked.

FLANGER.—Thomas W. Macfarlane, of Ellensburg, Washington. This invention consists of a novel device for removing snow and ice from the rails of railway tracks, and is especially adapted to remove the snow and ice usually left by the snow plow on the tops and sides of the track rails. The flanger is secured directly to the truck, and the cutter, with its attachments as the apron which throws the loosened ice and snow to one side, is operated with a piston rod connected with a cylinder attached to a suitable air or steam supply. A coiled spring returns the mechanism to the normal position when the air or steam pressure is removed.

UNDERGROUND RAILWAY CONDUITS.—Wilton F. Jenkins, Richmond, Va. This invention consists of a cylindrical tube or conduit the edges of which are formed in a peculiar manner at each side of the slot to give the requisite thickness to resist the weight of traffic in the street. Yokes pass under the conduit tube and secure the rails, thus obviating the use of bolts or rivets to fasten the rail. This connection between the rail and the yoke is a universal one and enables the rail to be grasped at any point without cutting holes in the rail or yoke. By the construction of the overhanging walls and stiffening web a vertical distance from the top of the slot rail to the outer periphery of the cylinder is secured so as to allow blocks of paving material to be laid in sufficient vertical depth close up to the slot rail so as to secure a substantial finish.

CONDUIT ELECTRIC RAILWAY.—Wilton F. Jenkins, Richmond, Va. This simple and effective device consists of a conduit tube provided with two horizontally projecting arms carefully insulated and bent to receive the two conducting wires which are laid loosely in a recess provided for them. A hook-shaped trolley is provided for each conductor which raises the wire from the support and is provided with a wiping attachment or pad which cleans the supporting arm at each passage of the trolley.

ELECTRICALLY OPERATED RAILWAY SWITCH.—William S. Gavey, Brooklyn, N. Y. This switching device is intended to be operated from a moving electric or other car. By an ingenious system the switch may be automatically operated by a moving car so as to be thrown before the car reaches it and to be thrown back after the car has passed, also to provide a switch system adapted to railways having numerous sidings so that each car will turn its particular switch, but pass over the other switches without affecting them. The switching is done by electro-magnets, the current being obtained from an overhead trolley wire with the aid of a contact pulley.

Miscellaneous.

AMALGAMATOR.—Nathan Leroy Raber, Corvallis, Oregon. This invention consists of cells, which receive the agents by the electrolysis of which the mercury may be cleaned or purified, and a lead or similar conductor extended longitudinally within the cell whereby an electrical discharge from end to end of the cell is secured. Various other devices for regulating the supply of the quickening agent, the mercury, etc., are provided. By the construction and arrangement of the several parts of the amalgamator the whole surface of the mercury at the point of contact with the thin stream of pulp is kept perpetually clean and active.

NOTE.—Copies of any of the above patents will be furnished by Munn & Co., for 25 cents each. Please send name of the patentee, title of invention, and date of this paper.

NEW BOOKS AND PUBLICATIONS.

A TEXT BOOK OF MECHANICAL DRAWING. Part III. Machine Drawing. By Gardner C. Anthony, A. M. Tufts College, Massachusetts. Published by the author. Pp. 50, 16 plates. Cloth. Price \$1.80.

This is an excellent work. The treatise is intended to teach the practical application of the principles of projection to the illustration of machinery, and to furnish such practical examples as may serve for problems to

the student and suggestions to the draughtsman. It is really refreshing to see a book on mechanical drawing which gives the proper amount of lettering and dimensions. The plates, with a few exceptions, are arranged so that they are visible while the text is being read; this is the proper way of inserting plates and maps, but is unfortunately a rarity. The whole work bears the stamp of being made by a thoroughly competent and conscientious draughtsman.

THE TINSMITHS' PATTERN MANUAL. Patterns for tinsmiths' work. By Joe K. Little. Chicago: The American Artisan Press. 1894. Pp. ix, 248. Price \$1.

This work treats in great detail of the development of tinsmiths' articles for the purpose of cutting out the pieces therefor from the flat metal. This it does elaborately, its purpose, evidently carried out, being to lay down general geometrical principles by which work other than that described in the book may be done. The text consists of a series of problems well illustrated, and an excellent index, with both page and paragraph references, is a feature worthy of being noted.

DAVID OF JUNIPER GULCH. A story of the placer regions of California. By Lillian Shuey, author of "California Sunshine," etc. Chicago: Laird & Lee. Pp. 418. Price \$1.

CRIME AND PUNISHMENT: A NOVEL. By Fedor Dostoieffsky. Translated from the original Russian by Frederick Whishaw. Chicago: Laird & Lee. Pp. 456. Price 50 cents.

THE EGYPTIAN HARP GIRL: A MYSTERY OF THE PERISTYLE. By "Quondam." Illustrated. Chicago: Laird & Lee. 1894. Pp. 292. Price \$1.

PAUL WEISS. Ingenieur au Corps des Mines. Le Cuivre. Avec 96 figures intercalées dans le texte. Paris: Librairie J.-B. Baillière et Fils. 1894. Tous droits réservés. Pp. viii, 344. Price \$1.

SCIENTIFIC AMERICAN BUILDING EDITION.

APRIL, 1894.—(No. 102.)

TABLE OF CONTENTS.

1. Elegant plate in colors showing a handsome colonial residence just completed at Ashbourne, Pa, for Charles Salmon, Esq. Two perspective views and floor plans. Cost complete \$11,500. Frank R. Watson, Esq., Philadelphia, Pa., architect. An elegant design.
2. Plate in colors of a Chicago dwelling designed for an architect's home, and recently completed at Morgan Park, Chicago, Ill. Two perspective views and floor plans. Cost \$4,200 complete. Mr. H. H. Waterman, architect, Chicago, Ill.
3. Two perspective views, interior view and floor plans of the elegant residence of Judge Horace Russell recently completed at Southampton, Long Island. Mr. Bruce Price, New York City, architect. An admirable design in the colonial style of architecture.
4. An English cottage at Buena Park, Chicago, Ill. Two perspective views and floor plans. Mr. James Gamble Rogers, Chicago, Ill., architect. A unique design in the Gothic style of architecture.
5. A residence at Southport, Conn. Two perspective views and floor plans. A picturesque design in the modern colonial style of architecture. Mr. W. W. Kent, New York City, architect.
6. A cottage at Freeport, Long Island, erected at a cost of \$2,600 complete. Perspective view and floor plan. A unique design. Mr. W. Raynor, Freeport, L. I., architect.
7. A residence at Rogers Park, Ill. Two perspective views and floor plans. Cost \$3,948 complete. An attractive design. Mr. C. W. Mellin, Chicago, Ill., architect.
8. Two perspective views and floor plans of a dwelling recently erected at Rogers Park, Ill., at a cost of \$3,730 complete. A unique design. Mr. Robert Rae, Jr., Chicago, Ill., architect.
9. A cottage at Morgan Park, Ill., erected at a cost of \$2,968 complete. Two perspective views and floor plans. An attractive design, treated in the English cottage style of architecture. Mr. H. H. Waterman, Chicago, Ill., architect.
10. The new St. James M. E. Church at Kingston, N. Y. Perspective and plans. Architects, Messrs. Weary & Kramer, of New York City and Akron, Ohio. Estimated cost, \$70,000. Style of architecture, Romanesque.
11. Miscellaneous Contents: Vibrations of tall buildings.—Artificial stone.—A simple and efficient dumb-waiter, illustrated.—An improved woodworking machine, illustrated.—The New Era electrical gas burner, illustrated.—P. & B. Rubberoid roofing, sheathing papers, and paints.—Improved wood-working machine, illustrated.—Foot power mortising machine, illustrated.—A large sheet metal ceiling, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITECTURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects. The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural Publication in the world. Sold by all newsdealers. MUNN & CO., PUBLISHERS, 361 Broadway, New York.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in the following week's issue.

- "D. B." metal polish. Indianapolis. Samples free.
- Stave machinery. Trevor Mfg. Co., Lockport, N. Y.
- Air compressors for every possible duty. Clayton Air Compressor Works, 26 Cortlandt Street, New York.
- The Improved Hydraulic Jacks, Punches, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.
- Nickel-in-alot machines perfected and manufactured Electrical supplies, Waite Mfg. Co., Bridgeport, Conn.
- Screw machines, milling machines, and drill presses. The Garvin Mach. Co., Light and Canal Sts., New York.
- Centrifugal Pumps for paper and pulp mills. Irrigating and sand pumping plants. Irvin Van Wie, Syracuse, N. Y.
- Emerson, Smith & Co., Ltd., Beaver Falls, Pa., will send Sawyer's Hand Book on Circulars and Band Saws free to any address.
- Split Pulleys at Low prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.
- Patent for Sale—Stall for comfort and cleanliness of milk cattle. Agents wanted at 50 per cent commission. M. Schembri, 306 Van Buren St., St. Paul, Minn.
- Toothpicks, match-sticks, kindling wood, etc. Can be made millions a day by the new patented machine. Partner wanted. "James," care of Scientific American.
- The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4; Munn & Co., publishers, 361 Broadway, N. Y.
- Patent Electric Vise. What is claimed, is time saving. No turning of handle to bring jaws to the work, simply one sliding movement. Capital Mach. Tool Co., Auburn, N. Y.
- Competent persons who desire agencies for a new popular book, of ready sale, with handsome profit, may apply to Munn & Co., Scientific American office, 361 Broadway, New York.
- Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway New York. Free on application.

Notes & Queries

HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information and not for publication. References to former articles or answers should give date of paper and page or number of question. Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn. Buyers wishing to purchase any article not advertised in our columns will be furnished with addresses of houses manufacturing or carrying the same. Special Written Information on matters of personal rather than general interest cannot be expected without remuneration. Scientific American Supplements referred to may be had at the office. Price 10 cents each. Books referred to promptly supplied on receipt of price. Minerals sent for examination should be distinctly marked or labeled.

(5958) T. R. B. asks: Will you please state in your answer to my inquiries of 24th what is the best size of wire to use for telephone lines? A. No. 12 galvanized iron or steel wire is generally used for telephone lines.

(5959) F. J. M. writes: Referring to article on "Wind Pressure," in SCIENTIFIC AMERICAN SUPPLEMENT, No. 950. 1. Why should the wind pressure against one side of a cube be less than upon a thin plate of same size? A. In the thin plate there is a vortex formed at the back of the plate which prevents reaction, while in a thicker body, like the cube, the vortical space is filled by a solid, allowing the displaced air time to return behind the cube and counteract the vortex made by the outward flow of air at the front edge. The same effect is observed under the same conditions in the movement of plates and solids through water. 2. Why should the wind pressure acting upon a hemispherical cup, when its convexity is turned toward the wind, be greater than upon a flat plate of equal diameter? A. The wind pressure is less when the convexity is turned to the wind than when a plane surface or concave one is turned to it. Convexity is a mistake in your question. It should be concavity.

(5960) B. writes: 1. I would like to get some data concerning the small vanes in exhausted bulbs which are caused to revolve by the action of the light. I think they are known as "Crookes' mill." What is the minimum intensity of light at which they will revolve? A. It will revolve in the dark, provided there is heat. Its action does not depend on light. 2. Suppose a 16 candle power lamp were placed at a distance of 6 inches from the vanes, what would be the approximate number of revolutions? A. A 16 candle power lamp at a distance of 6 inches will revolve the vanes quite rapidly, but the velocity varies with radiometers of different forms. 3. Are they for sale, and at what price? A. Radiometers are for sale by most dealers in physical instruments. The price is from \$3 to \$5. 4. Has a description of them ever appeared in the SCIENTIFIC AMERICAN, and if so, in what number? A. For information on Crookes' radiometer, we refer you to SUPPLEMENT, Nos. 13 and 26. Price by mail 10 cents each.

(5961) W. S. R. asks: 1. Please tell me how to make a Gramme ring motor. A. You will find a full description of a small Gramme ring motor in SUPPLEMENT 641. 2. Also how to make a two or three horse power water wheel for a brook with a fall of 12 inches and a force of 80 barrels per minute. A. SUPPLEMENTS 61, 380, and 704 contain descriptions of turbines for various uses. A. You can probably get the information you desire from these articles. 3. Is the Piano Company a reliable firm? A. We do not furnish information of this character. 4. How can I make a galvanic bichromate battery to run 641 motor? A. For instructions

for making bichromate battery, we refer you to SUPPLEMENT 792. 5. Is there any way to make a boiler to run a one horse power engine? If so, how can I make it and where can I get the material? A. For directions for making small boilers, see article on the subject contained in SUPPLEMENT 702.

(5962) B. S. L. asks: 1. Why, when a person looks at an object through the large end of an opera glass, the object appears smaller and at a great distance? A. The reversal of the glasses produces the effect, the negative lens being then in front of the magnifying lens. 2. Will No. 21 double-covered copper wire give just as good results on the armature of eight-light dynamo, SUPPLEMENT 600, as single-covered No. 20, and thus insure better insulation? And will not an addition of more wire on field magnets give a stronger current? Also is the sheet iron disk armature core to be preferred to the wire core? A. Double-covered copper is probably to be recommended for the purpose named. The E. M. F. will be a little greater and the current will be a little less. There are certain ratios of resistance between armature and field which are not advantageous. 3. Is it practical for an amateur to attempt the construction of a gas engine, and can you give me the address of a firm where gas engine castings are made? A. A gas engine is very troublesome to build. You might address gas engine manufacturers who advertise in our columns; but we doubt if any of them would furnish castings. 4. What are the dimensions of coil and size of wire used on a coil to produce a spark one inch in length? A. Exact dimensions of the induction coil asked for cannot be given. Consult SUPPLEMENT 160 for information in regard to a coil giving 1½ inch spark. This can be regulated to produce a 1 inch spark. 5. The formula for a good leather cement, also a good rubber cement. A. An India rubber cement is made of: 15 grains of India rubber, 2 ounces of chloroform, 4 drachms of mastic; first mix the India rubber and chloroform together, and when dissolved the mastic is added in powder. It is then allowed to stand for a week or two before using. Leather and Pasteboard, Cement for.—Strong glue, 50 parts, is dissolved with a little turpentine in q. s. water, over a gentle fire; to the mixture is added a thin paste, made with 100 parts of starch. It is applied cold, and dries rapidly.

(5963) B. T. writes: 1. We evaporate from 2,100 to 2,300 gallons of water per hour in our boilers. What should be the dimensions of such a boiler or boilers to do that amount of work with some degree of economy? A. The evaporative power of a boiler is approximately given by the formula $1.833 \left(\frac{S}{2S+F} \right) e =$ pounds of water per pound of fuel, in which S is the heating surface and F the pounds of fuel, and e the evaporative power of the fuel. Taking e=15 we have 10,448 pounds water per pound of coal. Taking this as representing your case, you will need a boiler to burn 230 pounds of coal per hour, or about 20 square feet of grate or natural draught, and a heating surface of 200 to 300 square feet. Conventional horse power of a boiler is not reliable. 2. What is the market value of mercury per pound? A. About 75 cents a pound. 3. What is the weight of one cubic foot of mercury? A. 846 pounds at 60° Fah. 4. At what temperature will mercury start to evaporate? A. It evaporates slowly at ordinary temperatures. It boils at 675° Fah. 5. Will mercury dissolve in alcohol, ether, or any other oil or grease? A. No. 6. If mercury be put in iron vessel, will it attack the iron? A. No. 7. If mercury be heated to 200 or 250 degrees, will it give off any gas or fumes so as to endanger the person handling the same? A. It will slowly produce bad effects; the practice is an unsanitary one. 8. Have you a good book on modern boilers? A. We can supply you with the following books: "A Manual of Steam Boilers," by Thurston, price \$5 by mail; also "Steam Boilers," by Rose, price \$2.50.

(5964) W. B. J. says: Can you inform me through your valuable paper how to mark fine steel tools with acid, using a rubber stamp? A. Have a plain border round the design, large enough to allow a little border of common putty to be laid around the edge of the stamped design, to receive the acid. For ink, use resin, lard oil, turpentine, and lampblack. To ¼ pound of resin put 1 teaspoonful lard oil; melt, and stir in a tablespoonful of lampblack; thoroughly mix, and add enough turpentine to make it of the consistency of printer's ink when cold. Use this on the stamp in the same manner as when stamping with ink. When the plate is stamped, place a little border of common putty around and on the edge of the stamped ground. Then pour within the border enough acid mixture to cover the figure, and let stand a few moments, according to the depth required, then pour the acid off. Rinse the surface with clean water, take off the putty border, and clean off the ink with turpentine. Use care not to spill the acid over the polished part of the article. For the acid, 1 part nitric acid, 1 part hydrochloric acid, to 10 parts water by measure. If the effervescence seems too active, add more water. 2. How are knife blades marked that have names on them? A. Knife blades are sometimes marked in this way, but generally the brand is placed on knives, etc., when they are in a heated condition by a steel stamp. 3. Can cast iron be plated with aluminum? If so, how can I do it? A. Yes; copper the iron, then deposit the aluminum, using the following formula: Fifty parts by weight of alum are dissolved in 300 of water and to this is added 10 parts of aluminum chloride. The solution is heated to 200° Fah., and when cold 39 parts of cyanide of potassium are added. A feeble current should be used.

(5965) F. L. asks: 1. Are all alternating generators excited by a separate direct current machine? A. No. Sometimes they are self-exciting, having a commutator in addition to the collecting rings. 2. Is an alternating current ever used for arc lights or for exciting the fields of a dynamo? A. It is often used for arc lighting, not for exciting dynamo fields. 3. Will the current alone be cut down by increasing the resistance of a coil or line, or will the voltage also be affected? A. Increasing the resistance of the circuit will tend to increase the potential at the terminals. 4. Is the earth's attraction greater at a high elevation than at sea level? A. No; it is less. 5. How is the displacement or tonnage of a vessel or ship computed? A. By various rules, some arbitrary and some based on approximate calculation of the immersed volume of the ship. 6. How do the supposed spiritualists and magicians perform the trick of lift-