

THE BOYNTON BICYCLE ELECTRIC RAILWAY.

NEW YORK, FEBRUARY 17. 1894.

The need of the day is rapid transit. Steam, cable, and trolley cars each in their own degree contribute to this end. The illustrations show one of the last developments in true rapid transit—the Boynton Electric sistance. In the railroad in question a narrow car with Bicycle Railroad—of which a line is now in process of sharpened ends is employed, and is mounted upon erection across Long Island, from Bellport to the Sound. two wheels, one at each end, and travels upon a single The idea of the bicycle railroad is to provide a sys-

tem of transit whose speed may be from seventy-five latter disposes at once of the violent transverse wrench-

to one hundred or more miles an hour. Air resistance being one of the most adverse factors at this velocity, a car of small cross sectional area is preferable. The inequalities of two parallel lines of rail is also a factor of rerail. It has the equilibrium of the bicycle, and like the

ing strains which affect four-wheeled vehicles of the everyday type. It is peculiarly well adapted for electric propulsion, the overhead rail giving a place for the current main.

Referring to our illustration, Fig. 1 represents the plan of the motor car, showing its sharpfront and rear ends, and its six compartments, each holding four passengers, who sit back to back. It is proposed in prac-(Continued on page 100.)



© 1894 SCIENTIFIC AMERICAN, INC.

Scientific American.

[FEBRUARY 17, 1894.

Scientific American.

ESTABLISHED 1845.

MUNN & CO.. Editors and Proprietors. PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

TERMS FOR THE SCIENTIFIC AMERICAN.

A. E. BEACH.

106

The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, 55.00 a year, for the U. S., Canada or Mexico. 36.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country. See prospectus, last page. (combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to one address in U. S., Canada or Mexico, on receipt of server dollars. To foreign countries within Postal Union, *sight* dollars and fifty cents a year.

Building Edition.

Building Edition. THE ARCHITECTS AND BUILDERS EDITION OF THE SCIENTIFIC AMERI-CAN is a large and splendid illustrated periodical, issued monthly, con-taining floor plans, perspective views, and sheets of constructive details, pertaining to modern architecture. Each number is illustrated with beautiful plates, showing desirable dwellings, public buildings and archi-tectura? work in great variety. To builders and all who contemplate build-ing this work is invaluable. Has the largest circulation of any architec-tural publication in the world. Single copies 20 cents. By mail, to any part of the United States, Canada or Mexico, 25.06 a year. To foreign Postal Union countries, \$5.00 a year. Combined rate for BUILDING EDITION with SCIENTIFIC AMERICAN, to one address, \$5.00 a year. To foreign Postal Union countries, \$6.63 a year. Combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN and SUP-PLEMENT, \$9.00 a year. To foreign Postal Union countries, \$11.00 a year.

Spanish Edition of the Scientific American.

Spanish Edifion of the Scientific American. LA AMERICA CIENTIFICA E INDUSTRIAL (Spanish trade edition of the SCIENTIFIC AMERICAN) is published monthly, uniform in size and typo-graphy with the SCIENTIFIC AMERICAN. Every number of La America is profusely illustrated. It is the finest scientific, industrial trade paper printed in the Spanish language. It circulates throughout Cuba, the West Indies, Mexico Central and South America, Spain and Spanish posses-sions-wherever the Spanish language is spoken. \$3.00 a year, post paid to any part of the world. Single copies 25 cents. See prospectus. MUNN & CO., Publishers, 361 Broadway, New York. The safest way to remit is by postal order, express money order, draft or bank check. Make all remittances payable to order of MUNN & CO.

draft or bank check. Make an reminute of the publishers in case of the publishers in case of any failure delay, or irregularity in receipt of papers.

NEW YORK, SATURDAY, FEBRUARY 17, 1894.

Contents.

Contents.							
(Illustrated	articles are	ma	rked	with	an	asterisk.)	
		~					

Agricultural devices, new 108	Gun, Maxim
Air, liquid, Prof. Dewar on 102	Inventions recently patented 1.8
Aluminum, coating 103	Jewfish, the* 107
Armies of Europe, the 99	Manganese steel 107
Bicycle railway, the Boynton* 97	Mars 106
Boilers, use of caustic soda in	Mexico. drainage of valley of 107
(5798) 109	Miles Standish's pipe* 107
Books and publications, new 108	Milk, skim, enriching 107
Bread, sour 102	Montgomery, new U.S. cruiser.* 105
Button fastener, Bell's* 102	Motor, street car, new 98
Carbon, what is it ? 101	Natural history notes 106
Cement mortar 102	Nitrate deposits in Colombia 103
Chicory, manufacture of* 101	Patent applications, divisional 98
Coal dump, Barrett's* 102	Patents granted, weekly record. 109
Colonial relics, Columbian Expo-	Plants, respiration of 106
sition* 107	Plaster, marble-like* 101
Coloring gelatino-bromide printe 99	Punch, a cold iron, Johnson's* 101
Court building. New York, new . 105	Putnam's torch* 107
Dextrine, white 102	Scorpions, do they commit
Eat, what shall we?	suicide
Electrical apparatus. new 108	Steam shovel, Boudrie &
Electric railway Boynton bicycle* 97	McManus ^{**} 100
Envelope, display, Billwiller's* 102	Stone, artificial
Exposition, California	Street cars, helping up hill 103
Feedwater heater and purifier.	Telephone, the Bell, how it has
Collins ^{**}	paid 103
Flour. chemicalized 100	Telephones, cheap
Gas lights, incandescent 98	Test paper, a new
Glass, compound	Torpedo, Fulton's, in 1805 104
Glass, expansion of 99	Trees, evergreen, removing 107

TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT

No. 946.

For the Week Ending February 17, 1894.

Price 10 cents. For sale by all newsdealers

PAGE I. AERONAUTICS.—The Internal Work of the Wind.—By S. P. LANGLEY.—A contribution to the mechanism of the flight of birds. —A contribution to the problem of souring.—Silbustrations...... 1512 11. ARCH & OLOGY.-Excavations at Dougga.-Remains of a Roman theater found in Tunis.-2 illustrations 1511

- V. BOTANY.—Effects of Electric Flash Light on Plants.—Interrupt-ed light and its effect on the heliotropism of plants..... Interesting Experiments in Germination.—By G. J. ROMANES.— The respiration of seeds and its necessity tested...... 15114
- VI. CHEMISTRY. Alloys.-By Prof. W. CHANDLER ROBERTS-AUS-TEN.-Continuation of these important papers, treating of the composition of ancient alloys, with analyses of the same 15125

CHEAP TELEPHONES. The expiration of the Bell telephone patents is revolutionizing the sale of telephones in this country. It will be seen by the advertisement of the Metropoli-

tan Telephone Company, of this city, who are licensed under the Bell Telephone Company, that they are now offering the genuine Bell telephone instruments for sale at \$1.25 each. As these instruments are accurately made, and yield the best results, they are likely to give a great impetus to the construction of short telephone lines in buildings and in country places.

A NEW STREET CAR MOTOR.

A recent number of the Morning Call, San Francisco, contains an account of the trial in that city of a gasoline car, the invention of Daniel S. Regan. The propulsion of the car is effected by the injection into the engine cylinder of a small quantity of gasoline, the vapor of which is mixed with air, forming an explosive mixture that is fired by electricity. A pressure of 280 pounds per square inch is produced on the piston. The trial car is said to have operated with great success, demonstrating an economy and ease of working alto gether superior to anything in the line of street car motors that has yet made its appearance. The Call savs a reward of £50,000, or \$250,000, has been offered in England for the production of a new form of street car propulsion that shall be better than the overhead trollev or the cable system. But this, we think, must be an error. The only reward offered in this direction, so far as we know, is that of the Metropolitan Traction Company, of this city, who offer to pay a reward of \$50,000 for a new system that shall be approved by the New York State Board of Railway Commissioners, as being superior for practical uses in the streets of New York to the cable or the overhead trolley.

THE CALIFORNIA MIDWINTER EXPOSITION IN GOLDEN GATE PARK, SAN FRANCISCO.

On May 31, 1893, in the city of Chicago, a meeting was held in the rooms of the California Club and the suggestion was made by Mr. M. H. De Young, vicepresident of the Columbian World's Fair, that a midwinter exposition should be held in San Francisco, California. The idea was acted on, and the next day the announcement was made. Work at once began in the appointment of officers, enlistment of State and city recognition, and in the soliciting of subscrip tions. Nearly half a million of dollars was soon obtained. The ground was broken in San Francisco on August 24, in the presence of a concourse of nearly 100,000 people. The work progressed rapidly. Advantage was taken of the Chicago Fair, and exhibits and attractions therefrom were secured. Six main buildings, distributed over nearly 200 acres of ground, lighted by 1,000 electric lamps and 15,000 incandescent lamps from Chicago, one hundred independent buildings, are some of the elements which unite to form what is termed the third most important exhibition the world has ever seen.

The fair grounds are situated in Golden Gate Park, San Francisco, the park being now in its best state, with its semi-tropical trees and plants, the lovely climate adding to the charms of the locality, which forms a setting for the architectural features. For by the use of staff beautiful buildings have been rap idly erected, and the system of the Chicago Fair has been followed in keeping in view the architectural elements of the scene. The cost of the fair, it is thought, will not exceed \$1,500,000, nearly half of which has been contributed by the people of San Francisco. As the Chicago Fair was termed the "White City," the name of Palm City has been bestowed on its western sister. The fair opened on Saturday, January 27, with due ceremonies and in the presence of an immense audience.

Speeches, a grand parade, concerts, and at night fire works and illuminations made the occasion a memor-15115 able one. The admissions on that day aggregated 72,248 people.

Throughout the grounds are distributed every under the old system each 630 square meters of street imaginable attraction, the Firth wheel, the scenic surface received light equal to only 32 candles. every railway, the cascade, foreign villages and the like, en-300 square meters of surface is now illuminated to the tertaining, and in some cases instructing, the visitors. extent of 100 candles. The lighting, therefore, is more A reproduction by cyclorama of the Hawaiian volcano than six times as great as that ordinarily employed Kilauea is described as wonderfully realistic. for streets. The fair is managed by the following executive committee: M. H. De Young, president and director-gen-The Maxim Gun in Action. eral; Irwin C. Stump, vice-president; P. N. Lilien-The Maxim gun has been well tested in the Matathal, treasurer; R. B. Mitchell, A. Andrews, F. G. beleland campaign. In the skirmish of October 25 the Berry, Eugene Gregory, J. H. Neff, and J. S. Slauson, Maxim gun effectually checked the natives. Although of Los Angeles. the natives were armed with Martini-Henry and Winchester rifles, they were powerless before the terrible Divisional Patent Applications. fire of the Maxim gun; which mowed them down like wheat before a scythe. In the morning the sight was A late decision of the Supreme Court involves certain considerations as to patents issued upon diviterrible, bodies being literally torn to pieces by the shot. sional applications, the results of which the *Electrical* Each time the natives approached they were quickly Engineer thinks are likely to be important and far repulsed with the aid of the machine gun. The Armreaching. Briefly, the dectrine now laid down by the strong 7-pounder has also rendered efficient service in court, as we understand it, is that only one patent the campaign. On one occasion a shell dropped harmlessly upon the ground, when the negroes immediately can be taken for a single concrete invention, or for any part of such invention; and consequently, that began firing upon it. The shell then exploded, killing

ing to cover different parts of the same subject matter, all except the one bearing the lowest serial number are void. Especially is it held by the Court to be inadmissible to distribute the subject matter of an invention between two patents, distinguishable from each other only by the different functions ascribed to a common mechanical structure.

We entertain no doubt that the ultimate effect of this decision will be wholesome and salutary. As to its immediate effect, there is certainly abundant room for interesting speculation. One important patent may be mentioned, which would seem to be in imminent danger of being overthrown by the new doctrinethe famous Berliner transmitter patent, which, in reality, covers the employment, as a transmitter, of a certain mechanical structure which, in its capacity as a receiver, was patented as long ago as November 2, 1880. There are also a very large number of patents on electric railway apparatus and devices, heretofore assumed by their owners to be controlling, and upon which a considerable number of pending suits have been based. which are founded upon divisional patents Some of these, at least, must unquestionably be obnoxious to the doctrine now laid down by the Supreme Court.

Compound Glass.

According to a report of the technical glass laboratory at Jena, O. Schott has introduced a glass which is of great technical interest and value. It is free from alkali, but can be worked before the blowpipe, has a small co-efficient of expansion, and is distinguished by many excellent qualities. Hitherto the view has been generally held that good glass must contain, together with silica and a divalent or trivalent metallic oxide, the oxide of a monovalent metal (an alkali metal or thallium). By the glass referred to (121¹¹¹) is free from alkalies and has the following composition :

BaO=25 per cent., ZnO = 5 per cent., Al₂O₃=4.5

per cent., B₂O₃=14 per cent., Mn₂O₃=0.08 per cent., $SiO_2 = 51.22$, $As_2O_5 = 0.2$ per cent.

Schott was led to the production of his compound glass (Verbundglas) by studying the state of strain in ordinary glass vessels and tubes cooled in contact with the air. A hollow glass vessel cooled in contact with the air has its outer skin in a state of compression, whereas the inside is in a state of tension; hence it is easily damaged on the inside, but is resistent on the outside. A hollow glass vessel, if introduced when cold into warm air, has its outer skin thrown into a state of compression; if, when it is hot, it is exposed to cold air its outer skin is thrown into a state of tension. This is the reason why cold air causes glass to crack more readily than hot air does. Schott succeeded in throwing the outer layer into a permanent state of compression by covering the glass vessel with a thin outer layer of glass which has a small co-efficient of expansion. The flasks made of this compound glass can be filled with boiling aniline and immediately sprinkled on the outside with cold water ; and glass dishes can be heated over the naked Bunsen flame without cracking. Pressure tubes of this compound glass can be made to meet all the requirements of practice. They have been kept in continuous use on locomotives for five months, and when heated to 200° C., they can be sprinkled with cold water without any fear of cracking.

Incandescent Gas Lights.

According to a paragraph in a recent number of the Journal für Gasbeleuchtung, a trial has been going on since June last in the Badgasse, Budapesth, and since. October in the Ofen Tunnel, with Dr. Auer's incandescent gas lights. So satisfactory is the effect, that when the Budget estimates come on for discussion, it is intended to put forward a request that all streets in which the electric light is not to be used shall be lighted by the incandescent gas system, as by it the amount of illumination afforded is increased by five or even six fold. In Agram also Dr. Auer's burners have been tried with equally favorable results. While

the static dischargeResults obtained	15121	
Energical States and the state of the states of the sta	15121	
ed end disks of steel magnets when immersed in electroives The Jeffrey Electric Coal Mining MachineA coal cutting ma- chine introduced in the English mines, undercutting 120 square feet per hourAn electric drill also in use there2 illustrations.	15121 15120	
VIII. HORTICULTURE Chrysanthemum Robert Petfield A new incurved chrysanthemum1 illustration	15115	
 MISCELLANEOUSA Japanese Flower SellerA interesting episode in Japanese street lifeI illustration. Budt Racing in BurmaA cance race with thirty-two paddlers 	15114	
in each boat 1 illustration.	15112	
Africa and of the customs of the natives.—Illustrations	15111 15112	
X. PHYSICS.—The Temperature of Ignition of Explosive Gaseous MixturesBy A. E. TUTTON.—An important contribution to ther- modynamics	15124	
XI. SOCIOLOGYHeredityBy M. F. PRICE, M DEffect of heredity on constitution and disease and morality The RecidivistBy JAMES WEIR. JrThe criminal natures of the habitual malefactor and of the accidental one and their char-	15116	
acteristics	15117	
XII. TECHNOLOGY Strength Lost by the TwistThe mooted question of the effect of twisting on the strength of cords and threads	15121	
Sugar from Cornstains	15115	

when more than one patent has been issued purport-several.

The Armies of Europe.

The military statistics of the European nations supply a suggestive object lesson in relation to our present civilization. The importance of the war footing of Europe cannot be overestimated. In case of a general war, the principal belligerent nations of Europe, excluding Turkey, could hurl 14,991,000 men into the contest. The standing army alone of the greater European nations consists of 3,274,000 men. Russia leads the list; her "peace footing" or standing army consists of 868,000 men. These soldiers are drawn from a population of 124,000,000. The enormous strength of this army may be shown by comparing it, with the army of Rome during the palmy days of the empire. The permanent military force of Rome on sea and land was only 450, 000. France comes next to Russia, the strength of the army being 600,000 men. This army is drawn from and charged upon a population of 38,500,000. The Chauvinistic spirit of the French people has been somewhat modified by the increased permanent military force of Germany, which now numbers 596,000 men, drawn from a population of 49,000,000. Austria, with Hungary, comes next, the army numbering 326, 000 men, the population of the monarchy being 41,000, 000. Fifth on the list comes Italy, whose armies number 247,000 men, drawn from a populaton of 30,000,000. England, notwithstanding her naval superiority, comes only sixth on the list, the population being 30,000,000 and the standing army 247,000. Spain has an army o 115,000 men. drawn from a population of 17,500,000.

With the size of the country the size of the army gradually decreases until the pitiful handfuls of men are reached who form the armies of Andorra, San Marino, and Monaco. Switzerland is an exception, as the constitution of this tight little republic forbids the maintenance of a standing army. When the "war footing" is considered, Germany leads with 4,000,000 men. Russia, which has the largest standing army, takes a second place as regards the war force, as she can only culture." muster 2,530,000 men. France, with 2,500,000 men, is not far behind. If the size of the war footing of France and Germany be compared with the population, it will be seen that France, taking population for population, is a little ahead of Germany in preparing her whole available material for war. The war strength of Austria-Hungary is 1,753,000 men; that of Italy, 1,650,000 men, while Spain comes next, with 1,083,000 men and Great Britain follows with only 713,000. Switzerland, in case of necessity, can furnish 485,000 trained men.

War is constantly becoming more expensive, and while the war cloud of Europe is settling down, the disgustingly maudlin, affectionate and silly, while the financiers of the great powers are looking with great apprehension at the cost of throwing armies into the field composed of millions of men. Emperor William will do well to increase his war fund locked in the Juliusturm of Spandau if 4,000,000 of men are mobilized, as 120,000,000 marks will not last long at the present average expense of armies. The statement which is sometimes made that the fortunes of war are decided behind the green baize doors of bankers' private offices contains more truth than is at first apparent. War is now a luxury, and, like all luxuries, can only be enjoyed at great expense. The fact of the expense connected with modern war has made it unattainable to a bankrupt country, and undoubtedly tends to make even the great powers think twice before leaping. Anything which helps to discourage war and favors the settlement of difficulties by pacific means should be encouraged, so that increase in the production of war material may be regarded as a step in the right direction.

What Shall we Eat?

Every once in a while there is recrudescence of vege tarianism and also many reappearances of special recommendations as to diet that are so extreme, not to say "cranky," as to suggest that the persons making them must have spoken out of the sufferings of stomachs so far from normal as rightly to be called "cranky."

The traveler from a distant planet, returning to his home and describing our habits, would say: "They prey upon other animals." It has a repulsive sound; the heat that warms our bodies, and into strength for but, of course, it is just what meat-eaters do, in spite of all the refinements and transformations that, as Emerson says, "intervene between the slaughter house and our plates," where the slice of steak or roast reposes so tranquilly as to give no hint that it was once alive and as full of sensitive nerves as is the mouse on which the cat so ruthlessly pounces. But let even the hypersensitive founders of the Society for the Prevention of Cruelty to Animals reflect a moment, and ask themselves if the deliberate killing of an animal, by intelligent and humane methods, is not a more merciful fate than the slow perishing by disease that contain much protein, and these are beef, some or old age, which certainly would occur in a state of unassisted nature.

ciful way of killing cattle; a leathern strap completely covering the eyes is slipped over the animal's horns before he is taken to the slaughter house. In the center of this strap is a perforated iron block, the hole being directly over the center of the forehead. Standing in this hole is a short, sharp, hollow steel spike, which is driven into the brain by a single blow of a heavy hammer, producing instant unconsciousness. Immediately, a sharp iron rod is made to penetrate that point in the base of the brain which corresponds to the "vital knot" of the human system, and absolute death is the result. The large blood vessels are then severed. As civilization advances, we see everywhere more humane laws being enacted for what must be considered the indispensable killing of animals, if man is to continue on his upward career, in knowledge, wisdom and happiness; for the brain worker, far more certainly than the muscle worker, must have flesh food to work upon.

The vegetarian can point to a considerable array of facts that sustain his theory. Many tribes of North American Indians have attained a very high physical development upon a vegetable diet; many Scotch farmers live principally upon oatmeal; meat is a comparative rarity among European laborers. Many Englishmen formerly lived on bread, cheese and beer (though cheese can hardly be called a vegetable); the Roman legionary carried a weight of sixty pounds and performed astounding feats of strength and endurance without eating flesh, and some people have substituted eggs and milk for meat, under the delusion that they are less atrocious than flesh-eaters; but the opinion of This the cow whose calf they have robbed of its natural food thu should be asked, before final judgment.

Dr. C. N. Folsom, then Secretary of the Massachusetts Board of Health, wrote twenty years ago:

"The Brahmins of India eat nothing which contains the germ of animal life, although they can hardly be said to have attained a vigorous physical or mental

Mr. Edison puts the truth here hinted at more tersely Im: in "Those that eat rice think rice," while Dr. Folsom still further says:

"Although physiologists are not agreed that animal food is absolutely essential to a high degree of civili- Im zation, there are certainly many facts which seem to indicate that it is resolvable into a greater amount of force than the other nitrogenous foods."

That the kind and quality of food gets into a man's thought and disposition is not to be denied. The physicians at Sebastopol, after the Crimean war, testified that when a Russian soldier was intoxicated he became Briton in that state became at once "full of fight;" and they accounted for it by the fact that the first lived on black bread and the second had meat. Dogs that are quiet and subdued on vegetable food grow fierce on meat, and there are persons of fine nervous organization who find in meat a stimulus similar to that of wine.

The great advances in analytical chemistry in these last two decades have done much to reveal wherein the 'potential energy" of foodstuffs lies, and the "training" of our athletes shows that we are beginning to prescribe food with as much precision as we can use the most familiar drugs—say as quinine and opium.

When James Russell Lowell went out to "rough it" among the Maine lumbermen, he was astonished to find that the essential article of their diet was fat pork. against which he at that time held a genteel prejudice; a few days of heavy tramping brought him to a complete appreciation of its merits as a heat and strength producer. These lumbermen labor intensely in the cold and snows of winter, and in the icy water in spring, and beans and fat pork are the staple of their diet and the modern chemist comes along with his physiological yardstick and tells us the exact reason why men performing the severest tasks prefer pork to the choicest cuts of beef.

Prof. W. O. Atwater says:

"The energy from the sun is stored in the protein and fats and carbohydrates of food, and the physiologists of to-day are telling us how it is transmuted into our work and thought. Professor Frankland determined the heats of combustion of many substances, and reckoned them in units called "calories." Among forty-five substances tested, he found that very fat pork contained an amount represented by 3,452, while fat beef contained 2,750, lean beef 807, and turnips only 139, while beans came up to 1,519, and peas to 1,476. Many of us do not require so much "energy" in our food, but we do need material which will restore the worn-out and ever-wearingout tissues of the body, and for this we must have foods kinds of fish and eggs. All food substances have more or less of water, but the driest of all is fat pork. For a most interesting study of the whole subject, where the relative value of different substances, for nutrition, is shown by an ingenious diagram at a glance, the read water, in the Century Magazine, beginning in May,

Fortunately, the healthful preparation of food is being studied by our scientists theoretically and by our wide awake, intelligent women practically. Mr. Edward Atkinson truly says:

"If the masses of the people are to be well nourished, each adult person must have the due proportion of protein, or nitrogenous material, of fats, and of carbohydrates, or starchy materials: because, if either one is deficient, vital force cannot be sustained. Neither can there be any true mental vigor or spiritual life when the body is not well nourished.'

There has been too much despising of "this vile body," as some have dared to call the exquisitely adjusted temple of the Holy Ghost which God has given into our individual keeping, and for the neglecting or abusing of which he will make inquisition. If we intend to care for the soul, we must first care for the body. He who knew "what was in man" set the example when he saw to it that the multitude was fed before he attempted to instruct them. -The Independent.

Coloring Gelatino-B70mide Prints.

The Archiv gives the following plan for getting different colors on bromide prints. The prints are feebly developed with eikonogen, fixed, washed and then immersed in a solution of :

Nitrate of lead	4]	parts.
Red prussiate	6	**
Water	100	**
s bleaches the image, which may then	be	$\operatorname{colored}$

18: Brown	
Schlippe's salt Ammonia. Water.	10 parts. 5 '' 150 ''
Yellow.	
Neutral chromate of potash	4 parts. 100 "
Green.	
merse the yellow prints in	
Iron perchloride Water	1 part. 10 parts.
Red.	
merse the yellow prints in	
Chloride of copper Water	1 part. 10 parts.
Nickel Green.	
Chloride of nickel Water	1 part. 10 parts.
Orange.	
Mercury bichloride Potassium iodide Water	3 parts. 4·5 '' 100 ''
	Br. Jour.
	_

Co-efficients of Expansion of Glass.

Most of the published data relate to glass of unknown composition, and are therefore of comparatively little use. Regnault is the only investigator who appears to have supplied information respecting chemical composition with the physical data; and even his researches do not enable us to draw any conclusion as to the influence of different oxides upon the expansion of glass. A careful and extensive investigation of the co-efficients of expansion of a large number of glasses of various compositions (made by the Jena firm) have been carried out by Prof. Winkelmann, Dr. Straubel, and Dr. Pulfrich, using a dilatometer according to Fizeau's method as modified by Abbe (Wied. Ann. 38, 453). The tabulated data occupy the best part of three large pages, and the principal results can only be given here. Of these the most striking is the predominating influence of alkalies upon the value of the co-efficient of expansion. By increasing the amount of alkali in a glass, its co-efficient of expansion could be increased until it approximated nearly to that of nickel or iron. The tables further show that the expansion of different glasses for equal intervals of temperature varies within much wider limits than has hitherto been believed : for example, a specimen of glass containing 12 per cent of alumina was found to have a co-efficient of expansion 0 00003369; whereas a specimen of zinc borate glass free from alkali has a co-efficient of expansion of only 0.00001097.

At the two large abattoirs of Lyons, France, the guards protect the animals to be slaughtered from seeing anything connected with the slaughtering of other animals, as terror is found to have an injurious effect | er is referred to a series of articles by Prof. W. O. Atupon the secretions and flesh of dumb creatures. Zurich, in Switzerland, twenty years ago, invented a mer. 1887.

In the case of the usual silicate glass it is found that metallic oxides, such as zinc oxide, alumina, lead oxide, and baryta, do not produce any considerable increase in the expansion. Phosphate glass behaves much like the ordinary silicate glass with respect to expansion, whereas borate glass is distinguished by a low co-efficient of expansion.

Artificial Stone.

Thirty parts of tin are dissolved in 40 parts of muriatic acid and 30 parts of sal ammoniac are added. A powder composed of freestone 50 parts, zinc oxide 20 parts, pounded glass 15 parts, powdered marble 10 parts and calcined magnesia 5 parts is prepared and made into a paste with the liquid above mentioned. Coloring matter may be added. The composition may be used as a damp-proof coating for walls or for repairing stone work or for moulding statues or ornaments.

THE BOYNTON BICYCLE ELECTRIC RAILWAY. (Continued from first page.)

tice to run trains of mixed trailing and motor cars, vestibuled throughout, with the front end of the front motor car and rear end of the rear motor car sharp. Each compartment has a side door.

The car is carried by two wheels. Each wheel is journaled in a frame at the bottom of a vertical shaft distinctly one of the guide wheels. It is an interesting or column rising through the car roof. The upper end | fact that in operation these wheels have very little to of this column carries a frame with four guide wheels, which have vertical axes, and between which is space for the upper guide rails. In passing around curves these four rollers turn the column, so that the axis of bands sprung around the steel wheels have not worn the large wheel is always normal to the curve. The through with 4,000 miles of travel.

ing in the floor of the car is large enough to permit this rotation, and four centering rollers, with horizontal axes, and distributed approximately at right angles to each other about the perimeter of the determined circle, press against bearing pieces, which arrangement keeps the spindle centered at its lower end. The car body swings on springs from the two columns. The springs are fastened near the level of top of the car. Thus the car body can spring up and down without affecting the columns and wheels. This is shown in Figs. 2, 5, and 7.

Fig. 3 is a view of the motor and driving wheel. The motor is of the Gramme type; the field, in part broken away, is seen with four of its coils of wire; back of it is seen the Gramme ring with its connections to the commutator and the brushes. The Gramme ring is bolted to the wheel; the field is carried by the stationary framework. When excited, therefore, the wheel and Gramme ring rotate, the field not moving. A sixpole motor, with armature forty-three inches in diameter, placed on a five-foot wheel,

and developing about 75 horse power, is a standard assigned by the inventor, and is employed on the car shown. The torque has a lever arm of about twenty inches.

On reference to Fig. 2, it will be seen that there is an upper rail to act as a conductor for the current. This cut shows also the two horizontal guide wheels which are to bear against the wooden beams between which the current rail is placed. This current rail weighs 12 pounds to the yard and is of 11/4 square inches section. With its casing it is shown in Fig. 4, where also are seen the guide beams.

In Fig. 5 is shown an interior view of the motor compartment, with the wheel and motor, the frame for the same, and the spring bearing for the car bodv.

Fig. 6 shows the electric plant as at present installed, with the switchboard, steam engine and four-pole 100 H. P. Westinghouse dynamo.

The whole driving structure which we have thus far described is shown in Fig. 7, and after what has been said, the cut will be found self-explanatory. In it is seen the driving wheel with the armature fastened to it, actuated by the field, which is shown in this case placed within the circle of the Gramme ring. The reversing switch and resistance box for control-

current reaches the top rail: thence is taken to the motor by a collector, and passes away therefrom by the bottom rail on the return circuit to the dynamo.

In Fig. 8 is shown a collecting device for taking current from the upper rail. At present frictional shoes are used instead of the brush shown. This shows very do, in many cases light being visible between their periphery and the beam which they are supposed to bear against. It has been found that soft rubber

wheel has only to turn through a small arc; the open- In Fig. 9 is shown the station near Patchogue, L. I.,



BOUDRIE & MCMANUS' STEAM SHOVEL,

with a car ready to start out on its travels, this time on a surface road. The great cheapness of the construction and the high velocity to be employed has induced the company to feel that an elevated road is the more expedient, and the larger cut shows the ideal ele vated bicycle road. The sharp-pointed car carried by two wheels and moving at the rate of 70 to 100 or more miles per hour, abolishing grade crossings and electric trolley wires, here appears in operation.

Some of the generalities of the system may be spoken of now. A motor car seating twenty-four people will weigh 6 tons, and the trailing car seating fifty people will weigh half this amount. The cars are 51 feet long, 4 feet wide and 7 feet high. A train of two motor cars with three trailing cars between them, accommodating 200 people, can be built within twenty tons. This is about one-tenth the weight of the Empire State Express, which also seats that number of people.

The maximum curve on the present road is one of nine degrees, and therefore is of only 640 feet radius.

The car in operation runs around this nine degree curve with the greatest ease of motion, the absence of side swaying of the car or passengers being particularly noticeable.

On curves the guide rails are displaced toward the ling the speed are also shown. It will be seen that the center of curvature, so as to tilt the top of the cars in-

ward. Two feet is the maximum displacement of the upper rails, and is gradually reached before the curve begins, giving a transition curve, so that the car enters the maximum curve with the full inclination. The rule is to give sufficient inclination for the highest speed. The upper rail is so high and the center of gravity so low that the pressure on the guides is very slight. Nine feet now intervenes between the track rail and guide rail.

On the top of the wheel columns is a section of an inverted U beam about four feet long, embracing the guide beam, so that if all the rollers should break, the car will still be maintained in its upright position. A similar arrangement is provided for the supporting

wheel, so that if anything breaks, the car end will be carried by a sliding shoe in perfect safety until it stops.

A STEAM SHOVEL FOR USE ON FLAT CARS.

To provide a platform for the shovel carriage whereby it may be readily moved from end to end of a train of cars, and the work of loading a train be thereby greatly facilitated, is the principal object of the invention herewith illustrated, which has been patented by Messrs. J. M. Boudrie and Thomas McManus, Rulo, Neb. Fig. 1 represents the improvement in use, Fig. 2 showing the clamping of the shovel carriage to the flat car, and Figs. 3 and 4 illustrating the track connection between two cars. In grooves or channels in the floor of each car are tracks, preferably of angle iron, and in the sill at the end of each rail is a transverse recess in which is a chair, the opposing chairs of meeting cars, or on the two ends of a car, being slightly different. In the one case the chair consists of a base plate with rigid curved arms at each side of the center, adapted to bear upon the web

and base of a rail inserted between them, while in the other case one of the curved arms is pivoted, and held normally in closed position against the rail by a spring. When the cars are coupled together, the tracks are rendered continuous from one end of the train to the other by short coupling rails whose ends are seated in the chairs, the pivoted arm of one of the chairs being raised against the pressure of the spring to facilitate the insertion of the rail. The shovel carriage is mounted on flanged wheels adapted to travel on the tracks, and carries a motor, mast, and hoisting machinery of any approved description, the carriage being firmly held to the car upon which it is located by brackets of a clamp form, hinged to the side edges of the carriage. The lower end of each clamping bracket has a set screw by which the clamps are held in clamping position, they being thrown upon the floor of the carriage when not needed.

Chemicalized Flour.

In order to render fine white wheaten flour equal in digestive and nutritive value to brown or whole meal, without introducing any of the bad qualities of the latter, the inventor mixes with it one-quarter per cent each of magnesium phosphate and sulphate. -W. Jones.



© 1894 SCIENTIFIC AMERICAN, INC

A HAND PUNCH FOR WORK ON COLD IRON. This is a strong and simple machine in which levers are so arranged as to be operated by hand, practically without friction and with great power, for punching

holes in metal. The improvement has been patented by Mr. Paul L. Johnson, of Bishop Hill, Ill. The frame is clamped to a suitable support and has at its



JOHNSON'S PUNCHING MACHINE.

lower end a lug which carries the die plate. The latter may, if desired, be held in place by a downwardly extending bolt and thumb nut. The vertically sliding punch bar is pivoted at its upper end to a drive bar, and the latter is pivoted at its upper end to a drive lever, the short arm of which is pivoted between lugs outer end, is connected by rods which straddle the frame with the elbow portion of a forked-handle lever, which also straddles the frame and the drive bar, the escape or discharge pipe. When the boiler is filled short arm of this lever being also fulcrumed to the frame. The handle lever and the drive lever each have the mud drum with the heater is opened, and the heat

a series of holes to receive the pivot pins of the connecting rods for the making of different adjustments, according to the length of stroke or the power required.

What is Carbon ? That carbon is a "metalloid"which, if it means anything, means something resembling, but not identical with, a metal - we have long been assured, chiefly by French chemists suffering from an excess of system. Now, however, it has advanced a step further, and presumably forms a basic oxide. No other hypothesis appears tenable to account for the existence of two remarkable bodies named respectively "carbon silicate" and

"carbon sulphate," the product of the reaction of ignor

may after all be merely a pseudonym for carbon disulphide. The speculation is enticing, and we commend | necting the mud drum with the heater are closed. it to the dilettanti.-Industries.

AN ARCH SUPPORT, WATER PURIFIER AND HEATER.

over the combustion chamber at its back end, and is an auxiliary steam generator as well as feed water heater, while aiding in securing the best results in keeping the boiler practically clean, by blowing off and otherwise. It has been patented by Mr. George W. Collin, of Atlanta, Ga. The heater is formed with curved end columns and connecting pipes, the latter having in their ends hand holes with removable cover plates, the heater being supported by the furnace walls and forming a firm support for the arch, which may be built directly upon the end columns and tubes. In each of the connecting tubes is a strip of sheet copper with serrated edges, to take up lime, etc., from the water, and prevent the formation of scale, the mud drum also being supplied with a similar plate, and the plates being readily remov-

the curved end columns of the heater, and has a valved [†] silicates used. and the fire started, the valve in the pipe connecting

> and flame passing backward under the boiler, up against the pipes of the heater, causes a circulation of water from the upper connection of the heater into the boiler, and from the bottom of the boiler through the mud drum and again into the heater, making a constant current one way through the device. When



arguing from the carborundum case, carbon sulphate the boiler. To blow off water from the bottom of the boiler, the valves in the feed pipe and in the pipe con-

Marble-like Plaster.

Zinc in the form of cuttings or dust is placed in This improvement, adapted for use in connection water, and after having been allowed to stand for with an ordinary boiler, affords a permanent arch some time boiled therewith, whereby it dissolves to



THE "C. B." BOILER ATTACHMENT.

able when necessary. At its upper end the heater is the extent of about 32 milligrammes per liter. The soconnected by suitable pipes with the steam space of lution is mixed with an equal quantity of a solution of the boiler, and one of its curved end columns is con- an alkaline silicate, preferably silicate of potash at 3 nected near its upper end with the boiler at or just B., and the mixture diluted with four times its weight below the lower water line. The feed pipe has a of water. One part of gypsum is mixed with two parts valved connection leading to the bottom of the boiler of lime and made into a paste with the liquid already near the top of the frame, while its long arm, near the and another leading to the mud drum, while the described, the product having, it is stated, a marblelatter is also connected by a valved pipe with one of like luster due to the employment of the mixture of

MANUFACTURE OF CHICORY.

Chicory or succory plant is raised principally in England, Holland, Belgium, France, and Germany. A small quantity is raised in the United States, most of which is grown on a few hundred acres in California. The plant belongs to the same family as the dandelion. It has a long fleshy and milky tap root. The plant when under cultivation grows to the height of 5 to 6 feet. It grows very quickly in a low temperature, the plant making about 7 inches in about three weeks. In some countries it is grown as fodder and herbage for cattle. The plant blossoms in August and September and can be recognized by its bright blue flowers, which measure about $1\frac{1}{2}$ inches across. The soils best adapted for its growth are deep, friable loams. The process of cultivation is about the same as that required for carrots, excepting that it is not sown earlier than the first week in May, lest it should run to seed. About four pounds of seed is the quantity required to sow per acre either broadcast or in rows, the latter being the best method, yielding roots of greater weight. The crop is ready for digging up in November. The analysis of chicory shows the following constituents: Water, 9.09; soluble salts, 4.20;

soluble extractive substances, 41.29; soluble gummy resinous substances, 5.22; dextrine, 6.12; saccharine matter, 11.36; cellulose, 19.40; caramel, 2.10; carbon, 1.18; empyreumatic oils, 0.04. In some countries it is used as a substitute for coffee. Other substances have been tried for the same purpose and abandoned, not being agreeable or beneficial to some constitutions. When

mixed with coffee it adds to it additional color, bitterness and body. For the preparation of chicory the older stout white roots are selected, and after washing they are sliced up into small pieces and kilndried. In this condition it is sold to the chicory roaster. The roasters are made of rolled steel about 3 feet in diameter, about 3 feet in length and tapering down to about 1 foot at the ends. They are drawn from the ovens, on a track

ance and printer's ink found in a column serving for the fractional distillation of "scientific" residues, which appears weekly in an evening paper. Chemists will be disappointed to learn that the first named substance is nothing more mysterious than carborundum. They will, however, have ample room for admiration concerning the second, as it is said to be concerned in the production of



"coal balls" found in coal measures, and by passage feeding water from the feed pipe, the water is through the vegetable tissues of plants to produce first forced into the mud drum, to be taken up "chemical changes resulting in the formation of car. by the current through the heater, thus passing bonate of lime and iron pyrites." We are tempted to into the boiler at a high temperature, the steam suggest that sulphate of iron may be meant, but then, which is formed passing into the steam space of fitted up on each side, by means of movable frames in which they revolve. At one end of each roaster shaft is a gearing wheel which connects with a piece of shafting running the length of the ovens in the rear. This wheel geared to another on the rear shaft causes the roaster to revolve. From 200 to 400 pounds of dried chicory is put into a roaster with a quantity of olive oil or fat to prevent it from burning, where it revolves over a coke fire for about 134 hours, at the rate of 12 to 16 revolutions per minute. An iron carriage running on a track is then wheeled directly in front of the oven; the iron frame with roaster is then drawn from the oven on to the carriage, which is the same height and width as frame, and then wheeled away to the cooling floor, where the roaster is emptied and refilled again with dried chicory and run back over the track again to the oven, where it is replaced over the fire. The cooling floor is made of brick or cement and is about 30 feet square. After cooling, the chicory is put into the grinding machine. The material passes down through a hopper and between the teeth of a number of 8-inch rolls, which crush and grind the material into small particles, which is then conveyed by means of traveling cups to a wire bolt. The bolt is about 20 feet in length, the meshes of which run from about 4 to 40 to the inch. The ground material passes into this bolt, which revolves at the rate of 28 to 30 revolutions per minute, separating the fine particles from the coarse, which falls or sifts down through the netting to the openings at the bottom, and into the bags below. It is then packed into barrels and is ready for the market. In this country coffee is adulterated with about 2

per cent of chicory. Chicory is imported to this progressive stages in applying the fastener the comcountry in 100 to 150 pound bags, the average price being about 2½ cents per pound. Ground chicory brings about 5¼ cents per pound. The annual importation of chicory amounts to about 10,000,000 pounds. In San Joaquin County, California, about desired. The ends of the wire having been passed 400 acres are raised, furnishing in good years a profit of about \$300 per acre. The root when dried brings about \$200 per ton. The sketches were taken from the plant of the American Chicory Manufacturing notch in one ear, and the tongue on the outer edge Company, Jersey City.

APPARATUS FOR DUMPING COAL CARS, ETC.

This is a strong and rapidly working apparatus, for use in connection with an ordinary car, to automatically dump the load into a chute when the car has been raised to the required height. It has been patented by Mr. William H. Barrett, of Weir, Kan. The elevator cage is operated by cables in the usual way, and carries a dumping platform mounted on tilting frames, the platform having tracks on which that liquid air-produced with so great an expenditure the ordinary dumping car may be run. The car is held in position by swinging clamps on opposite sides of the car, with arms engaging the flanges and faces of the wheels, the clamps being fulcrumed on the sides of the platform, and having lower projecting ends pivoted to connecting rods extending beneath the car to a connection with an eccentric on a shaft journaled in increase in conductivity; so there was every reasonbearings beneath the platform. The latter shaft has and the experiments with liquid air had multiplied the levers or arms which project above the platform, and number and increased the cogency of these reasons-



Scientific American.

[FEBRUARY 17, 1894.

to pass downward.

AN IMPROVED BUTTON FASTENER.

This is a simple device, readily applied for securing an ordinary style of buttons to garments. It has been patented by Mr. Robert Mowry Bell, of Santa Cruz, Cal. Figs. 1 and 2 show the clamp plate or blank and the fastening wire, Figs. 3 and 4 illustrating



BELL'S BUTTON FASTENER.

pleted stage being represented in Fig. 5. The fastening wire, in the form of a staple, is passed through two of the holes of the button and through the fabric, a collar being employed as shown in Fig. 6, where through the nearly central opening in the clamp plate, the ears at each end of this plate are then folded down upon the central portion, the wire lying in the of the other ear being bent down under the central portion. The invention also provides for some variations in the form of the blanks.

Professor Dewar on Liquid Air.

It is said that Faraday, when he was asked what was the use of certain of his discoveries. retorted with the conundrum, "What is the use of a baby?" Professor Dewar recently, at the Royal Institution, attempted to answer the question in a different way, by showing of time, skill and money-had distinct uses, although those uses were scientific ones, and were useful only as establishing a basis for new scientific theories or as confirming old ones.

The first scientific hypothesis to which he alluded was that as the metals decrease in temperature so they by means of these levers the clamps may be swung in to suppose that when the temperature of absolute zero

> of minus 274 deg. C. was reached, then the metals reached the point of absolute conductivity. Next to this the lecturer alluded to the uses to which liquid air had been put in establishing and confirming the refractive indices of oxygen air and nitrogen, and then proceeded to answer a number of interesting (if not burning) scientific questions.

How long, for instance, does it take for the mercury in a Torricellian vacuum to vaporize ? It vaporizes at once, as the professor showed by painting the outside of a newly created vacuum bulb with a sponge dipped in liquid air, when it was seen that a tiny mirror of mercury was instantly formed on the glass. Does a low temperature make any difference to the absorption of light by a colored surface? It certainly does. Professor Dewar showed that a surface painted with red oxide of mercury, when cooled by the liquid air, changed its color from bright red to orange. Organic coloring matter changed also, but not so quickly. Had a low temperature any effect upon the conductivity of a vacuum tube? Yes; it had. All the vacuum tubes which Professor Dewar painted with liquid air at once began because the intense cold froze the vapor, which, though imperceptible and imponderable and otherwise undetectable, nevertheless was an aid to conduction. Does a low temperature increase the cohesive power of metals? It did, as Professor Dewar offered (by the proxy of his indefatigable assistant) to show by experiment to any one who waited till after the lecture. The tensile stress of iron increased at the temperature of liquid air from thirty-four tons per square inch (at ordinary temperature) to sixty-four tons, and every chute is also provided with a gate supported from the The last experiment but one of the lecture answered causes which lead to the production of sour bread.

outer end of a lever on the inner end of which is a decisively the vexed question whether metals increased weight normally holding the gate raised. The inner, their magnetic qualities at these low temperatures by end of the lever, extending into the elevator well, is showing that an iron bar magnet did so to the extent lifted by the cage to close the chute at the time that of 50 per cent. The last experiment of the lecture the car is dumped, and the load is thus retained in answered no question in particular, but it was the the chute until the car starts downward, when the source of the greatest satisfaction to the professor, and weight drops and the gate is lifted to permit the load aroused a burst of enthusiasm in his audience, which included much of fashionable and nearly all scientific London. He first liquefied in a test tube some of the air of the room, and then-a tour de force-solidified it.-Daily Graphic, London.

Cement Mortar.

There is a common superstition, which probably retains its hold upon builders, says the American Architect and Building News, solely through the profit that they find in maintaining it, but which sometimes really imposes upon laymen, to the effect that cement mortar is improved, in cold weather, by the addition of lime to it. As the mason ingenuously explains to his employer, the heat developed by the lime in slaking keeps the cement warm, and thus prevents it from freezing; and, on this theory, the advent of a frosty day is utilized by multitudes of sharp builders to load the mortar, which they have agreed to make of sand and cement only, with a quantity of lime, which saves cement, and makes the mortar easy to work, but destroys its waterproof qualities and injures its strength and hardness more or less, according to the quantity used. It is hardly necessary to say that the influence of the lime in "warming" the mortar is purely mythical. Lime mortar, without cement, is not much injured by freezing, while cement mortar is totally ruined, so that a mortar containing a large proportion of lime would be harder, after freezing and thawing, than one containing cement only; but it would gain the qualities of lime mortar only as it lost those of cement mortar.

White Dextrine.

A writer in the Wollen-Gewerbe states that an entirely white dextrine, perfectly soluble in water, is now prepared by diluting 4 pounds and $6\frac{1}{2}$ ounces nitric acid of 1.4 specific gravity with 317 quarts water in which 2,205 pounds of starch are stirred. This mass is formed into cakes, which are at first dried in the air and afterward at 176° Fahrenheit, and the cakes are then ground and the powder sifted, and heated from 212° to 230° Fahrenheit for one or one and a half hours; in external appearance, this preparation cannot be distinguished from starch flour, and is perfectly free from nitric acid. In the preparation of dextrine in the wet way, with diluted acid, it is remarked that the time at which the last of the starch has been converted into the dextrine must be carefully noted, as the continued influence of the acid causes the dextrine to become rapidly saccharose.

AN ENVELOPE FOR THE DISPLAY OF LACES, ETC. This envelope is made of paper, cardboard, or other suitable material, in a very simple and inexpensive manner. Its sides are folded over part of the back from end to end, and from the back extend ends which fold over the sides at the ends, the ends having side flaps glued to the under side of the back. Openings or pockets are thus formed at the edges of the sides and ends, so that a portion of each piece of goods held by the envelope will be exposed for examination. The improvement has been patented by Mr. Charles J. Billwiller, Nos. 31 and 33 Walker Street, New York City, and is especially designed to facilitate the display of laces, embroideries, trimmings, and other small goods, the articles being so held that they will



or out. The dumping of the car is effected by guides to resist the passage of electricity through them, on opposite sides of the elevator well, the guides curving outward toward the chute, and being clasped by shoes on opposite sides of the tilting platform. When the car and the platform are in a horizontal position the rear end of the car rests on posts on the cage, and the load is placed a little behind the center of gravity, so as to keep the car level. The car has at one end a swinging end gate engaged by a chain extending from the top of the cage, whereby the gate will be held up as the car is tilted in dumping, the gate again dropping to place as the car returns to horizontal position. r

BILLWILLER'S DISPLAY ENVELOPE.

be kept clean and in good condition, and yet permit the retailer to cut off portions as desired.

Sour Bread.

L. Briant has investigated the nature of the acids contained in sour dough, and gives the results of a number of analyses. It appears that the bulk of the acidity of sour dough is due to lactic acid, but that a certain proportion, varying from one-third to onefifth, consists of acetic acid, while in most cases the amount of butyric acid present is very small. In a other metal increased its cohesive qualities similarly. future paper the author purposes dealing with the

The Bell Telephone Company.

To an inquirer about Bell Telephone Company earnings the Boston Transcript gives the following figures:

	Net income.	Year's increase.	Per cent gain.
1885	\$1,809,996.48		
1886	1,973,350.76	\$163,354.28	9.0
1887	2,237,608.12	264.257.36	13.3
1888	2,436,463.56	198,855,44	8.9
1889	2,661,888.69	225,425.13	9.22
1890	2,869,418.35	207,529,66	7.8
1891	3,126,819.90	257,401.55	8.97
1892	3,411,679.78	284,854.88	9.11
1000		AU1,001.00	9 11

It was figured that an increase of 9 per cent in 1893 would be tantamount to earning some 19 per cent on the whole \$20,000,000 capital, although all of the new stock did not participate in all of the 1893 dividends. Here is another table of interest:

	Surplus earnings applicable to dividends.	Equals on stock per cent.
1885	\$1,809,996.48	18.09
1886	1,973,350.76	19.73
1887		20.8
1888	2,436,463.56	24.25
1889		26.72
1890	2,869,418.35	22.95
1891	3,126,819.90	20.85
1892	3.411.674.78	19.49

The following is from a recent compilation of the **Boston Herald:**

The present company was organized in May, 1880, with an authorized capital of \$10,000,000, and issued capital of \$6,500,000. This was increased to \$7,350,000 by giving a right to the National Bell Telephone Co.'s sharcholders to subscribe for \$850,000 stock at par. From that day until recently subscription privileges at par have been issued, and sundry extra and valuable rights have been given to shareholders. None of these is included here. The National Bell Telephone Company had a capital stock of \$700,000. When it concluded to reorganize as the American Bell, it sold 500 shares in its treasury for \$600 per share to meet its "immediate wants," presumably floating debt. It then gave each shareholder six shares for one and turned the property over to the new company for \$6,500,000, taking pay in stock at par. The first year ended Feb. 28, 1880, and included two months of the National Bell year. In 1884 the fiscal year was changed to the calendar year, and covered but ten months. The total dividend payments and capital at the end of each year have been :

	Dividends.	Capital.
1880-81	\$178,500	\$7,350,000
1881-82.	416,500	7,350,000
1882-83	595,000	7,350,000
1883-84	1,051,479	9,602,000
1884	1,440,315	9,602,000
1885	1,562,236	9,802,100
1886	1,568,336	9,802,100
1887	1,568,336	9,802,100
1888	1,789,878	9,962,100
1889	1,888,913	11,303,900
1890	2,213,913	12,500,000
1891	2,625,000	15,000,000
1892	2,919,080	17,500,000
1893	*3,337,500	20,000,000
Total	\$23,106,096	
Average per year	1,650,435	\$11,209,035

* Estimated.

The company began paying extra dividends in 1884. They are included above, and in detail have been: 1884, **\$**288,063; 1885, **\$**392,044; 1886, **\$**392,084; 1887, **\$**392,084; 1888, \$597,726; 1889, \$600,000; 1890, \$750,000; 1891, \$900,000; 1892, \$991,863; 1893, \$1,125,000. The average regular and extra dividend per year has been \$1,650,435. The average capital has been \$11,209,035. The average rate of dividend has been 14.72 per cent.

Nitrate Deposits in Colombia.

In the December Bulletin of the Bureau of the American Republics, Mr. C. F. Z. Caracristi, C.E., gives the following report on the nitrate beds of the Val du Par. lying between the spur mountains of the Sierra Nevada de Santa Marta, in the Department of Magdalena, Republic of Colombia, South America.

The nitrate beds of Chile and Peru have, for a number of years, been coveted as properties of vast value, and have added not only to the wealth of the opebut to that of the country in which they with the stalagmitic formations that cover the walls dustry. and floor, and in this form was much sought for in the earlier days of American civilization. It was used then, as now, in the manufacture of gunpowder, and formed quite an industry, which has since disappeared; yet in India, where labor is cheap, the collection of sedimentary "saltpeter" continues. In the same country it is also obtained in large quantities, for exportation by the evaporation of nitrogenous water collected from "seeps," after the same manner as salt is produced. The niter produced in Chile, however, differs from the sedimentary nitrate, and is known in mineralogy as "nitrotine," or soda niter, and its component parts are nitrogen pentoxide 61.891 per cent, sodium (soda) 38.109 per cent = 100 per cent. It somewhat resembles niter (saltpeter), but more readily deliquefies and burns on coals with a yellow flame.

In the district of Tarapaca, a Peruvian province now the road. The road is now in running order from occupied by Chile, it is found in the dry pampas extending over forty-five leagues. Here it is mixed with sodium bichloride (common salt), magnesium carbonate and shells of very recent origin. This nitrotine is converted into regular niter, or saltpeter, by the displacement of the sodium and the addition of the required amount of potassium. It is also found and worked in the great desert of Acatama, Chile; but in these regions it is found as an incrustation in the earth of decomposed porphyritic rock, and was doubtlessly of feldsparic and calcium origin. No shells are present, and no sign of sedimentary action is here visible. These beds have, of late years, attracted great attention, although they lie at a considerable distance from transportation. Nitrate is used largely in the industrial arts, is a splendid fertilizing medium, and is the base of nearly all known explosives, because the nitrogen pentoxide stands in mutual repulsion with all other substances. And while its atoms will readily combine with atoms of other bases, the least chemical convulsion will instantaneously bring about a separation of the two or more bases and produce explosion. It is the explosive base of gunpowder, guncotton, nitro-glycerine, americanite, giant powder, etc.

The nitrate deposits I discovered in Colombia are of a nature identical with those of Chile, and I have but little doubt that thorough exploration would show the deposits to be almost as extensive as those of that country. My own investigation showed the existence of about thirty miles square of nitrate beds, having a thickness of from one to ten feet.

The stratum carrying this niter is a bed of slaty gypsum (calcium sulphate), in which are embedded large quantities of shells (calcium carbonate), iron oxide, salt, and magnesia. The vein lies at a depth of from eight to twenty feet below the surface, and rests upon the carboniferous sandstone of the region. It is very evident that the deposit is of recent date, and that the nitrate was produced by the chemical reaction of vegetable and other substances operating on the lime in its various forms. The only visible difference between the nitrate of Colombia and Chile is that the nitrification has, in part, been produced by the phenomenal functions of the microscopic plant which is closely allied to the "bacteria" so common to the cave and Indian niter.

I would estimate the visible supply at over 7,372,800,000 tons of nitrate material, assaying from 1 to 13.50 per cent nitrate.

The carboniferous sandstone has prevented the filtration of the niter, and the gypsum has, in part, been a protection to the substance. The niter itself is of a yellowish or light brown color and is found in crustations between the slaty layers of calcium sulphate. In its purer state it is of a white color, translucent, micaceous, and arborescent, and sometimes transparent, and having a hardness of 1.96; gravity, 2.01. When crystals are found, the analysis is:

Nitrate of soda	23.90 per cent.
Chloride of soda	34.05 "
Sulphate of calcium	8.46 "
Sulphate of alamina	
Magnesia	trace.
Insoluble silica	24.68 "
Water	5.50 "
Total	100.00 **

But the average deposit, taking the vein as it comes without picking or other separation, would give the following average, which I consider very promising from a commercial standpoint:

Niter	11.406	per cent.
Calcium carbonate	32.516	46
Calcium sulphate	20.121	دد .
Silica	32.412	""
Calcium phosphate	2.500	6 E
Ferro-oxide	0.022	66
Vegetable matter and salt	1.020	46
Total	100.000	

crude state, a fertilizer of the best quality. The calcium phosphate is fossilized bone. I must also note give over 42 per cent sulphur and which would make

Santa Marta to Rio Frio, and about six miles are graded beyond Rio Frio in the direction of Rio Savilla. This leaves about thirty-five miles of road still to be built, at a cost of \$105,000, to which amount the Colombian government, according to its original contract with Senor Don Manuel J. de Mier and his successors, is to contribute about \$30,000.

It is quite obvious that the development of the nitrate industry on the Atlantic coast of South America would mean a great saving in the cost of transportation of the article to both Europe and North America, and the American farmer who has to buy fertilizers would be highly benefited by the advantages offered by the niter beds of Colombia. The reduction of the cost of fertilizer has been a question of great moment to the American farmer-so much so that in nearly all the agricultural States legislation has been enacted having in view the reduction of cost and the assurance of the purity of fertilizing compounds.

Investigation, made by State and federal authorities. has proved the fact beyond dispute that the agricultural possibilities of certain localities of the United States are largely restricted and governed by the cost and power of the fertilizer offered forsale. It is, therefore, obvious that the reduction of the cost of niter and other alien fertilizing substances would redound to the great advantage of the American farmer, with whom the question of cheap fertilizer is one of too much importance to be overestimated.

The cost of producing and delivering one ton of caliche, or crude niter, at Pueblo Viejio would be about \$2.50, and the cost of shipment to the United States would be \$3.80, delivered in New York, making a total of \$6.30. This estimate is on the material in its crude state, and as it would take eleven tons of caliche to produce one ton of nitrate of soda, at a cost of \$69.30, and the present market value would be only \$50, it is evident that it would be necessary to separate the niter before shipping. I estimate the cost of separation, mining, and transportation to New York City at from \$8.31 to \$11 per ton. Then, besides the nitrate of sodium, we would have calcium phosphate (land plaster), an excellent fertilizer, 4,600 pounds, calcium phosphate 550 pounds, sodium bichloride (common salt), and vegetable matter 220 pounds. The above would be the residuum or by-products remaining after the refining process of the caliche has been gone through with. Or, to put it more plainly, we would have 7,370 pounds of fertilizing substances out of a possible 22,000 pounds, and of the residuum remaining, one-half would be calcium carbonate (ordinary lime).

In conclusion, I beg to state that I have every reason to believe that franchises or grants will be given by the Colombian government to any responsible individual or corporation that might guarantee to work the nitrate beds of that country.

Helping Street Cars up Hill.

A trolley line in Oil City, Penn., climbs a grade of nearly 14 per cent for almost 1,000 feet in one part of town. John B. Smithman, president of the company operating this line, has invented and patented a scheme for helping the cars up and down this slope. It consists of a counterpoise, lowered in a well, and connected by cable with the cars. A well is now being bored for this purpose, and is nearly finished. It is sunk from the top of the hill, and will go to a depth of 1,000 feet. The "balance," as it is called, will be a cylindrical iron bar, $4\frac{3}{4}$ inches in diameter and 40 feet long. A single car, Mr. Smithman estimates, weighs about seven tons, but on a 14 per cent grade it would require only one ton of vertical pull in the well to counterbalance it; and that is the weight so employed. A cable, running over a big, stout pulley, will connect the counterpoise with the car; and only one car at a time will be helped either up or down the hill; and, obviously, after an up trip the next one must be a down The above shows plainly that the deposit is, in its trip. The cable is attached to a "grip" on the car, and will run in a conduit. Mr. Smithman has invented a "differential" drum, which should render a hole half that large quantities of iron pyrites are to be found in as deep as the grade is long available, but he will not the archaic formation of the adjacent mountain, which use it in this first experiment. He has also thought of having a series of holes and weights where a gra

found. "Potassium niter" is found in caves mixed the manufacture of fertilizer in the region a great in- very long.-N. Y. Tribune.

The manufacture of nitric acid could also be made an industry of importance and profit.

Coating Aluminum.

At a recent meeting of the Berlin Physical Society The deposits lie at a distance of about sixty-five miles Professor Neesen demonstrated a method of coating from the city of San Juan de la Cienaga and are, in aluminum with other metals. This consists in dipping part, on the waters of San Sebastian River, which flows the aluminum in a solution of caustic potash or soda, into the great sea level lake of "Cienaga Grande." or of hydrochloric acid, until bubbles of gas make Navigating communication could be established with their appearance on its surface, whereupon it is the nitrate beds $b\bar{y}$ conducting the waters of the dipped into a solution of corrosive sublimate to amal-Aracataca River into the San Sebastian. This work gamate its surface. After a second dipping into would cost not in excess of \$5,000, as a canyon already caustic potash until bubbles of gas are evolved, the exists connecting the two rivers. By this work a metal is placed in a solution of salt of the desired draught of about six feet could be carried from the falls metal. A film of the latter is rapidly formed, and is so firmly adherent that, in the case of silver, gold, or of San Sebastian River to Pueblo Viejio, from which point navigation communications already exist to copper, the plate can be rolled out or polished. When Barranquilla and Santa Marta. When the Santa coating with gold or copper, it is well to first apply a Marta Railroad shall be completed to the village of layer of silver. When thus treated the aluminum may Fundacion, the niter beds will be only half a mile from be soldered with ordinary zinc solder.

FULTON'S TORPEDO.

The torpedo. that formidable modern maritime weapon of war, did not meet with great success at its advent, and it required more than sixty years, during which it was completely abandoned, for people to take it into their heads to see in it one of the most efficient means of attack, and especially of defense, against a naval force. Its inventor was not this person or that person, but simply Robert Fulton, who also invented the first submarine boats, and it is harsh to state that for the brig and the torpedoes were thrown into the of the mechanism and use of the torpedoes with the sole glory that surrounds his memory comes to him water. The current of the tide carried them unim- him and gave him an account of the experiment

from the applicationof steam to navigation—an application that he merely improved and in which he had been anticipated by the Marquis of Jouffroy in 1783.

I04

Fulton wrote a very remarkable book, in which he describes his apparatus and makes judicious remarks upon the advantages that might be dethererived from from a military, politi-



Fig. 1.-TORPEDO AT ANCHOR AND PLACED IN SUCH A WAY AS TO BLOW UP A SHIP COMING INTO CONTACT WITH IT. A, inclination under influence of current. B, projection in direction of length.

the eminent mechanician to speak for himself:

In order to convince Mr. Pitt and Lord Melville six feet through the effect of the explosion. It broke that a ship can be destroyed by the explosion of a torin two in the middle and the two parts sank. In the pedo under its bottom, the Dorothea, a strongly conspace of twenty seconds there was nothing more to be structed Danish brig of 200 tons burden, was, on the seen of the vessel except a few debris that were floating here and there. 14th of October, 1805, anchored in the roadstead of Walmer, near Deal, at a mile from Walmer Castle, which was then the residence of Mr. Pitt. Fulton adds:

"There were put at my disposal and under my orders two longboats with a crew of eight men, commanded by Lieutenant Robinson. I prepared two

pended them in such a way that they sunk to a depth of fifteen feet in the water. They were afterward made fast separately to the two ends of a slender rope 80 feet in length. The brig drew 12 feet of water.

"Each boat, with a torpedo in its stern, started from the shore at about a mile from the place where the brig lay and in front of the vessel. The rope that connected the two torpedoes was taut, and the boats were thus situated at 80 feet from each other. They then approached in such a way that one of them kept to the starboard and the other to the port side of the brig.

"As soon as the rope had passed beneath the buoy of the brig,* the torpedoes were thrown into the water and were soon carried along by the tide until the rope touched the cable of the brig's anchor, while the current carried the torpedoes under the

"This experiment, thus re-

when it was announced that the experiment was post-its means of defense, these high English personages poned until the next day (the 15th), at five o'clock in the afternoon, because pressing business had called Mr. Pitt and Lord Melville to London.

"On the 15th Admiral Holloway, Baron Sidney Smith, Captains Owen and Kingston, Colonel Congreve and the majority of the officers of the fleet, under the command of Lord Keath, were present.

"At forty minutes past four, the longboats stood

know perfectly the effects and have preserved an impression of the results that it has been possible to reach."

Fulton, speaking in a note of an interview that he had with Count de Saint Vincent, gives us an account of a jocose remark that the latter made :

"In the first place, in the morning, the count was very communicative. I entered into all the details made with the

Dorothea. "After a few moments of reflection, the count said to me: 'Pitt is the biggest fool that ever existed to encourage a species of warfare useless to those who are the masters of the sea, and which, if it succeeds, will deprive them of this superiority."

After succeeding, at least partially, in alarming the British power, it only remain-

Fig. 2.- A TORPEDO BOAT PREPARED FOR AN ATTACK.

cal and humanitarian point of view. But let us allow peded under the keel of the brig which, at the ex-led to Fulton to try to reassure his compatriots by showpiration of eighteen minutes, appeared to rise about ing them the efficiency of his new weapon. Consequently, in August, 1807, he rebegan his experiment in the port of New York. There were two fruitless experiments. One of them failed in consequence of a false maneuver and the other through the defective position of the fire locks in which the pr ming powder was placed. But, the third time, the experiment fully succeeded, and the vessel, which was this time again a 200 ton brig, was blown up under the same conditions that the Dorothea had been. In the following chapters, Fulton explains the methods of employing his

> the torpedo at anchor, placed at the entrance to roadsteads and ports in such a way as to blow up ships coming into contact with it (Fig. 1).

> We shall not reproduce the description of this weapon, which is of no interest to us henceforth; but, in studying its working, we perceive that we are here in presence of the first blockade torpedoes, that is to say, one of the submarine defenses now rightly considered as the most formidable, or at least the most efficient and the most reliable, as physicians say of a remedy whose effect is certain.

> There is nothing, up to the possibility of causing the torpedoes to return to the surface, that did not attract Fulton's attention and receive a satisfactory solution. The following, in fact, is what he says:

'In order to render it easy to remove the torpedoes from the channel. I have devised a very simple mechanism that will hold them under water at algiven depth and for any number of days whatever. The movement of it can be regulated for a day, a week, a month, or a year, and, at the appointed time, the torpedoes will emerge. At the same instant each will automatically put its lever at rest, so that it will no longer be able to explode. And it will therefore be possible to handle them with safety. Having no time to have this improvement engraved, I am having a model of it made that I shall present to Congress, and which will facilitate the understanding of it." Finally, Fulton finishes this

my country, that this experiment was made in England, and in the presence of more than a hundred reempty torpedoes having a specific gravity of only two spectable witnesses and brave officers of the royal torpedoes with advantage and with the least risk to or three pounds more than that of salt water, and sus navy, for, if Congress adopts the torpedo as a part of the assailants. The first of these chapters treats of A 180

After congratulating himself over the result obtained,

"I consider it a fortunate circumstance for America.



peated several times, taught the men in the boats how it was necessary to go to work, and proved to me indubitably that when the torpedoes are properly placed with respect to the current of the tide, they will go of themselves under the ship.

"I then filled one of the torpedoes with 180 pounds of powder and timed it for eighteen minutes."

Fulton melancholily adds: "Everything was ready,

* In former times, a buoy was always stationed over the anchor, to the flukes of which it was attached by a rope.

+The torpedo was wound up by means of a clockwork movement,



Fig. 3.-BLOWING UP OF THE BRIG DOROTHEA WITH A FULTON TORPEDO.

chapter with some very judicious observations, not a word of which is to be changed, even to-day.

Upon considering this subject under all its relations. I remain persuaded that it would be impossible for any enemy whatever to enter a port in which torpedoes are used without exposing himself to a danger that all the courage possible could neither avoid nor surmount. Prudence and reason would make him abandon such an undertaking. It is even proba-

ble that, knowing us to be thus prepared, he would never attempt it, or that, if he did, the catastrophe of one vessel would suffice to guarantee us in the future against new hostilities."

In the following chapter Fulton describes a system of harpoon thrown by means of a small cannon or a blunderbuss, to which the torpedo is attached by a rope of variable length (Fig. 2).

It is unnecessary to say that this system is not utilizable to-day with our vessels all armored with iron; so we shall not dwell upon it. We cannot terminate this short retrospective review without citing the proposition that Fulton made to the government of his country and which figures in his book. We give it in order

to show that this ingenious inventor was also a patriot and a man of noble heart:

"Moreover, in proposing this new plan of attack and defense, I do not pretend to abandon to others the finest cruiser of her class. The Montgomery is known care of executing it. If it is adopted in all its extent, with the proper number of men skilled in this maneuver, and if it is judged proper to put these men under my orders, and an enemy then enters our ports, I will satisfy my fellow citizens with the courage necessary to assure the success of the operation.

"But in proposing this, I wish to be well understood, in order that I may not be accused of aiming at a situation or command in a public station.

"My views are constantly directed toward an independence too dear to my feelings to allow me to desire to sacrifice them to ideas of any ambition whatever.

"I see here only a useful and, at the same time, hon-

that I can serve my country without any other motive than that of discharging the debt of a good citizen."

At our epoch, when torpedoes are adopted by all navies, it has appeared to us of interest to recall the labors of Fulton.-La Nature.

THE NEW UNITED STATES CRUISER MONTGOMERY.

orable occupation, and it is to me a happiness to think vertical, three cylinder, triple expansion engines drive the two four-bladed propellers. The indicated horse power is 5,400. A protective deck varying from 0.43 to 0.3 inch thick is provided. The battery is composed of eight 5-inch guns and two 6-inch rapid-fire guns. There are also three torpedo-launching outfits and a secondary battery composed of six 6 pounders, two 1-pounders and two machine guns. For our illustra-The Montgomery, a sister ship of the Detroit, tion of the Montgomery we are indebted to Marine

and Railway.

THE CRIMINAL COURT BUILDING OF NEW YORK.

For many years the criminal courts of New York and the Grand Jury have been housed in a miserable fire-trap which should have been condemned long ago as unsanitary. In this rickety old building, ill-lighted, worse ventilated and reeking with sewer gas, other city offices were quartered, so that the space devoted to the criminal courts was totally inadequate, while the District Attorney has been obliged to occupy rented offices. At length the city fathers awoke from their lethargy, and on October 25, 1890, the corner stone was laid of a large and imposing edifice. The site is an historic one, being part of



THE NEW UNITED STATES CRUISER MONTGOMERY.

entire course, thus demonstrating that she was the as a partially protected cruiser, a class of vessels which are now considered as very important adjuncts to the armored cruisers. After the tidal correction was made the speed was found to be 19 knots, so that the contractors (the Columbian Iron Works) will receive \$200,000 in addition to the contract price, which was \$612,500. The test was conducted with a steam pressure of 166 pounds, and the average number of revolutions was 180. The engines worked without any mishap, but the steering device was injured, or the speed would have been even greater.

The Montgomery is 257 feet long; 37 feet wide; Two draught, 14½ feet; displacement, 2,000 tons.

which we illustrated in our issue of September 2, 1893, what was known in; colonial times as "The Comsucceeded in making 18.85 knots per hour over the mons." The building occupies the block bounded by Center, Elm, White and Franklin Streets, and is connected with the city prison, usually called the "Tombs," by a bridge, which will probably be known as a "Bridge of Sighs." This bridge, which crosses Franklin Street, will enable accused persons to pass directly from the prison to the courts without being exposed to the gaze of the curious. The new building is 115 feet in height, and measures 188 by 190 feet, and in its plan allowance has been made for the widening of Elm Street.

The style adopted by the architects, Messrs. Thorn, Wilson & Schaarschmidt, is a modernized Renaissance, and the effect of the exterior is imposing. The edifice is constructed of light red pressed brick with trimmings of terra cotta and Belleville stone, and the





THE NEW CRIMINAL COURT BUILDING, NEW YORK.

© 1894 SCIENTIFIC AMERICAN, INC

to the Street Cleaning Department and the Bureau of of the annoyance by ordinary means, directs its sting Contagious Diseases. On the main floor is the Court upon the point affected with the intention, not of killof Oyer and Terminer, Court of Special Sessions and a ing itself, but rather of destroying the cause of its police court. On the first mezzanine story are various offices connected with the court. On the second floor are the rooms for the Court of General Sessions, judges' rooms, etc. On the second mezzanine are the executive offices of the Street Cleaning Department, the Grand Jury room, Coroners' Court, District Attorney's offices, etc. The fourth story is devoted to the Board of Health and the Excise Board. The amount the brain or seriously lacerate the great dorsal blood which the city has been paying for rented offices will now be saved. The building is all finished in natural wood and the lighting, heating and ventilation systems are as perfect as money can make them. Six elevators render the various offices easily accessible. Some of the principal court rooms are to be decorated at the expense of the Municipal Art Society by the best American mural painters.

It is customary for all important courts to be approached from an impressive vestibule or ante-room, to emphasize the dignity of the law, as in the Salle de Pas-Perdus, in the Palais de Justice, at Paris, and the arrangement is preserved here. From a large marble vestibule, the visitor enters the great rotunda, which we illustrate. This rotunda is sixty feet square, and is built of marble, elaborately sculptured in delicate figures and tracery. On each side grand stairways of iron and marble add to the imposing effect. The newel posts will be surmounted by elegant bronze electroliers. This huge rotunda is covered by an ornamental glass roof. The whole rotunda is treated with excellent taste, and it is one of the finest rooms in America, and compares favorably with the grand vestibule of the Paris Opera House, which it sure, and is, therefore, an acquired character. As such somewhat resembles, although, of course. the rotunda lacks much of the fine work which has been lavished on the Opera House. The entire building, with furniture, will have cost about \$1,500,000, and the disposal of this money reflects credit alike upon the architect and contractors, and New York may now well be proud of this fine edifice.

Natural History Notes.

Do Scorpions Commit Suicide ?- The question as to whether scorpions commit suicide or not by directing their sting against their own body when they are placed within a circle of fire or are tortured in some other manner by this element is one that has given rise to the most animated discussions. The opinion that they do is probably held by many persons at present. But Mr. Bourne's experiments on some Madras species have demonstrated : (1) that the poison has no effect upon the scorpion that receives it, and (2) that these animals are easily and quickly killed by a moderate heat (50° C.) Besides, when they are discommoded by too bot an atmosphere, or, according to Lankester, by the vapor of chloroform, scorpions have the habit of were exposed, it was found that the minimum temperaagitating their tail in the air and of darting their sting forward above the head as if to strike some invisible enemy. If, by means of a lens, the solar rays are concentrated upon a scorpion's back the animal is observ ed to immediately rase its tail and endeavor to remove the cause of excitation therewth. So the true explanation of some, at least, of the alleged cases of suicide among scorpions would appear to be this: The animals have really been killed by the heat to which they were exposed, and the observers have erroneously believed ture for the latter function, in the case of the wheat that the strokes of the tail were designed to put an end to the animal's sufferings.

My own experiments, says Mr. R. I. Pocock, are whol y in favor of this conclusion. Upon placing a speciment of Euscorpius in a corked test tube and holding the latter over a slow fire, I have found that fall in the respiration curve when the optimum temas soon as the temperature of the air in the tube begins to rise the animal gives signs of great distress and death. beats the space for some seconds in brandishing its tail. and afterward falls into a state of insensibility. At of carbonic acid formed in the normal and intra-molethis moment the glass of the tube was, nevertheless, but slightly warm to the hand. Taken from the tube and placed near an open window, the animal rapidly revived; but, upon a repetition of the experiment for a third time it died. It never tried to sting itself. I have made also some experiments upon Euscorpius present investigations have also supplied fresh conand Parabuthus in concentrating the solar rays upon firmation of the fact that, by the withdrawal of oxygen, them by means of lenses and in putting mustard upon production of carbonic acid at once sinks in amount, the membrane between the plates of the back. In but remains constant for a long time at the lower level, both genera. I have witnessed tentatives made to re- and immediately rises again to the original amount move the cause of irritation by scratching the place affected with the point of the tail, but great precautions were always taken not to sting themselves. It appears, however, that scorpions have been seen to cal relation between the normal and intra-molecular sting themselves under similar circumstances. One observer mentions, even, in the case of a scorpion of the Indies, that blood issued from the wound made by the sting—a detail that strengthens the probability of the accuracy of the observation But, a priori, it is not periments in pedigree moth breeding, Mr. Merrifield probable that the scorpion intended to kill itself. It has demonstrated the possibility of producing artiis not impossible that a blow directed at hazard against ficially from a single brood of a moth, subject to seaan invisible enemy accidentally reached its author, or sonal dimorphism, four distinct "temperature" variethat, in the case of localized irritation, as happens with ties, viz.: summer markings with summer coloring. The alkalinity of a soap may be nicely gauged by this the use of a lens or the application of acids, whisky, or summer markings with an approach to spring coloring, test.

pain.

Finally, it may be conceived that the cerebral faculties are deranged by the torture and the approach of death, and that the scorpion, no longer recognizing its own body by the sense of touch, stings it as he would sting any other object within its reach. A blow thus directed in one way or another may chance to pierce vessel and thus cause death independently of the action of fire.

So then, although it is admitted that scorpions sometimes kill themselves, our verdict should be, it seems, accidental suicide, or suicide through lesion of the brain.

Inheritance of Acquired Characters .- Owing to their coiling, the shells of Ammonoidea and Nautiloidea have furnished biologists with much evidence bearing on theories of evolution, and now Professor A. Hyatt has discovered yet another point, which, he claims, proves that acquired characters have been inherited. Coiled Nautiloidea have, as every one admits, been gradually derived from straight forms, such as Orthoceras. The cross section of an Orthoceran, or even of a slightly curved Cyrtoceran, or loosely coiled form, is circular or elliptical, but the section of a close-coiled form like Nautilus, shows an impression of that part which comes in contact with the preceding whorl, so that there is a re-entrant curve. In old age, however, when the shells again uncoil, this impressed zone disappears, and the section becomes circular again-a fact which seems to show that the feature is directly due to pres it is not found in the early, uncoiled stages of those Nautiloidea that are close coiled in the adult; at least it is not so found in any of the Silurian or Devonian species. But at last, in the Carboniferous, Professor Hyatt has found a species that seems to prove his point; for, in Coloceras globa/um, which is in many respects a highly specialized species, seven specimens examined have shown this impressed zone existing while the shell was still in the partly curved or cyrtoceran stage. The same early appearance of the impressed zone is likewise seen in numerous Jurassic, Cretaceous, and Tertiary species, including the living Natilus pom *pilius.* This, then, seems due to the inheritance of a character in successively earlier stages of individual development, according to a well known law; while the character so inherited is believed to be an acquired one.

The Respiration of Plants.-Mr. Anton Amm gives in Pringsheim's Jahrbucher (vol xxv., p. 1) an account of some investigations on the intra-molecular respiration of plants. With regard to the relations between the amount of carbonic acid produced in this function and the degree of temperature to which the plants ture, as in the case of normal respiration, was below freezing point, since at 0° C. a significant amount of the gas was given off. As the temperature rose, intramolecular respiration also gradually increased; but this increase was not proportional to the rise of temperature. In both wheat and lupine seedlings the optimum was reached at 40° C., which coincides with the optimum for the normal process. On the other hand, while there is, doubtless, a maximum temperaplant and Lupinus luteus somewhere about 45° C. there can, properly speaking, be no such point in the intra-molecular, process, since, in absence of oxygen, seedlings cannot stand temperatures between 40° and 45° C. without prejudice to their vitality, and the rapid perature is passed is due to the commencement of

The author finds the relation between the amounts cular processes to vary with the temperature.

The relation between the amounts of carbonic acid are not misleading, water on its surface does not freeze gas formed in the two processes varies in different except in the region of the poles. If earth were viewed stages of development of one and the same plant, the from Mars, it is plain that the polar white caps would fraction increasing with increasing development. The be much larger than those of Mars are. when oxygen is again supplied. Finally, the results show that the different organs of a plant, e. g., flowers and leaves, give an almost identirespiration, while the organs of different species show quite a different relation. Effect of Temperature on the Coloring of Lepidoptera.-By careful and long continued temperature ex-

iron roof is covered with tiles. The basement is devoted mustard, the scorpion, not succeeding in ridding itself spring markings with summer coloring, and spring markings with spring coloring. The conclusions reached as a result of this series of experiments are that the coloring and markings of the moth are affected by the temperature to which the pupa is exposed, 'the marking being chiefly produced by long continued exposure; that the coloring is effected chiefly during the stage be fore the coloring of the perfect insect begins to show that a low temperature during this stage causes darkening, a high temperature producing the opposite effect, a difference between 80° and 57° being sufficient to produce the extreme variation in darkness caused by temperature; a further lowering of temperature having no further effect: that nearly the full effect in coloring may be produced by a range of temperature of from 76° or 80° to 65° in *autmnaria*, and from 73° to 60° in *illustraria*; that dryness or moisture during the entire pupal period has no appreciable effect on the coloring of the adult.

A general conclusion which the author ventures to suggest (provided we accept the theory of Professor Weismann, that existing forms of North American and European Lepidoptera have come down from a glacial period) is that "icing" the pupa causes the insect to revert to its earlier form, and that experiments of the nature here recorded might be of materal assistance in tracing the evolution of the markings on the wings of the most highly developed forms.

Mr. Merrifield states that it is possible to cause either the summer or winter form to take on the coloring of the other, and produce from moths from the summer pupa specimens that resemble those from the winter pupa, but not vice versa.

Mars.

The following questions and answers are from a recent number of Popular Astronomy:

Why do astronomers think that the white spots about the poles of the planet Mars are snow or ice ? G. B. D.

Answer.-In connection with this question it was noted by the querist that the telescope shows a change in size of these white patches during the seasons of winter and summer on the planet Mars. This is the main reason why it is thought that the patches consist of ice and snow. It might be added that some good observers have seen indications on the surface of the planet that might be explained by supposing that a fall of snow had covered a considerable area. No astronomer would feel himself justified from his observations or what he knows of the surface of the planet, in assigning snow or ice as the cause of these white spots. Other plausible reasons could be assigned. Some observers have intimated that clouds in the planet's atmosphere might produce the appearance observed. This explanation does not seem as satisfactory as the former one.

From appearance in observation the atmosphere on Mars contains less clouds than that of the earth. If capacity for heat depends on the vapor in the atmosphere, how is it that the temperature of the planet's surface seems so high compared to that of the earth, notwithstanding its greater distance from the sun?

G, B. D.

Answer.-We are not aware that observers are agreed, or generally think, that clouds are less No the atmosphere of Mars than in our own. That would be an impossible thing to determine by observation at the distance of Mars, if we remember that our clouds do not run probably much above two miles in height on the average, except, as it might be inferred, that certain changes in color of surface markings are due to the presence of clouds. It is probable that the density of the atmosphere of Mars is less than that of the earth; the spectroscope also indicates that there is watery vapor in the atmosphere of Mars. From all that is known, or may be fairly inferred by analogy, we would say the temperature of Mars ought to be much lower than that of earth. But if appearances

Astronomers do not give any reason for this unexpected difference in surface temperature on the planets. There is no known explanation.

A New Test Paper.

A very sensitive test paper may be easily prepared from mallow flowers (alva). The violet petals only are used, rejecting the green part of the flower. Fifty petals being infused in 100 c. c. of cold water, a faint violet solution is obtained. This liquid becomes

Ponceau red	on additio	on of	mineral acid.
Wine red	"	**	organic acid.
Violet red	**	**	acid salts.
Greenish blue	**	""	alkaline salts.
Green	"	**	alkaline carbonates.
Green (yellowish)	"	"	soaps.
Yellow	"	44	potash, eoda or ammonia

There were many curious historical relics in the Government building, but a number of these could than chilled cast iron shares. The side plates of the not be thoroughly enjoyed without an understanding of the story connected with them. The famous torch of Israel Putnam attracted many visitors. Anything connected with General Putnam, who is one of the most picturesque figures in American history, must always be of interest to Americans. The torch was made of birch bark, rolled into the form of a cylinder, about one and one-half inches in diameter. The story connected with the torch is as follows: In the year



MILES STANDISH'S PIPE,

1739 Putnam removed from Salem to Pomfret, an inland Connecticut town, forty miles east of Hartford. Our hero applied himself to farming in the new country with the same vigor he afterward displayed in his warlike exploits. One night seventy-five sheep and goats were destroyed by wolves, or rather one she wolf, which had infested the vicinity for years. At last this wolf became such an intolerable nuisance that Putnam and five neighbors agreed to pursue the animal until caught. At last they tracked the wolf to her den. The people soon collected with dogs, guns, straw, fire and sulphur, and every attempt was made to force her from the small cave or den. Neither smoking straw nor burning sulphur had any effect on the animal. Mr. Putnam proposed to his negro man to enter, but the negro declined. Angered at this, Putnam stripped off several pieces of birch bark which had become rather dry and rolled them up to form a torch; lighting this, he proceeded through the long and tortuous passages. After groping around for some time he came in sight of the wolf, who growled. The friends of Putnam had fastened a rope to his leg, so that he could be drawn out, if he should be in danger. When the wolf growled they pulled the rope, and he was dragged out with many bruises. He loaded a gun with buckshot and descended again. This time the wolf was shot, and he was pulled out again, to the detriment of his clothes and skin. After being refreshed (history sayeth not how),

he descended again, and, perceiving that the wolf was really dead, he kicked the rope, and in a moment Putnam and the wolf appeared, to the exultation of the assembled people. The torch was ever after preserved as a memento of the occasion.

Another curious and historical relic of an earlier date which was also exhibited in the Government building was the pipe of Miles Standish. This pipe is carefully preserved in a wooden case. Miles Standish was born in Lancashire, England, in 1584, and died in Duxbury, Mass., in 1656. He was chosen captain of the Pilgrims, although he was not a member of their church. The temper of Miles Standish was none of the sweetest but he made himself very useful to the colonists by his courage and determination. As agent for the colony he visited England in 1625, and for the remainder of his life he occupied the

times as long as ordinary carbon steel pins. Manganese steel plowshares wear six or seven times longer Blake ore crusher made of hard carbon steel are worn out in two months, whereas when made of manganese steel only one-fourth of an inch was worn away in ten and a half months. In respect to railway wheels, it is believed that chilled cast iron wheels run about one-third the mileage of manganese steel wheels before the first turning; and, again, the average mileage of the latter is 51 per cent greater than that of the composite or steel-tired wheel.

Drainage of the Valley of Mexico.

According to the British consul at Mexico, the great work of draining the valley of Mexico, comprising over thirty miles of canal and six miles of tunnel, is within measurable distance of completion. On May 16, 1893, 63.19 per cent in the grand canal had been excavated. When finished this canal will be 29% miles long. Of the tunnel 70.63 per cent had been completed, and of the remainder 983 lineal yards of heading-perhaps the most troublesome part of the work-had been done. The total cost of the canal and tunnel, from the time when the committee of management took charge of the work in 1886 to last May, has been over \$7,000,000. Though a good deal of money had been expended, mostly in preliminary work and surveying, very little of the canal and tunnel had been constructed, so that the foregoing measurements may be fairly taken to represent the work done for the given amounts. The cost of the work has been heavier than was expected. When the contract for constructing the canal was let to Messrs. Pearson & Son in 1889, the cost was estimated at about \$5,000,000. A sum of \$3,800,000 has been spent, and about \$2,300,000 more will be required to complete it. Owing to the unexpected amount of water met with in working the tunnel, the cost per lineal yard has been much in excess of the contract price. As the water is completely dominated along the whole line of the tunnel, and all the ventilating shafts are finished and equipped, it is probable that the estimate for finishing the work, which is based on the average cost per yard, will be found to be within the mark.

THE JEWFISH.

The jewfish abounds on both the coasts of Florida and in tropical seas. The jewfish is frequently found in the deep holes and channels in the salt water inlets. The specimen we illustrate weighed about three hundred and fifty pounds, and was captured near Tampa Bay, Florida, by Mr. H. Bomford. The huge fish after being harpooned twice and wounded in three places on the head with a hatchet, lived two days, and was finally butchered and sold. It required theservices insure the life of the tree. Not one in twenty propof three men to land the fish, and they worked an erly treated in this way ever perishes in removal.



Removing Evergreen Trees.

There are many localities, says the Country Gentleman, where a natural growth of evergreen trees in the borders of woods and the margins of swamps affords opportunities for procuring pines and cedars. Rows of suitable size and only a few feet high might be transplanted for an occasional ornament of the home of the farmer, or for shielding the cattle yards in winter. The difficulty is that most farmers are not aware that they can be removed with safety. They have witnessed some attempts, and the result, so far as they have observed, is dead trees. They suppose



PUTNAM'S TORCH.

the work to be exceedingly difficult or expensive. There is no doubt that much needless labor is expended in the unnecessary attempts which have been made, and what has been published on the subject has not greatly helped the matter. An excellent work on forest trees, and one of the best that has been published in the country, gives the following directions for transplanting: "In planting trees that are not small, the roots should be extended on all sides to their full length. Some advise removing large evergreens with a ball of frozen earth around the roots, and the roots are almost uniformly cut short." The writer appears not to have been aware that the length of the roots of nearly all trees is at least as great as their height, and if those which he describes as not small are only 12 feet high, then the roots extending 12 feet on each side "to their full length" would occupy a circle 24 feet in diameter-which would obviously be quite impracticable. We have found the practice of cutting a ball of earth, or rather a flat mass, and conveying it with the tree, even if the roots are cut much shorter than would seem necessary-we have found this practice much the safest and surest in removing trees from their native localities. If the mass of earth is large enough to hold the tree upright when set on the surface of the ground, it is safe to

These remarks do not apply to nursery trees. The work may be done any time of year.

A single instance will serve to illustrate the matter. Two neighbors, who lived 12 miles from a fine locality of handsome white pines, went to procure a wagon load each for ornamenting their grounds. One of them took up six or eight trees with a good mass of earth on the roots. The other, despising such care, tore out his 50 trees with denuded roots. These all died, the others all lived.

It is not necessary to do the work in winter with "frozen balls." For small trees from 3 or 4 to 7 or 8 feet high, the spade may do all the work with a tough or matted soil





THE JEWFISH.

Enriching of Skim Milk.

This invention relates to a preparation of oil ("artificial cream") which may be readily and permanent-

position of magistrate. The colonial relics in some of | hour and a half to accomplish it. Specimens of jewfish | ly incorporated with any liquid, and is intended to be the State buildings were specially interesting and have been captured which weighed over five hundred employed chiefly for enriching skim milk, and render valuable pounds. It is said that even the largest jewfishes are it available as cattle food. The preparation is made by simply mechanically emulsifying any suitable oil good eating, the Cubans considering them a great deli-Manganese Steel. cacy. Some of the stories related of the strength of with a solution of glue or gelatin, and finally diluting Manganese steel, containing about 43 per cent of with water to any desired consistency. To 1 kilo of oil the jewfish are very remarkable, and it is said that about 50 grammes of glue may be used. "Artificial manganese and 1 per cent of carbon. H. M. Howe says boats have been towed out to sea by this fish. The that the most important single use for manganese steel jewfish will often break hooks and lines which are cream" keeps well, and may be mixed with any liquid by simply stirring it in. It separates again only very is for the pins which hold the links of dredgers of the strong enough to capture a good sized shark. Mullet elevator or bucket type. As they resist the abrasion bait is usually used in catching the jewfish. This fish slowly, and, in so doing, rises to the surface exactly caused by the sand and grit between them and the frequently floats on the surface of the water, apparlike natural cream, and it suffices to stir the liquid to links in which they turn, they last from six to eight ently asleep, and is sometimes shot instead of being obtain as perfect a mixture as before. -G. Dierking.

RECENTLY PATENTED INVENTIONS. Engineering.

DITCHING MACHINE. - George M. Pilcher, Logansport, Ind. This machine has a swinging boom, a driving rod operated by cable mechanism and movable converging shovels working in guides at the lower end of the driving rod, to force the shovels downward and together, the machine having an attachment adapted to break up frozen ground and rock. The machine is adapted, as it is moved along, to rapidly and economically excavate a smooth wall ditch, the carriage being provided with a boiler and engine of any suitable type, and the shovels being raised and lowered by suita ble hoisting mechanism.

Railway Appliances.

HAND COUPLING DEVICE .- William E. Burriss, Kansas City, Mo. The extensive use of the old style link and pin coupling, notwithstanding the many improvements made, has led the inventor to devise this device, which consists of a spring-controlled extension rod, to be attached to the arm, and which when not in use will be concealed beneath the coat sleeve, but which may be readily elongated and held in extended position to guide a link when cars are being coupled, obviating the necessity of trainmen going between the cars for this purpose. The device is of simple construction and inexpensive, and has received the in dorsement of prominent railway officials

SWITCH OPERATING DEVICE -Handley P. Cogswell, Brooklyn, N. Y. The switch rail is, ac cording to this invention, connected with a switch lever located about centrally of the track, and adapted to be operated by shoes connected with and extending be neath the car. The improvement is especially applicable to street cars, enabling a switch to be readily opened or closed from a moving car.

RAILROAD TIE.-John C. Lee, Beaver, Texas. This is a metallic tie having on itsends ele vated track supports, each having dovetailed recesses to which are fitted jaws, the jaws as well as the sup port being bound by a bolt upon the foot and web of the rail. The rail is thus forced into firm contact with the tie, and the latter is prevented from tilting on its foun dation. The bottom of the tie is transversely ribbed under the rail seat to prevent lateral movement.

Electrical.

ARC LAMP.-Manuel R. Gutierrez and Milton T. Thompson, Jalapa, Mexico. The carbons of this lamp are arranged on pivotal supports, so that they are held at varying angles while being consumed, the arrangement being such that there will be nothing to intercept the rays of light from falling directly below the lamp, no portion of the carbon supports being below the arc formed. The lamp occupies only a small space, and is light and easy to handle.

AUTOMATIC CIRCUIT CLOSER.-Henry Lewers, Carson City, Nev. A simple and effective de-vice for firealarm circuits is provided by this invention. A tube of insulating material permanently closed at one end contains a spring to which is fitted a follower, while a stopper of insulating material fitted to the open end of the tube carries two electrical contact pieces, there being a circuit-closing pin in the central bore of the stopper, and a cap with fusible or explosive material for holding the contact plug away from the contact pieces. The device is actuated to give an alarm when heated above a certain temperature.

Mechanical.

LET-OFF MECHANISM FOR LOOMS. Jeremiah C. Bill, Willimantic, Conn. Combined with a pivoted counterbalanced arm over which the warp threads pass is a pivoted sliding cam connected with and rocked on its axis from the arm, a friction wheel loose on the axis of the cam being moved laterally by the cam and geared to the warp beam, while a power-driven friction wheel also on the axis is engaged by the other friction wheel when the cam is rocked from the counterbalanced arm. The invention is an improvement on a former patented invention of the same inventor, the device being of simple construction, with but few parts and not liable to get out of order, although very sensitive and automatic in operation.

COMPENSATED PENDULUM 'MOTOR.-John M. Cayce, Nashville, Tenn. According to this improvement two aligned shafts are arranged coincidently with the fulcrum of a tilting frame, and provided one with a weighted pendulum and the other with a weighted arm projecting m an opposite direction, there being pulleys mounted on the shafts and on a superposed rock shaft, with belts arranged to cause a given motion to the rock shaft to impart a reversed motion to the pendulum and counterweight.

MOTOR.-John C. Lueneburg, Lakefield, Minn. This is an improvement on a formerly vention sists of a main driving shaft rotated by gear wheels moved by a sprocket chain, a reciprocating crosshead carrying spring-pressed pawls adapted to engage the strands of the chain. The motor is especially designed for readily and powerfully propelling vessels, vehicles, etc., by the strength of the occupant.

through a longitudinal slot of the finger piece. The construction is strong and simple, and the jaw may be very conveniently locked and unlocked for adjustment to various sized objects.

SAW CLAMP.-Fernando W. Seaver, Bennington, Ind. This is a strong and simple device for holding saws to be dressed, and consists of an upright frame whose upper ends are secured to a long jaw, and on this frame is fulcrumed a swinging frame with side levers carrying a jaw at their upper end, the jaws having flat surfaces adapted to fit snugly against a saw Both hands may be used to place the saw, which is fixed by a single movement of the foot by a treadle-operated cam mechanism.

Agricultural.

CANE PLANTER. - Eligio Olivera y Martinez, Havana, Cuba. This is a machine of strong and simple construction, which cuts the cane in suitable lengths for planting as fast as it can be fed to the cutters, and then deposits the cane in the furrows prepared to receive it while the machine is advancing. The machine is also provided with markers, to be carried in the direction of either side, and has a covering device for closing the furrows after the cane has been deposited, the cutters and planting cylinders being automatically operated as the machine is drawn over the ground.

PEA SHELLING MACHINE.-David A. Gaither, Williston, Tenn. The peas as gathered from the vines and poured into the hopper of this machine are fed to thrashing or hulling cylinders so grouped, and sustaining such relation to each other, that the pods will be broken, the peas thrashed out, and the pods separated and delivered in one direction while the peas go into an off-take chute, where they receive an air blast to free them from all foreign particles.

COTTON CULTIVATOR.-Henry Nehrmever, Reinhardt, Texas. This machine has at its front end opener or weeding plows to cut the plants to form the rows, while a series of finger plow gangs is arranged to travel between the paths of the weeding plows over the rows or intended stand, the beams of the latter plows having their frontends pivotally connected to the mainframe. and their rear ends held for independent vertical movement. The machine is particularly adapted to thin out irregular growths and bring them to a proper stand in a quick and economical manner, five or more stands being obtained at one operation of the machine.

Miscellaneous.

SHINGLE BUNCH AND BINDER.-William J. Munro, Joseph Hart and David Batey, Sedro, Wash. According to this invention shingles are bunched to occupy the least possible space for kiln drying or transportation, the shingles being arranged in substantially the usual way, but the invention providing a novel form of binder occupying scarcely any space, easily applied, and having the necessary strength, the bunching being thus effected more economically than by the ordinary method.

SASH FASTENER.-Wellman E. Cline, Doylestown, Ohio. This is a lock and stop, consisting of a casing in which a locking wheel is eccentrically pivoted, a spring-controlled operating lever being eccentrically connected with wheel by a link. The device is inexpensive and may be applied to a window frame for engagement with the sash, or attached to the sash for engagement with the frame, in either case permitting the sash to be readily raised or lowered from a locked position, upon releasing the lock, the sash being otherwise firmly held.

TRANSOM LIFTER.-George M. Garland, Des Plaines, Ill. This invention provides a simple mechanism by which one or a series of ventilators may be conveniently worked. A bell crank lever pivoted at its angle to the transom frame is connected by one of its arms through a link with the free end of the transom, the other arm being connected with an operating cable Pivoted rod connections guide the movement of the transom and bell crank lever, and the device is quite inexpensive.

COAL SCREEN, ETC. -George W. Cross, Pittston, Pa. The screening surface of this screen is constructed of segmental plates in which are openings corresponding to the meshes of wire screens. The openings of the screen are, however, separated by walls of a peculiar undulating form, presenting alternate convex and concave surfaces, to cause the coal or other lumpy material to practically pause and turn at the meshes, instead of sliding over them, thereby facilitating the sizing of coal.

VEHICLE SEAT.—Charles M. Kellogg. Chetek, Wis. This seat has a lazy back section which has a hinged connection with the back proper of the seat, and is connected with spring-cushioned slides, so that when one presses against the lazy back section it will fall back somewhat against the tension of the spring. The seat is designed to very comfortable, enabling one to assume any desired position in traveling. ICE CREAM FREEZER. - Thomas J. Harton, Waco, Texas. This freezer is essentially a re voluble cylinder divided into a series of compartments. the central one being adapted to receive the cream moulds or receptacles, an end compartment receiv ing milk or lemonade, etc., and intermediate compart. ments holding ice or other freezing medium, the cylinder being supported in a suitable casing and revolved by a crank. ENVELOPE FASTENER.-Paul E. Go non, New York City. A separate straight elastic arm attached to the envelop flap is, according to this invention, adapted to be bent or crimped near its ends to engage apertures in the back of the envelope, and when released to enter the envelope by its elasticity, whereby the flap is locked to the back of the envelope without using an adhesive substance.

gages the shauk, a button projecting from the plate. containing the goods to be vended, while a package discharging mechanism arrested by the spring is released by the pressure of the coin. The machine may be adjusted to deliver various small articles in separate packs

TRAP. - Hubbard S. Goff and Alvin B. Judkins, Los Angeles, Cal. This invention covers an improvement in animal traps, which may also be used to catch fish. It has oppositely arranged spring-pressed jaws pivoted together at their inner ends, one of them having an opening to facilitate baiting, a locking mechanism holding the jaws open, a trigger releasing them, and a hook closing the bait opening.

ANCHOR FOR VESSELS. - Ruben Zertuche, Saltillo, Mexico. This anchor is more especially designed for fiat-bottomed vessels, the anchor consisting of a flat rectangular plate of sheet metal, designed to be supported by the anchor chain in a nearly horizontal position in the water below the vessel and not to take hold on the bottom, the column of water bearing upon the fiat plate serving to hold the vessel steady, keep its head to the wind, and prevent drifting to leeward.

VESSEL CONSTRUCTION.-The same inventor has obtained another patent for a novel construction of the hull of a vessel, according to which a flat plate extends beyond both sides and flush with the stem and stern, there being a buoyant compartment between the plate and hull, and braces removably connected with the hull and plate. The vessel is designed to be of very light draught and have great stability.

TENT.-George Tolmie, Carbon, Wyoming. A door-closing strip extends across the threshold of the door opening, according to this invention, while a flooring strip is connected with the threshold portion of the closing strip, there being inside cords adapted to fold the closing strip upward over the opening, or open it out, from the inside

PNEUMATIC TIRE.-William R. Barrett, Passaic, N.J. This tire has an inner inflatable tube with the usual valve, an outer split cover with interlocking coils at the meeting edges, washers encircling the valve of the inner tube, while a flexible fastening rod has one end held to one washer and the other end screwthreaded to engage the other washer. This tire may be readily fastened to a wheel, and its cover readily opened to give access to the inner tube, which may be easily taken out and a new one substituted.

STAND ATTACHMENT FOR BICYCLES. Elihu S. Bishop. Milton-on-the-Hudson, N. Y. A bracket which may be readily applied to the bicycle frame has a pivotally connected spring-controlled leg, which also carries a brake shoe and a locking device. When not in use the attachment may be readily folded up out of theway

BADGE. - James R. Lee, Baltimore, Md. This badge consists of a ribbon on the face of which is secured a separate emblem-bearing fabric by means of a novel form of foundation, which maintains the fabric in convex form for the better display of the emblem.

MARKING DEVICE.-Edward W. Dodge, Augusta, Ga. This device comprises an open frame within which is stretched an ink ribbon or fabric, with both surfaces exposed, the device forming a transfer slate, to be written upon with a stylus when the charac ters traced are transferred to the articles beneath

DESIGN FOR A SPOON. - Austin F. Jackson, Taunton, Mass. In this design the handle is waved or serpentine and has beadlike representations forming the border of a central panel, above which is the simulation of a shield.

Note .-- Copies of any of the above patents will be furnished by Munn & Co., for 25 cents each. Please send name of the patentee, title of invention, and date of this paper.

NEW BOOKS AND PUBLICATIONS.

OBJECTS OF INTEREST TO ENGINEERS AND OTHERS IN AND ABOUT PHILA-DELPHIA. Philadelphia. 1893. Pp. 109.

Philadelphia, pre-eminently a manufacturing city, is treated in this work as an engineers' inspection field. The different factories and engineering objects situated in it and about it are here indexed and their addresses and striking features given, with full references to the accompanying map. It is issued by the Engineers' Club. and is in all ways an admirable publication.

DE VALVE DIAGRAMS. A French method for constructing slide valve diagrams. By Lloyd Bankson. New York: D Van Nostrand Company. 1892. Pp. 29. Price 50 cents. SLIDE VALVE DIAGRAMS.

Eight folding plates are required to elucidate the short text of this book. It gives a graphic method of solving slide valve problems and from its conciseness and simnlicty will, we are sure, be found of use to the designer of engines.

NGUAGE. Prepared by more LISH

upon the corps of editors. The distinctive features indicate a thorough systemization of the work. Thus the etymology is placed after the definition. In the definition of words the most common meaning is given first, the order of usage replacing the historical order hitherto favored. For giving the pronunciation of words what is known as the scientific alphabet is used. This alphabet has been prepared and recommended by the American Philological Association and adopted by the American Spelling Reform Association. This is an immense advance over the arbitrary system used in so many other works of this character. Quotations are referred to book, page, and edition, as well as to the author's name, so that they are susceptible of verification in the library. New quotations have been sought for, the works of 3,000 authors having been read by nearly 1,000 readers. Disputed pronunciations and spellings, various pronunciations of words and nearly 5,000 pictorial illustrations have all received the fullest consideration and the most advanced treatment. It is claimed that it will contain 280,000 words and terms-55,000 more than in any other dictionary. The prospectus develops this and other salient features and indicates very advanced views on the part of the editors as to the proper methods of constructing such a work.

The Art Wall Papers of H. Bartholomae & Co., of West Twenty-third Street, New York, and a branch of the National Wall Paper Company, afford the subject of a beautiful set of plates recently published by the firm in folio form, in heavy board covers. They include views of the hall, parlor, library, dining hall, and boudoir, elegantly and artistically furnished and decorated in new and rich styles designed by the artist of the firm, Mr. Paul Groeber, of Rutherford, N. J., who also makes the drawings for this folio. The artist received a special medal at the World's Columbian Exposition for the architectural design and decorations of the pavilion of the National Wall Paper Company's exhibit.

From Thomas J. Dowling, Commissioner, having charge of the Bureau of Statistics of Labor of New York State, we have received four volumes published by the Bureau, and principally compiled under the direction of his predecessor, Charles F. Peck. They treat of "Strikes and Boycotts," "Rates of Wages," and 'Economic Development for Ten Years."

Any of the above books may be purchased through this office. Send for new book catalogue just published. MUNN & Co., 361 Broadway, New York.

SCIENTIFIC AMERICAN BUILDING EDITION.

FEBRUARY, 1894.-(No. 100.)

TABLE OF CONTENTS.

- 1. Elegant plate in colors showing a suburban dwelling at Plainfield, N. J., erected at a cost of \$4,800 complete. Floor plans and perspective elevation. A tasteful design. Messrs. Rossiter & Wright, architects, New York.
- 2. Plate in colors showing an elegant residence at Pelham Manor, N. Y Perspective view and floor plans. Estimated cost \$7,000 complete. An excellent design.
- 3. The Jamaica Club House, recently erected at Jamaica, N.Y. Perspective views and floor plans, also an interior view. Cost \$9,000 complete. Messrs. Haus & Oborne, architects, Brooklyn, N. Y.
- 4. A beautiful residence at Portchester, N. Y., recently erected for A. V. Whiteman, Esq. Perspective and floor plans. Mr. Frank W. Beall, architect, New York.
- 5. Engravings and floor plans of a suburban residence erected at Ashbourne, Pa., at a cost of \$4,800 complete. An attractive design. Harrison Allbright, Esq., architect, Philadelphia, Pa.
- 6. A suburban dwelling recently erected at Edgewater, Ill., at a cost of \$10,216. Floor plans and perspective elevation. Mr. F. B. Townsend, architect, Chicago.
- 7. A colonial cottage at Buena Park, Ill., recently completed for Guy Magee, Esq. Floor plans and per-spective elevation. An artistic design. A modern half-timbered cottage at Wyncote, Pa.,
- 8. erected at a cost of \$4,250 complete. Floor plans and perspective elevation. Mr. A. S. Wade, Philadelphia, Pa., architect.
- 9. A modern colonial residence at Oak Lane, Pa., erected at a cost of \$6,800 complete. Perspective view and fioor plans. Mr. F. R. Watson, of Philadelphia, Pa., architect. An attractive design.
- 10. The residence of Rev. Samuel Scoville at Stamford, Conn., erected at a cost of \$6.616. Mr. W. W. Kent, architect, New York. An excellent design.
- Examples of interior decoration and furniture in the Moorish style. 12. A Queen Anne dwelling at Jenkintown, Pa., recently completed at a cost of \$5,000. Messrs. Burke &
- Dolhenty, Wyncote, Pa., architects. A STANDARD DICTIONARY OF THE ENG- 13. Miscellaneous Contents: The growth of plants in odd places - Acoustics in building

WAVE AND CURRENT POWER.-Singleton Husted and Irvin P. Doolittle, Los Angeles, Cal. An intake box arranged near the shore is adapted to receive water at the highest point of the waves, and a raceway leading from this box contains a water motor the raceway being arranged in the path of the under tow, or outgoing current, to make use of its suction or exhaust. If desired, a number of intake boxes may be connected with each other, to permit a very large amount of water to pass down the raceway at the receding of the waves.

WRENCH.-William A. Papoun, Baker City, Oregon. In this tool a toothed shank carries the fixed jaw, a movable jaw with a handle part sliding on

VENDING MACHINE.-Edward D. Valentine, New York City. This machine has an upright coin passage in which a flat spring is arranged to be the shank. In the movable jaw is a sliding finger piece coin passage in which a flat spring is arranged to be possible connections. Simplicity, accuracy, and com-engaging bevels on the jaw, while a toothed plate en pressed upon by a descending coin, a swinging frame prehensiveness are alleged to be three features impressed

than two hundred specialists and other scholars, under the supervision of Isaac K. Funk, editor in chief; Francis A. March, consulting editor; Francis A. March, consulting editor; Daniel S. Gregory, managing editor. Associate editors, Arthur E. Bost-wick, John Denison Champlin, Rossiter Johnson. Volume I. New York, London and Toronto : Funk & Wagnalls Company. 1893. Pp. xx, 1060.

We have received the first volume of Funk & Wagnalls dictionary. When we consider that the work is designed to surpass, in its number of words, all preceding dictionaries of the English language, that it takes cognizance of the most recent philological developments in the way of spelling, pronunciation, and derivation, that it is profusely illustrated with not only wood cuts but also with very elegant colored plates, the utter inadequacy of a review within the limits of our space will be apparent. Its list of editors embraces many names in all possible connections. Simplicity, accuracy, and comsteam power brick machine, illustrated.-A new style stamped ceiling, illustrated.-The telethermometer or distant temperature indicator .- The improved Thatcher furnace, illustrated .- Improved sash chains and fixtures, illustrated.-An improved sliding door latch, illustrated.-Aluminite in cement plaster.-Fire losses of 1893.-Graphite paint .--- The Columbian sash and door lock, illustrated.—An improved sash lift, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITEC-TURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural Publication in the world. Sold by MUNN & CO., PUBLISHERS, all newsdealers. 361 Broadway, New York.

Chai

hu

Chu

Ciga Ciga Ciga

Circ Clan

Clov Coal

Con

Com Con Cool

Cop

Cors

Crac Crai Cres Cres

Cult Cult

Curl Curr Curr

Cut-Cutt

Cut

Den Den

Den Deri Desi Desi Dige

Dra Dril Dril

Dyn Dyn Ear

Egg Ela

Elec Elec Elec Elec Elec

Ele Ele Ele

Ele Ele Ele

Emi Emo Eno Eno

Eng Eng Eng

Business and Personal.

The charge for Insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at mublication office as early as Thursday morning to appear in the following week's issu

The new material, " Linenoid," Westfield, Mass. "U.S." metal polish. Indianapolis Samples free.

Improved iron planers. W. A. Wilson, Rochester, N.Y. For coal hoisting engines. J. S. Mundy, Newark, N. J. Handle turning machinery. Trevor Mfg. Co., Lockport, N. Y.

Microbe Killer Water Filter, McConnell Filter Co., Buffalo, N. Y.

Wanted-Light machinery or specialties to build. P. G. Fleming's Machine Works, Elizabeth, N. J.

Pipe frame truck baskets, steel and wooden trucks etc. L. M. Moore, Rochester, N. Y. See page 399. Steam Hammers, Improved Hydraulic Jacks, and Tube

Expanders. R. Dudgeon. 24 Columbia St., New York. Screw machines, milling machines, and drill presse

The Garvin Mach. Co., Laight and Canal Sts., New York. Centrifugal Pumps. Capacity, 100 to 40,000 gals. per minute. All sizes in stock. Irvin Van Wie, Syracuse, N.Y. Carborundum – hardest abrasive known. Send for prices of wheels, powder, etc. The Carborundum Co.

Monongahela. Pa. Models and experimental work. Small articles made

in quantity for the trade. For catalogue, etc., write L. G. Winn Mfg. Co., Indianapolis.

Guild & Garrison, Brooklyn, N. Y., manufacture steam pumps, vacuum pumps, vacuum apparatus, air pumps acid blowers, filter press pumps, etc.

The best book for electricians and beginners in elec tricity is "Experimental Science,"by Geo. M. Hopkins By mail. \$4; Munn & Co., publishers, 361 Broadway, N.Y

For the original Bogardus Universal Eccentric Mill, Foot and Power Presses, Drills, Shears, etc., addres

J. S. & G. F. Simpson, 26 to 36 Rodney St., Brooklyn, N. Y. Patent Electric Vise. What is claimed, is time saving No turning of handle to bring jaws to the work, simply one sliding movement. Capital Mach. Tool Co., Auburn N. Y.

Competent persons who desire agencies for a new popular book, of ready sale, with handsome profit, may apply to Munn & Co., Scientific American office, 361 Broadway, New York.

🕼 Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway New York. Free on application.



HINTS TO CORRESPONDEN'IS.

- HINTS TO CORRESPONDENTS.
 Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information and not for publication.
 References to former articles or answers should give date of paper and page or number of question.
 Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.
 Bu yers wishing to purchase any article not advertised in our columns will be transhed with addresses of houses manufacturing or carrying the same.
 Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.
 Books referred to promptly supplied on receipt of price.

Minerals sent for examination should be distinctly marked or labeled.

(5796) A. M. S. asks: 1. I have a small electric battery motor rated at one-sixth horse power at 10 volts. Now I wish to run it from a lampcurrent from an Edison standard dynamo rated at 8 1-5 kilowatts, 125 volts, with 60 amperes as working load. How shall I proceed? Shall I have to put any lamps in the circuit? If so, how many? A. According to your figures, your motor can absorb a maximum of 71/2 amperes at 10 volts. If used on a 125 volt circuit, you must put lamps or other resistance of 11 ohms and 10 amperes capacity in circuit with it. The system would involve great waste of energy. Sixteen 28 candle 31 volt lamps, four in parallel and four in series, or ten %4 candle power lamps in parallel, would give the result approximately This is on the assumption that the motor is shunt wound. 2. What would be the results to motor should I put on full potential of 1:0 volts ? The motor is wound as follows: Armature 3 coils 11/2 pounds No. 21 wire, field magnet single coil of 4 pounds No. 16 wire. A. It would burn out both field and armature.

(5797) D. D. W. writes: 1. Is the one horse power eight light dynamo, SUPPLEMENT, No. 600, a high tension machine? If not, what is a high tension and also low tension current? A. There is no such thing as a high tension or low tension current. A circuit described, reference being maximum difference of potential existing between an two points of it. 2. With one-half horse power will give about one-half as much current; one-fifth hor power, one-fifth as much current, as with one hor power? A. On short circuit this would be the gener effect; on a circuit of high resistance the voltage would vary mostly; on an intermediate circuit both voltage and amperage would vary. 3. Will motor No 641 and 161, with drum armature, run all right with cu rent from this machine? A. The voltage is too high for the motors mentioned. (5798) J. O. F. asks: If a small amour of caustic soda water accidentally introduced into stear boilers with feedwater would cause priming? We be our double effect with very strong caustic soda water an have a considerable (inaccessible) leak, which, when stea is shut off and vacuum broken, allows the soda to ent the steam chamber, and when steam is again turned on blown into feedwater heater. There can certainly be b a very small amount, but am unable to account for t behavior of boiler water otherwise. A. Phre caustic soc in small quantity will keep a boiler clean from incrustation by frequently blowing off the boiler, and will not cau

serious foam. We assume, although you do not state it, that a little sugar goes into the boiler with the soda which we have no doubt is the cause of the foaming. As a remedy, the water that leaks into the steam chamber should be blown out and wasted by an outlet in the pipe eading to the heater.

(5799) E. P. W. asks (1) how to make carbonic acid gas. A. Pour hydrochloric acid on marble dust. 2. What pressure it takes to liquefy? A. 36 atmospheres at 32° Fah. 3. How to condense it after expansion? A. By pressure applied by a pump.

(5800) R. S. C. asks: 1. How are the spots made on the barometer which you will find inclosed ? A. They are marked with a cobalt compound ; possibly the chloride. 2. How is fuse wire made for 110 volts? A. Fuse wire is calculated for amperage, not for voltage. 3. How should the hand power dynamo described in SUPPLEMENT, No. 161, be wound to give about 12 volts, to run an electric dental mallet? A. Use a drum armature with 500 turns of wire. See our SUPPLEMENT, No. 599. It is better to make the whole core of iron washers. 4. Where can I get the directions for making a steam siphon? Also what size suction and discharge pipe should I use for a quarter inch steam pipe ? A. The size of discharge nozzle should be from two to three times the diameter of the steam nozzle. The smaller size for greater elevations, suction five times diameter of steam nozzle. The steam nozzle should be taper like a short hose nozzle and stop at three times its diameter from the discharge pipe mouth, which would be bell shape, to allow an easy entrance of the water. We have no detailed illustration of the siphon ejector. 5. Can the telephone used by the Bell Telephone Company be made by anybody after the last of January ? A. 'The receiver can, not the transmitter.

TO INVENTORS.

TU INVENTORS. An experience of forty-four years, and the preparation of more than one hundred thousand applications for pa-tents at home and abroad, enable us to understand the laws and practice on both continents, and to possess un-equaled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices which are low, in accordance with the times and our ex-tensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broad-way, New York.

INDEX OF INVENTIONS Ror which Letters Patent of the United States were Granted February 6, 1894, AND EACH BEARING THAT DATE. [See note at end of list about copies of these patents.]

 ISee note at end of list about copies of these patents.]

 Acid and caustic alkali, making nitric, Lunge & Lyte.

 Addressing machine, E. E. Hanna.

 Sild, 23

 Advertising, apparatus for successively isplay-ing tablets for. F. J. Beaumont

 Acid and caustic, E. E. Hanna.

 Advertising, apparatus for successively isplay-ing tablets for. F. J. Beaumont

 Aerial vessel, J. Blanchard

 Aterial vessel, S. Spaeth

 Alarm. See Electric alarm. Fire alarm. Over-flow alarm.

 Aluminous minerals, purifying, H. F. D.

 Schwahn

 Aluminous minerals, purifying, H. F. D.

 Aluminous flooride, making, W. Ackermann.

 Schwahn

 Animal shears, J. K. Priest.

 Automatic sprinkler, R. W Newton.

 Automatic sprinkler, R. W. Newton.

 Automatic sprinkler, R. W. Newton.

 Automatic sprinkler, R. W. Newton.

 Stard

 Automatic sprinkler, R. W. Newton.

 Stard

 Ballot folder, I. W. Litchfield

 Ballot folder, I. Schwahn

 Stard

 Stard

 < Battery. See Electric battery. Secondary bat-tery. Beam anchor plate, A. E. Krause. 514,151 Bed bottom, spring, M. C. Silver. 514,386 Bed, folding, C. B. Adriance 514,022 Bedstead. folding, P. G. Le Dan 514,326 Bicycle, Moehn & Graves. 514,139 Bicycle, M. Pope. 514,339 Bicycle, H. M. Pope. 514,349 Bicycle, eupporting attachment, A. K. Sherwood. 514,044 Binder for papers, etc., temporary, E. L. Brund-age. 512,379

 Bicycle, H. M. Pope.
 514,252

 Bicycle supporting attachment, A. K. Sherwood. 514,044
 Fert.

 Binder for papers, etc., temporary, E. L. Brund.
 514,024

 Bit. See Drill bit.
 513,979

 Bit. See Drill bit.
 513,979

 Bit. See Drill bit.
 514,178

 Bolter fue scraper, automatic. Kingsland & Hill.
 514,178

 Boiler fue scraper, automatic. Kingsland & Hill.
 514,178

 Boller fue scraper, automatic. Kingsland & Hill.
 514,178

 Boller fue scraper, automatic. Kingsland & Hill.
 514,128

 Boller fue scraper, automatic. Kingsland & Hill.
 514,120

 Bottle opener, capped. W. Painter
 514,200

 Bottle opener, capped. W. Painter
 514,201

 Bottle washer, H. Portevin.
 514,201

 Box. See Feed box. Knockdown box. Packing
 514,201

 Box. See See Torunse.
 514,414

 Box. See Gar brake. Car and air brake.
 514,424

 Box care, removable, D. Cree.
 514,426

 Box care, opener and handle for shoe polish of 514,826
 Flow

1	
hir. See Reclining chair. Shoulder and back bracing chair. sck carrier, sales, W. M. Kinnard	Heater, J. Hauser Hoe, weeding, A. Evans Hoist drum for discharge
ck, identifying, N. H. Bledsoe	docks, D. T. Denton Holdback, vehicle, W. Fin Hook. See Lacing hook.
14,008 10k, drill, O. K. Schmidt	Hop torrefying apparatus Horse stopping de vie, H. Horseshoe, W. R. Kinneau
Im, A. Schuyler	Hot water heater or stean Hub detaching device, wh Huller. See Clover huller
ar holder, P. Sattelkau	Incubator, L. Kuhner Inb le, A. M. Adsit Inbalers, apparatus for 1
514,236, 514,237, 514,239 cuit controller, E. J. McEvoy	McLean Injector, J. Morrison Insect tray, A. Y. Smith.
clamp. ver huller feeder, Kailor & Reeves	Insecticides or similar sub applying, G. Boas Insulated pipe coupling, E
grading, L. Auimann	Insulator, J., B. Gray Iron. See Curling iron. Ironing machine, H. E. Sn
king, broiling, baking, etc., apparatus for, M. E. Jehu	Jack screw, J. D. Lynch Joint. See Rail joint.
dolph. 514,275	Kiln. See Brick kiln. Knockdown box or crate.
ying press, letter, J. H. Taylor	Ladder, extension, J. R. M Ladder, extension step, E Lame W B Robins
set steel, C. Scholl	Lamp, argand, E. Miller, J Lamp, electric arc, R. M. I Lamp, electric arc, W. B.
coupling. Shaft coupling. Tubular coupling. dle or crib, extensible, C. B. Adriance	Lamp, electric arc, G. G. V Lamp globe holden arc, J. Lamp hood, electric arc, S
amery apparatus, G. T. McLauthlin	Lath bolter, H. Joncas Lathing, metallic, W. Eck Leg, artificial, D. Hersnoe
tivator, straddle row, G. M. Clark	Life-preserver, W. S. Beat Liquid separator, centrifu Lock. See Hasp lock.
tain or shade rollers, adjustable hanger for, S. R. Smith	Locks, tool for forming k lor Locomotive diaphragm, E
ter. See Sod cutter. Weed cutter. Wire cutter. ting board, J.T. Sheffield	Locomotive running gear, Locomotives, motor cont tric, S. H. Sbort
ntal handpieces, angle attachment for, F. K. Hesse	Loom shuttle, P. L. Kobel Looms, electric shuttle r bard
rrick, S. R. French. 514,355 sk, curtain, J. F. Wilmot. 514,108	Lumber, metal plated, C. Mail bag fastener, L. Arn Mail bag fastener, S. M. F.
cester, E. Meurer. ger. See Potato digger. mer socket G. W. Knapp. 514,230	Measure for laying off dre Measuring or indicating in E. Hitt
h, supported, J. B. Timberlake	Measuring vessel, G. W. Meat mixer, L. Wagner Mechanical motor, P. Frid
or ör window clamp, G. W. Lake	Merry-go-round, J. Thom Metal goods for artistic of, L. Hausmann
Ill bit and reamer for earth boring, A. G. P. Creed	Meter. See Electric meter Mirror, J. Jacobson Moulder's flask, Travers &
namo and motor, M. Waddell	Moulding making machin Motor. See Electric moto Mucilage, collapsible tub
g crate, J. west	Music rack for musical Weser.
cetric arc light future, S. Bergmann	Nuckel from copper, electi D. Ricketts
setric conductor, underground, H. A. Seymour 514,133 setric currents, load governor for, F. E. Pritch- ard	Nut lock, L. D. Frenot Nut lock, J. W. Schoaf Nut locking device, J. Wa
ectric currents, means for generating, N. Tesla 514.168 setric light, incandescent, N. Tesla	Ores, earths, clays, etc., s ing the constituents o Ores, smelting, W. L. Aus
ectric motor, J. D. Ihlder	Overflow alarm for recept Package, C. Nelson
ctrical resistances, instrument for measuring and regulating, G. B. Lawrason	Packing for journals, man lan
and caustic soda, J. Greenwood	Paper box, Reber & Sefto Paper boxes, machine f
ectrostatic instruments, induction mechanism for, Ayrton & Mather	Paper sheets, method of a ing, separable, C. S. B Pastry tin, A. Eiche
evator, J. Naylor. Jr	Phosphate rock, appar Hughes Picture hook, J. B. Hall
Keeler	Pill machine, A. Colton Pin, C. D. Rutherford Pipe wrench and cutter, o
dery wheels, manufracture of, O. Terp	Pipe wrench and cutter, of Pitcbfork, A. E. Hamman Pitching machine, H. To Plong components's C. S.
gine, Atwood & Perkins, Jr	Planter and fertilizer dist & B. M. Harrington . Planter seed dronning me
graving plates, composition of matter for mak- ing chalk, Miller & Crosse	Plaster composition, J. H Potato digger, A. H. Dod Power, electrical transmi
rm gate. W. H. H. West	Precious metals, recovering Press. See Copying press Pressure gauge, W. H. B
ed box, folding, R. H. Sobmidt	Pressure gauge, bourdon. Pressure gauge, recordin Printing carpet yarn, app
nce tension device, wire H. C. Pratt. 514,130 nce wire ratchet, G. W. Williams. 514,106 na wire strotcher M. Divon 512,000	Pump, J Rieppel Pump, rotary, V. Bries
nce wire stretching device, Stevens & Case 514,288 nder. See Car fender. rmenting mixtures apparatus for preparing	Rail chair, G. H. Sellers. Rail joint, R. Herman Railway cattle guard J. 1
and manipulating, B. Schumm	Railway. closed conduit of Railway collisions, device & Faltinowsky
bers of reed cane, separating, T. E. Phillips, 514,027, 514,028 le for newspaper clippings, G. W. Sherman 514,244	Railway conduit. electric Railway, conduit electric Railway crossing, C. H. V
re alarm and sprinkler, W. A. Guthrie	Railway, electric, F. M. A Railway, electric, O. A. H Railway electric signaling
re escape, C. Aller	Railway signal, F. L. Do Railway signal, F. L. Do
bard	Railway switch, A. F. Sc Railways, closed conduit mour
re trap for elevator shafts, automatic, T. G. Lamb	Rake. See Hand rake. Ratchet drill, double-act Reciprocating engine. N.
oat and sinker attachment, P. S. Redfield 514,054 oorcloth, method of and apparatus for manu- facturing, H. W. Godfrey <i>et al.</i>	Reclining chair, J. C. All Reclining chair, S. A. Ch Reel. See Wire holding
our bolt, W. D. Gray	Register. See Cash regis Rheostat, J. T. Birch Sasb balance, A. M. How
org. see Filchlorg. ortune telling machine, coin-operated, F. F. Dennis	Sash 1astener, H. W. Rho Sash holder, Leverett & Saw, circular, J. E. Bott.

		<u></u>
k	Heater, J. Hauser	514,145
. 514,010	Hoe, weeding, A. Evans Hoist drum for discharge apparatus of coal or ore docke D. T. Depton	514,419 514 962
514,426	Holdback, vehicle, W. Finlay	514,219
514,008	Hop torrefying apparatus, G. L. Jaeger Horse stopping de wie, H. J. H. Toft	514,265 514,100
. 514,358 . 514,095	Horseshoe, W. R. Kinnear. Hot water heater or steam generator. C. Phelps.	514,011 514,026
514,164 514,181	Hub detaching device, wheel, G. H. Butler Huller. See Clover huller.	514 084
8, 514,240	Inta le, A. M. Adsit. Inhalers, apparatus for heating air for. W. S.	514,298
7, 514,239 514,019	McLean Injector, J. Morrison.	514,022 514,093
F14 102	Insecticides or similar substances, apparatus for	514,388
d 513 973	Insulated pipe coupling, E. E. Clift	514,205 514,304 514 221
513,980 514,150	Iron. See Curling iron. Ironing machine, H. E. Smith	514,137
. 514,338	Ironing machine, M. E. Wendell Jack screw, J. D. Lynch	514,049 514,091
e 514,079	Journal bearing, adjustable, E. W. McGuire	514,331
. 514,275	Knockdown box or crate, J. J. Herbert Lacing hook, shoe, C. E. Van Norman	514,367 514,395
514,204	Ladder, extension, J. R. McLaren, Jr Ladder, extension step, E. W. Hammon	514,020 514,223
514,213 514,242	Lamp, W. B. Robins. Lamp, argand, E. Miller, Jr.	514,036 514,158
e t	Lamp, electric arc, K. M. Hunter Lamp, electric arc, W. B. Luce	514,225 514,425 514,139
514,401 514,251	Lamp globe holden arc, J. T. Dempster Lamp hood, electric arc, S. Bergmann	514,417 514,057
.514,021 .514,097	Lath bolter, B. Joncas Lathing, metallic, W. Eckstein	514,081 514,313
. 514,210 . 514,209	Lige, artificial, D. Hersnberger Life-preserver, W. S. Beale	513,977 514,156
514,031	Lock. See Hasp lock. Locks tool for forming key slots in. W. H. Tay-	014,100
. 514,046 514,018	lor Locomotive diaphragm, E. M. Roberts et al	514,248 514,337
e 514.000	Locomotive running gear, R. Helmholtz Locomotives, motor controlling device for elec-	514,320
514,090	Loom shuttle, P. L. Kobertz.	514,135 514,232
3, 514,074 514,201	bard	514,089
514,355	Lumber, metal plated, C. D. Kubach Mail bag fastener, L. Arnold	514,233 514,404
514,351 7, 514,374	Mail bag fastener, S. M. Ferguson Measure for laying off dress charts, L. A. Call Measuring or indicating instrument clostring.	514,183 514,063
. 514,230	E. Hitt. Measuring vessel. G. W. McKim	514.075 514.377
. 514,235 . 513,985	Meat mixer, L Wagner Mechanical motor, P. Frichette	514,048 514,356
. 514,085 . 514,105	Merry-go-round, J. Thompson Metal goods for artistic purposes, manufacture	514,893
513 097	Meter. See Electric meter. Water meter.	514.070
514,140	Moulder's flask, Travers & Petersen	514,101 514,053
J. 514,373	Motor. See Electric motor. Mechanical motor. Mucilage, collapsible tube or package for, J. A.	
514,051	Symonds. Music rack for musical instrument cases, J. A.	514,290
513,990 514,202 514,058	Musical instrument attachment, G. Brown	514,259
514,115	D. Ricketts. Nut lock, W. J. Devers.	514,276 514,217
ur 514,133	Nut lock, L. D. Frenot. Nut lock, J. W. Schoaf	514,315 514,339
514,030 la, 514,168 514,170	Ores, earths, clays, etc., separating and recover- ing the constituents of H F D Schwahn	514,091
514.241 514.131	Ores, smelting, W. L. Austin. Organ, R. Hope-Jones.	513,974 514,146
514,077 514,429	Overflow alarm for receptacles, R. Byrne Package, C. Nelson	514,116 514,159
514,167 ig 514 395	Packing for journals, manufacturing, H. B. Dev-	514,394
ne 514,318	Padlock, permutation, F. N. Silvey	514,887 514,033
ls. 514,267 514,305	Paper boxes, machine for making, E. A. John- ston	514,149
m 513,975	Paper sheets, method of and apparatus for mak- ing, separable, C. S. Bird	514,059
514,023	Phosphate rock, apparatus for treating, S. Hughes	514.006
514,123 C.	Picture hook, J. B. Hall Pill machine, A. Colton	514,222 513,986
514,009 514,138	Pin, C. D. Rutherford. Pipe wrench and cutter, combined, J. Green	514,132 514,000
514,076	Pitchfork, A. E. Hammarstrom Pitching machine H Torchiani	514,100 514,069
re	Plane, carpenter's, C. S. Hinnershotz Planter and fertilizer distributer, combined, A. J.	514,226
514,054	& B. M. Harrington Planter seed dropping mechanism, N. S. Burch	514,071 514,411
514,015	Potato digger, A. H. Dodd.	514,065 514,065
514,102 L.	Precious metals, recovering, W. P. Miller	. 514,157
514,372	Pressure gauge, W. H. Bristol. Pressure gauge, bourdon, W. H. & E. H. Bristol.	514,255 514,256
514,300 514,250 514 319	Printing carpet yarn, apparatus for, W. Shaw Printing carpet yarn, apparatus for, W. Shaw	514,282
514,130	Pump, J Rieppel	514 336 514.063
513,989 514,288	Rack. See Music rack. Rail chair, G. H. Sellers	. 514,243
ng 514 340	Rail joint, R. Herman. Railway cattle guard, J. M. Lee Railway closed conduit clostric F. M. Ashloy	514,224 514,152
514,042	Railway collisions, device for preventing, Klaffky & Faltinowsky	514.083
27, 514,028	Railway conduit. electric, F. M. Ashley Railway, conduit electric, R. C. Beardsley	514.114 514.056
514,244 514,362	Railway crossing, C. H. White.	. 514,343 . 514,113
514,279 513,972	Railway electric signaling apparatus, E. C. Wiley Railway rail support, G. W. Cady.	514,898 514,179
514,094 514,160	Railway, series electric, M. A. Cattori Railway signal, F. L. Dodgson	. 514,303 . 514,118
n- 54, 514,155	Railway signal, A. H. Johnson. Railway switch, A. F. Schinner	. 514,192 . 514,037
or 514,220 G	nailways, closed conduit for electric, H. A. Sey- mour.	. 514,134
514,423	Ratchet drill, double-acting, J. Meahl Reciprocating engine, N. Tesla	514,127 514,169
514,034 u-	Reclining chair, J. C. Allen Reclining chair, S. A. Chase	. 514,403 . 513,981
514,186 514,317	Register. See Wife holding reel. Register. See Cash register.	514 904
514,390	Sasb balance, A. M. Howard. Sasb fastener, H. W. Rhoads.	514.00 514.00
F. 514,418	Sash holder, Leverett & Ramsay Saw, circular, J. E. Bott	. 514,328 . 514,297
514,400	Saw, combination hand, J. O. Johnson Sawmills, variable friction feed mechanism for.	• 014, 9 81
514 910	Reisson on shoons D. Kemphana	- U11/019

	Bricks, method of and apparatus for forming, H.	Dennis	Saw, circular, J. E. Bott.	514,297
h i	H. Keller	Foundry use, rap and draw pin for, E. T. Wires 514,400	Saw, combination hand, J. O. Johnson	514,080
it :	Bridge gate. F. Carlson 514,064	Furnace. See Gas furnace.	Sawmills, variable friction feed mechanism for,	
	Broom and lantern holder, combination, J. C.	Gauge. See Pressure gauge.	W. Fleming	514,314
1e	Huxhold	Gas burner, 011, J. M. Ferguson 514,218	Scissors or shears, P. Kamphaus	514,082
שו	Burner. See Gas burner.	Gas burner regulator, Brooks & Wolfreys 514,143	Scoop, M. L. Schoch	514,038
.,	Buttonholestrip and making same, F. A. Cook 514,415	Gas engine, B. H. Coffey 514,211	Screen. See Fly screen.	
it	Cabinet, P. Marvel 514,126	Gas engine, H. Pokony	Screw elevator, portable, J. T. Ayers	514,299
ao [:]	Cable grip, J. A. Tauberschmidt 514,389	Gas engine, vapor, W. W. Grant 514.359	Screw making machine, D. P. Johnston	514,007
96	Can. See Seamless self-opening can. Shipping	Gas furnace, natural, F. Denz	Seaming machine for sheet metal ware, R. Flani-	
se	can.	Gas making apparatus, C. C. Gilmore 514,185	gan	513,994
~1	Can opener, I. W. Low 514,014	Gas regulator for water heaters, A. H. Schlueter. 514,428	Seamless self-opening can, E. Norton	514,025
aı	Canopy, W. Cole, Jr 513,984	Gate. See Bridge gate. End gate. Farm gate.	Secondary battery. H. H. Carpenter	514,260
ze	Capo tasto, L. L. Filstrup 514,263	Fence gate.	Separating machine, O. M. Morse	514,016
	Car and air brake coupling, S. J. Galloway 514,184	Gate, O. C. Miller 514,375	Separating solids from sludge, apparatus for, W.	
CU.	Car brake. J. Smith	Gate controlling apparatus, head. Winder & Car-	Birch	514,300
8.	Car coupling, P. C. Brown (r) 11,403	penter	Separator. See Liquid separator.	
~	Car coupling, H. C. Trask 514,291	Governor, W. H. Watson 514,294	Shaft, adjustable, A. M. Howard	514,004
r -	Car coupling, W. F. White 514,296	Governor for reversing engines, C. Hammen 514,187	Shaft coupling, safety, C. A. Sellon	514,384
or	Car fender, safety, G. Latz 514,234	Grain binding machine, C. A. Postley 514,029	Shears. See Animal shears.	
-	Car, railway, M. Le Grand 514,196	Gratebar. J. M. Sinclair 514,136	Shipping can, C. Wright	514,052
	Car, railway, C. H. Newbury 514,332	Grate, open fireplace, W. L. McDowell 514,269	Shoestring fastener, S. J. Simmons	514,284
+	Car safety guard, street, G. T. Foster 514,121	Grip testing machine, T. E. J. & W. Schaibly 514,281	Shoulder and back bracing chair, Harvey & Amos	514,189
10	Car, safety non-telescoping railway, L. M. Wor-	Guard. See Car safety guard. Railway cattle	Shoe case, J. Lochner	514.208
m	den	guard.	Sifter, mechanical ash, W. Christie	514,261
	Car ventilator, filtering. C. E. Robbins	Gun, compressed pulp, w. B. Benson 513,407	Signal. See Railway signal. Three-position sig-	
D11	Carriage curtain fastener, C. A. Behlen 514,346	Gun, machine, F. M. Garland	D8i.	F14 907
nđ	Carriage top, C. G. Ridout et al.	Guns, lever action for breakdown, G. W. Cilley 514,414	Signaling apparatus, E. R. wilder	514,251
	Cartridge, R. J. Gatling	Hame, Hunter & Blankley	Signaling device, electric, J. N. Connolly	514,212
ш	Case. See Bookcase. Show case. Traveling	Hame coupling, A. F. Fine	Signaling system, Noyes & winternalder	514,140
\mathbf{er}	Cash negister and indicator () [Jerendel 51/902 51/902	Hammer, spring, F. F. Sneparu	State attachment, J. M. Davis	514,117
	Cash registers combined drow ciertar	Handle for pape tube of a Prower	Sod cutter and crasher, D. E. Reardon	214,000
18	Cash registers, combined draw ejector and lock	Hamon I Middleton 51/000	Soldering composition, H. winoughby	514,104
ut	Coch registering and indicating machine I I	Harrow disk C M Clark 514 900	Sole Sitting mathematic, L. F. Hawkins	514 990
	Wobstor 514 174	Harrow englo I Dredor 51/066	Spinning mule, sen-acting, J. Moornouse	014,000
ne	Cash registering meching A Webster 514 173	Hasn lock C T Spanoor 514 341	Scharo (arpenter's folding & C Parry	514 390
da	Cash registering machine, I. Webster 514 175	Hat hodies method of and means for developing	Steam and bot water boiler R McGregor et al	514 876
	Cash registering machine I I & A Webster 514 176	dved stiff R Eickemever 513 992	Steam engine, G. Vyne	514 396
JU	Costor I R Sutliff 514 947	Hay loader, C. M. Gates 513.996	Steam or other fluid pressure engine, C. F. Wenn-	0.1000
se	Chain drive R J Ha ill $514,001$	Heater See Hot water heater.	herg	564,295
		· ALCOLULI HADEL HEADELS		

Scientific American.



Medicine used as an injection, proprietary, H. F. Bader 24 193	office and from all new
Milk, Orange County Milk Association 24,172	
Oils and ointments, hoof, C. F. Kissel	
Paper and envelopes, writing, Z. & W. M. Cane 24,156	
Paper, book and letter, R. S. Patterson	
Paper holders, roll, National Candy Mould and	
Pharmaceutical preparation for the skin. H. Fink-	- 25 A
elpearl	
Pills, A. Schmidt	
Drug Company 94 102	
Remedy for toothache, neuralgia, burns, and	
wounds, topical. E. Dahlhaus	
tain J. Hungerford Smith Company 24.174	IMAGI
Soap, Wabash Soap & Chemical Company 24.187	
Trousers, Hull & Company	
Whisky, J. Cartun 24,200	

A printed copy of the specification and drawing of any patent in the foregoing list, or any patent in print issued since 1853, will be furnished from this office for 35 cents. In ordering please state the name and number of the patent desired, and remit to Munn & Co., 350 Broadway New York.

Canadian parents may now be obtained by the in-ventors for any of the inventions named in the for-going list, provided they are simple at a cost of \$40 each. If complicated the cost will be a little more. For full instructions address Munn & Co., 361 Broadway, New York. Other foreig pate to may also be obtained.



Canvassers wanted to sell the Improved Hall Typewriter Writes all languages. Price, \$30. Great inducements to agents. IS Send for catalogue and terms. Address N. TYPEWRITER CO.. 611 Washington Streets Roston. Nass. IS Mention Scientific American.

Batent 25-1b. Slow Feed Oat Mangers. Price **\$1.60.** VAN NESS CO., 50 Warren St., N. W. Y. WARNER, 140 N. Broad Street, Phila



LANTERNS J. B. COLT & CO., New York, Manufacturers. Catalogues and information Tree.

THE DENSMORE"

Did you ever consider that in typewriting the real work is performed at the keyboard-and the lessening of fatigue resulting from muchine with light touch? This is one of several essential features in which the Densmore demonstrably excels every competitor.

Recently awarded contract to supply machines to the U.S. War Dep't.

Now ready, the 1894 Model with strong new features, pronounced by Pres. Frisbee, Wells College, "a fine study," and by many others, "The World's Greatest Typewriter" indeed.

Represented in every large city. Pamphlets free.

Densmore Typewriter Co. 202 Broadway, New York

12,500 Receipts. 708 Pages. Price \$5. Bound in Sheep, \$6. Half-Morocco, \$6.50. This splendid work contains a careful compilation of the most useful Receipts and Replies given in the Notes and Queries of correspondents as published in the Sci-entific American during the past fifty years; together with many valuable and important additions.

Over Twelve Thousand selected Receipts are here collected; nearly every branch of the useful arts being represented. It is by far the most comprehensive volume of the kind ever placed before the public.

The work may be regarded as the product of the stud-les and practical experience of the ablest chemists and workers in all parts of the world; the information given being of the highest value, arranged and condensed in concise form convenient for ready use.

Almost every inquiry that can be thought of, relating to formulæ used in the various manufacturing indus-tries, will here be found answered.

Instructions for working many different processes in the arts are given.

Those who are engaged in any branch of industry probably will find in this book much that is of practical value in their respective callings.

Those who are in search of independent business or employment, relating to the bome manufacture of sam-ple articles, will find in it bundreds of most excellent suggestions.

IT Send for Descriptive Circular.

MUNN & CO., Publishers, SCIENTIFIC AMERICAN OFFICE, 361 Broadway, New York.

Founded by Mathew Carey, 1785. HENRY CAREY BAIRD & CO. Industrial Publishers, Booksellers, and Importers, S10 Walnut St., Philadelphia, Pa., U. S. A. EFOUR new and Revieed Catalogue of Practical and Scientific Books. 38 pares. 8vo, and our other Catalogues and Circulars, the whole covering every branch of Sci-ence applied to the Arts sent free and free of postage to any one in any part of the world who will furnish his to any of address.

HE POPULAR SCIENCE MONTHLY, now in its twenty-second year, discusses the practical sides of government and politics, domestic and social economy, education, sanitation, hygiene, food products and agriculture, natural history, scientific exploration, discovery, invention, the practical arts, the science of living. All articles are brief. The contributors are mainly specialists in their respective fields.

Sold everywhere, 50 cents a copy. bscription price, \$5.00 a year. D. APPLETON & Co., New York.

Has produced more ballast, road metal, and broken more ore than all other Breake s combined. Builders of High Grade Mining Machinery, for for the low more CATES IRON WORKS, o. Clinton St., Chicag 136 C, Liberty Street, New York. 237 C, Franklin St., Boston, Mass EAFNESS

GATES ROCK & ORE BREAKER

Capacity up to 200 tons per hour.



and HEAD NOISES relieved by using and HEAD NOISES relieved by using Wilson's Common Sense Ear Drums New scientific invention, entirely different in construction from all other devices. As-sist the deaf when all other devices fail, and where medical skill has given norelief. They are safe, comfortable, and invisible; have no wire orstring attachment. With for pamphlet. If Mention this gaper. WILSON EAR DRUM MFG. CO., LOUISVILLE, KY,

KNITTING MACHINERY. Knitted underwear is in vogue. The best

machinery for its manufacture. snch as SHIRT MACHINES, SLEEVERS, BAR STITCH MACHINES, etc., are made by SCOTT & WILLIAMS, 2077 E. Cumberland Street, Established 1865. Philadelphia, Pa., U.S.A.

LIFE SAVING DEVICES.— A COL-lection of suggestions of devices for communicating be tween the shore and stranded vessels, offered to the London Daily Graphic by various correspondents. With Tonious Lawy of the of various correspondents. With 100 illustrations. Contained in SCIENTFIC AMERICAN SUPPLEMENT, Nos. S43, S49, S50, S51, S52, S54, S61, S62, S64, S69, S71, S74 and SS4. Price 10 cents each, or \$1.30 for the series. To be had at this office and from all newsdealers.



Scientific American.





Star * Maps II(aps By Richard A. Proctor, F.R.A S.

× ×

A series of twelve elegantly printed Maps of the Heavens, one for every month in the year. Specially prepared for use in North America. With descriptions ccompanying each map, giving the names of the prin-ipal stars and constellations, showing their relative positions at given hours and days of the month.

A most beautiful and convenient work, specially adapted for the use of those who desire to acquire a general knowledge of the starry realms. To which is added a description of the method of

preparing and using artificial luminous stars as an aid in fixing in the mind the names and places of the various stars and constellations, by Alfred E. Beach. Altogether this is one of the most popular, useful and valuable works of the kind ever published One quarto volume, elegantly bound in cloth. Price 62.50, postpaid.

> MUNN & CO., Publishers, 361 Broadway, New York

SCIENTIFIC DIVERSIONS.-DEscriptions of some interesting and easily performed ex-periments. Cold water made to boll by the heat of the hand; the density of liquids illustrated; the draughting teetotum; the enchanted spiral; the wineglass pendu-lum-bob; steam balloons. With 6 figures. Contained in SOLENTIFIC AMERICAN SUPPLEMENT, No. 930. Price 10 cents. To be had at this office and from all newsdeelers.



PA

THOMAS DEVLIN & CO. C FINE THINNING AFE



URNISHED WECALDWEL

PUBLICATIONS FOR 1894.

The prices of the different publications in the United States, Canada, and Mexico are as follows:

RATES BY MAIL.	
The Scientific American (weekly), one year -	\$3.00
The Scientific American Supplement (weekly), one year,	5.00
The Scientific American, Spanish Edition (month- ly), one year,	3.00
The Scientific American Architects and Builders Edition (monthly), one year	2,50

COMBINED RATES.

	The Scientific American and Supplement \$7.00
	The Scientific American and Architects and Build- ers Edition, 5.00
t	The Scientific American, Supplement, and Archi-
Ĕ,	tects and Builders Edition, 9.00
t	Proportionate Rates for Six Months.
C	This includes postage, which we pay. Remit by postal or express money order, or draft to order of

Nepera Chemical Co., Nepera Park, N. Y. MUNN & CO., 361 Broadway, New York.



STEEL, IRON, COPPER, ZINC, BRASS, TIN, all other Metals Perforated as Required for Grain Cleaning and Min Machinery, Woolen, Cotton, Paper and Pulp Mills, Rice, Flour and Oil Mills, Suga Mait Houses, Distillaries, Filter Presses, Stone, Coal and Ore Screens, Brick an e Works, Filters, Spark Arr sters, Gas and Water Works, Oll, Gas, and Vapor Stove meeting, eds. Standard Sizes Perforated Tin and Brass always in Stoci And all other ing Machinery, and Malt Hou Tile Works, FY Coffee Machin THE HARRINGTON & KING PERFORATING CO., Chicago And 284 Pearl Street, New York.



Scientific American.



BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies. 25 cents. Thirty-two large quarto pages, forming a large and splendid Magazine of Architecture richly adorned with elegant plates in colors, and with other fine engravings: illustrating the most interesting examples of modern architectural construction and

of a variety of the latest and best plans for private resi-dences, city and country including those of very moderate cost as well as the more expensive. Drawings in

have won for it the Largest Circulation of any Architectural publication in the world. Sold by all news-