The limitations of the early manufacture of glass were an advantage to the early workers. The small size of the first sheets of colored glass made it necessary that the designer should execute his work in small pieces. insuring a juxtaposition of color. Much of the beauty which we now recognize and admire in old work is due to the fact that the artist or artisan was forced to subdivide his design into almost infinitesimal pieces in order to execute the same with economy in reference to material employed. Many happy accidents have thus been handed down to us.

The celebrated windows at Notre Dame owe their great brilliancy and charm of color to the above-mentioned fact. The celebrated glass at Saint Chapelle, so much written about, owes also its effect to this min uteness of detail.

The windows of the Seven Sisters in York Cathedral, England, are said to have been made by apprentices, and also, we are told, were executed from a lot of remnant glass that was supposed to be practically worthless. The result obtained was so successful, and has been so much praised by connoisseurs from that time to the present, that these windows now stand as possibly the best example extant of their peculiar kind of work.

If we look at the early Dutch, Belgian, French, or English specimens, we find practically the same influences at work in all these different schools-a certain simplicity of background with an elaboration of detail in some one central point, in most cases an escutcheon or family coat-of-arms. In the early Swiss glass we find this idea of centralization of ornament carried still further, while the regular escutcheon, family coat-ofarms, etc., were executed as in other cases, and imaginative center pieces were invented by the designer. Great numbers have been handed down to us, filled with all sorts of fantastic castles, knights, etc., just as the mood happened to strike the artist or artisan at work.

More elaborate glass treatment is to be found in the early figure work placed in the large cathedrals and churches throughout Europe. Here the same influence was at work, and in almost all cases secured an excellence of color which could not have been obtained by preconceived design, and that was the necessity of the workman to so subdivide his design as to represent all details by very small pieces of glass. The result in these larger windows was the same as in the smaller lights already mentioned, and beauty and juxtaposition of color was obtained, unsurpassed, unrivaled even at the present day.

Age has also added to the beauty of cathedral glass. The climate in certain countries, especially in England, has so soiled and dimmed these windows that they now have an artistic quality of color unrivaled by any work produced at first hands. This point was most strikingly exemplified when, a few years ago, an attempt was made in England to cleanse certain of the old cathedral windows, the beauty of which had been famous for many centuries. No sooner had the workmen performed their task than the windows were found to be crude and garish in color, much of the very quality which had caused them to be models for later glass work was destroyed, and the value of the windows completely lost. This is but one of the many instances which could be given to illustrate the statement that the peculiarity of the color of the old windows is produced by age and accident more than by the ability of the glass workers first executing them.

The modern glass worker is expected to obtain the rare color of the old work with the more perfect design and drawing of modern times. The task is not an easy one. In order to obtain the brilliancy of color of the old cathedral glass, the modern designer must of necessity so subdivide his window as to gain the same juxtaposition of color by the use of very small pieces. As these pieces are of necessity fastened together by the leads, the result is a large mass of black in the completed window. For this reason many black: in fact, the color is visible only on a bright, sunshiny day. This depth of color has been called for by the great number of black lines introduced, and by the mechanical necessity of putting the glass together with leads. An effort is being made at the present time to overcome this difficulty. The modern designer is attempting-with what success will soon be shown-to in color by the juxtaposition of different tones, but is

ing of any importance has some small portion of leaded glass. Every city hall, every State bouse, every private residence of any importance, has one or more leaded lights, in many cases a great number, and this constant demand for leaded work has created a school of glass in America which is unsurpassed by any other at the present day. The use of the delicate American opal for the accentuation of the ornament against a background either in clear white, white rippled, white Venetian or white cathedral, has opened up a field of design which has never been equaled.-Kate Field's Washington.

A FENDER FOR CABLE OR TROLLEY CARS.

The illustration represents a light and inexpensive device, readily transferable from one end of the car to the other, for picking up and carrying without injury until the car is stopped persons who may be caught in the way of a moving car. It has but few parts, may be readily raised and lowered by the gripman or motorman, and its supports are clear of the tracks, bumpers, and drawheads of the car. It has been patented by Mr. Louis F. Trinchard (address in care of F. Querens, Jr., P. O. box 905, New Orleans, La.) The main frame of the fender consists of two end bars, shown in full in the small figure, and a front bar held at its ends in the eyes of the end bars. A central intermediate semicircular socket section of the end bar rests on a pivot bar of a bifurcated hanger, there being a latch above the pivot bar, and the rear end of each end bar is received in an opening in a transverse suspension bar connected by a yoke with a bridge bar just behind the dashboard, as shown in the broken-away portion of the main view. On this bar is an elbow lever connected with a hand lever, by moving which to the right or left the fender may



TRINCHARD'S CAR FENDER.

be raised or lowered. The front bar of the fender frame has at its ends rollers adapted to travel on the rails when the fender is lowered.

Well Cared For.

This means much in homing pigeon keeping. Your feed must be of the best, and your supply of water the freshest and in plenty; also a pan of grit and ground oyster shells, good small Canadian peas, and some vetches, together with hulled oats, are the correct standard feed for the American racer at this period, with a few handfuls of small corn during an occasional cool spell or after a hard fly, and you must not forget the bathtub on every bright and warm day. The bathtub for the racing homer. I think, is a superb institution and works wonders, despite the fact that very many of the best Belgian fanciers rarely supply them to their birds. It is within the power of any of our of our most prominent designers have lowered the condition, if they are patient, attentive, and watch was soon put out, and not much damage was done. tone of glass so that their windows are almost their birds closely, giving them the best quality of feed This case recalls one reported from Louisville, Ky., a obtainable, and not try to breed from and race their few months ago, the Boston Journal of Common adds, birds at the same time. All this, coupled with a clean, sweet loft, ample ventilation, and enough exercise without fatiguing them, will certainly have good results; but if they think all this too much trouble and feed and breed indiscriminately, with lots of hemp seed, common and cracked corn, and lazily loaf around produce a stained glass window which is not only rich in the sunshine and the loft all day, then they will score more misses than hits, and the 200 miles station also light in color. The mechanical difficulties are will settle them sure.-Amer. Fancier.

Correspondence.

Repairing Commutators.

To the Editor of the SCIENTIFIC AMERICAN:

In your issue of April 27, G. H. G. asks for some composition for filling cracks in a commutator. You reply that the only way to repair will be to take the commutator apart and replace the mica. But if he happens to have no appliances for this work, a temporary repair can be made of thick shellac solution and dry plaster of Paris. Fill the crack with the shellac, then put on the plaster, kneading with a knife blade until it is stiff and smooth. Let it dry five or six hours or longer before scraping off the top even with the surface. It should be thoroughly dry before the armature is used.

I have used this method for repairing street railway motor armatures for more than a year, and no armatures have come back in that time for a fault due to this filling. A. A.

Covington, Ky.

A New Italian Lake.

To go to bed in a plain and to get up on the banks of a lake, to lie down an agricultural laborer and to wake a fisherman, is not a common experience, says the Florentine correspondent of the Scotsman, even in these days of telluric storm and seismic convulsion. Such, however, is precisely what has just happened, and not many miles from Rome. Alighting at the station of Monte Rotondo, famous for a Garibaldian victory, which preceded by a few days the Garibaldian defeat at Mentana on November 2, 1867, you proceed to Leprignano, not far from Castelnuovo di Porto. This is a hamlet numbering about one thousand souls, chiefly agricultural in their calling. It stands some 600 feet above the sea level, on a plateau to the right of the Tiber, near the valley watered by the Gramicia torrent. Few visitors but those interested in Etruscan antiquities are ever seen at Leprignano, quite unattractive as it is, except for the ruins of Capena, that ancient Etruscan city whose importance may even now be gaged by the number and quality of its tombs. On the morning of the 8th instant, however, the little hamlet was conscious of a profound rumbling, the preliminary to further sounds of similar import, announcing the noise it is now making in the world. On the 12th and 13th the rumbling was repeated, and on the latter date it was found that the soil occupying a space of six hectares had collapsed, and that the vacuum had been filled with water, forming quite a respectable lake. Sulphurous gases bubbled up to the surface, disclosing the springs from which the lake is fed, while from its raw margin emanated similar exhalations, finding their vent through the numerous cracks that run their eccentric course around it. All the countryside turned out to witness the improvised sheet of water, and some young peasants, more adventurous than their fellows, advanced toward the brink, only to feel the earth giving way beneath them and to get a good ducking. The extreme unsteadiness of the surrounding soil, indeed, favors the view that the lake will gradually widen in circumference, for already there have been landslips at various points of its margin, followed immediately by a rise of the water.

Fires Caused by Incandescent Lamps.

An investigation into the cause of a fire in a Winter Street dry goods store, in Boston, recently, resulted in demonstrating that an incandescent electric lamp will generate sufficient heat to set inflammable material into a blaze. The fire in question, for which a still alarm was given, was caused by allowing an incandescent lamp to remain for a few moments on a pile of cotton cloth in the packing room. The person in charge left the room for a few moments, not dreaming but that it was safe to leave the lamp on the cloth. young flying fanciers to bring their birds into fit racing When he returned the cloth was blazing. The fire

very great, but the improved leads now used, and the modern stiffening bar, it is hoped, will be able to overcome these.

In household work the modern designers may truthfully be said to have far surpassed the work of their ancient fellow-craftsmen. Outside of the simple, clear leaded lights of the Dutch and Belgian school, and the heraldic light of the middle ages with their coats-ofarms, escutcheons, etc., little household glass can be Now, however, this has been changed. Every build- in the atmosphere.

Honors for Lord Rayleigh.

The fortunate discoverer of argon has been made the a new light is attached the globe becomes only warm London Chemical Society.

A recent issue of the SCIENTIFIC AMERICAN (May 11, 1895) in a review of the late meeting of the National Academy of Sciences, held in Washington, also calls attention to the fact that the Barnard medal was this

which demonstrates the same thing. The fire started, says the Insurance Herald, while the window dresser was preparing a Christmas snow scene. The window was lighted with incandescent lights, which it appears had not been changed for a year, except when made necessary by accidental breakage. The carbon in an incandescent globe has a life of 600 hours, and as it wears out the carbon loop offers increasingly less resist-

ance to the current, and, therefore, increasingly more heat is thrown off upon the glass bulb and even upon the metal stems to which the globes are affixed. When

recipient of the Faraday medal, which is a gift of the under continuous use, but after it gets old the globes are hot and the stems attain burning heat. The dresser was filling the floor of the window with loose cotton upon cheesecloth, to represent snow. This was packed closely around the stems and globes of the electric lights, and there is no doubt that the inflamsaid to have been executed up to the present time. year given to Lord Rayleigh for his discovery of argon mable cotton, touching the burning hot stems and globes, caused the fire.