

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. LXXVI.-No. 14. Established 1845.

## NEW YORK, APRIL 3, 1897.

[\$3.00 A YEAR. WEEKLY.







LEFT MIDDLE FINGER MEASUREMENT.

RIGHT EAR MEASUREMENT.

TRUNK MEASUREMENT.

- HEAD LENGTH MEASUREMENT.



## MEASUREMENT OF THE STRETCH AND THE LEFT FOOT. THE BERTILLON SYSTEM OF IDENTIFICATION BY MEASUREMENT,-[See page 214.]

© 1897 SCIENTIFIC AMERICAN, INC.

# Scientific American.

ESTABLISHED 1845.

MUNN & CO., - - - EDITORS AND PROPRIETORS.

#### PUBLISHED WEEKLY AT

No. 361 BROADWAY, - NEW YORK.

#### TERMS FOR THE SCIENTIFIC AMERICAN. (Established 1845.)

#### The Scientific American Supplement (Established 1876)

(ESTIDITSTED 15/0) is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for the U. S. Canada or Mexico. \$6.00 a year, or £1 4s.8d., to foreign countries belonging to the Postal Union. Single copies 10 cents. Sold by all newsdealers throughout the country. See prospectus, last page. **Combined Rates.**—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to one address in U. S., Canada or Mexico, on receipt of seven dollars. To foreign countries, eight dollars and fifty cents a year, or £1 14s. 11d., postage prepaid.

#### Building Edition of Scientific American.

(Established 1885.)

THE BUILDING EDITION OF THE SCIENTIFIC AMERICAN is a large and splendidly illustrated periodical, issued monthly, containing floor plans and perspective views pertaining to modern architecture. Each number is illustrated with beautiful plates, showing desirable dwellings, public buildings and architectural work in great variety. To architects, builders, and all who contemplate building this work is invaluable. Single copies 25 cents. By mail, to any part of the United States, Canada or Mexico, \$2.50 a year. To foreign countries, \$3.00 a year, or ±0 128, 4d. Combined rate for BUILDING EDITION with SCIENTIFIC AMERICAN, to one address, \$5.00 a year. To foreign countries, \$6.50 a year, or ±16 8, 9d. Combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN, and SUPPLEMENT, \$3.00 a year. To foreign countries, \$11.00 a year, or ±2, 25, 2d., postage prepaid.

Export Edition of the Scientific American

## (Established 1878)

(Established 1878) with which is incorporated "LA AMERICA CHENTIFICA E INDUSTRIAL," or Spanish edition of the SCIENTIFIC AMERICAN, published monthly, uniform in size and typography with the SCIENTIFIC AMERICAN. Every number contains about 100 pages, profusely illustrated. It is the finest scientific industrial export paper published. It circulates throughout Uba, the West Indies, Mexico, Central and South America, Spain and Spanish possessions-wherever the Spanish language is spoken. THE SCIENTIFIC AMERICAN EXPORT EDITION has a large guaranteed circula-tion in all commercial places throughout the world. \$3,00 a year, or \$0 128, 4d., postpaid to any part of the world. Single copies, 25 cents. MUNN & CO., Publishers, 331 Broadway, New York. The safest way to remit is by postal order, express money order, araft or bank check. Make all remittances payable to order of MUNN & CO.

The Readers are specially requested to notify the publishers in case of any failure, delay, or irregularity in receipt of papers.

## NEW YORK, SATURDAY, APRIL 3, 1897.

#### Contents.

#### (Illustrated articles are marked with an asterisk.)

Archæological news	Manna of the desert.       212         Oath, the Hippocratic.       218         Paints, ready mixed*       212         Patent statutes amendments.       210         Patents granted, weekly record       0         Of       220         Photographs, luminous.       215         Science notes.       215         Sewing machine ripper, Batchelor       215         Ior S*       218         Steam engine, rotary*       218         Trolley, underground, New York 210       210         Water, some uses of.       215         Wax, grafting (7139).       220         Work, ouick.       218
Inventions recently patented 219	Work, quick

### TABLE OF CONTENTS OF

## Scientific American Supplement

## No. 1109.

#### For the Week Ending April 3, 1897.

Price 10 cents. For sale by all newsdealers.

PAGE
I. ASTRONOMYStory of a Celestial WandererAn article by Miss MARY PROCTOR
II DACTURDIOLOCY The Pasteriology of Mills 1779
II. BACIERIOLOGIThe Bacteriology of Milk
III. DYEINGEaster Egg DyesFormulas 1773
IV. EDUCATION.—Technical Education in Europe.—By C. P. BROOKS.—First installment of an important paper
V. ELECTRICITY – Watt and the Measurement of PowerBy WILLIAM HENRY PREECEAn interesting and important paper by a user promium classifician
Positions of the Magnetic Poles
VI. EXPLOSIVESTetra-Nitro-CelluloseA new explosiveBy H. N. WARREN
VII. MECHANICAL ENGINEERINGRotary Pumps and Engines.
- Their origin and later development. An important paper giv- ing a historical resume of the rotary pump from 1588 on, illus- trated with clear drawing showing the construction of various
forms of pumps and engines.—9 illustrations
motor.—6 illustrations 1773
VIII. METALLURGYNote on the Inter-diffusibility of Metals 1773
1X. MISCELLANEOUSA Convenient Reading Table for Students.
-A description of a curious revolving reading desk1 illustra-
tion 1773
The History of the Mirror 1773
Engineering Notes 1773
Electrical Notes 1773
Miscellaneous Notes
Selected Formulæ
X. NATURAL HISTORYThe Problem of InstinctBy ALFRED
R. WALLACE.—A most important study by a naturalist of great
Playfulness of Voung Tigers -1 illustration 1779
VI DALLWAVO A Circle Deil Deileren A description of the
Al. KAILWAYSA Single Kall KallwayA description of the
Calletet single ranway in which the cars are properted either by here $-7$ illustrations $1775$
Horses of by hand power.—/ mustrations
XIITECHNOLOGYThe Action of Oil on India Rubber 1773
XIIITRAVEL AND EXPLORATIONThe Insurrection in Crete.
-A graphic account of the exciting times in Crete by a corre-
spondent in Athens.—Fully illustrated with portraits and views
The Catacombs of Paris.—A description of the ossuary under-
neath Paris

### SECTION SEVEN OF THE AMENDMENTS TO THE PATENT STATUTES.

In a recent issue we commented editorially upon a bill embodying certain amendments to the patent statutes of the United States which had been signed by the retiring President in the closing hours of his administration. Our readers may or may not have noticed that, although we discussed the provisions of each amendment in detail, we were careful to place by itself, and publish without any comment, a certain section 7 which reads as follows :

"That in every case where the head of any department of the government shall request the Commissioner of Patents to expedite consideration of an application for a patent, it shall be the duty of such head of a department to be represented before the Commissioner, in order to prevent the improper issue of a patent."

Our silence with regard to this section was due to a reluctance to make any criticisms which might have been based upon a misconception of its real scope and purpose : for we are free to confess that at the first reading it appeared to be a most foolish, ill-considered, and unnecessary measure.

We eagerly sought for enlightenment as to the interpretation of this measure, being unable to grasp its full meaning ourselves. We were unable to obtain any explanation of the meaning of the amendment at the Patent Office; the chairman of the committee which formulated the original bill was no better informed, and we were finally referred to the author of the section in question. Briefly stated, it provides that where the head of a department undertakes to hasten a decision upon a patent application, he shall also take upon himself the responsibility of seeing that the Commissioner of Patents does his duty and does not issue the patent improperly. As it has been explained or otherwise, as he may choose, in order to prevent the improper issue of a patent which, being issued, may become a burden upon the government."

While we are satisfied that this amendment was protect the interest of the country at large, we think it with which the bill was finally pushed through.

The amendment certainly seems to take the form of Patents and the work of the Patent Office. If the is not so qualified, it must be either because of his inwe to suppose that the head of some other department or his irresponsible clerk would be more capable?

There is a further objection to the amendment in the fact that it places the head of a department in the anomalous position of being plaintiff and defendant at one and the same time. In one breath, as a supposed friend of the case, he urges that it be taken up for consideration, and in the next he is instructed to put obstacles in the way of the grant of a patent. The application is no longer a matter to be determined between the client's attorney and the Commissioner: but it must be argued in a triangular fashion between the attorney, the Commissioner, and a third somebody, whose claim to standing in the case is the fact that he has asked for its early consideration, and is there "to prevent the improper issue of the patent."

To appreciate this amendment at its full value, one has only to consider the history of the bill up to the time when section 7 was added. The bill was drawn up by a committee of the highest authorities and most distinguished practitioners of patent law-a branch of the law, be it said, which is admitted to be particularly complex and abstruse. The amendments carried the sanction of the American Bar Association, and they were only drawn up in their final form after extensive correspondence with patent solicitors and others specially learned in this branch of law. They then re-

stood as the friend of the inventor and would-be patentee.

Section 7 of the amendments, however, will change all this at a stroke, and inventors will in the future hesitate to disclose their plans to heads of departments who, if they considered that a patent would "impose a burden upon the government," would use every effort to secure its defeat.

### THE UNDERGROUND TROLLEY IN NEW YORK CITY.

The street railroad commission of New York has granted the application of the Metropolitan Traction Company to operate its lines by the underground trollev system—a change which will affect some forty miles of railroad lines in New York City.

It is a well known fact that the problem of transportation in New York presents special difficulties which arise from the nature of the site upon which the city is built. All the elevated and surface systems of transportation run mainly in parallel lines from north to south along the full length of the island. By far the greater part of the travel is in a north and south direction, and although the different arteries of travel lie but a block distant from one another, there is at all times of the day more or less crowding, and during the "rush" hours the congestion is attended with great discomfort and more or less delay. As the important change which is contemplated by the Metropolitan Traction Company is directed primarily to relieving the traffic upon the Broadway cable road, the lines which are to be electrically equipped are those which lie immediately to the east and the west of this road, and extend from the Harlem River south through the whole length of Manhattan Island.

The present Eighth Avenue horse car line will be equipped throughout with the new system. Commencby the author of the amendment, "He (i. e., the head ing at the Harlem River, the new line will run on this of a department) should be represented by his law officer avenue to Fifty-ninth Street, where there will be a cross line of the same construction from First to Tenth Avenue. From Fifty-ninth Street the new line will continue on Eighth Avenue over the present route to a terminus at Canal Street and Broadway. Another drawn up with the best of intentions and a desire to branch will start from Fifty-ninth Street and run down Sixth Avenue to West Broadway. At Fulton Street it possesses features which are strongly objectionable and will be carried east to Church Street, and through which have probably been overlooked in the haste Church Street to a terminus in Battery Place. The company has announced that the first part of the work to be undertaken will be the Sixth and Eighth Avenue a vote of lack of confidence in the Commissioner of lines below Fifty-ninth Street, and it is expected that they will be in running order by the middle of the au-Commissioner of Patents is not qualified to prevent tumn. The company intends to put in the same sys-"the improper issue of a patent," who is? And, if he tem on the Fourth and Madison Avenue line, which runs from the Harlem River to the Post Office. It will capacity or partiality. If he is incapable of judging also construct a line on Amsterdam Avenue, from Manwhat is proper or improper in his own department, are hattan Avenue to Sixty-fifth Street and through Sixtyfifth Street to Eighth Avenue.

It will be seen that the proposed system will give a greatly improved service between the northern and southern portions of the city. It will give a parallel service on each side of Broadway which cannot fail to relieve the congestion, especially in the lower city. The cross line at Fifty-ninth Street will very materially contribute to the convenience of cross town travel, inasmuch as passengers from Amsterdam Avenue and Eighth Avenue can cross over to Madison Avenue and continue down on the east side of the city, and on the other hand, passengers from the Harlem district over the Madison Avenue line can cross over at Fifty-ninth Street and continue down Sixth or Eighth Avenues to the shopping district, both of which journeys can be accomplished without change of car.

It is the intention of the company to push the work through with all possible dispatch, and have the whole forty miles of line in operation before the close of the year. If they succeed in doing this, it will rank as one of the most remarkable feats of railway construction on record of any kind, and will be entirely without a parallel in the records of street railway construction. The managers of the company claim that they will be able to build at this high rate of construction because of the comparative simplicity of the construction and the enormous force of men which they will crowd upon

ceived the careful consideration of the House commiteach section of the work.

tee; were passed by the House, and forwarded in due course to the Senate. Here, at the eleventh hour, without the knowledge of the gentlemen of the bar who formulated the bill originally and without consul tation with any who were likely to possess any special knowledge of such matters, this amendment was inserted, and the friends of the bill deemed it wisest to accept the amendment in order to avoid the in this way. defeat of the whole bill.

Looked at from any point of view, it is difficult to see what good this amendment can work to the government or to anyone else. It is certainly advisable that the heads of departments should be kept well advised as to the progress of invention in those fields with which the government is especially concerned; and it has been the custom of inventors to seek the advice of heads of department and their aid in hastening the hearing of such patent applications as might affect the <sup>9</sup> interests of the various departments. In this respect, a las far as it legitimately could do so, the government The iron conductors will be of a T-shaped cross section

It will be known to many of our readers that the Metropolitan Traction Company has been operating for some time several miles of underground trolley system on a branch known as the Lenox Avenue line This was built largely for experimental purposes, and the designs for the present proposed extensions have been based upon the experience which has been gained

In its broad features the construction will be similar to the one mentioned, which was fully illustrated in the SCIENTIFIC AMERICAN for February 22, 1896. The main features of the new system are as follows: The conduit, which is placed in the center of the track, carries two conductors, one for the supply and one for the return current. It will be shallower than the one on Lenox Avenue, and from the interior of the conduit an open passageway, about 5 inches in width, will connect with the street surface and will be closed with the customary slot rails, leaving a narrow opening for the plow.

and will be placed about six inches apart. They will be carried on every third yoke, and the yokes will only be about 70 per cent of the weight of those on Lenox Avenue line. The rails will be of the Crimmins type, which is designed to reduce the injurious effects from the wheels of street traffic. They will be exceptionally heavy, weighing no less than one hundred and seven pounds per yard, which is seven pounds heavier than the heaviest rail at present used on the trunk railroads of the country.

The estimated cost of the new lines completely equipped is between \$6,000,000 and \$7,000,000.

> THE "ROTARY" STEAM ENGINE. BY PROF. R. H. THURSTON, CORNELL UNIVERSITY.

The "rotary" steam engine, as it has been for a century called, is one of those seductive classes of mechanism which have been tantalizing the inventor and engineer for generations. From the time of James Watt, who a century and a half ago, nearly, devised this form of engine, it has been continually coming forward in shapes various, new and old, only to disappear promptly on being put to the test of daily operation under conditions permitting its exact performance to be ascertained. In Watt's patent of 1769, in its fifth claim, we read :

"5thly —Where motions round an axis are required, I make the steam vessels in form of hollow rings or circular channels, with proper inlets and outlets for the steam, mounted on horizontal axles, like the wheels of a water mill. Within are placed a number of valves that suffer any body to go round the channel in one direction only. In these steam vessels are placed weights, so fitted to them as to fill up part or portion of their channels, and yet capable of moving freely in them by the means hereinafter mentioned or specified. When the steam is admitted in these engines between these weights and the valves, it acts equal on both, and so as to raise the weight on one side of the wheel. and, by the reaction of the valves successively, to give a circular motion to the wheel, the valves opening in the direction in which the weights are pressed, but not in the contrary."

But far back of the days of James Watt are found the originals, the prototypes of the most successful of recent forms of rotary engines, of the steam turbines. Hero, of Alexandria, a century and more before the Christian era, published descriptions of the reaction steam wheel, and gave drawings showing its form and method of action. In 1629 Branca described the companion form, the "impact" steam turbine, which is to-day a favorite and successful machine in certain fields of work.\*

Since the beginning of the century thousands of inventors have attacked the problem, and hundreds of such inventions have been made, not one of which has been successful in competition with the reciprocating engine in its own wide field. The steam turbines are coming into use in the special field of high speed machinery, mainly in driving electric machinery. Here, too, it is only the simplest of all these forms, and the most ancient of types, which are in any sense successful. The steam turbines seem to have come to stay. For this there exist interesting and special reasons both theoretical and practical. The reasons for the failure of rotary engines as a class is a marked feature of the century of growth of the steam engine. Those reasons are readily discovered, as we shall presently see.

In the accompanying issue of the SCIENTIFIC AMERI-CAN SUPPLEMENT + will be found an historical review of the inventions of this class of engines, and its illustrations include practically every class of machine of this type yet produced, and even among these many resemblances will be noted, closely relating one to another. It will be seen that all come into one or another of these classes: (1) the simple system of gearing without valves, of which the now well known Holly engine and pump are typical examples; (2) the system in which the steam chamber revolves, and work is performed by reaction in a manner first investigated by Sir Isaac Newton; (3) the system in which the issuing jet of steam impinges upon the vanes of a revolving "steam wheel;" (4) that in which a rotary motion is given a wheel having fixed vanes, or some equivalent, by introducing sliding abutments and valves between which and the vanes of the wheel steam may be introduced and there may expand; (5) revolving wheels or disks, set eccentrically with the cylindrical casing, in such manner that sliding vanes, passing into and out of the wheel, may intercept the steam and compel it to act in such a way as to force the disk to turn. A wonderfully interesting collection, illustrating the ingenuity of the mechanic and inventor in a remarkable manner, is shown in the historical article referred to and our readers will do well to study it minutely.

usually are that it is superior to the reciprocating machine in simplicity, in its lower cost, its greater com- more, as computed by the best authorities to date. pactness, its less volume and weight as well, and, sometimes that it is more economical of fuel. The latter claim need not be here discussed further than to say it would seem that the mechanical and kinematic posthat it has no foundation in any case known to us. Fabulous claims are often advanced relative to the reduction of weight and volume effected by the use of of the rotary engine has been made integral with either these machines, and these are sustained in the case of of the constructions illustrated by us; no rotary has the steam turbine, of whatever form; as its enormous reduced the cost of power in steam consumed below speed of best effect permits corresponding reduction of the figures attained by even the ordinary reciprocating size for a stated power. The other forms have not yet proved superior to the now common high speed engine; which, in fact, has probably attained a higher speed than is usual with the rotary engines. For many years, a small engine, designed by Captain Ericsson, was in



THE GRECIAN IDEA OF HERO'S STEAM ENGINE. 120 B. C.

operation at the Delamater Iron Works, in this city, driving an electric lighting system, one of the earliest ever installed, and was regularly speeded at 1,250 revolutions a minute.\* The Brotherhood, a balanced reciprocating engine, is said to have been experimentally driven up to 2,700 revolutions a minute; but the steam turkines range between 5,000 and 20,000 with varying sizes, the smallest having, of course, the highest speed.

The essential, economical and practical characteristics of a thoroughly good steam engine to-day are: (1) Regular speed; (2) economy in the use of steam; (3) inexpensive construction; (4) compactness and lightness; with which qualities must always be combined safety in operation. The best modern reciprocating engines regulate to a degree of nicety which is quite wonderful. One firm of American builders guarantees a high speed engine, not to vary one revolution a minute from its rated speed, and the introduction of the later forms of shaft governor, with their peculiar "inertia effects," has made regulation practically perfect. The best contemporary construction of mill engine, with its high steam and multiple cylinder arrange



work. The birds weigh 25 to 50 pounds and sometimes

In all these respects the rotary engine has usually failed to satisfy the market up to the present time, and sibilities have been fully exhausted in the endeavor to solve the problem in this way. No perfect regulation machine; none has attained a higher maximum speed, the turbines excepted; none has been proved to have inherent possibilities of giving out power in larger proportion of work performed to weight or cost of the machine, when placed in competition with the reciprocating engine of similar commercial class.

The inherent difficulties meeting the inventor in this field are principally those of securing satisfactory regulation and especially of attaining a satisfactory economy of steam and fuel. A variable cutoff, adjustable by the governor, seems to be the essential feature productive of both economy and steady speed, and this has not been realized in such manner as to satisfy the market in this class of engines. Further, it seems practically impossible to avoid serious wastes by leakage in these engines, after a little wear, however carefully the machine may have been originally constructed. It soon loses its tightness, and steam pours past its valves and abutments.

The steam turbines, however, must be set apart from the other rotary engines, as possessing some peculiar and promising features, especially in respect to wastes of heat and steam. The common forms of steam engine waste enormously, especially in their smaller sizes, by the condensation of steam, at entrance, by the then comparatively cold cylinder wall, which is continually alternately heated and cooled by the prime steam and the exhaust. This fluctuation of temperature of the metal and of the water which is precipitated in the cylinder causes a waste of from twenty per cent, in the largest and best engines using dry steam, to fifty per cent, and often much more, of steam entering from the boiler; thus adding from twenty-five to one hundred per cent or more to the otherwise purely thermodynamic demand for steam and fuel. In the steam turbines, on the other hand, there is no such fluctuation of temperature of cylinder wall, and this machine is thus entirely free from the most serious, and often enormous, waste of the reciprocating engine. It is this fact which accounts for the remarkable economy often now attained with this class of engine, and once its speed is made satisfactory, or conveniently adaptable to ordinary machinery, it would seem that it might prove a formidable rival in many cases to the now standard forms of engine.\*

Should this prove to be the fact, we shall have the singular and interesting spectacle of the world going back to the time of Hero, two thousand years, to find the simplest and cheapest and most economical of steam engines.

## DIPHTHERIA IN COLD AND HOT COUNTRIES.

Dr. Schellong, of Königsberg, has recently published a valuable monograph in Virchow's Archiv on "Diphtheria in the Tropics." He admits the correctness of Trousseau's saying, that the disease in question is to be seen in all seasons and also in all climates. He shows, however, that this opinion is correct as far as mere distribution of the malady is concerned, but is otherwise misleading. Diphtheria is, in fact, very unusual in any tropical country, and when it occurs it is purely sporadic and always mild. Schellong has carefully investigated the sanitary records of low lying malarious plains in tropical islands and continents. but diphtheria has proved no more prevalent there than in high ground. The disease is very rare in the West Indies, Guiana, the coast of Brazil, tropical East and West Africa, Madagascar, Hindostan, and the Indian Archipelago. Hence dampness of the soil is not necessarily a cause of diphtheria, nor does it in any way promote its diffusion. It is not prevalent ven in the poor districts of crowded tropical tow On the other hand, it is frequent in the highland villages of Peru, and in subtropical districts and warm temperate climates-Havana, Jerusalem, Cairo, Santiago, Montevideo, the north of South Africa, and Brisbane, in Queensland. In temperate climates, south as well as north, it is almost universally distributed, the Cape, Adelaide, Sydney, Melbourne, Tasmania, New Zealand, and the south of Chile and Argentina being as little free from diphtheria as are the cities and villages of Europe, the United States, Japan, and northern China. As intense heat is experienced in summer in several of the places just mentioned, it would appear that perpetual heat is necessary to kill the germs of diphtheria, while a few weeks of cold keep it alive and allow the disease to be endemic even in Cairo and Brisbane. Schellong, who illustrates his monograph by means of a good chart, does not believe in racial immunity.-British Medical Journal.

The claims made by inventors of the rotary engine

\*"History of the Growth of the Steam Engine." R. H. Thurston "International Series." New York, London and Paris. Pp. 8, 17, 100.

+ The first of a series of articles upon the history, peculiarities and de fects of the rotary engine will be found in this week's issue of the SCIENTI-FIC AMERICAN SUPPLEMENT, which article will be continued in the two issues following .- ED.



BRANCA'S STEAM TURBINE, A. D. 1629.

ment, has brought down the consumption of steam to 12 pounds per horse power per hour. The costs of construction have become not far from \$10 per horse power for such engines as are supplied our light and power stations. The weights of reciprocating steam engines have been brought down from the half ton of a half century ago, per horse power, to one-tenth that figure ordinarily; and in marine, and especially torpedo boat construction, to one-twentieth and even less; while the aeronauts are building, as in the cases of Maxim and of Langley, steam engines lighter for their power than the swiftest birds that Nature has produced in her ages of steady evolution. Six pounds per horse power is now regarded by these inventors as a heavy weight for their

\* "Stationary Steam Engines for Electric Lighting." New York: J. Wiley & Sons.

\*The theoretically best speed of orifice is infinity for the "Hero engine" and about 1,000 feet per second for the single wheel guide curve turbine.

THE MANUFACTURE OF READY MIXED PAINTS.

No one who is unacquainted with the manufacture of ready mixed paints has any idea of the great amount of time and care which are expended in the mere operation of mixing. At first sight it would seem as though the proper mixture of white pigment with linseed oil could be easily secured, and was a very simple mechanical operation. As a matter of fact, however, the process is long and tedious, and requires the construction of a large amount of heavy and costly machinery. The quality of a paint depends very largely upon the intimate mechanical mixture of the atoms of oil and pigment, and experience has proved that this can only be secured by many hours of manipulation in the various agitators and mills of a paint factory.

The accompanying illustration, which is a vertical section taken through the factory of the James E. Patton Company, of Milwaukee, will give the reader some idea of the construction in a modern paint works. The operations commence on the highest floor of the factory and are carried on continuously in machines which are placed on the succeeding floors, the contents being finally gathered in storage tanks on the lowest floor. The first machine is known as a chaser, and it is here that the dry white pigments and the linseed oil first come in contact. Pigments and linseed oil are placed in the right proportion in an apparatus which works somewhat on the same principle as a common mortar mill. Here they are worked up into a rather stiff paste, and as soon as the mixture has reached the proper consistency it is dropped into a mill which is built somewhat on the lines of an agitator. From this mill the material passes through double mills located on the ground floor into a final finishing mill. In passing through these machines the paint is ground to a remarkable fineness, and as it leaves the last mill sufficient linseed oil is added to the mixture to bring it into the proper state of consistency for the brush. The paint is then carried into long, horizontal steel reservoirs, inside of which are shafts which carry a number of steel propeller wheels, which serve to keep the paint in a continual state of agitation. As the thrust of the wheels is in the direction of the final outlet from the tanks, they drive the fluid in that direction. Below the storage tanks is a series of large cylindrical tanks into which the white liquid is drawn in the quantities



ble proportions of coloring pigment with it, each tank having, of course, its own color.

Centrally placed within each tank is a vertical shaft. to which are attached a number of agitators, the shaft being driven by means of bevel gearing from a horizontal shaft arranged above the tanks.

The liquid in the storage tanks is kept in a state of continual agitation until it is finally drawn off into barrels for shipment. The constant agitation is necessary,



of course, to prevent the solid pigment from settling in the tanks, and it serves to keep the liquid paint at the proper consistency

Although the excellence of a paint depends largely upon the thoroughness with which the materials are ground and mixed, it is also determined largely by the quality and proportions of the pigments. It is a mistake to suppose, as many people do, that the body of all paints is formed of pure white lead. The product of the factory of which we are speaking consists of a mixture of lead with oxide of zinc or other unchangea ble pigments, the long experience of the manufacturers required. Here it is tinted by mixing certain unvaria- having shown, it is claimed, that these constituents, in the proportions employed, give a paint which is more durable and one that holds its color better than a paint which is made from pure white lead.

A NEW AUTOMATIC SCREW CUTTING DIE HEAD.

A new automatic opening and adjustable screw cutting die head, for use on turret head and other screw machines, is represented in the accompanying illustration. It is especially designed for threading the ends of bicycle hubs, tubing cups, cones and other bicycle fittings, as well as other short threads of a similar nature, such as used on water, steam and plumbers' specialties. The die head is provided with a central stop or gage, which may be adjusted to the length of thread to be cut. When the work strikes this gage the threading dies fly open, releasing the thread, and the die head may be withdrawn. The die head is also provided with a graduated adjustment, being entirely independent of the opening movement, and by means of which the dies may be set for cutting the required size. The head proper and shank is made in one piece, thereby securing great strength and rigidity. The front of the head is provided with four cross slides which carry the threading dies; the threading dies of course being interchangeable for those of other sizes of threads or renewable when worn out. The cross slides are provided at the back with lugs projecting into eccentric slots in a spring-actuated cam, a partial revolution of which in one direction closes the dies.

sufficient tension at all times for opening the dies. The which they again pass forwardly by an upper channel turn. Three screws in the hub of the back plate pass through the shank of the tool without touching it and serve to hold the gage in position. Two of the screws are fixed, while the third acts as an adjusting screw for varying the position of the gage. When the work

strikes the gage, the back plate is moved back enough to release the locking pin from the cam, which instantly flies around and the dies are opened. The locking pin passes through a circular slot in the back platelong enough to allow all necessary adjustment for the diameter of the screw. The index plate covers the slot, and by a pointer indicates the adjustment by graduations on the circumference of the back plate, the graduations being made to read by hundredths. The die head is closed by the small handle shown, and the dropping of the locking pin into the hole in the cam locks the dies securely. The die head may also be closed automatically by means of a pin screwed into a threaded hole opposite the handle, and attaching a taper piece to the tail stock or bed of the machine, which will engage the pin as the head is brought back. It will be seen that every part of the die head is most effectively protected from chips and dirt.

This die head is manufactured by the Geometric Drill Company, New Haven, Conn., who have established a wide reputation for the ingenious tools and high class of workmanship they produce, being especially identified with their patent system of geometric drilling and turning. They also have the distinction of making the smallest as well as the largest automatic screw-cutting die head for turret lathe use, as they furnish these tools for threading any size from No. 17 wire gage to 6 inches diameter inclusive.

## AN IMPROVED BOILER.

The illustration represents a boiler in which a series of segmental and longitudinal water legs form passages or channels for the products of combustion, the channels being connected together alternately at opposite ends of the boiler, whereby the products of combustion are caused to traverse the channels consecutively. The improvement has been patented by Thomas Barnes, of Vancouver, Canada. An auxiliary shell is formed in its lower half with a water leg sufficiently depressed at its front end to afford room for the fire box, ash pit, etc., and the fire box at its rear end opens into channels formed by water legs, one of which extends about half way the length of the boiler, while the other extends from one head of the boiler to the other. There is a hood on the front end of the boiler into which the channels open, and on its rear end are two hoods, one above the other, the lower one being water jacketed and the upper one being held on the rear end of the shell, the hoods being preferably made in the shape of hinged segmental doors, so that they may be readily opened for conveniently cleaning the channels as well as the flues. The latter are somewhat less in diameter than the inside width of the corresponding water leg, so that each flue is completely surrounded by the water in the leg.



A NEW DIE HEAD.

while a movement in the opposite direction throws When the hoods are closed, the smoke and gases from the them open. The spring which actuates the cam has fire box pass by the lower channels through the lower one end fastened to a small collar held in position on rear hood, then forwardly and through the front hood, the shank by small set screws, and is gaged to give and by other channels to the upper rear hood, from



THE PATTON PAINT MILLS, MILWAUKEE, WIS.

back plate has a slight movement endwise, but does not and flue to the smokestack. The boiler is provided with suitable drain pipes and manholes, and is designed to utilize the heat generated to the fullest advantage.

#### The Manna of the Desert.

The manna sent to the Israelites on their journey out of Egypt to the Holy Land is regarded as identical with an edible lichen in Kerner and Oliver's "Natural History of Plants," and the older view that it was the sap of a tamarisk, exuded under the influence of a parasite, is held to be without foundation. Mr. M. J. Teesdale reviews the subject in the February number of Science Gossip, and the evidence he brings forward is opposed to the conclusion to which reference has been made. He shows that an exudation from the twigs of the tamarisk (Tamarin gallica) has more points of resemblance with the manna of the Israelites than either the edible lichen or the sweet gums exuded by leguminous shrubs, such as Alhagi maurorum or A. desertorum-both known to the Arabs as camel's thorn.

## SCENES ON THE COLUMBIA RIVER, OREGON.

We have been favored by Mr. H. H. Shank, of Hagerstown, Md., with the accompanying photographs and some notes of characteristic scenes on the Columbia River, Oregon, which were gathered during a recent tour in the far Western States.

been confined to the Old World, but include (as they too seldom do) a tour among the natural wonders of his native land, is impressed with the inconsistency of those people who roam, year by year, among the mountains, lakes and rivers of Europe, and neglect the natural beauties of their native land. Majestic and impressive as the Alps may be, they do not lift their heads any more grandly than the summits of the Rockies, the Cascades or the Sierras; and nowhere are they clad with such a wealth of noble verdure as is spread about the base of our Western mountains. The Rhine may seem to sweep in stately fashion beneath beetling cliffs and hills that soar loftily above its waters, but in the presence of the awe-inspiring heights and depths and changing shadows of the "Gorge of the Columbia River," the Rhine becomes an insignificant memory, and the mind's sense of dimension is baffled in the effort to take in this infinitely greater, nobler and more majestically beautiful Rhine of our native land.

All too little known by the tourist is the land "where rolls the Oregon;" and those Eastern travelers who chance to spend a few weeks under its cloudless summer skies, where the atmosphere is so clear that mountain peaks which are over one hundred and fifty miles distant from the spectator stand out with clear cut profile, and on every side the eye roams easily over unwonted breadth and distance of landscape-such travelers experience a sense of novelty and change which the mere summer trip to Europe can never awaken.

'The Gorge of the Columbia" is the name given to a great natural rent in the wall of the Cascade Mountains, through which the Columbia River finds it way to the Pacific Ocean. In places the towering walls of rock rise for thousands of feet all but perpendicularly from the edge of the waters. Elsewhere the slope is more gradual and the inclination will be maintained with remarkable regularity from the shores of the river to an altitude of many thousands of feet. Elsewhere again the sides of the gorge are rent into fantastic and colossal

the accompanying illustration. They are situated on the Oregon or southern side of the river, and stand out apart from the parent cliffs in solitary grandeur, guarding, like a pair of giant sentinels, the line of the Transcontinental Railroad that threads its way between solitary pine, secure from the woodman's ax. In some course of the river through the gorge, finding a pre- for common salt in order to compensate for its loss gineering will be installed. The machinery hall will

carious footing between beetling cliff and foaming torrent, with the occasional variation of a long viaduct or "trestle" of timber to carry it across the bed of a mountain waterfall. Of the latter there are several, the most notable being Latourelle Falls, a few miles down the river, where a stream leaps over 400 feet from the overhanging precipice, and Multnomah Falls with its unbroken fall of 850 feet.

About sixteen miles below The Dalles, an important river

#### The Craving for Salt.

spondent writes that this subject was discussed at a restated that sodium chloride was consumed as an article whose ashes were washed and their potassium salts of necessity by nearly all races, and that most of the crystallized out. The traveled American whose journeyings have not lower animals were fond of it, although there were ex- Samples of the salt had been analyzed and found to be



HERCULES PILLARS-DETACHED PILLARS OF ROCK ON THE BANKS OF THE COLUMBIA RIVER OREGON.

liking for the salt than the carnivora, and in the same way agricultural populations, who were more or less vegetarians, were invariably large consumers of it. The tribes who ate no salt led a pastoral or nomadic existence, whose regimen was almost exclusively animal. them. On the very crest of the larger rock stands a This, said the writer, had led Bunge to formulate the theory that as vegetables contained principally po-



of the French Congo, between Lake Sangha and Lake In a recent number of the Lancet the Paris corre- Tchad. Salt was unknown in this vast territory, which was as large as France; for it was substituted an artificial cent meeting of the Société de Biologie. M. Lapicque salt extracted from a certain number of selected plants,

> composed of potassium salts only. When, on their first entrance into the country, the French had endeavored to sell common salt they found it unsalable, the natives preferring their own. This disposed of the theory propounded by Bunge, and, the writer thought, weakened another theory advanced by Ringer and others, who maintained that potassium salts had the property of a protoplasmic poison and cardiac depressant.

> M. Lapicque inclined to the belief that salt was of use only in procuring for man and animals a gustatory stimulus. M. Trouessart stated that dearth of salt in besieged cities had been made up by the use of saltpeter. M. Giard told his colleagues the story of the chimpanzee of the London Zoological Gardens, which, deprived of salt, had taken to drinking its own urine. As soon as it had been provided with a block of bay salt it had ceased to drink its urine, and used to sleep with the salt held tightly in its arms. According to M. Samson, oxen and sheep would, on large farms, abstain for weeks together from the salt placed within their reach, while at certain other periods they ate largely of it. This variability of appetite for salt was due to the variation, according to the season of the year, of their diet.

## Stockholm Exhibition.

The Stockholm Exhibition of 1897 will comprise engineering, building industry, machinery, implements, transport, shipbuilding and navigation, electricity, fisheries, military science, sport, traveling, fine arts, education and instruction, hygiene, scientific appliances, etc. The site of the exhibition, according to Kuhlow's German Trade Review, is commodious and picturesque, and will include the Northern Museum and the Bostrom Villa. The exhibition buildings proper are numerous, and the more important are to be, it is said, very striking. The large hall for the industrial section occupies a good position on an elevated terrace, and it is claimed for it that it is one of the largest wooden structures ever built. The building will have a dome 300 feet high, surrounded

shapes. Two of the most noted of these are shown in ceptions to the rule. The herbivora betrayed a greater by four turrets, of which some, if not all, will be fitted with elevators. The view from these points will be a striking one, the environs of Stockholm being of unusual beauty. At each side of the central structure will be a pavilion. To the left of the entrance is the building for the various offices, and those of Norway, Sweden, and Denmark are located there. To the right lies the Northern Museum, which respects the journey by this railroad is one of the tassium salts, these latter replaced the sodium salts in is still in course of erection, and where in an auxiliary most picturesque in the world. It follows the tortuous the economy, and the vegetarian instinctively craved building the sections for hygiene, education, and en-

be situated at the Saltsjön and will be built of iron and glass alone, with an area of about 100,000 square feet. The fisheries exhibition will be located on the borders of the sea, and there will also be found the exhibition of boats, etc. Fishery forms one of the more important industries in Sweden, and this section is to be made large and interesting. The section for forestry will also be comprehensive, as will the agricultural section, the agricultural department being much interested in the

shipping point for the produce of Eastern Oregon, is Memeluse Island, situated well out in the middle of the river. Memeluse is the Indian name for dead, and this island of the dead was formerly used by several of the local tribes as the last resting place for the bodies of their memeluse friends whose spirits had embarked for the happy hunting ground. The Indians do not inter their dead, but place the body upon a raised staging, upon

matter. The art exhibition will in all probability be entirely international. There will be three large halls for Sweden, Norway, and Denmark, and smaller buildings for other countries. The two large universities in Sweden -Lund and Upsala-will also be represented, as well as the medical college, Stockholm.-Journal of the Society of Arts.

MEMELUSE ISLAND-AN INDIAN BURIAL GROUND ON THE COLUMBIA RIVER, OREGON.

A GERMAN antarctic meteorological station will shortly

which are also placed certain of the belongings of the through the kidneys. This theory was, however, weak, be established in Victoria Land. The station will be deceased. It takes but a few years' exposure to the for it did not explain why certain peoples who had not run in connection with the German South Polar Expedition, which will have for its object the determielements to reduce such a burial ground to the access to sea salt replaced it by salts of potassium obnation of the meteorological conditions during the condition shown in this weird reproduction of the tained by the incineration of plants. camera.

## Such a people were the negro inhabitants (a million) severe antarctic winter.

#### THE BERTILLON SYSTEM OF IDENTIFICATION BY MEASUREMENT.

It is estimated that there are about 1,500,000,000 people upon the face of the earth at the present time. If any one had been so bold as to affirm, only a few years ago, that it would be possible to give such a description of any one individual that he could be positively identified among all these millions, his statement would have been met with ridicule. To-day, however, thanks to the researches of Quetelet, the Belgian scientist, and the subsequent labors of Dr. Alphonse Bertillon, a celebrated French anthropologist, we are able to record such a detailed description of any given individual that his identification becomes a matter of absolute certainty.

Although it is true that the Bertillon System of Anthropometric Identification, as it is called, is primarily intended for the prevention of crime, this is only one of the objects of the system. In every case where the establishment of the identity of an individual is desirable, whether for his own benefit or that of his family, or the State, this ingenious and highly scientific system may be applied. The victims of the cable car or the railroad accident, the slain upon the battlefield, the unclaimed bodies at the city morgue, all present cases for which Bertillon has made full provision: and in instances where the body has been mutilated be yond all possibility of recognition by the usual methods of identification, the system would be simply invaluable. Further instances of its possible usefulness would have been the prevention of frauds on the United States Pension Bureau by parties who have assumed the name and condition of others, the detection of false claimants to estates, the prevention of the landing of Chinese who come to this country bearing the name and papers of others of their countrymen who have returned to China. It requires a long acquaintance with this race to be able to distinguish one celes tial from another, and by the present methods of identification it is almost impossible for the government officials to detect a fraud of this kind.

Perhaps there is no sphere in which the benefits of the system would be more immediately felt than in the army, where it would act as a check upon desertion from the very day of its introduction. In time of war, moreover, it would serve as an infallible identification of the killed and wounded, and in subsequent years, as suggested above, it would prevent fraud upon the Pension Bureau of the country. The question of its introduction into the army is being actively urged by Dr. Paul R. Brown, United States Army, to whom we are indebted for valuable assistance in the preparation of the present article.

The Bertillon system for measuring criminals has re- middle finger tip of the left hand. The trunk measure- would mean slightly concave, without brackets or un-

ceived its most extensive trial in France, where it has been carried out for over ten vears with the thoroughness for which the police of that country is famous. It is in general use also in Belgium, Switzerland, Russia and several South American republics, and is being tested in England. It was introduced into the United States by Major R. W. McClaughry in 1887, and is now in operation in Illinois. Michigan, Wisconsin and the State of Massachusetts. It was adopted by the police department of the city of New York on March 6, 1896, and in May of the same year its use was made obligatory in all the prisons and penitentiaries of the State of New York.

The accompanying illustrations show the practical operation of the Bertillon system at police headquarters in this city. It varies in no essential particulars from that of the countries and States above mentioned, only such slight modifications as were suggested by local conditions having been made in minor details. The system is made up of three distinct parts. First, the measurement of certain unchangeable "bony lengths" of the body; second, a careful description of the features of the face; third, a careful localization of all the scars and marks upon the body. Of these three the first records are by far the most important, because the most permanent and unalterable. Bertillon states that the experience of the last ten years has shown the "almost absolute immutability" of the human frame after the twentieth year is passed. The great diversity of dimension which the skeleton shows in different subjects, and the facility and precision with which it may be ment, or the height of a man when seated, is taken by details regarding the marks, scars, etc., upon the body. measured, render this means of identification by far the most reliable that could be adopted. Increasing age and mutilation will produce changes in the features, but they cannot affect the measurements of the frame. The analysis of the features of the face, and the description and localization of scars upon the body, add their accumulated testimony to the unchanging record of the measuring apparatus.

The bony or skeleton lengths adopted by the police department as admitting of easy measurement and description are as follows: The length and width of the head; the cheek width; the lengths of the foot, the middle finger, the little finger and the cubit, that is, from the elbow to the tip of middle finger; the height standing; the height seated; and the stretch; and in addition to these the right ear length, which, while not a skeleton measurement, remains virtually the same through life.

The apparatus which is used for taking these dimensions is very simple, as will be seen by reference to the illustrations. In taking the height the criminal is made to stand barefooted with his back to the wall and his



backbone to the left of the graduated vertical scale. The square is then brought down with its vertical edge in contact with the vertical edge of the scale and the height read off. About three feet to the left of the scale is a vertical strip which projects about an inch from the wall, and on the opposite side of the scale is a horizontal scale with long graduation lines, as still to the wall, is made to extend his arms and move to the right or left until the tip of the middle finger of



Bridge a Border

over the back of the head. The thumbscrew is then tightened and the measurement checked by passing the instrument again over the head. The width of the head and over the cheeks is taken in the same way.

The measurement of the foot is taken with a caliper rule somewhat similar to that used by a shoemaker. The subject is placed on the stool, standing on his left foot and steadying himself as shown in the illustration. The graduated stem is placed against the inside of the foot with the fixed arm in contact with the heel. and the sliding arm is then brought in lightly against the toe. Care is taken as before to check the reading.

In measuring the left middle and little fingers, the back of the caliper rule is used, two small projections being provided on the fixed and sliding arms. The finger to be measured is bent at right angles to the back of the hand, and the measurement is taken from the tip of the finger to the knuckle, as shown.

The cubit measurement is taken from the elbow to the tip of the middle finger. The forearm and hand are placed, with the palm of the hand downward, upon the surface of a trestle on which is a caliper rule; the edge of the table, the axis of the forearm and hand, and the graduated stem of the rule all being parallel. The elbow is placed against the fixed arm of the rule, and the loose arm is then brought up to the middle finger and the measurement read off on the scale.

The measurement of the right ear is taken with a caliper rule, which has a flat fixed branch which is steadied by pressing it against the head and is brought down until it grazes the upper border of the ear. The stem is held parallel with the axis of the ear, and the loose arm is pushed up until it just touches the lobe of the ear.

It will be apparent to the reader from this description and the illustrations that this system will give a series of very accurate measurements. As each one is read off it is written down on a printed card, similar to the one which is shown on this page.

The measurements being all taken, the next analysis is that of the features of the face. As these are liable to change with age or disfigurement, no measurements are taken, but, instead, an elaborate and exhaustive description is given. Taking the nose as an example, the profile of the bridge may be rectilinear, convex or concave, and the term sinuous might be applied to qualify each of the above descriptions. Thus a nose might be convex sinuous, that is it might be generally shown in the illustration. The criminal, with his back convex and also somewhat undulating in contour. Then again each of these types might vary so far as its base was concerned, this being either elevated, horizonthe right hand touches the vertical strip. The meas- tal or depressed. The subdivision might be carried urer then presses the arms of the subject lightly against | still further by certain arbitrary marks as follows: [conthe wall and reads off the "stretch" as indicated by the cave], concave, concave, where in brackets the word

> derlining it would mean moderately concave, and underlined, it would mean extremely concave. This system of seriation could be applied to any features of the face. The eyes will vary from the pale blue of the Scandinavian to the very dark brown of the negro. In the Bertillon system there are seven distinct classes of eyes enumerated, with nine subdivisions. The mouth, the chin, the brow, have all been analytically classified, divided and subdivided - even the complexion being noted in respect of its coloration, which may vary from the sanguineous coloration of the florid Englishman to the pigmentary coloration of a dark Italian, with all the intermediate graduations between the two extremes.

The third step in registering a criminal is to make an exact record of all scars, marks or deformities. To assist in locating these on the body, certain anatomical points, known as "guiding points," are employed, and the particular mark is described as being such a distance from one of these points.

Finally, the subject is placed before the camera, two negatives, a full face and profile being taken and the nhotograph are mounted in the center of the identification card.



#### IDENTIFICATION CARD.

squarely upon it with his back to the wall, and taking the height as before with the portable square.

The measurements of the head are taken while the subject is still seated and are read off on a pair of calipers provided with a graduated arc. In taking the length the left point of the calipers is held at the

We reproduce a fac-simile of the style of cards in use at the police department of the city of New York. In addition to the data recorded on the face of the card, there is provision on the reverse side for recording the particulars of the name, aliases, crime, date of sentence, peculiarities of habit, criminal history, etc., and there are six ruled spaces for inserting

placing a stool against the wall, seating the criminal After each card has been made out in duplicate and filed, the examination is complete, and the department is in possession of a means of future identification which may be said to be absolutely infallible.

The method of filing the cards adopted at the identification bureau in Paris, over which Dr. Bertillon still presides, is as follows : The cards are filed in two large root of the nose, and the right point is brought down cases, in one of which they are classified alphabetically,

and in the other according to measurements or anthropometrically. The latter case is divided horizontally into three equal compartments for lengths of head, and into three vertical divisions for breadths of head, and there are other subdivisions for the three classes of finger, foot, and cubit lengths. The cards are filed in boxes numbered I to V according to the above leading measurements. If the police desire to know whether a criminal has been previously measured, he is identified or otherwise by looking in the alphabetical collection; that is if he gives his right name. If the prisoner claims that he has never been arrested before, he is measured and search is made in the measurement collection. The head is say 187 millimeters. The medium head measures from 185 to 190 millimeters; so the card is put in the medium class. This eliminates 100,000 cards from the 150,000 in the collection. The breadth of head being below medium, two-thirds of the 50,000 are eliminated, leaving 16,666. The middle finger eliminates some thousands more, bringing the remainder down to 5,555. The length of the foot reduces the number to 1,850, and the cubit length brings it to 620. Following out the process in respect of the height, little finger, ear, trunk and stretch, the remainder is represented by a dozen cards which are classified according to the color of the eye. The card is now located, and the photographs and facial description place the identity of the two cards beyond the possibility of a doubt. Our sketches were made at the Identification Bureau of the New York Police Department through the courtesy of Commissioner Andrews.

## Luminous Photographs.

These photographs, according to J. A. Randall in an article on "The Magic and Mystery of Photography," published in the American Journal of Photography, January, were first introduced at a ball in Vienna. where programmes were decorated with a luminous picture representing an alchemist at work. "There are several ways of making luminous photographs, the simplest being that of W. B. Woodbury. A sheet of cardboard is coated with a luminous paint and exposed to light under a glass positive or transparency. On removing the cardboard to a dark room a striking and brilliant phosphorescent image is seen, with all the gradations of the positive. The effect may also be produced by arranging a series of glass tubes, containing a phosphorescent substance, behind a thin glass positive; on exposure to light the luminosity of the tubes will shine through the positive in proportion to its density. When viewed in the dark, a glowing image is the result. Another method, which can be applied to an ordinary print on thin paper, is as follows : Take a sheet of cardboard, and spread over it as evenly as possible a thin coating of starch paste; when still tacky dust over it an even layer of powdered calcium or barium sulphide, rubbing it well over with a brush to make it adhere in every part. Then take the print, which should be light, and fixed and toned as usual, and saturate it with a mixture of castor oil and oil of turpentine, taking off all excess with a clean rag. The print, thus made semi-transparent, is next pasted upon the prepared cardboard, and the whole well dried before the fire. A print thus prepared, when exposed to light, receives the rays on the phosphorescent sulphide beneath, which becomes luminous in proportion to the absorption which has taken place; it is therefore luminous in the dark by the light transmitted. A silver print is soon destroyed by this process, for the sulphide attacks the image; it can be applied to the carbon or other processes not having silver as a basis. Moonlight pictures and landscapes give the most striking effects as luminous photographs."

#### **← ● →** Some Water Uses Well to Remember.

The Phrenological Journal gives the following useful hints on the applications of water in severe attacks of illness. The adult members of a family should keep them in mind for an emergency.

A strip of flannel or a soft napkin, folded lengthwise and dipped in hot water and wrung out, and then about one-seventh of the heat passes away by direct raapplied around the neck of a child that has the croup, diation.

#### Science Notes.

The roller steamer Ernest Bazin has been finished at Rouen and will shortly have a sea trial.

P. Regnard and T. Schloesing have examined the gases obtained from a liter of blood, and found that they contained 20.4 c. c. of nitrogen and argon, the latter gas accounting for 0.419 c. c. of the mixture. In addition to satisfying themselves that argon is dissolved in the blood, they state that if there is an increase in the amount of nitrogen present, there will also be an increase in the amount of argon.—Comptes Rendus, exxiv, 302.

The Swiss government has sanctioned the manufacture and use of weights made of glass. They are of slightly conical shape with rounded bottom edge, and provided on top with a knob to facilitate handling. The designation is moulded into the knob. The glass used for these weights is of special composition, highly refined, and carefully annealed so as to reduce to a minimum the danger of breakage.

We regret to record the death of Mr. Harry Proctor, youngest son of the late R. A. Proctor, whose name was for many years so closely associated with the English scientific journal Knowledge. He died or December 20 last, after having recently attained his majority. The young man, like his father before him, betrayed a predilection for things scientific; but, unfortunately, constitutional weakness thwarted all serious efforts in this direction.

The largest spectroscope in the world has just been completed by Mr. John A. Brashear, of Allegheny, Pa. the well known astronomical instrument maker. It was made for the private research laboratory of Dr. Hans Hauswaldt, a wealthy scientist of Magdeburg, Germany. The instrument contains a concave diffraction grating with 110,000 lines per inch, made on the famous ruling machine of Prof. Henry A. Rowland, of the Johns Hopkins University.

"It has been found by M. J. Puluj," says the Electri cal World, "that substances which fluoresce most brightly under the visible cathode rays give off the greatest amount of Roentgen radiation. M. Puluj believes that Roentgen ether waves originate in the bombardment by negatively charged molecules from the ca thode and in the abrupt loss of charge in these. He finds that these Roentgen ether waves may cause fluor escence of calcium sulphide, but believes that invisible as well as visible radiations emanate from a screen of this substance. M. Puluj states that vacuum tubes of all kinds glow when subjected to the action of Roentgen rays.

M. B. Renault has long worked at the indications of bacteria found in geological strata, and now publishes the general result of his observations in a paper illustrated with a large number of drawings. As might be expected from their simple structure, bacteria appear to have been coeval with the first appearance of organic life on the earth, the coccoid form being appa rently earlier than the bacillar. Indications of their presence are found in bone, teeth, scales, and coprolites, as well as abundantly in vegetable tissues, the spores and sporanges of ferns appearing to have been especially subject to their attacks. The species are, as a rule, distinct from those at present in existence. Ann. des Sciences Naturelles (Botanique), 1896.

Professor Meidinger, of Carlsruhe, finds wonderfully little difference between the heat radiating power of a Bunsen flame and that of an illuminating gas flame, per unit of area, that is. In this he confirms the conclusions reached in 1865 by Prof. Magnus, who also found that making a Bunsen flame luminous by means of salt, etc., did not increase its radiative power. The inference would be that there is next to no actually solid substance in a luminous flame, or else that the higher temperature of a Bunsen flame (1,750° C. as against 1,300° C.) makes up for its deficiency in solid particles. A gas blowpipe flame, on the other hand, rapidly falls off in heat radiating power as the air is more and more forcibly driven through it. From an ordinary Bunsen flame, says the Progressive Age, Prof. F. Plateau, of the University of Ghent, has for many years carried on a series of observations on the mode in which insects are attracted to flowers, the results of which are published in the Bulletin of the Royal Academy of Sciences of Belgium. His conclusions are not in accord with those of Darwin, that the bright color of the corolla acts as a beacon to attract Nothing so promptly cuts short a congestion of the insects. He believes that they are attracted chiefly by some other sense than that of sight, probably that of smell. In the case of the dahlia (single) and other species of Compositæ, the removal of the conspicuous ray florets had but little effect on the visits of insects nor had the removal of the conspicuous part of the corollain other flowers, as long as the nectary remained. On the other hand, says Nature, the artificial placing of honey on otherwise scentless flowers resulted in their being immediately visited by numbers of insects. Where the same species varies in the color of the flower, Ordinary headaches almost always yield to the as between blue and white, or red and white, insects simultaneous application of hot water to the feet and visit quite indifferently flowers of different colors belonging to the same species.

#### Archæological News

An excellent guide to the archæological treasures of Rome has recently been published by a well known German archæologist, Herr Helbig. It is a most useful work for any one who wishes to make a study of the art treasures of the Eternal City.

In a paper read before a late meeting of the Paris Academy of Sciences, by M. Berthelot, on "The Age of Copper in Chaldea," the author said the analysis of a spear carrying drawings and inscriptions, and at least 4,000 years old, showed that the metal was nearly pure copper, neither tin, lead, arsenic, nor antimony being present in appreciable quantities. The oxidized portion was nearly pure atakamite, 3CuO.CuCl<sub>2</sub>+4H<sub>2</sub>O. The description of these and similar objects as bronze is shown to be erroneous. Copper appears to have preceded bronze in the manufacture of tools.

The plans for the restoration of Malmaison, which were prepared with the aid of M. Daumet, are now complete, says the Architect. The estimated cost of the works is 480,000 francs, and does not comprise the outlay on the decoration of the interior or on the gardens. M. Osiris, who has enriched France with so many costly memorials, intends to have the restoration scheme carried out in its integrity. Malmaison will recall associations of Bonaparte and Josephine for many a year to come. The charge of the building will be undertaken by the Department of Fine Arts. The coming international exhibition has incited M. Osiris to further generosity. In 1889 he offered 100,000 francs to reward the author of the work which was considered to be most interesting as an example of art, industry or public utility. A similar sum will be available for the exhibition for 1900, and, as in the former case, the selection will be left to the syndicate of the press.

Under the will of the late Lady Wallace, the whole of the collections at Hertford House, Manchester Square, London, so far as they are contained on the ground floor, the first floor, and the galleries, have been bequeathed to the British nation, on condition that the government shall provide a site in some central part of London and build a museum to contain the collections, which are to be kept together and styled the "Wallace Collection." The collection is probably the finest private one in the world, and its money value is roughly estimated at considerably over \$5,000,000, and some experts have even estimated the value as high as \$17,000,000. The Borghese, the Lichtenstein, the Ellesmere, and perhaps one or two of the collections of the Rothschild family may equal or surpass it in pictures alone; three or four houses in Europe may have as much old furniture of the highest class; possibly in Germany or Austria some one might be found with as good armor. But it is the combination of all these things, and of many other departments, that makes the Wallace collection unapproachable.

The fiftieth anniversary of the founding of the French school at Athens, Greece, is to be commemorated by an archæological congress to be held in Athens from April 26 to 28 of the present year, says Architecture and Building. The announcement is made by a committee composed of the rector of the University of Athens, the general ephor of antiquities at Athens, and the heads of the various archaeological schools under the presidency of M. Homolle, director of the French School. It is proposed that this congress, in case the experiment proves a success, shall be the first of a continuous series of such congresses, to be held at such places and times as the congress itself may determine. In case this congress is made a permanent institution, it may meet in future years at different cities of Europe and America. The subjects proposed for discussion in the congress are such as have a general interest and bearing. The discussion of purely scientific problems is not proposed so much as the consideration of practical questions of method in the organization of work and questions of educational interest.

We have several times, says Nature, called attention to Dr. G. Folgheraiter's interesting observations on the magnetization of Etruscan vases. Hitherto there has been a slight uncertainty as to whether the magnetization may not have undergone some modification during the many centuries that have elapsed since these vases were baked. In his latest contribution to the Atti dei Lincei, Dr. Folgheraiter dispels any doubts on the matter by his observations on some vases which were pieced together from scattered fragments discovered in excavations at Arezzo. If the magnetization of the terra-cotta had in any way altered since they were broken, it is clear that the different portions would have been differently affected, and the mended vases would have shown somewhat irregular magnetization. So far from this being the case, they were found to be as regularly magnetized as those which had been excavated entire, the opposite poles at the mouth and base being exactly 180 degrees apart. The only remaining element of uncertainty is what was the orientation of the vases in the kiln; and Dr. Folgheraiter hopes that further excavations may lead to the discovery of potteries of the Etruscan epoch containing vases in situ. Should he be successful, we may look forward to exact determinations of the magnetic elements, which will greatly add to our knowledge of terrestrial magnetism.

will usually bring relief in a few minutes.

A proper towel folded several times, and dipped in hot water, quickly wrung and applied over the site of toothache or neuralgia, will generally afford prompt relief.

This treatment for colic has been found to work like magic.

lungs, sore throat, or rheumatism as hot water, when applied early in the case and thoroughly.

Hot water taken freely half an hour before bed time is an excellent cathartic in the case of constipation, while it has a soothing effect upon the stomach and bowels.

This treatment, continued a few months, with the addition of a cup of hot water slowly sipped half an hour before each meal, with proper attention to diet, will cure most cases of dyspepsia.

back of the neck.

# Scientific American.

## [April 3, 1897.

ter shows that the elevation

is constantly increasing. Near

the margin, where the elevation is slight, the summer sun

has melted the surface, so

that it is solid and hard and

firm under foot. Its surface is pitted by circular depres-

sions caused by melting, and

the walls of these wells are

seen to be made of pure ice.

If the journey chances to be

the glacier that is rapidly moving, the surface is so

rough that traveling across it is impossible. Within

a few miles of the margin, the elevation of the ice is

one or two thousand feet above the sea level, and look-

### A NEW FAST JOB PRINTING PRESS

Printers everywhere cannot fail to be interested in the fast automatic feed card and envelope press shown in the accompanying illustration, which has been recently patented in the United States and sevthe Harris Automatic Press Company, of Niles, Ohio. like northern Europe and America, with many penin- It looks like a plain, but as one traverses it the barome-

In all considerable job printing offices a number of presses are usually kept employed on small work, such as the printing of cards and envelopes, etc., about a thousand impressions per hour being the ordinary rate of speed, and each press requiring the close attention of a feeder. The Harris press is self-feeding, the cards and envelopes being supplied to it by the pack, and it works easily at speeds ranging from 8,000 to 10,000 impressions per hour. Working at this rate, it is about as much as one hand can do to open envelope boxes or packages of cards for feeding, and replace in the boxes or packages the printed work, but the feeding, printing and delivery are automatically performed. The press is designed to do all classes of work, from the finest half tone on glazed cards to the thinnest manila envelopes, taking sizes from the smallest envelope corner to  $a_{11} \times 13$  inch plate. It prints from curved electro or stereotype plates, readily adjusted to exact position on the impression cylinder by clamps, and adapted to be "underlaid" with good results, as the plates are only three-sixteenths of an inch thick, the "making ready" of all kinds of jobs being thus greatly facilitated.

The points which will first attract the attention of the practical printer are the nicety and exactness of the

feed and the connected parts. The cards or envelopes are placed in a pile within the space formed by the vertical rods or posts in front of the impression cylinder, these guards and supports being quickly adjustable for all sizes of stock, and the bottom card or envelope is automatically pushed forward by the feeding mechanism to the printing cylinders. For envelopes the flap is engaged by fingers, by which the envelope is fed forward through a gate, so nicely adjusted, according to the thickness of the paper, as to prevent the passage of more than one envelope at a time.

In printing cards, the bottom card of the pile is pushed forward by fingers which extend beneath the card, but which have on their upper face an adjustable flange or lip, to be raised just sufficiently to nearly equal the thickness of the card. In the adjustment of this lip or flange, as in that of the gage to prevent more than one card or envelope to be passed at a time to the printing cylinders, the devices are very simple, and admit of almost instantaneous adjustment for any special thickness of cards or paper. The feeders are carried on a light reciprocating frame, and, should an envelope or card fail to be fed forward, an automatic throw-off device lowers the impression cylinder and a friction clutch or brake stops the press, thus preventing the smearing of the tympan sheet and the spoiling and wasting of stock. The press gives perfect register, the stock being "overfed" against adjustable gage stops on the impression cylinder and held there by two short tapes until pressed under the types, and the adjustment of the impression is easily and accurately made when the machine is running at full speed. The printed stock is delivered on a circular tray at the back, the tray betribution and roller adjustment and interchangeability apparently leave nothing to be desired. The company making outfit. The press occupies a floor space of 3 feet 6 inches by 5 feet, and weighs 1,100 pounds.

## THE GLACIERS OF GREENLAND. BY PROF. RALPH S. TARR

That great triangular area of land between northern Europe and America, by some strange reason called Greenland, is almost entirely covered by snow and ice. ing onward toward the interior of Greenland, there is a eral foreign countries, and is being manufactured by Its margin is that of an extremely irregular land quite great plateau or mountainous expanse of snow and ice.



## THE HARRIS AUTOMATIC CARD AND ENVELOPE PRESS.

sulas projecting, and many fjords, bays and straits in- | land, this interior must be a highland of mountains and denting the coast. The projecting parts of the land, irregular topography, but it is entirely smoothed over the peninsulas and islands, are mainly free from glaciers, though even upon these, in the protected valleys not only obscured the topography of the land, but has and on the higher peaks and plateaus, there are gla- raised the level of Greenland far above the normal. It ciers of great or small size. However, taken as a whole, is impossible to say how much this snow fall amounts the margin of Greenland is free from ice. All the to in the course of a year, but it can hardly be less interior is ice covered and the total area of the ice is than ten feet. Practically none of this melts and but a estimated to be about five hundred thousand square portion of it is blown away to regions where melting miles. In some parts of the interior this great ice cap | can occur. Hence, if no means of escape could be attains an elevation of not far from ten thousand feet. | found, the elevation would continue to increase prac-



made during the autumn, it is possible that the form of precipitation may be that of snow: but it is very much more likely to be in the form of rain. However, as the high interior is approached, the climate becomes colder and colder, and even in summer rain does not fall, nor does the surface of the ice cap melt and show the solid ice of the glacier. It is then a snow-covered glacier, sometimes with hard surface, at other times enveloped in soft and drifted snow. According to the description of Peary, the summer climate in the interior of Greenland is one of the most disagreeable of any that have so far been found in the world. This constant fall of snow, with almost no loss by melt-

ing, has completely buried the interior of Greenland. Whatever the land condition beneath the ice may be, it is so effectually buried that even the great irregularities appear to produce no effect upon the surface of the ice cap. Judging by the margin of Green-

tically indefinitely. A thousand years at this rate would increase the elevation ten thousand feet. It happens that the ice find means

by the ice. The fall of snow in summer and winter has

of escape other than that of wind action and melting. As the snow accumulates, the pressure of the crystals against one another, under the burden of the snow above, causes an increased compactness, and eventually a change from the loose condition of snow to that of solid ice, as one may change a snowball to ice by pressure. There is a question in the minds of some whether ice is a viscous body or not, and hence it may be well not to speak of it here as a viscous substance. In any event, it cannot be denied that ice moves and behaves like a viscous body. If we should pile a mass of wax upon a table and subject it to pressure, it would spread outward from the center of pressure in all directions, because the wax is a viscous body. The same is true of ice, which, although apparently brittle, will flow when subjected to a strong but slowly applied pressure. The weight of the accumulation of snow in the interior of Greenland squeezes this ice that has been formed and causes it to move outward from the center of greatest elevation. ing slowly revolved and thus laying out the printed After passing the land margin of Greenland one It is possible also that this movement is aided somematter in such a way as to prevent offset. The ink discomes to an ice wall, sometimes very precipitous, but what by gravity, for it may be that the land base in more often sloping so that it can be ascended. This the interior of Greenland is higher than the land wall rises one or two hundred feet above the base, and margin, and that there is, therefore, a gradual slope No means of determining the rate of this ice movethough if by chance the ascent is made on a part of ment are at hand. The studies of the Greenland ics

Fig. 1.-LAND MARGIN OF CORNELL GLACIER.

furnish with the machine, when desired, a small plate then the ascent becomes more gradual. Here the sur- from inland to the sea. face of the ice is generally smooth and easily traversed,

sheet have been entirely too limited in number to allow even a guess upon this point. Some of the tongues from the ice have had their movement measured, but the great ice cap itself has never been studied from this standpoint. One has but to look at the glaciers of Greenland to see that the rate of motion of the ice cap is exceedingly slight, probably to be measured by only

sea. The ice from the interior advances toward the sea and then, as it comes to this margin, changes its course course changed nearly at right angles to the general direction of the movement of the ice cap itself.

land has a slope of considerable steepness, and in some somewhat in accordance with the topography. It cases a precipice of ice from fifty to one hundred feet slopes down into the valleys and in some cases has its in height. The ice rests directly on the ground and is evidently in motion. The evidences of movement are in the first place the banding of the ice, a banding due If one should travel across Greenland near the coast, to layers of gravel and pebbles whose sources must be

As has been said, the edge of the glacier near the

a few inches a year. If the movement were more rapid than this, the surface would be broken by cracks caused by the strains on the ice as it moved over its bed. Cracks or crevasses are confined to small portions of the glacier where the ice is moving down the valley toward the sea, and hence moving rapidly.

The surface of the glacier is absolutely free from all foreign materials, with the exception of moraines, which extend seaward from the few mountain peaks that rise above the surface of the ice near the margin. Beyond the limit of mountainous islands m the ice, or nunataks, even this supply of débris is absent. The second exception is found in a small amount of dust transported to the ice surface from the land by the action of the wind.



at some place other than their present position, for oftentimes there are pebbles of rock different in kind from that over which the ice is moving. The second evidence of motion is found in the more or less continuous series of low hills and ridges of gravel and bowlders which have been brought by the ice and piled at its foot. There must be a supply for this material, much of which is foreign to the region, and this supply is of course the ice. In order to bring them, it must of necessity have moved. As it comes to the margin, where it is ending, it is prevented from proceeding further, partly because its movement is then diagonal to the general motion of the ice sheet, and hence down into the valleys, and partly because the melting by

Fig. 2.-NORTHERN END OF GLACIER, SHOWING ICEBERGS AND FRAGMENTS OF GLACIER ICE FLOATING IN THE FJORD.

and over the ice surface near the margin there is a considerable quantity of it. It represents the acto darken the surface of the glacier. Indeed, it generally remains below the surface at a depth of a few inches or a foot; for, being dark in color, it absorbs the solar heat and bores its way into the ice by warming and melting it. Making a beginning of this sort in one place, the dust from other neighboring areas is washed toward the depression, and so a considerable quantity -perhaps as much as a quarter of a pound of dust—is found in a depression whose diameter is six or eight inches. The hole is bored into the ice only so far as the sun's rays can reach directly, which, of course, is not very far in this latitude, where the sun does not rise high in the heavens. These dust-filled depressions are known as dust wells, and they render the surface of the

the winter they are frozen over and buried beneath the snowfall. The next summer they are perhaps reached again by the melting and added to by the accumulation of that year. In the meantime they are moving onward toward the margin and finally disappear into the sea with the ice itself. There is a zone extending from the land outward for a distance of a few miles where these dust wells occur. Beyond this zone, partly because the dust does not reach so far and partly because the melting action of the sun is not powerful enough to cause the wells, these phenomena are not observed.

Moving onward toward the sea in all directions, the ice near its margin encounters different conditions in different places. The movement of the ice in the glacier is in some respects not unlike that of a river. It resembles the river in this respect that it will seek and follow the lowest ground; but it differs in doing this less rapidly and successfully. Coming to the land margin, the glacier finds the topography to be irregular. There are hills, and ranges of hills, with intermediate valleys; and while, within terminate in the sea, there are two important condi- which during the summer season varies from a few a few small portions or valley glacier tongues into the ties, but must break.

a bay, then another small peninsula or series of islands, little further inland, where the ice exists, he would at along the contact of this with the land, crossing a divide, as he did upon the land, and then, descending, would cross the very rough surface of an ice tongue, which extends down toward the fjord valley, and finally he would again ascend to another divide. From is a distinct slope downward on both sides, and it is glacier near the land margin exceedingly irregular. In numerable crevasses, some of which are very deep. So the accumulation of a moraine, or a barrier caused by

the summer sun pre-This dust is made of extremely fine particles of clay, and parallel to the general trend of the coast line, he vents its further progress. Evidence of this melting would pass over a mountainous peninsula, then across is partly the piles of accumulated materials at the base of the ice sheet and partly the drainage along cumulation of years, and is not in sufficient quantity and so continue in succession along such a series of the margin. This marginal drainage of the ice is valleys and hills. If the journey happened to be a exceedingly interesting. The water is furnished chiefly by the melting of the ice, and it comes not merely first pass over an ice covered highland, or possibly from melting on the front, but also from the surface. Every few feet along this margin there are tiny cascades and rills, and in some cases even rivulets, flowing rapidly down the front, and joining the stream that skirts the margin of the ice between the glacier and the land. Sometimes the water which flows one divide of the ice cap margin to the opposite there along the margin is deflected from the immediate contact of the ice, and is forced to pass down some evident that the ice is slowly moving down this slope, steep and rocky slope, forming then a beautiful cascade while in the central depressed portion of the glacier or waterfall. At other times it escapes beneath the ice, tongue proper the movement is outward to the sea, through a tunnel, reappearing again at distances varywith such rapidity that the surface is cracked by in- ing from a few feet to several hundred yards. Again

> ice, prevents the water from passing along as a stream and transforms it locally to a lake. These marginal lakes, some of which cover an area of a square mile, are exceedingly abundant, and in them the streams are depositing clay beds.

> Along this land margin one can sometimes penetrate beneath the glacier in one of the ice caves which the marginal streams have cut in the glacier. Here he can see the ice, with a load of rock for tools, engaged in carving its bed. The bowlders and gravel in the bottom layers are firmly frozen in the ice, and, as they are dragged along, they are grinding upon the rock, for they are the tools with which the glacier does its work of erosion. Along these bottom layers the ice is discolored for variable distances, sometimes to the height of one hundred feet above the base. This discoloration is due to rock fragments that the ice is carrying, and at first glance one gets an erroneous impression concerning the amount of this material that is being carried. Where streams have cut valleys in the ice front, as they course down its margin, it is seen that the discolora-





Fig. 3.-DISTANT VIEW OF LAND MARGIN OF CORNELL GLACIER.

the margin of the ice, all the land excepting the high- | rough is the surface by reason of these crevasses, and | tion of the ice surface is due to the action of meltest peaks is covered, the ice movement at the margin is the effects of melting, that it is practically impossible ing, which has washed down over the surface a sheet mainly down the valleys. Therefore, since the valleys to cross the surface. The rate of glacier movement, of rock fragments which have been derived from only a relatively few layers. Above its bed the ice is carrytions along the ice margin, the contact of the greater feet to nearly one hundred feet a day, is so rapid that ing only a small amount of debris, and this decreases part of the ice with the land itself, and the entrance of the ice cannot bend when it passes over the irregulari- as we ascend, until, finally, the upper part of the glacier is pure, clear, white ice. Where it is present in clear ice.

Another kind of glacier front in this region is the sea wall of the valley tongue which is in rapid movement. This in places rises one or two hundred feet above the water, and extends to depths several times as great beneath it. As seen from the fjord it is a wall in any position by removing and inserting a pin. On of marble whiteness, absolutely free from all impurities. Whatever rock debris the ice is carrying into the sea it is transporting below the water level. The top of this ice front is extremely irregular, partly by the cracking along the crevasses and partly by the action of melting. It is so irregular that travel over the end of the glacier is an impossibility.

In the front of the ice one sees numerous cracks, and the whole mass has an extremely unstable position. That this cracking does really represent instability is every now and then plainly proved, by the reports that proceed from the ice front, and by the fragments which one may see drop from its top and sides. Along the front of a large glacier there is a constant shower of these ice fragments, and the sea near by is littered with the bits of the glacier that have thus fallen into the sea.

Not only are fragments thus broken off by the melting and cracking above the water, but the ice is made unstable by the action of the waves at the shore line. When the tide is low one may see extensive undercut cliffs and sea caves of ice, which add distinctly to the instability of the ice cliff. This loss from the glacier front partly balances the advance, but not entirely. As one watches the front of one of the Greenland glaciers, every once in a while he sees a great block, hundreds of yards in length, crack off from the ice front and float away. Sometimes this ice breaks off from the glacier without producing much commotion, but much more frequently the masses of ice fall forward as they break off, and stir up the water, producing waves whose effects are felt miles away. The reason for the breaking off of these large bergs is the advance of the glacier into the fjord so far that the buoyancy of the water lifts and cracks it.

Hence the glacier which covers so large an area of Greenland advances outward until it is either destroyed by melting along the land margin or until it reaches some place in the sea where it breaks off and floats away. So long as the supply and these causes for the destruction of the glacier exactly counterbalance one another, the front of the glacier will remain permanently in one position; but if the supply exceeds, then the front of the glacier must advance upon the land and extend farther out into the sea; but, on the other hand, if the causes of destruction exceed the supply, the front of the ice must withdraw. This withdrawal may be accounted for either by a decrease in the supply of snow or a change in the climate, which causes an increased melting.

Studies along the margin of Greenland show that land now bare has within very recent geological times been encompassed by ice. In that part of Greenland near latitude 74°, where my studies were carried on, I found proof that the glacier has reached at least thirty miles further, covering all the land, some of which reaches nearly three thousand feet above the sea level. This means a very much greater extent of ice than the present. Even now the glacier is in process of retreat, and moraines that were evidently built at the base of the ice are now at some distance from it. Some of these moraines have been left by the ice so recently that no vegetation whatever, not even lichens, has found time to develop on the rock. Therefore, even at present the Greenland glacier is engaged in a withdrawal from the land, and this has been in progress for some time and has succeeded in uncovering a part of the margin of Greenland. How far this will go, and whether Greenland may again become the seat of a temperate climate and the site of a temperate flora, as it was before the glacial period, no one can even estimate.

Cornell University.

A FIRE ESCAPE AND WATER TOWER. The illustration represents an improved fire depart-

the bottom of the glacier, it is stratified with layers of the lazy tongs on one side are pivoted to a platform to be raised, and the corresponding members on the other side carry rollers which loosely engage the under surface of the platform, the latter having posts and chains forming a railing on its sides and ends. On the platform is a turntable which may be turned to and locked an extended portion of the turntable is pivoted a ladder, connected near its outer end to a yoke from which a rope passes over a pulley at the top of a post on the turntable and thence to a windlass, by means of which the ladder may be placed at any desired angle to connect the turntable and platform with the window of a building, the ladder preferably being made with extension sections, and its position as extended being indicated by the dotted lines. On the front of the truck platform



### HENNESSEY'S FIRE ESCAPE AND WATER TOWER.

frame is a reel, one end of the shaft of which is hollow and adapted for connection with a water pipe, the inner end of the shaft being connected with a hose wound on tice my Art. I will not cut persons laboring under the reel, and the outer end of the hose being connected with a threaded pipe in the platform raised by the are practitioners of this work. Into whatever houses lazy tongs, the latter pipe being adapted to receive a hose nozzle for the use of the firemen. The lazy tongs. guy rods or ropes leading to the ground.

### BATCHELOR'S RIPPING ATTACHMENT FOR SEWING MACHINES.

The illustration represents a simple device readily attachable to a sewing machine table and operated by a lever connected with the needle bar for rapidly ripping seams or cutting material. It was patented in July last by Francis M. Batchelor, of Portland, Oregon, and, as will be seen by the accompanying letter, this inventor has sold his patent for a handsome sum of money. The following letter speaks for itself:

American Steel Company,

Portland, Oregon, March 6, 1897.

Messrs. Munn & Company. Gentlemen: I am pleased to advise you that I have just sold my United States patent, No. 569,827, which you obtained for me on the 28th of last July, for \$50,-000 spot cash.

If it will do you any good or be of any interest to your readers, you are at liberty to use this information in any of your several publications.

#### Very truly yours, F. M. BATCHELOR.

Fig. 1 is a sectional side view and Fig. 2 is a plan



slot in a lever, G, fulcrumed and held vertically adjustable at the upper end of a post, H. The outer end of the lever has an elongated slot engaging a stud, J, secured on the needle bar, K. The table carrying the ripping attachment may be readily adjusted and secured in proper position on the sewing machine table. We desire to congratulate Mr. Batchelor upon the success he has attained with his patent. His letter was sent to us without any solicitation on our part.

#### \*\*\*\*\* The Hippocratic Oath.

A correspondent of the Medical Record seeks information regarding the Hippocratic oath, taken by physicians upon graduation.

He states that he has inquired as to the substance of this oath of many physicians, who have been unable to give him a satisfactory answer. It is highly probable that but a few of our best educated physicians ever knew the text of the oath they were taking. The Medical Record gives the following translation of the oath in full:

"I swear by Apollo the physician, and Æsculapius, and Health, and All-heal, and all the gods and goddesses, that, according to my ability and judgment, I will keep this oath and this stipulation—to reckon him who taught me this Art equally dear to me as my parents, to share my substance with him, and relieve his necessities if required; to look upon his offspring on the same footing as my own brothers, to teach them this art, if they should wish to learn it, without fee or stipulation; and by precept, lecture, and every mode of instruction, I will impart the knowledge of the Art to my sons, and those of my teachers, and to disciples bound by stipulation and oath according to the law of medicine, but to none others. I will follow that system of regimen, according to my ability and judgment, I consider for the benefit of my patients, and abstain from whatever is deleterious and mischievous. I will give no deadly medicine to any one if asked, nor suggest any such council; and in like manner I will not give to a woman a pessary to produce abortion. With purity and with holiness I will pass my life and practhe stone, but will leave this to be done by men who I enter, I will go into them for the benefit of the sick, and will abstain from every voluntary act of mischief when in extended position, are preferably steadied by and corruption, and, further, from the seduction of females or males, of freemen and slaves. Whatever in connection with my professional practice or not in connection with I see or hear, in the life of men, which ought not to be spoken of abroad, I will not divulge, as reckoning that all such should be kept secret. While I continue to keep this Oath unviolated, may it be granted to me to enjoy life and the practice of the Art, respected by all men, in all times. But, should I trespass and violate this Oath, may the reverse be my lot."

#### Laws of Teaching.

1. There is no school unless the father, the mother, the teacher, and the pupil keep school together.

2. Know thoroughly the subject to be taught and

explain to the pupil why you teach it. 3. Gain and keep the attention of the pupils. Excite their interest.

4. In your teaching use language that your pupils understand.

5. Begin with the known and go by easy steps to the unknown. Take the whole class with you !

6. Excite self-activity in the pupils and lead each to discover truth. Show the class how to study.

7. In each lesson let a halt be made and then have pupils fix points already made, the conclusions reached, view of the improvement, the knife, A, sliding in a slot and the premises upon which the conclusion is based.

8. The teaching must touch the whole nature of the child and stimulate to higher action and more industrious habits of work, of silence, of obedience, honesty and truthfulness. Three-fourths of education is a habit of work.-J. M. Greenwood in Midland Schools.

## A Quick Piece of Work.

ment apparatus by which a platform may be readily raised and lowered to make connection with windows, enabling the firemen to enter the upper stories of a building for rescuing persons and facilitating the throwing of streams of water where desired in a burning structure. The improvement has been patented by Michael W. Hennessey, of No. 203 Sands Street, Brooklyn, N. Y., the inventor being chief machinist on the United States cruiser Columbia. On the truck is a platform frame, and means are provided for readily swinging the platform into level position when the truck stands on uneven ground. On the platform are two pairs of connected lazy tongs, the lower members of which on one side are pivotally connected with a stationary bracket, while the other lowermost members | in the apex of a peak-shaped rest, B, secured on a table, are pivotally connected with a cross piece sliding in bearings and formed with screw nuts in which screws a longitudinal screw rod. The outer end of this rod carries a hand wheel, by turning which the cross piece is moved forward or backward by the screw rod, closing guide, E, engaging a vertical slot, A<sup>2</sup>, in the blade, and

SEWING MACHINE RIPPER-A \$50,000 INVENTION.

C, resting on a sewing machine table, D. The material to be ripped or cut is advanced on the apex of the rest against the cutting edge of the reciprocating knife. ting in the foundations, steam mains, and air piping The latter is guided in its up and down movement by a required for the apparatus. The heating plants were completed and the building ready for occupancy within or opening the lazy tongs. The uppermost members of in the upper end of the knife is a pivot, F, engaging a one week from the date of the fire.

One of the quickest pieces of work on record in the way of installing a ventilating plant was recently completed at Harrisburg, Pa., says the Engineering Record. It may be remembered that the building containing the assembly rooms of the Senate and House of Representatives at the State Capitol was destroyed by fire on February 2. An unoccupied church was temporarily secured, but this building being without a suitable heating plant or any ventilation whatever, it was necessary to install a new plant before the building could be occupied. Accordingly, an order was telegraphed on February 4 to a blower company, instructing them to ship two 6,000 foot coils with 60 inch fans as soon as possible. One apparatus was placed on board the cars within twelve hours and the duplicate within thirty hours from the receipt of the order. In the meantime, a large force of men was at work on the ground, put-

## RECENTLY PATENTED INVENTIONS. Engineering.

SMELTING FURNACE.-Charles Bishop, Tacoma, Washington. For fusing all kinds of ore, using oil as the fuel, and with or without charcoal mixed in the ore, this inventor has devised a furnace whose combustion chamber has its bottom formed into a chamber to receive the molten metal, the grate being at the lower end of the stack and in an inclined position over the com bustion chamber, into which discharge a number of fire boxes connected with an oil supply. The lower end of the grate projects into a slag discharge which leads to the outside of the furnace.

#### Railway Appliances.

SWITCH.-D. Fred Carver, Brooklyn, N.Y. This invention relates to switches in which the main line rails have a continuous and uninterrupted tread through the switch, and the invention prevents the wheels from cutting into the rails. The main rails are spread wider than the normal gage and a riser is placed between the normal and widened gage lines for receiving the wheel flanges, a second riser being provided for the tread of the wheel. The second riser, which leads to the siding, overlaps the main rail tread. Various novel details are also provided. The risers and auxiliary devices are designed for the inside of the curve, the switch tongue, which is the only movable part of the switch, being at the outside curve.

SWITCH OPERATING DEVICE.-Wilson A. Clapp, Pittsfield, Mass. This is a simple and inexpensive device, applicable to any form of sliding switch, whereby the switch may be opened or closed from a moving train, and at a distance in advance of the train entering the switch. The mechanism for operating the shifting or trip devices may be readily applied to an engine or car without interfering with any of its working parts. 'The switch is adapted to be set automatically by means of a trip bar held in a hanger below the engine, or the device may be operated by means of a hand lever.

CAR BRAKE.-John W. Buford, Jr. Jackson, Tenn. This brake is designed to remain automatically applied while the car is at rest or while the engine is not pulling, but will be released the moment the car is started ahead. In descending an incline the brakes may be applied only partially, and when it is ne cessary to back a car the brake [ ressure may be taken off entirely. A shifting lever is fulcruned beneath the car in connection with a longitudinally slidable shaft, there being two brake beams between which is located a spring pressing the beams apart to normally apply the brakes, there being means for drawing the brake beams apart against the tension of the spring and a connection be tween the beams and a shifting lever.

PARLOR AND SLEEPING CAR.-James M. Osgood, Boston, Mass. This inventor has devised an improved car in which the chairs or seats employed for day use may be readily converted into sleeping berths so arranged that the berths of a section will overlap each other to a certain extent. The several sections of the car are also provided with separating partitions that may be compactly folded in the side framing of the car in the day time and extended transversely in connection with the berths at night. An intermediate partition divides a section into two compartments for night use, and the seats or chairs are so attached to the floor that they may be all moved to one end, thus making a reception room of the body of the car. Further details relative to this invention may be had by application to the Osgood Car Company, 37 Tremont Street, Boston, Mass.

### Electrical,

TELEGRAPH REPEATER.-Charles W. Leiser, Carlinville, Ill. A cheap and efficient instrument is provided by this inventor, one that needs but little care after being once adjusted to the circuits over which it is to be worked. It comprises two relays provided with armature levers, each having two spring contacts furnished with limiting pieces, two stationary contact points for each armature lever, two batteries connected with the main lines and with the forward stationary contacts of the relays, while the electrical connections, the relays and their armatures, are oppositely arranged with respect to each other. The instrument may be constructed of common telegraph relays at small cost, obviating the necessity of building special new instruments.

#### Mechanical.

PIPE WRENCH.-William H. Furbee and Thomas Barrett, Mannington, West Va. This is an improvement in what are known as chain wrenches, the chain being held at one end to the handle and having at its other end a gripping link, a portion of the handle being arranged to engage and operate the gripping link. When once adjusted it may be used on a considerable

material into pieces of the right size and shape, when a conveyor carries the cut pieces to a former which makes the shape of the box, which is then carried to a position to receive the articles to be packed. The cigars, cigarettes, or other articles to be packed are mechanically arranged in regular lines or rows before being conveyed to the unfinished box.

OPERATING JIG PLUNGERS.-Adren L. Heaston, Bingham Canon, Utah. In ore concentrating jigs this invention provides a device for operating the plungers in such manner that a quick drop is given to the plunger to cause the water to be dashed upward with great force through the screen to readily separate the valuable particles from the tailings. The plunger is secured to a lever pivoted on the tank, and near its pivoted end, the long arm of the lever being slowly raised by a cam, and quickly returned by a spring, thus throwing the water upward against the material contained in a sieve.

PIPE COUPLING AND FITTING.-William H. Le Chard and John A. Best, Atlantic City, N. J. In long screw pipe couplings and fittings intended to withstand high pressure, this invention provides the threaded portions with plain surfaces whereon are comressed soft metal collars for packing and making tight joints, such packing collar being kept always at hand when the sections are coupled or uncoupled. The sockets, locks or jamb nuts employed, and also the mouth portions of the fittings, are so shaped that the soft metal collars will be effectually compressed between such opposing surfaces, the collars being wider at their inner than their outer peripheral surfaces.

#### Agricultural.

FARM GATE.-George W. and John E. Lilly, Sedalia, Mo. This invention is for an improvement in horizontally swinging gates adapted to close automatically by gravity, and whose free ends may be adjusted as required to swing over stones or other obstructions, such adjustment also facilitating the sepa rating of small domestic animals, as sheep and swine, from larger ones, as horses and horned cattle. The gate is formed of horizontal slats and pivoted vertical connecting bars, and hinged alongside is a triangular device formed of a right angular rod and a tension rod, while a toothed plate secured vertically to the gate proper en gages the pointed end of the device.

#### Miscellaneous.

AERIAL PHOTOGRAPHIC APPARATUS. -William A. Eddy, Bayonne, N. J. In apparatus to be carried by a kite string to properly support photographic cameras for taking negatives of the surroundings from a great altitude, this inventor has devised a novel form

of hanger, which, with a boom extended from its lower lower end, are connected with the kite string, the hanger supporting a platform to which the camera holder is hinged, there being means for elevating the rear end of the holder, over which also extends a hinged arm adapted to engage the shutter operating button, and a string extending downward from this arm to the ground. By drawing on this string the shutter of the camera is operated to make the exposure at the desired time. The platform may carry several cameras, the strings being connected and all simultaneously operated in the same way.

SEWING MACHINE HEMMER.-Mary R. K. Fowlkes and Mary E. J. Bennett, Selma, Ala. The improved hemmer devised by these inventors is designed to produce hems of any width, from one-fourth of an inch to eight inches, and it may be applied with very slight changes to either lock stitch or chain stitch ma chines. The improvement comprises a base plate with front slot and parallel graduations, in combination with a slotted gage bar with foot, a cross bar with clamp bolt secured in the slot of the base plate and a separate hem turner.

TYPEWRITING ATTACHMENT FOR ADD-ING MACHINES.-George W. Dudley, Charleston, West Va. Two patents under the foregoing title have been granted this inventor for improvements upon an invention formerly patented by him, according to one of which it is intended to extend the scope of the machine by providing it with a fully equipped alphabet, with numerals and characters, adapting the machine for making statements of accounts and doing all kinds of clerical work involving the use of letters or figures. The object of the invention covered by the other patent is to enable the combined adding and printing machine to operate upon and print directly on blank books, such as bank books, pass books, etc., and to this end the printing carriage and its associated parts are reorganized to ena ble the blank book to be readily placed in the machine and the extensions, and the totals to be printed directly on the pages.

ICE CREAM FREEZER.-George S. W. Brown, Athens, Pa, This is a household appliance compris compact form, and designed to be of great utility. Within the frame of the freezer is a revolving freezing cylinder, and the mixture that is to be frozen is held in a receptacle that is vertically adjustable in relation to the cylinder, a scraper being suspended from the frame so as to bear against the cylinder, scraping off the frozen cream and allowing it to drop into a receptacle below. FILTER.—Edon A. Brashear, Western Port, Md. This filter has a central inlet at its bottom and a central filtered water chamber opening at the bottom into a surrounding sand space, there being two ver tically adjustable concentric tubes forming an upward passageway for water and sand, and both tubes being open at their lower ends and forming a compound valve with the bottom of the filter to cut off the sand by their successive action, while forming a tight joint. The filter is designed for household purposes or larger uses, and the sand used as the filtering medium may be agitated and cleansed from time to time by the admission of water under pressure.

tral light, while transparent panes are located exteriorly of the reflectors and extending from the back of one reflector toward the reflecting face of the adjacent reflector. The lamp frame consists of two sections connected by a vertical hinge joint, and a series of light reflectors secured to the frame is grouped around the central light, whereby the rays are first concentrated and objects in the immediate neighborhood of the lamp.

BASKET-William R. Yerby, Athens, Ga. This invention is for a cheap and durable basket designed especially for farm use in the gathering of products, the basket being readily made without the use of skilled labor. It is composed of an open rectangular framework, held together by brace wires, while a bag having pockets at its upper edges receives the four upper bars of the frame. the bottom of the bag being engaged by penetrating points and supported on the wires

BELT FASTENER. - Jonathan Hill, Jersey City, N. J. This is a fastener for machine driving belts, consisting of a locking bar terminating in heads, washers passing over the heads of the bar and a key passing through the washers and engaging the straight side face of the locking bar. The fastener is readily applied to connect the ends of a belt, the locking bars and keys being given a curved form when the belt is placed on a pulley, and the point of a junction forming a ridge extending away from the pulley.

DOOR SPRING AND CHECK. - Christian Bayer, New York City. A swinging arm is mounted on the door casing, according to this invention, there being a barrel on the free end of the arm and in the barrel a rotating block through which extends a rod connected with a shaft designed to rotate on the door, there being a spring connected at one end to the shaft, and a chain extending from the other end of the spring around the barrel on the arm. The construction is simple, and the device is not liable to get out of order, while it operates effectively to close doors without slamming them.

TRACE CARRIER.-Edward A. Cotham and George Wells, Monticello, Ark. This invention is for a buckle especially adapted for use on the backband of a harness, there being on the buckle a safety snap or its equivalent adapted to be attached to the trace, such snap or other device having a swivel connection with the buckle to prevent chafing or rubbing the sides of the horse

HORSE DETACHER.-James H. Dunnington, Washington, Pa. This is an attachment for the front axle of the vehicle, and also the thills, the portion connected with the thills being readily disconnected from the portion attached to the axle to permit the forward or thill carrying section to be quickly disen-gaged, and thus admit of the instant release of an unruly or runaway horse. The device is very simple and inexpensive, the disengagement of the animal being effected by pulling on a cord extending to convenient reach of an occupant of the vehicle

Note.-Copies of any of the above patents will be furnished by Munn & Co. for 10 cents each. Please send name of the patentee, title of invention, and date of this paper.

#### NEW BOOKS, ETC.

THEORY AND CALCULATION OF ALTER-NATING CURRENT PHENOMENA. By Charles Proteus Steinmetz, with the assistance of Ernst J. Berg. New York: The W. J. Johnston Company, 253 Broadway. 1897. Pp. xvii, 431. DIE SIEDESALZ-ERZEIGUNG VON HUDEN Price \$2.50.

In this work we have a very valuable contribution to what may be properly termed the greatest development of the new electricity. The title discloses its subject, which is treated by a high authority. Dr. Steinmetz has long been known as one of our best electrical mathe maticians, and in this work at last we have his contribution to the world's work issued in really good shape. The time has gone by when electricity can be treated entirely from the practical aspect. Theory is absolutely required, and the mathematical treatment given to the different theoretical studies is imperative. Formerly the higher mathematics were kept out of electrical books as far as possible, but the new school of educated electricians, well versed in analytical mechanics and in the calculus, will hope to find in such works as that of Dr. Steinmetz a percursor of many others.

KRAFTUEBERTRAGUNGS-WERKE DIE Technische und RHEINFELDEN. Wirthschaftliche Darstellung der Wasserkrafte des Ausnutzung der Rheins bei Rheinfelden. Herausgegeben von der Allegemeinen Elektri-citäts-Gesellschaft. Berlin : Druck von H. S. Hermann. 1896. Pp. 173. Transmission of power has received great attention in Europe, and electricity has lent itself to the work with great effect. This monograph is devoted to the river Rhine as a source of power and to the development of the power depending upon its flow. It treats of a most important enterprise in the use of water power and electrical energy. It is profusely illustrated and well printed, and gives the details of the work in several general divisions, such as water power, the generation of electric nergy, its transmission and utilization.

lic buildings, such as the new parliament building and the cathedral, which is being constructed, the various institutions of learning and office buildings as well as residences. Special chapters are devoted to descriptions of the parks, the streets and squares, canals, bridges, street railways and other means of communication. The then directed to properly light the streets, instead of systems of water supply and of sewerage, the lighting of diffusing the light all around, and unnecessarily lighting the city, the fire brigade and the street cleaning department are fully treated. The book also gives an account of the industries represented in Berlin, as well as of the markets and other buildings provided by the municipality for the convenience of the public. The illustrations are excellent and numerous, and the work is highly creditable to the publishers as well as to the editors.

THE A B C OF THE X RAYS. By William H. Meadowcroft. New York: The American Technical Book Company. Pp. 189. Price in paper 50 cents, cloth 75 cents.

The present work by the author of another well known book bearing in part the same title will, we are convinced. be very acceptable to many. The book is excellently illustrated, well printed and has a very satisfactory index. The radiograph, with accompanying photograph of a mummy's hand, that of an Egyptian princess, may be cited as an example of the illustrations, some of which in half tone work are of unusual clearness

TABLES FOR THE QUANTITATIVE ESTI-MATION OF THE SUGARS. With ex-planatory notes. By Dr. Ernst Wein. Translated, with additions, by Wil-liam Frew. London: E. & F. N. Spon. New York: Spon & Chamber-lain. 1896. Pp. xiv, 128. Price \$2.40.

This work in the original German has been very widely sed both in Germany and America by sugar chemists, and is regarded by them as a standard work on this subject. It is largely made up of tables, only enough text being introduced to explain them, so that it amounts in great part to a reprint of an important set of tables for practical use, the text and headings being translated and the whole put into English dress

THE COMMERCIAL ORGANIZATION OF FACTORIES. A handbook for the use of manufacturers, directors, auditors, engineers. managers, secretaries, accountants, cashiers, estimate clerks, prime cost clerks, bookkeepers, draughtsmen, students, pupils, etc. By J. Slater Lewis. London: E. & F. N. Spon, 125 Strand. New York: Spon & Chamberlain, 12 Cortlandt Street. 1896. Pp.xxxvi, 540. Price \$12.

We have to rely upon the title of this book to tell to ome extent the ground it covers. It treats of the management of the force of a factory and of the use of the different kinds of time registering systems. In some places it affords somewhat curious reading, the English system of personal interference being quite strongly brought out in some of the provisions. In it is elucidated at great length many systems of conducting the different departments of an establishment. As an example we would refer to the portion devoted to the ticket system of keeping exact account of the work done by each man, of the time wasted by him, of his late comings, etc. The illustrations of the book are numerous—including the shape and inscriptions of checks for time, of paper slips, of tickets and bill heads. Certainly

ANFAENGEN BIS AUF IHREN GEGEN-WAERTIGEN STAND NEBST EINEM ANHANGE UEBER SEESALINEN. Von Carl Baltz, Elder von Balzberg. Berlin: Wilhelm Ernst & Sohn. 1896. Pp. 159. Also an atlas of 19 plates. Price \$8.

This is a very exhaustive work on the methods and apparatus for the production of salt from salines. The subject is treated in a very interesting manner, the chronological order being followed in most of the chapters of the book. Although continental European procedures are described with most detail, still improvements due to Englishmen and Americans are not omitted, so that the author may rightly claim to have produced a thoroughly complete work. So fat as we know, no similarly exhaustive work has been published hitherto, and the fact that the book received the highest award in a prize competition is further evidence as to its thoroughness, All improvements made since 1860 are described very fully, the apparatus for boiling, drying, and purifying the salt being treated with considerable minuteness. A separate chapter is devoted to methods introduced at a comparatively recent time, such as the hot air method, the cooling method, the vacuum method, the Rittenger-Piccard method, also the production of salt by utilizing the heat of the sun's rays. Another chapter treats of the various uses to which salt is put in the household and in different industries and arts. This chapter is particularly interesting. The production of salt from sea water forms the subject of the last part of the book, and there is appended a catalogue of works bearing on the matter treated in the book, so that reference to the original works utilized is made very easy. Education by Correspondence.-We have received the 1897 catalogue of the International Correspondence Schools, Scranton, Pa. The catalogue con tains a description of the courses of instruction in the schools and states the methods by which the work is conducted and a history of the institution. Correspondence schools are not intended to take the place of regular institutions of learning, but in many cases the correspondence school admirably meets the requirements of those who for the want of time and means cannot attend regular schools where scientific and technical subjects are taught. The instruction papers are sent out and questions are furnished which the student must answer. When a set of answers is received by the school it is examined, corrected, and returned with such suggestions and criticisms as will enable the student to understand the subject thoroughly.

range of sizes of pipes, the nose or projection of the ing the freezer, a tank for storing the cream when frozen, handle tilting the gripping link to properly engage the an ice water tank or refrigerator, all built in cheap and pipe, while a bail holds the link to the head of the wrench without interfering with the link by the swinging of the handle.

EXHAUST FAN.-Samuel Rembert, Memphis, Tenn. This is an improvement in fans de signed to facilitate the conveyance through piping of seed cotton, cotton seed, etc., and the construction is such as to avoid injury to the conveyed material by con tact with the blades of the fan. The fan casing has a lateral inlet, and held to and revolving with the fan is a perforated guard, which is arranged between the blades and the side of the case having the inlet opening, thus forming a passage for the cotton along the guard and between it and the case, while the turning of the guard plate facilitates the flow of the material.

CIGARETTE BOX MACHINE.-Domingo Perez y Bunol, Havana, Cuba. This machine not only makes the boxes but packs the cigarettes. It comprises a series of mechanisms acting together to form a sheet of paper into the shape of a box, then introduces the articles to be packed in the boxes and closes the latter. A paper or cardboard feed device supplies periodically the necessary material for each box, a cutter dividing the inwardly converging reflectors is grouped around a cen- and effectiveness of its work. The publication above re-

LAMP. - William H. Kincaid, Santa Barbara, Cal. According to this invention, a series of

BERLIN UND SEINE BAUTEN. Berlin: Wilhelm Ernst & Sohn. 1896. Three parts in two volumes, 1550 pages, 2150 illustrations in the text, 18 plates and 5 maps. 4to. Price stitched, \$15 exclusive of importation expenses.

This work is very comprehensive in its scope and deals with every department of architecture and all kinds of public works in the city of Berlin and its chief suburb, Charlottenburg. Owing to the fact that Berlin is the seat of county and provincial authorities as well as of those of the Prussian kingdom and of the German empire, the number of public buildings is very large. The municipality also is world famed for the thoroughness

## Business and Personal.

The charge for insertion under this head is One Dollar of line for each insertion; about eight words to a line Advertisements must be received at publication office as early as Thursday morning to appear in the follow ing week's issue.

Marine Iron Works. Chicago. Catalogue free.

"U. S." Metal Polish. Indianapolis. Samples free.

Yankee Notions. Waterbury Button Co., Waterb'y, Ct

Handle & Spoke Mchy. Ober Lathe Co., Chagrin Falls, O

Improved Bicycle Machinery of every description The Garvin Machine Co., Spring and Varick Sts., N. Y.

Concrete Houses - cheaper than brick, superior to stone. "Ransome," 757 Monadnock Block, Chicago.

Foreign Worrall Clutch Patents for sale outright or on royalty. Great success in United States. Address American Twist Drill Co., Laconia, N. H., U. S. A.

The celebrated "Hornsby-Akroyd" Patent Safety Oil Engine is built by the De La Vergne Refrigerating Ma chine Company. Foot of East 138th Street, New York. Ma

The best book for electricians and beginners in elec-tricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4. Munn & Co., publishers, 361 Broadway, N.Y.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.



HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters or no attention will be paid thereto. This is for our information and not for publication. References to former articles or answers should

References to former articles or answers should give date of paper and page or number of question. Inquiries not answered in reasonable time should or repeated : correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn. Bu yers wishing to purchase any article not advertised in our columns will be furnished with addresses of buses manufacturing or carrying the same.

in our columns will be furnished with addresses of houses manufacturing or carrying the same.
Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.
Scientific American Supplements referred to may be had at the office. Price 10 cents each.

to may be had at the office. Price 10 cents each. **Books** referred to promptly supplied on receipt of Minerals sent for examination should be distinctly marked or labeled.

(7135) M. P. S. writes: In your issue of January 16, under the head of Science Notes, you state the coldest region on earth is the country around Werchsiansk in Siberia where the thermometer sometimes falls below 68° Centigrade below zero (90° Fah. below zero). Are you not in error when you say 68° C. =90° Fah.? Does not 68° C. =154§° Fah.? The formula is § C. +32=Fah., or at least I was so taught. A. The article you refer to is correct. The degrees below 0° C. are minus quantities, so that the addition, being algebraic, involves an arithmetical subtraction. Those not conversant with algebra, for degrees below 0° C. may proceed as follows: If the result of the multiplication of degrees below zero Centigrade by § is (a) less than 32, subtract it from 32; if (b) greater than 32, subtract 32 from it. The result of a 1s to be expressed as degrees above zero Fah. ; the result of b is to be expressed in degrees below zero Fah. But treated algebraically the formula is correct. Thus  $-68 \times \frac{9}{5} =$  $-122\frac{2}{5}$ ; adding 32 we have  $-122\frac{2}{5} + 32 = -90\frac{2}{5}$ . This process gives a fraction more than 90° Fah. below zero as the equivalent of the Centigrade degrees, which corresponds with the article, except that the fraction is omitted, as of inconsiderable amount.

(7136) G. F. H. writes: 1. Is there a compound, not poisonous, which, when paper is moist ened with a solution of it and a current of electricity passed through the paper, will give the same or similar result as is obtained by like treatment of paper moistened with a solution of ferro-cyanide of potassium? That is, will there be traced on the paper a permanent blue line or a distinct line of any color? A. A solution of po-tassium iodide acts thus. A very dilute starch solution may be added to the iodide solution to intensify the color 2. Can paper be so treated as to become a conductor when dry, the current being of the strength of one gravity cell? If so, what is the treatment required ? A. No; except by brazing or coating with black lead or some such treatment. The conducting powers of paper charged with chemicals, as used in chemical telegraphic recorders, is due to the presence of moisture.

(7137) R. G. R. asks: 1. I have a motor having a ring armature about 31/2 inches in diameter. The armature is wound with about No. 24, the field with

also adapted for flexible objects like leather. It will not withstand boiing water well, as this softens the glue. (7139) E. G. B. asks for a recipe for

Resin	4 "
Lard	2"
Beeswax	2"
Melt over a slow fire, or	
2. Melt together equal quantities resin and	beeswax.

and add enough tallow to produce the proper consistency. Grafting wax:

- Alcohol, 90 per cent...... 5 " The resin is melted in an iron vessel. The turpentine

is added, next the tallow, and finally the 90 per cent alcohol. Stir the ingredients thoroughly and cool.

(7140) H. J. F. asks: 1. Can I deposit zinc upon carbon plates? If so, how and what is the process ? Can you furnish me formula for above ? A. Zinc can be deposited on them electrolytically. See our SUPPLEMENT, Nos. 994, price 10 cents by mail. 2. I have constructed a battery, using carbon and zinc for elements, exposing to the action of the solution 96 square inches, and obtain 8 volts for about one hour, and after that time it drops about 35 per cent per hour. Can you recommend a solution that will give longer life ? I do not care as to the consumption of zinc. A. As regards your battery, if you have used good bichromate solution, no improvement can be suggested, unless it is to use larger vessels, so as to have more solution. We assume that your zincs are well amalgamated; neglect of this will make the battery very short lived. 3. How much power can I derive from 8 light dynamo used as a motor? A The dynamo named should give over 1/2 horse power. 4. Can I not use the 8 light dynamo described in SUPPLE-MENT as a motor to run a 20 foot boat and run same by battery ? A. The dynamo could be so used. You should use storage batteries. 5. What is the output of dynamo in watts? A. About 50 watts. 6. What kind of battery do you recommend and how many for a two gallon electroplating apparatus ? A. Eight or ten gravity batteries.

See our SUPPLEMENT, No. 310, for electroplating.

(7141) H. B. asks: 1. Which is the best battery to use in electroplating, or why is the Smee or Bunsen used more extensively than the gravity ? Could not the first be used ? A. The high resistance of the gravity battery tells strongly against its use for electroplating. On the other hand, its great constancy is much in its favor. There are no absolute grounds in favor of any one kind of battery. Each kind has its good and bad points. 2. Would it cost more to use a gravity cell than a Smee or Bunsen, as the first has to be closed four or five hours a day, the Smee or Bunsen being used from one-half to two hours? A. The gravity cell can be run perhaps cheaper than any other. If the upper two or three inches of solution are withdrawn by a large India rubber syringe when the battery is out of action, the closing of the circuit will not be required. 3. How is the gold solution used in plating made? Also the A. See our SUPPLEMENT, No. 310, price 10 cents silver? by mail. 4. What shape and weight are the gold and silver anodes usually ? A. Plates are used of area proportional to work. The weight has no effect on the action. 5. In a storage battery and on a dynamo, which is the posi-tive and negative terminal? In charging a battery, how are the terminals connected? The negative and negative or the positive and negative? A. The purple colored plate of a storage battery is termed the positive. It corresponds to the copper or carbon plate in a primary battery. For charging connect the cells in series, positive to negative. 6. When lead is substituted for the copper in the gravity cell, does it need to be insulated where it comes through the two solutions ? A. The lead plate should not come through the two solutions. It should lie at the bottom of the jar in the copper sulphate solution. A gutta percha insulated lead or copper conductor should connect with it and lead out of the battery jar.

(7142) J. McL. writes: 1. What is the difference between American wire gage and Brown & Sharpe's gage? A. They are identical. 2. If I make electric motor described in "Exper.mental Science "onehalf size, what change would I have to make in the wire and what part of the original power would I get? A. It would give you about one twenty-fifth of the power of the larger dynamo. The sizes of wire would be de-termined by the voltage desired. 3. Where can I get a good description of how to make a sensitive galvanometer, not the mirror type? How can I make a tangent galvanometer without having resistance colls? A. For gal. vanometers we refer you to SCIENTIFIC AMERICAN, No. 12, vol. 61, also SUPPLEMENT, No. 794; price 10 cents each prepaid by mail. Resistance coils form no part of a galvanometer; they are used in connection with it to determine resistance of conductors. 4. How is the mag netic meridian found in using a tangent galvanometer? A. By the compass needle. Set the instrument so that the needle points to 0 on the scale.

Alloys, etc., tank for treating, F. A. Thum Animal trap, C. B. Trumble Aromatic nitrosulfo chlorids, making, B. R. Sei-	578,953 579,026	Game cour Garbage ca Gas burnes
Asphalt pavement heating apparatus, C. H. John- son.	578,930	Gas genera Gas genera
Axle box, J. W. Skilton. Baling press, M. E. Brown. Barrel, composite, O. W. Crawford	578,949 578,857 578,857	Gas manuf Gas meter,
Barrel cover, M. H. Parks. Basket, W. R. Yerby. Basket making machine, E. Horton.	578,768 579,030 578,876	Gate, R. K Gate, T. Sa
Batteries, charging secondary, I. Kitsee Battery. See Electric battery. Storage battery. Battery, S. J. Martin.	578,823 579.001	Generator.
Bean picker, G. F. Crippen Bed, folding couch, D. C. Storr Bedstead brace, J. F. Anderson	578,861 578,844 578,804	Gold from Gold from tracting
Belt fastener 4 Belt shifter, F. Taylor. Bicycle, A. B. Clark.	578,991 579,100 579,042	Gold separ Grain dislo Grain, rota
Bicycle, F. E. Guy. Bicycle canopy, C. Sturll. Bicycle handle, F. B. Fanning	578,921 578,783 578,734	ing, J. Grape shea Grease sep
Bicycle saddle, J. E. Plew	578,871 578,900 578,837	Grinding a Gun, maga Guns, com
Bicycle support, W. J. McGinniss. Bicycle support, H. Sebald.	578,886 578,761 578,838	for bold Half round Hand grip,
Binder or holder for papers, temporary, J. Baer Binder or holder for papers, temporary, J. Myers. Bit. See Drill bit	579,033 579,073	Handle. S Hanging, o
Blacking case, shoe, C. E. Eckfeld Bobbin holder and thread catcher, O. C. Burr Boiler.	578,732 578,811	Heater and Heater att
Bolt. See Seal bolt. Book, combined bill and record, R. G. Craig Book rack, A. D. Linn	578,973 578,755	Horse deta Hose bridg Hose supp
Boot or shoe, J. F. Warner. Bottle, J. F. Pope Bottle stopper, T. F. Langley.	578,794 578,770 578,996	Hydrocart lce cream lce cream
Bottle stopper, F. Schenker, Bottles, lock sealing cap for, S. W. Morgan, Box. See Paper box. Salt box.	579,013 578,756	Incandesc S. E, Fa Incandesc
Box, F. H. Chase. Box fastener, J. F. Gilliland. Brace. See Bedstead brace.	578,967 579,057	for hen Index mak Indicator.
Bratioing machine, O. Dickhaus Brake. See Car brake. Wagon brake. Bridge substructure, W. E. Phelps	578,916 579,007	Ink ribbon Insecticide Insulator,
Brush, A. C. Establook Brush, E. I. Miller. Brush machine, M. Young.	579,107 578,999 578,907	Jack for se Jig plunge Joint. See
Buckle, back band, J. W. Cronan. Buffer, S. D. King. Buffing or polishing device H. A. Webster	578,975 578,752 578,752	Jute, mach Menzie Knife Se
Buggy spring, C. W. Hewitt. Burglar alarm, M. P. McDermott. Burial casket. W. Hamilton	578,874 578,893 579,091	Knob spin Lacing hoe
Button setting machine, A. J. Shipley Cabinets, means for securing partitions of. C. C. Doten	579,017 578,728	Lamp burn Lamp burn Lamp, elec
Call and call answering apparatus, electrical, E. H. Owen et al Camera, magazine, S. D. Williams	579,075 578,905	Lantern, H Lantern, r Latch and
Can. See Garbage can. Can heads, machine for attaching gaskets to, I. Bloch	579,104	Lighting d Lightning Liquid mix
Can opener, H. Berntsen. Can opener, H. A. Frants. Can opener, R. B. Stewart.	579,086 579,089 579,084	Liquids co drawin Load bind
Carbinate Structure F. B. Grove Carbinate J. W. Buford, Jr.	578,985 578,964	Lock, W. S Lock, W. S Log turne
Car brakes, automatic slack adjuster for, J. B. & H. E. Downing. Car coupling. C. H. Smith.	578,978 579,020	Lubricator Lumber h Magazine.
Car, dumping, E. S. Hart. Car, metallic railway, F. Heron. Car, parlor and sleeping, J. M. Osgood	578,986 578,990 579,005	Manure ca Match cab Match ma
Car, pneumatic motor, H. Haupt Car, sleeping, J. I. Newburg Carding machine, J. T. Meats	578,738 578,897 579.117	Meat cutte Meat safe Metals and
Case. See Blacking case. Cellars, etc., of concrete, means for constructing	578,931	Meter. Se Meter seal Milk, creat
Centering machine, Bulock & McLauchlin Chair. See Dental chair. Check, bond, note, etc., L. Loeser.	579,037 578,824	Mining, et Mitten, ca Mould, S
Checkrein hook, A. H. Arp. Checkrow chain or wire, J. W. Parker. Chlorocyanid salts and making same G. J. At-	578,806 578,830	Motor. Se Mowing an Music star
kins	578,908 579,038	Musical in Musical in Musical in
Cigarette machine, Bucklin & Hartigan Cigarette machine feeding device, J. F. Hartigan Circuit breaker, H. P. Kelly	578,715 578,741 578,750	Needlewon Nickel fro N. V. H
Cleaner. See Dental clamp. Cleaner. See Tube cleaner. Clip for holding sheets, blanks, etc., S. G. Brown.	578,858	Nozzle, D. Nut lock, J Oil tanks,
Chipping norses, etc., apparatus for driving cutters for, W. Clark. Clock setting mechanism, electric, C. M. Crook	578.915 578,976	Orange kn Ores, redu
Coating mixtures, device for applying, F. H. Cloudman.	579,043 578,885	Flaher Organ fan Oven, bak
Coffee machine, W. Borchers Coffee pot, drip, J. F. Pierce. Coffin, E. L. Snader.	578,910 578,769 578,781	Overshot chiner Oyster tor
Collar and trace, breast, F. Raynor Compression roll for slashers, J. Sullivan Cooking utensil, M. F. O'Callaghan	578,772 578,951 578,765	Package f Padlock, 7 Painting r
Copper ore and mattes, reducing, A. L. Grant Corset. F. K. Hickok Coupling. See Car coupling. Pipe coupling.	578,817 578,926	Paper box Paper box Wusso
Crochet machine, J. Ashworth Curtain drying frame, lace, R. S. Corlett	578,835 579,102 578,970	Paper hol Pen, R. W Pen, foun
Cycle saddle, C. F. Batt	579,034 579,119 579,094	Percussio Pew back Webb
Dental clamp, J. A. Dunn Desk, H. D. Hermany. Door binder. Newhall & Cook	578,729 578,743 579,074	Photograp Pianofort Picker. S
Door spring and check, C. Bayer Drawer pull and sample holder, G. W. Campbell Drawing roll clearer, J. Thomson, Jr.	578,962 578,913 579,095	Picture fr Pile fabrie Pipe. See
Egg tester, E. Lane	579,065	Pipe coup Best. Pipe wren
Electric accumulators, paste for, R. Linde Electric battery, H. N. Farley Electric carrier apparatus H. M. Noor	578,887 578,867 578,967	Placket fa
Electric elevator, S. D. Strohm	579,024 579,028 579,012	Planter at Planter, c Plow, W
Electric machines, construction and regulation of, T. H. Hicks. Electric machines from heat, means for protect-	579,059	Plow atta Pneumati C. F. P
ing, J. P. B. Fiske Electric motor and dynamo, W. S. Horry Electric motor controlling mechanism, F. R. Bacon	579,051 579,062 578 707	Pot. See Press. Se Press, O. S Printing

[APRIL 3, 1897. 578,906 578,957 Arran, G. W. Walker. 578,957 ara, G. W. Walker. 578,957 tescent, G. S. Barrows. 578,711 ator, acetylene, J. H. Couper. 578,977 ator, acetylene, J. H. Wilcox. 578,847 ng, J. B. de Lery. 578,847 ng, J. B. de Lery. 578,863 to 578,867 Farm gate. 578,863 to 578,867 Ball. 578,947 578,709 578,947

 

 e Farm gate.
 578,709

 sawyer
 578,947

 el and mechanism for making same,
 578,947

 ht metal, U. & F. L. Eberhardt.
 578,731

 r. See Gas generator.
 578,740

 ores, extracting, H. R. Cassel.
 578,757,720

 n ores, sprocess of and apparatus for ex-ray, B. C. Hinman.
 578,731

 rator, hydraulic, Barr & Johnson.
 578,746

 todging attachment, M. P. Kneiff.
 578,754

 tating cylinder for germinating and dry-ax, T. Hornhauer.
 578,709

 A. Tilden.
 578,764

 parator, W. J. Baldwin.
 578,769

 nobit stop and cartridge ejector
 578,959

 rdt, S. F. Harke.
 578,852

 See Bicycle handle.
 578,852

 ornamental, C. W. Jackson.
 578,852

 see Brede water heater.
 578,959

 oft achrent, J. Booke & Ensign
 578,959

 ec Checkrein Booke.
 578,958

 ec Checkrein Booke.
 578,958

 ec Checkrein Booke.
 578,959

 ortanger, J. H. Donnngton.
 578,959

 oft see Fred water heater.
 578,959

 ortanger, J. Honnhacen.
 578,958

 acher, J. H. Dunnington. zer, rallway, C. A. & C. J. Grimes....... ort, O. Bagley Jon engine, E. Merry... freezer, G. S. W. Brown. mould, C. Memcke............ ent light fixture for railway cars, etc., arraday 578,851 579,068 579,040 578,889 578,763 578,723 578,758 579,008 578,932578,832 579,097 578,722 578,818 578,727 578,942 578,942 578,923 578,868 578,775 578,899 578,816 578,842 , apparatus for placer, C. D. Galvin... ber's, A Slomka... lee cream mould. Electric motor. ee Electric motor. nd reaping machine, H. E. Olson...... nd, O. A. Bronson..... Istrument, E. Wheaton.... Istrument, P. Zintzsch...... Istrument, stringed, C. Henlein...... K fabric, J. Vialon..... 578,766 578,809 578,797 579,031 stransta, subtraction of the second stransform 579,111 578,706 578,717 578,744 578,744578,961 579,088 578,912 578,925 578,860 578,833 578,745 579,082 578,920 578,791 579,067 579,105

ction, electropneumatic, Hastings & rty., and case, M. Clark... ke, A. Rauber... or undershot wheel for propelling ma-or undershot wheel for propelling ma-try, J. H. Highsmith... mags, S. T. Richardson... for mustard, etc., C. Gulden, Jr... Troast & Amwake... machine, cloth, R. E. Menzie... x, R. P. Brown... x, Shucks, machine for making, W. H. ow, Sr... M. Robinson... ntain shading, F. Van Gerpen... r, S. M. Rhone... on wheel, F. M. F. Cazin... ks, attachment for extension of, I. H. ubic apparents actual W. A. Eddy 579,029 579,092 578,955 578,773 578,813 phic apparatus, aerial, W. A. Eddy.... te or planette, J. Strong... See Bean picker. rame, metallic, R. Liebmann... c, M. Drolet. > Tobacco pine 579,027 578,980 578,782 578,936 578,917 c, M. Drolet. Tobacco pipe. ling and fitting, long screw, Le Chard & 578,933579,053ich, Furbee & Barrett..... r heat distribution in buildings, J. H. Piping for heat distribution in buildings, J. H. Mills. Planing machine, L. L. Bartlett. Planter attachment, S. W. Myers. Planter, corn, W. T. M. Brunnemer. Plow, W. Easley. Plow attachment, H. C. Alexander. Plow attachment, H. C. Alexander. Plow attachment, H. C. Alexander. Poles attachment, H. C. Alexander. Press. See Baling press. Press, O. Smith. Printing machine, W. Scott. Printing machine, K. Scott. Printing machine, A. B. Dick. Printing press, C. G. Harris. Projectile, W. H. Bell. 579,070 578,946 578,730 578,849 578,943 579,051 579,062

about No. 10, speed 2.200 revolutions, volts 6. Now I want to convert it into a dynamo. How am I to reduce the speed ? A. Do not attempt to reduce the speed, but the speed? A. Do not attempt to reduce the speed, but run with large belt wheel on countershaft so as to main-tain a speed of 2,000 to 3,000 revolutions per minute. You may not get much satisfaction from it, as a motor is often poorly adapted for use as a dynamo. 2. Why will not the current from an induction coil run a motor? A. It will run a special motor adapted for high tension electricity. It will not run an ordinary motor, because it produces an almost infinitesimal current of alternating and very high frequency type at enormous potential, and very high frequency type at enormous potential while ordinary motors are adapted for currents of widely different character. 3. Should the above described motor run connected as a shunt? A. Yes.

(7138) A. H. C. says: Can you inform me where I can get a cement which is not soluble in alco hol and that will hold glass? A cement, for example, that would mend a glass whisky or brandy flask so that it would hold liquor. A. Take the best kind of glue; pour on an equal quantity of water; let it soak overnight; next morning melt it over a gentle heat, and add fin Paris white or white lead; mix well, and add a little acetic acid, carbolic acid, oil of cloves, or any other ethereal oil, to prevent putrefaction. This cement is TO INVENTORS.

## INDEX OF INVENTIONS For which Letters Patent of the United States were Granted MARCH 16, 1897, AND EACH BEARING THAT DATE. [See note at end of list about copies of these patents.]

Electric motor controlling mechanism, F. R.		Press, O. Smith	579,019
Bacon 57	78,707	Printing machine, W. Scott	578,778
Electric motor regulator, R. M. Hunter 57	79,063	Printing machine, fabric, S. H. Sharp	579,016
Electrical controlling apparatus, B. C. Van Emon. 57	78,954	Printing machine, stencil, A. B. Dick	578,726
Electricity meter, A. Raps 57	79,079	Printing press, C. G. Harris	578,739
Elevator. See Electric elevator.		Projectile, W. H. Bell	579,035
Elevator, J. S. Muckle 57	79.071	Propelling means for boats, R. Fryer	578,815
Elevator, W. A. & H. W. Placier 57	79.076	Propelling mechanism, vessel, J. Hays	578,987
Elevator mechanism, J. S. Muckle,	79.072 L	Pruning tool, reversible, D. C. Searles	579,083
Engine. See Hydrocarbon engine. Rotary engine.		Pump, J. Stumpf	578,950
Traction engine.		Pump, air lift, Miller & Thompson	579,069
Envelope J. Price 57	79 077	Pump, rotary, F. Marburg, Jr.	578,938
Exeguator G W King 57	78 751	Puzzle, J. C. Dando, Jr.	579.045
Extractor See Tree extractor		Rack. See Book rack	
Everlage frame S Hummel 57	78 \$21	Rail for preventing derailments, safety, H. Bier-	
Fubric Son Needlework fubric Pilo fabric		mann	578.854
Woven fabria		Railway, J. I. Newburg.	578,896
Fan Arbaust & Dombort 57	70.091	Railway crossing signal, C. Selden,	578,840
Farm gato C W & I E Lilly	79 66	Railway crossings, arrangement for closing or	,
Function of the second se	,000	opening bars at H Biermann	578.853
radeet, automatic measuring, registering and re-	70 719	Railway rail bond electric, McTighe & Childs	578.829
Food water boster W. I. Shenard	~ 001	Railway rail joint L. W. Kennedy	578.882
Feed water neater, w. L. Snepard	10,00±	Railway rail joint, L.D. Trammell	200 700
Feed water puriner, w. L. Snepard	70,000	Railway switch D F Carver.	578 966
Fence wire reel, Gibbons & McDonald	78 706	Railway switch, D. F. Carroll	578,924
File, capinet, A. J. wens	70,130	Railway switch E Schuler	579 015
File for holding papers, G. O. Farber	10,910	Rospor real rake W Butterfield	578,719
File, paper, S. B. Tily	70,101	Roof Soo Fonce wire reel	0.0,010
Filter, E. A. Brasnear	79,059	Refrigorator car ventilator screen G F Brown	
Fire escape, J. H. Higgins.	79,000	In the second se	579 087
Fire escape and water tower, M. w. Hennessey 57	70 005	Poin guard attachment for shafts A B Rue	578 001
Fire extinguisher, v. E. Campbell	10,500	Relinguate attachment for sharts, R. D. Ructing	570 112
Fire hose, telegraph, J. Buchtel	10,110	Releasing device, animal, J. 1. Daily	578 007
Fishing line attachment, L. H. McManon 20	18,192	Repeater, C. W. Leiser	510,551
Flue cover, E. H. Huenereid	10,140	W C Allon	570 050
Flushing tank for water closets, urinals, etc., au-	70 007	W. G. Allell.	570.054
tomatic, J. Holleran	(8,921	Rope coming machine, J. Garseu	579,054
Foot, artificial, W. L. Richen 57	79,009	Rotary engine, J. F. McElroy	570 059
Frame. See Curtain drying frame.		Salt box, T. Tellersen	510,954
Fruit pitter, P. M. Trask 57	78,790	Sample holder, W. D. Smith	578,843
Furnace. See Metallurgical furnace. Smelting		Sanitary trap, M. F. Moran	5/0,821
furnace.		Saw ning machine, J. C. Ballew	579,103
Furnace noisting and charging apparatus, blast,		sawmills, compined set works and index mech-	F#0.000
Rotthoff & Neeland	79,011	anism for, R. D. Inman	518,928
Furrow opener, disk, F. R. Packham 5	(8,941	Sawing machine, B. G. Luther	218,826
Gage bar tightening device, N. Nelson	18,164	scare, computing, J. H. Swinart	018,184
Game apparatus, W. H. Reiff 57	19,080	scar1 pin securer, I. H. Jonannes	018,822

APRIL 3, 1897.]

Scissors or shears, B. Wesselmann..... Scraper, G. B. Wilder,..... Screw machine, F. Schulze... Seal bolt, G. S. Tiffany... Seal lock, Wheelwright & Tiffany... Seeder, broadcast, G. W. Eltzroth... Separator. See Gold separator. Grease separa-tor

 Coparator.
 Coperator.
 <thCoperator.</th>
 Coperator.
 Coperato

 Snuttle, self threading, J. B. Daudein
 578,000

 Signal. See Railway crossing signal.
 Skins into horny material, conversion of, C.

 Marter
 578,000

 Skirt, cycling, L. L. Hirsh
 578,000

 Skirt, cycling, L. L. Hirsh
 578,000

 Spectacle frame, F. A. Stevens.
 578,000

 Spindle and bearing, L. J. Murray
 578,103

 Spindle and bearing, L. J. Murray
 578,813

 Spindle machine flier, E. E. Bradley
 578,856

 Spool, jack, Dingman & Klingin
 578,902

 Spring, See Buggy spring, Door spring.
 578,102

 Spring, See Buggy spring, Door spring.
 578,173,022

 Spring, See Buggy spring, Door spring.
 578,173,022

 Spring, See Buggy spring, Door spring.
 578,173,023

 Square, folding, E. G. Stoy
 578,263

 Steam boiler, J. J. Hogan
 578,737

 Steam topiler, J. J. Hogan
 578,737

 Stereortype making machine, Curtis & Titsworth
 578,936

 Storepipe be making machine, Curtis & Titsworth
 578,936

 Storepipe thimble, P. J. Haas.
 578,737

 Storepipe thimble, P. J. Haas.
 578,708

 Storepipe thimble, P. J. Haas.
 579,008

Thrashing machine band cutter and feeder, G. F. Weiss.
Thrashing machine spreader and regulator com-bined, Nunamaker & Williams.
Tobacco feeding and dressing mechanism, J. F. Tobacco pipe, J. Townsend.
Tobacco pipe, J. Townsend.
Tobacco pipe, J. Townsend.
Tobacco pipe, M. Takine.
Toilet appliance. M. Rhine.
Tool holder, C. W. Justus.
Toy savings bank, C. G. Glover...
Traction engine, A. J. Martin...
Tratoin on engine, A. J. Martin.
Tratoin wheel, J. A. Justice.
Trap. See Animal trap. Sanitary trap. Steam trap.

578,786

578,898 579,050 578,740 578,788

578,881

579.05

578,971 578,888 578,932

# Scientific American.



DESIGNS. 

 Belt, L. Sanders.
 26,756

 Bicycle fork crown, C. H. Metz.
 26,764

 Bicycle rack, H. A. Dolge.
 26,765

 Button, campaign, W. G. Ashby.
 26,755

 Button setting tool, W. B. H. Dowse.
 26,765

 Carpet, A. Danby.
 26,765

 Porss shield, I. B. Kleinert.
 26,771

 Fork, corn, M. M. Donnelly.
 26,772

 Lamp, bicycle, Havell & Williams
 26,762

 Mowing machine section knife, W. M. Brinkerhoff
 26,778, 26,779

 Mowing machine section knife, W. M. Brinkerhoff, 25,050
 26,050

 Mowing machine section knife, W. M. Brinkerhoff, 26,779
 26,778, 26,779

 Photographic mount, J. W. McCabe.
 26,761

 Pile holder, G. S. Webber
 26,771

 Shelf key, A. S. Held
 26,772

 Strainer, well, A. D. Cook.
 26,773

 Tool handle, J. A. Praut.
 26,773

 Water wheel, hurdy-gurdy, F. M. Bookwalter
 26,773

 Windmill tower anchor, O. J. Ziegler
 26,773

 Woren fabric, H. W. Smith.
 26,778

 Wrench, R. D. Shafer
 26,778

 Writting shield, T. H. Burchell.
 26,758

221



A printed copy of the specification and drawing of any patent in the foregoing list, or any patent in print issued since 1863, will be furnished from this office for locents. In ordering please state the name and number of the patent desired, and remit to Munn & Co., 361 Broadway, New York. Special rates will be given where a large number of copies are desired at one time.

Canadian patents may now be obtained by the in-ventors for any of the inventions named in the fore-going list, provided they are simple, at a cost of \$40 each. If complicated the cost will be a little more. For ful instructions address Munn & Co., 361 Broadws?. New York. Other foreign patents may also be obtained.



ELECTRO-CHEMISTRY, RECENT AD-

Pêscel » Bicycles KNOWN QUALITY You are making no experiment in buying a Crescent Bicycle. 56,000 men, women and children bought Crescents in 1895; 70,000 in 1896. Owners of Crescents are all around you. Ask them about Crescent quality. They know how good it is. Crescent agents will explain the many improvements for 1897. We want you to ride a Crescent this year. WESTERN WHEEL WORKS, Chicago New York Catalogue free. Agents everywhere. 10 、 WE UNDERSELL ALL! <u>ria</u>? Catalogue 2 cts. OHIO ELECTRIC WORKS, Cleveland, Ohio. ZENTMAYER'S • MICROSCOPES

in use by the leading Professors and Colleges throughout the world. The acme of perfection in the art of Microscope making. Heartily in-dorsed wherever used. Complete illustrated catalogue of micro-scopes and optical apparatus sent free. Mi-crometer Rulings in English and Metric scales. J. ZENTMAYER, 10 Phila.. Pa. 211 South Eleventh St.

MANUFACTURE OF BICYCLES.-A MANUFACTURE OF DICICLES.—A very comprehensive article giving the details of con-struction of every part of these vehicles. With 15 en-gravings. Contained in SCIENTIFIC AMERICAN SUP-PLENIENT, NO. 908. Price 10 cents. To be had at this office and from all newsdealers.



# Scientific American.

Sha

INCOMPARABLE FOR THEIR RICH CREAM-LIKE

LATHER.

WILLIAMS' SOAPS-in principal forms-sold by Dealers everywhere.

iams

ving Joaps

NO OTHER

SO SOOTHING

REFRESHING.

LUXURIOUS.

Williams' Shaving Stick

[APRIL 3, 1897.

The Waverley Bicycle for 1897 is

the acme of bicycle construction. New and expensive principles of construction involved make the

cost of building enormous. Hence the price is **\$100.** 

The only bicycle

with true bearings

Last year the Waverley was as

good as any wheel in the market-

better than most. Because new machinery was not needed for its

continued construction, the price of the improved 1896 model has been reduced to **\$60**—a saving of

Indiana Bicycle Co., Indianapolis, Ind.

LOCK UP YOUR WHEEL! Keep your Bicycle safe from strang-ens by using THE GEN THE LIGTER GEN (OMBA ATION LOCK 12 combinations. % oz. weight. Price cents. Illustrated catalog of Bi-cycle Sundries free to dealers only. GEO. W. NOCK. 148 N. Fourth St. Philadelphia, Pa.

CROOKES TUBES AND ROENTGEN'S

CROOKES TUBES AND ROLATGENS Photography.—The new photography as performed by the use of Crookes tubes as a source of excitation. All about Crookes tubes. SCIENTIFIC AMERICAN SUPPLE-MENT, Nos. 181, 189, 238, 243, 244, 792, 795, 905, 980, 1050, 1054, 1055, 1056, 1057, also SCIENTFIC AMERICAN, Nos. 7, 8, 10 and 14, vol. 74. These profusely illustrated SUPPLEMENTS contain a most exhaustive series of articles on Crookes tubes and the experiments performed with them. Among then will be found Prof. Crookes' early lectures, detailing very fully the experiments which so excited the world, and which are now again exciting attention in connection with Roentzen's photography. Price 10 cente each To be had at this office and from all newsdealers.

\$25 to you. Catalogue Free.



card

business 1896 catalo

Sen

beautifully illustrated, largest circulation of any scientific journal, weekly terms \$3.00 a year; \$1.50 six months. Specimen copies and HAND BOGK ON PATENTS sent free Address

MUNN & CO., 361 Broadway. New York.

Registers an accurate account of work done on print-ing presses, grain tallies, weighing, measuring and other automatic machines. Counts up to 1,000,000 and repeats automatically. Simple, accurate, durable. Spe-cial counters to order. EF Send for circular. C, J. ROOT, Bristol, Conn., U.S. A.

#### PRICE \$2985 **BRASS SPECIALTIES** RA MU U CG CG CA Our New Catalogue for 1897 contains 260 pages of bargains. Single Buggy Harness \$3.90; Double Buggy Harness \$12.75; Road Wagons \$19.95; Top Buggies \$29.85; Road Carts \$8.90; Phaetons, Surreys, Spring Wagons, Delivery Wagons, Milk Wagons, Farm Wagons & everything on wheels at prices never before heard of. If interested, send &c.(stamps), postage for 260-page catalogue No. 2. R made from Sheet Brass, Rods or Wire. F. E. CHESTERMAN CO., 241 Arch St., PHILA., PA (NM) MURRAY TOP BUGGY NICKEL MURRAY ROAD CART Electro-Plating PRICE WE SELL DIRECT TO THE CONSUMER SUBJECT WE SELL DIRECT TO THE CONSUMER CONCINNATION OF CONSUMER CINCINNATION Apparatus and Material тне lanson& VanWinkle \$**3**<sup>90</sup> Co., Newark, N. J. Liberty St., N.Y. CINCINNATI, OHIO, U.S.A. 35 & 37 S. Canal St., Chicago.

# Trade Marks.

PRESIDENT McKINLEY, on March 9, issued a proclamation promulgating the treaty recently ratified between the governments of Japan and the United States providing for the reciprocal protection of Patents, Trade Marks and Designs in those countries.

> Citizens of the United States may now obtain patents in Japan. Japan has been very active in adopting American and European inventions; and as patents heretofore have been granted only for inventions made by native Japanese, the foreign inventor could not obtain protection foreign inventions becoming public property as soon as publication had taken place. Foreigners may now obtain Japanese patents, provided the application is filed before the invention becomes publicly known or used in Japan. The population of Japan is estimated at about forty-five millions. For further particulars, cost, etc., apply to

Messrs. MUNN & COMPANY. 361 Broadway, New York City,

## April 3, 1897.]





**ROTARY ENGINES** 

The various efforts that have been made by inventors during several generations to overcome the dethis form of motor will be discussed in a series of articles now being published in the

# Scientific American Supplement,

beginning with the issue of April 3d, and extending over a period of three weeks. These articles give the history and development of the Rotary Engine from the year 1588 to the present day. The engravings which accompany the article have been pre-pared from works on the subject of Rotary En-gines and from patent drawings of recent inventions, many of them showing devices of the greatest ingenuity and interest. Copies 10 cents each

See editorial by Prof. Thurston on anothe page of this issue.

MUNN & CO., Publishers, 361 Broadway, New York City. SUPPLEMENT, \$5.00 a year. Combined rates, with SCIENTIFIC AMERICAN \$4.

HYPNOTISM Sixty ways, \$5; my method, \$2, 100 page book, 10c. Occult Forces, S0c. Prof. Anderson, S. A. 47, Masonic Temple, Chicago



in

MAKE ICE CREAM

Polar Star Instant Freezer

ICE-BOATS-THEIR CONSTRUCTION ICE-BOATS-THEIR CONSTRUCTION and Management, With working drawings, details, and directions in full. Four engravings, showing mode o construction, Views of the two fastest ice-sailing boat used on the Hudson river in winter. By H. A. Horsfall N.E. Contained in SCIENTIFIC AMERICAN SUPPLE WENT, 1. The same number also contains the rules and regulations for the formation of ice-boat clubs, the sail-ing and management of ice-boats. Price 10 cents.

 $sigma_{\mathcal{O}}$ Portable Striking Bag. A Home Gymnasium. Stand in corner when not using. Agents Wanted. Send for Illustrated Catalogue. Hawthorne & Sheble, 600 Chestnut St., Philada.; Par





n not attended by loss of life, they often result in the loss of much to restore an arm or leg or both. Artificial limbs with



840 pages, 782 fine cuts, substantially and beautifully bound. Price in cloth, by mail, **\$4.** Half morocco, **\$5.** 

This splendid work is up to the times. It gives young and old something worthy of thought. It has influenced thousands of men in the choice of a career. It will give anyone, young or old, information that will enable him to comprehend the great improvements of the day. It furnishes suggestions for hours of instructive recreation.

> Send for illustrated circular and complete table of contents.

MUNN & CO., Publishers, Office of the . .

SCIENTIFIC AMERICAN,

enable a man to look as well and work as well as ever. They are comfortable and convenient and last for years without needing repairs. Over 18,000 in use all over the world. Maker to the United States and other Governments.  $[B^{\sigma}]$  Send for illustrated book of 544 pages, free. A. A. MARKS, 701 Broadway, New York City. 361 BROADWAY, - NEW YORK.

ACCIDENTS WILL HAPPEN

MARKS' PATENT RUBBER HANDS AND FEET

Scientific American.

[APRIL 3, 1897.

## Advertisements.

### ORDINARY RATES.

Inside Page, each insertion - - 75 cents a line Back Page, each insertion ---- \$1.00 a line  $\mathcal{F}$  for some classes of Advertisements, Special and Higher rates are required.

The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisements at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at Publication Office as early as Thursday morning to appear in the following week's issue.



The Easiest Running Wheel in the World.

# THE BLACK MFG. CO., ERIE, PA. Nickel Silver Watches

We are casing all sizes of movements in this new metal. It takes a better finish and is more enduring than sterling.

It supersedes the old nickel plate, and enables one to have a perfect timepiece at small cost.

Our Solid Gold and Filled Cases, as well as Sterling Silver and Enameled patterns, are in greater variety this season than ever.

New specialties have been added.

Our '97 Model

# Trump Cyclometer,

the 10,000 mile wheel recorder, are all shown in our new catalogues, which will be sent to all.



The American Bell Telephone Company,



Capt. J. R. DeLamar, of New York City, is one of the largest owners and workers of Gold Mines in the world. After the most careful investigation he purchased in August, 1895, two Griffin Mills, and his report is so remarkable as to demand the careful attention of every one

125	Milk	Street,
Bos	ton, i	Mass.

This Company owns Letters-Patent No. 463,569, granted to Emile Berliner November 17, 1891, for a combined Telegraph and Telephone, covering all forms of Microphone Transmitters or contact Telephones. interested in Gold Mining. We give it in his own words.

BRADLEY PULVERIZER CO. Gentlemen:—The two Griffin Mills have been in operation now for 90 days on the hardest rock, with the exception of corundum, that I have ever met during my mining life. They have taken the rock direct from the breaker, and they average about 20 tons to each machine, 40 mesh fine, without elevating or bolting. We simply put a 4 mesh screen around the Griffin Mill, and the stuff comes out 40 mesh fine, without elevating or bolting. We simply put a 4 mesh of the or even the they average about 20 tons to each machine, 40 mesh fine, without elevating or bolting. We simply put a 4 mesh of the or even they average about 20 tons to each machine, 40 mesh fine, without elevating or bolting. We simply put a 4 mesh of the or even they average about 20 tons to each machine, 40 mesh fine, without elevating or bolting. We simply put a 4 mesh and even they average about 20 tons to the function of the order 10 more (friffin Mills, We have tried highspeed rolls and dry stamps, and after looking into the Huntington Dry Pulverizer, the Narod Pulverizer, the Stedman Pulverizer, the Frisbie Lucco, the Cook, and various other dry pulverizers, unheitatingly recommend your Griffin Mill to any one. Yours truly, (Signed) J. R. DELAMAR.

# HOW IO GRIFFIN MILLS WORK.

DELAMAR'S NEVADA GOLD MINING CO., SALT LARK CITY, UTAH, Nov. 24, 1896. DeLamar Mill, DeLamar, Nevada, we beg to state that we often run 300 tons per day with 10 of your mills in operation, and on one occasion these 10 mills produced 408 tons in one day. I have no besitancy in stating that they will regularly produce at least 30 tons per day each on our ore, which is extremely and unusually hard. Yours very truly, H. A. COHEN, General Manager.

These strong letters coming from such representative men are conclusive evidence that we are right in claiming that the "Griffin Mill" will produce a larger amount of finer pulp at less cost than any other stamp or pulverizer made.

Let us send you a free copy of our illustrated pamphlet, which will tell you all about the Mill and bring to you other evidence of its great achievements.

# BRADLEY PULVERIZER CO., 92 STATE ST., BOSTON, MASS.