

Francisco—the leading shipbuilding plant on the Pacific coast—has borne fruit; and the firm is to build a craft for the imperial Japanese government in substantial token of the impression made in the East by the Charleston and the Olympia, the fabrications of that yard. An order for a duplicate vessel was placed at the same time with William Cramp & Sons, of Philadelphia.

The vessel, designated by the Japanese as a second class, unarmored, protected cruiser, is unlike any vessel in our service; and is modeled after several swift cruisers of English build constructed for other nations, the best of which boats is the Japanese Yoshino, which took a very active part in the late Chino-Japanese war, and during her wide service proved herself an exceptionally effective craft.

The cruiser to be built by the Union Iron Works is an enlarged and bettered Yoshino; and it is no small credit to the Pacific yard that it is willing to trust its standing upon the development of lines peculiarly English and to start afresh where the patient practice of its rival has halted.

The new ship will have a load water line length of 396 feet; an extreme beam of 49 feet; and upon a normal displacement of 4,760 tons will draw 17 feet 7½ inches of water.

There will be twin screws, each screw being driven by a triple expansion engine. These engines, which are in separate compartments, are of the four cylinder type; and each will have a high pressure cylinder of 40 inches, an intermediate pressure cylinder of 60 inches, and two low pressure cylinders of 66 inches in diameter. The common stroke is three feet, and when they work at their maximum power the engines will develop 15,000 indicated horse power, and will induce a speed of quite 22½ knots an hour. The probability is that this speed will be exceeded.

Steam will be supplied by four double-ended and four single-ended boilers, in four separate watertight compartments; and forced draught will be induced by large blowers exhausting directly into the closed fire rooms. The normal coal supply will be 350 tons, but the bunker capacity will be for 1,000 tons; and upon this liberal allowance the vessel will have an exceptionally wide radius of action. The coal will be stowed abreast the boilers and the engines for the sake of added protection; and to lessen the tax of handling, it will be arranged to fall right in upon the fire room floors.

There is a double bottom from stem to stern, and a cellular form of structure prevails along the water line region. This arrangement, in conjunction with the disposition of coal, and a protective deck, 4½ inches thick on the slopes and 1¾ inches thick on the flat portion, extending from bow to stern and generally about the level of the water line, offers excellent protection against high explosive shell fire, and guarantees shelter for the vitals and the preservation of stability.

The Japanese know only too well the danger of conflagration in action and its vital menace to efficiency, and with a view to protection, every bit of woodwork will be fireproofed. The ship will be lighted by electricity and ventilated by natural and artificial means; and comfortable and healthful accommodations are planned for the complement of 405 persons.

The armament will consist, in the main battery, of two 8 inch quick-firing rifles and ten 47 inch quick-firing rifles, and, in the secondary battery, of twelve 12 pounders and six 2½ pounders. The 8 inch guns are mounted one on the forecabin and one on the poop deck, and each will have an arc of fire of 270°. These guns are protected by steel shields, and, in their rapid-fire mechanisms, are beautiful evidences of skill. Each projectile weighs 210 pounds, and a speed of fire of four aimed shots in sixty-four seconds has been attained by a well trained crew. While our own 8 inch guns fire a shell of 250 pounds, our best practice has been one shot in a minute and a half. The 47 inch guns are mounted on the main deck, in 3 inch armored sponsons, and are further protected by shields. The forward and aft 47 inch guns fire dead ahead and dead astern, respectively, and have a total arc of fire, each, of 130°. The rest of these guns, in broadside, have a radius of fire of about 100°.

The 12 pounder guns are mounted on the main deck amidships and one at the bow and one at the stern, on each side, in sponsons. These guns likewise have effective arcs of fire. The 2½ pounders are carried on the hammock berthing and in the military tops.

The whole armament is capable of great rapidity of fire, and all the guns will be manufactured by the celebrated Armstrong firm, of Newcastle, England. The ammunition for the heavier guns is raised by electrical hoists, while that for the secondary battery will be raised by hand. There are five torpedo tubes, one in the stem and two on each broadside, for the discharge of 14 inch Whitehead torpedoes.

The new ship will have the characteristic handiness of maneuvering common to the Yoshino and her type, and will form, with her sister ship, a valuable addition to the new Japanese navy.

We are indebted to the Union Iron Works, of San Francisco, for plans and particulars.

Scientific American.

ESTABLISHED 1845

MUNN & CO., - - - EDITORS AND PROPRIETORS.

PUBLISHED WEEKLY AT

No. 361 BROADWAY, - - NEW YORK.

TERMS FOR THE SCIENTIFIC AMERICAN.

(Established 1845.)

One copy, one year, for the U. S., Canada or Mexico.....\$3.00
One copy, six months, for the U. S., Canada or Mexico..... 1.50
One copy, one year, to any foreign country, postage prepaid, £1 10s. 5d. 4.00
Remit by postal or express money order, or by bank draft or check.
MUNN & CO., 361 Broadway, corner Franklin Street, New York.

The Scientific American Supplement

(Established 1876)

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for the U. S., Canada or Mexico. \$6.00 a year, or £1 4s. 5d., to foreign countries belonging to the Postal Union. Single copies 10 cents. Sold by all newsdealers throughout the country. See prospectus, last page. Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year, to one address in U. S., Canada or Mexico, on receipt of seven dollars. To foreign countries, eight dollars and fifty cents a year, or £1 15s. 11d., postage prepaid.

Building Edition of Scientific American.

(Established 1885.)

THE BUILDING EDITION OF THE SCIENTIFIC AMERICAN is a large and splendidly illustrated periodical, issued monthly, containing floor plans and perspective views pertaining to modern architecture. Each number is illustrated with beautiful plates, showing desirable dwellings, public buildings and architectural work in great variety. To architects, builders, and all who contemplate building this work is invaluable. Single copies 25 cents. By mail, to any part of the United States, Canada or Mexico, \$2.50 a year. To foreign countries, \$3.00 a year, or £2 12s. 4d. Combined rate for BUILDING EDITION with SCIENTIFIC AMERICAN, to one address, \$4.00 a year, to foreign countries, \$5.00 a year, or £3 9s. 3d. Combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN, and SUPPLEMENT, \$8.00 a year. To foreign countries, \$11.00 a year, or £2 5s. 2d., postage prepaid.

Export Edition of the Scientific American

(Established 1878)

with which is incorporated "LA AMERICA CIENTIFICA E INDUSTRIAL," or Spanish edition of the SCIENTIFIC AMERICAN, published monthly, uniform in size and typography with the SCIENTIFIC AMERICAN. Every number contains about 100 pages, profusely illustrated. It circulates throughout Cuba, the West Indies, Mexico, Central and South America, Spain and Spanish possessions wherever the Spanish language is spoken. THE SCIENTIFIC AMERICAN EXPORT EDITION has a large guaranteed circulation in all commercial places throughout the world. \$3.00 a year, or £2 12s. 4d., postage paid to any part of the world. Single copies, 25 cents.

MUNN & CO., Publishers, 361 Broadway, New York.

The safest way to remit is by postal order, express money order, draft or bank check. Make all remittances payable to order of MUNN & CO. Readers are specially requested to notify the publishers in case of any failure, delay, or irregularity in receipt of papers.

NEW YORK, SATURDAY, JULY 3, 1897.

Contents.

(Illustrated articles are marked with an asterisk.)

American ships for Japan*..... 3
Bacteria used of..... 8
Balloons, army*..... 10
Battleship Massachusetts, figure of Victory for*..... 7
Bicycle brake, Bergfeldt's*..... 6
Books, new..... 12
Presentis, Prof. death of..... 4
Cruisers, American, for Japan*..... 3
Egyptian crocodile mummy, an..... 10
Flooring materials, wearing qualities of*..... 6
Fluorine, liquefaction of..... 5
Presentis, Prof. death of..... 4
Glacier eruption, a..... 9
Government without taxation..... 5
Heavens, the, for July..... 9
Indians, Yukiah, last of*..... 11
Insanity in animals..... 7
Inventions recently patented..... 12
Kite balloon, Parseval's, German army*..... 10
Lands, the public..... 5
Locomotive valve testing device, Sadler's*..... 6
Marine statistics..... 5
Metals, the fatigue of..... 4
Notes and queries..... 13
Patent decision, recent..... 8
Patent office rules abrogated..... 4
Patents granted, weekly record..... 12
Pump, the world's biggest*..... 8
Railroad building, fast..... 5
Railroad rails, expansion of..... 9
Science notes..... 9
Swing, Bausman's*..... 7
Switch, railway, Lickstrom's*..... 7
Victory, figure of, for a battleship*..... 7
Yacht, fastest steam..... 5

TABLE OF CONTENTS OF Scientific American Supplement

No. 1122.

For the Week Ending July 3, 1897.

Price 10 cents. For sale by all newsdealers.

I. AUTOCARS.—The Engineer Motor Car Competition at the Crystal Palace, London.—Detailed description of the several horseless carriages which were presented in the competition.—The reasons for giving up the race are also given.—6 illustrations..... 17934
II. BOTANY AND HORTICULTURE.—Lathyrus Splendens.—1 illustration..... 17941
Solandra Grandiflora.—1 illustration..... 17940
III. CHEMISTRY.—The Prevention and Removal of Smells.—By FREDERICK H. GREEN..... 17936
IV. CIVIL ENGINEERING.—The Blackwall Tunnel Beneath the Thames.—A detailed description of this most important engineering work, accompanied by illustrations of the engineers, the completed tunnel and the machinery used in constructing the same.—A most full and elaborate paper.—13 illustrations..... 17927
V. GEOLOGY.—The Arctic Sea Ice as a Geological Agent.—By RALPH S. TARR..... 17941
VI. HYGIENE.—Efficiency of Kerosene Tests..... 17937
VII. MARINE ENGINEERING.—Note on the Bessemer Fleet..... 17931
VIII. MEDICINE.—The Study of Crime and Degeneration from a Medical Standpoint.—By WILLIS S. ANDERSON..... 17937
IX. METALLURGY.—Smelting Furnace Burning Kerosene as Fuel.—2 illustrations..... 17931
X. MISCELLANEOUS.—Reception of the Emperor and Empress of Russia by the French Academy, October 7, 1896.—1 illustration..... 17938
Engineering Notes..... 17933
Electrical Notes..... 17933
Miscellaneous Notes..... 17933
Selected Formule..... 17932
XI. MUNICIPAL ENGINEERING.—Lighting American Cities..... 17936
XII. PHOTOGRAPHY.—X Rays and Photographic Compounds.—Some researches in fluorescent action.—By V. E. JOHNSON..... 17932
XIII. STEAM ENGINEERING.—Independent Surface Condenser.—1 illustration..... 17934
XIV. TECHNOLOGY.—Recent Information on Light Alloys..... 17932
Note on the Leather Industry of Germany..... 17941
Acetylene for Yacht Lighting..... 17941
XV. TRAVEL AND EXPLORATION.—Stockholm.—13 illustrations..... 17938
Alaska Developments..... 17940

PROPOSED BRIDGE ACROSS THE ST. LAWRENCE AT QUEBEC.

We have received from Mr. Charles Baillairge a sketch of a design which was made by him some forty years ago, for a proposed trussed railway suspension bridge across the St. Lawrence River, opposite Quebec. Our correspondent points out that the question of a bridge of this kind at Quebec is by no means a new one, and that this design, which we now have before us, was submitted as being the best solution of the problem of conveying the railroad and highway traffic across the river. Attention is called to the fact that this sketch of over forty years ago embodies the best features of modern practice for long span railway bridges. The distance across the river, opposite Dufferin Terrace, from cliff to cliff, is 4,800 feet, and this was to be spanned by three 1,200 foot river spans and two 600 foot shore spans. The bridge was to have been built on the trussed suspension system and was to have a double deck, the lower deck being used for railroad traffic and the upper deck for highway and pedestrian traffic. The foundations were to have been carried down more than 150 feet below high water, the piers being built of solid first-class masonry up to the level of the lower floor or deck of the bridge.

The plan view shows an arrangement of five cables. The center cable was to hang in a vertical plane, the four outer cables being considerably "cradled." Mr. Baillairge points out that this old design is quite applicable in its broad features to the conditions of modern bridge building, and that it would merely be necessary to make such changes in the details as would be called for by modern developments in the manufacture of steel and general bridge material. It is pointed out that the deep foundations could be constructed on the principle of the Hawkesbury River piers erected a few years ago in Australia by the Union Bridge Company, of New York, in which some of the piers were carried down through mud and sand to a depth of 180 feet.

THE NEW RULES OF PRACTICE OF THE PATENT OFFICE ABROGATED.

The revised rules of practice of the Patent Office, which were promulgated by the late Commissioner of Patents, were abrogated Saturday, June 19, by Secretary Bliss on the recommendation of Commissioner Butterworth, and the original rules of practice, which were in force April 1, 1892, have been reinstated. The original rules referred to numbered in all two hundred and twenty-nine, and they were condensed by the late Commissioner to eighty-eight.

In abrogating the revised rules of his predecessor, Mr. Butterworth has incorporated several amendments bearing upon the practice of the Patent Office. Of these, rule 17 reads as follows:

"An applicant or assignee of an entire interest may prosecute his own case, but he is advised, unless familiar with such matters, to employ a patent attorney, as the value of a patent depends largely upon the skillful preparation of the specification or claims.

"An applicant may be represented by (a) Any person who, at the date of approval of this rule, is in good standing as a practitioner before the Patent Office.

"(b) Any attorney-at-law in good standing in any court of record in the United States or in any of the States or Territories thereof.

"(c) Any person of good moral character who shall show to the satisfaction of the Commissioner of Patents that he is duly qualified to act as attorney in the prosecution of cases before the office."

THE FATIGUE OF METALS.

An investigation of the fracture of a steel rail on the Great Northern Railway, in England, has brought out some interesting facts bearing upon the question of the fatigue of metals. On the occasion in question a Bessemer steel rail, which had been in use for about twenty-two years, broke into nearly a score of pieces beneath the wheels of a Great Northern express train, causing a serious wreck. An examination was carried out by Mr. Thomas Andrews, M. Inst. C.E., and in a paper on microscopic observation on the deterioration by fatigue in steel rails, he gives some very interesting particulars regarding the appearance of the broken fragments of the rail. The composition of the rail was as follows: Carbon 0.53 per cent, silicon 0.12 per cent, phosphorus 0.08 per cent, sulphur 0.09 per cent. The microscopic examination revealed a large number of fine hair cracks, and Mr. Andrews concludes that the continual hammering of the wheels had developed these minute fractures throughout the body of the metal and produced the remarkable simultaneous failure which occurred at many points of the rail. The occurrence of such hair-like cracks in manufactured steel is not uncommon, and just what it is that causes them is an open question. It is possible they occur in the process of rolling, and that in the case of steel rails they are to be traced to this origin more than to the severe concussion of the traffic which passes over them. This supposition is borne out by the fact that such cracks are to be found in the newly finished output of the mills,