## Engineering Improvements.

STEAM-ENGINE .- LOUIS DALLA-DECIMAS, Courbeoie, ADOLPHE KECHEUR, Billancourt, and AUGUSTE CHAGNAUD, Cognac, France. This invention provides an engine having three cylinders arranged radially about a common central chamber, each cylinder having two passages leading respectively from its inner to its outer end. A valve controls each of the passages. To pistons in the cylinders, piston-rods are rigidly secured, so as to have a rectilinear reciprocating motion. Each of the pistons carries at its outer end a head provided with a transverse slideway, engaged by the crank-pins of rotatable pinions. A gear-wheel rotates upon the axis from which the cylinders radiate, and engages the pinions. The rotation of the gear-wheel controls the motion of the valves.

## Mechanical Devices.

DADOING AND TENONING MACHINE.-ALOIS KOHLER, New York city. The purpose of this inven-tion is to provide an improved machine by means of which certain parts of the framing for door and window casings may be cheaply and rapidly produced. The apparatus consists of a frame slidable upon the main frame of the machine and carrying two shafts, one provided with the dado-heads and with a cut-off saw between the heads, and the other provided with the tenoning heads. The frame can be moved toward and away from the stock placed upon the working-table. The device constitutes a compact and easily operated machine, which may be so set, that accuracy and uniformity of the work may be attained with the use of ordinary labor.

WAVE-MOTOR.-JOHN W. PITTS, Hueneme, Cal. This invention provides a wave-motor having a float or buoyant vessel containing gearing and a frame hung from a mast attached to the gearing, so that the diversities of movement occurring between the frame and the vessel will be transmitted to the gearing in a manner adapted for practical use.

# Railway Appliances.

AIR-BRAKE.-WILLIAM T. HAMAR, Atlanta, Ga. This invention provides an improvement in the main piston of the triple valve of an automatic air-brake system, used for the purpose of passing air from a train-pipe to the auxiliary air-reservoir located on the car in the position of "brakes applied." The invention provides means for recharging the auxiliary air-reservoir while the brakes are still applied or before the airis discharged from the brake-cylinder, so that the auxiliary air-reservoir is ready to perform its full and effective work at its normal pressure in a second application of the brakes, immediately after the brakes are taken off.

AUTOMATIC SIGNALING MECHANISM FOR LOCOMOTIVES.—MASON A. BAMBOROUGH, Chicago, Ill. The object of this invention is to provide a signal ing mechanism for locomotive engines, which is designed to sound automatically the whistle or gong, as may be desired, at or near stations, crossings, switches, or other In connection with the locomotive whistle or bell, a rod is connected which extends downwardly, A lever is transversely arranged beneath the locomotive and engages the rod. A lever-arm, jointed to and swinging freely from the outer end of the lever, is adapted to engage a trip-block alongside the track, so as to operate the whistle or gong.

## Miscellaneous Inventions.

BOTTLE-STOPPER. - URIAH L. RIFE, Newport, R. I. This bottle-stopper has a plug adapted to engage the end of a bottle-neck. A metal sleeve depends from the plug and has a number of longitudinal slits forming fingers. A bushing of yielding material surrounds the sleeve, the sleeve being extended the entire length of the bushing so as to prevent buckling. A stem movable through the plug has a bulb at its lower end to expand the sleeve, a head on its outer end, and a spring between the head and the plug.

CRATE.-EDWARD S. SHELLHOUSE, Carey, O. The folding crate provided by this inventor has a base composed of parts rigidly connected, with sockets interiorly located at the corners. An upper folding section having side pieces is also provided and has a hinged connection with the corresponding parts of the basesection. End pieces are adapted to rest upon the end portions of the base-section, and have corner-posts arranged to enter the sockets in the base. The corner-

come the deterioration due to the expansion and contraction caused by the successive heating and cooling of tin-plates while being annealed, these inventors have connected with the body of the annealing-pot, flanged near its interior edge, a removable top composed of sections suitably connected, and an arched top brace having a dovetail slide detachably connected with two of the sections. By constructing the pot in detachable remova-ble sections, expansion and contraction, it is claimed, are so neutralized that twisting and cracking are prevented.

HARNESS-LOOP .- JOHN T. CONDON, Lemars, Ia. The device of this inventor is an improvement in the class of skeleton metal loops which are applied to various portions of harness, more especially to neck-yoke, breast, hame, and breeching straps, for the purpose of securing the ends of the straps at points contiguous with the buckles. The loop comprises obtuse augled side bars, having pendant ears and four connecting bars, one being curved inwardly. The middle of the three bars is located in rear of the bottom one and confines the loop of the strap. The front bar is curved to accommodate the buckle-tongue, its ends being in contact with the buckle-frame.

DRAFT-CLEVIS FOR PLOWS .- STACY H. SNOW-DEN, Arcturus, Va. By means of the improvements embodied in this draft-clevis for plows, the inventor is enabled to regulate the amount of land cut by the plow, and to secure a regulation of the depth of a plow when in operation. The clevis has a latch provided with a notched wing and with a stop wing at an angle thereto. A draft connection is provided consisting of two hooks swiveled together, one of the hooks being adapted to be secured in different engagements with the clevis, by means of the notched wing ; and the other hook being adapted for connection with the whiffletree. By adjusting the swiveled hook, the plow may be made to sink more deeply or to exert a greater lateral force.

CORE FOR PAPER ROLLS .- JOHN J. MORAN and SIDNEY E. SMITH, New York city. This invention pro-vides a core for rolled paper, such as that which is used in printing-presses. The core is made collapsible or capable of being removed from the roll of paper after it has been wound, thereby avoiding the necessity of shipping cores in the rolls and returning the cores to the mill after the paper has been used, and also obviating the expense of procuring cores sufficient to supply the needs of the mill while other cores are in transit or held at the printing-office.

BEDSTEAD.-BENJAMIN F. BAILEY, Ellisville, Miss By means of the durable support provided by this inventor, bed-slats may be conveniently attached to the side rails of a bedstead, the support for the slats being of such character that it will not harbor vermin and will add materially to the strength of the rails. Tips are provided for the ends of the slats, which tips are adapted for engagement with the supports on the side rails. When placed in position, the slats serve to tie the side rails together wherever a slat is placed, thus adding to the strength of the bedstead.

CARPET-BEATER.-CHARLES M. COMSTOCE, Wind sor, N.Y. This carpet-beater consists of a handle having a cylindrical section provided with longitudinal grooves in opposing faces, the grooves having inclined lower faces. The end portions of a rattan bow engage with the grooved surfaces of the handle extension. Clamping-sleeves conforming with the shape of the extension of the handle and with the outer formation of the members of the bow, are also provided. These sleeves receive the members of the bow and are passed over the extension portion of the handle. By this means the members of the bow will be subjected to a wedge-like action to clamp them firmly to the handle extension, thus providing a secure fastening for the rattan.

PROTECTOR .- HOWARD K. FOILANSBEE, Wellington, O. This invention provides an improved protector especially designed for use in an ordinary vest-pocket to keep the walls thereof spread apart to permit the protection and reception of cigars. When closed, the device forms a casing for a single cigar or other article. The protector consists principally of two oppositely arranged members and a folding device to connect the members with each other and close them so as to form either a casing or a means whereby the members are spread apart.

CIGAR-LIGHTER. - AUGUSTUS C. GRUHLKE, Waterloo, Ind. In this invention a cigar-lighter is provided, which is suspended from the ceiling so as to hang near a show-case. The lighter in question is automatically enkindled by an electric spark when drawn toward the person desiring to use the device; is automatically extinguished when released; and is so constructed that the electric current cannot be short-circuited.

HAIR-FASTENER.-SETH W. HERRICK and CALER R. LUNGER, London, England. Hither the duplex combe employed in hair-dressing have been permanently riveted or hinged to each other. These constructions have the disadvantage of permitting only a small degree of separation at the jointed sides. Difficulty is also experienced in placing the comb exactly upright after folding the hinged portions together. These objections are overcome in the present invention, by providing a comb consisting substantially of two entirely separable combs, so designed as to be canable of interlocking. One of the combs is provided for this purpose with guideways extending longitudinally of the teeth. the other comb having blades or prongs adapted to enter these guideways. TIME-OPERATING VALVE. -- THOMAS KITSON Stroudsburg, Pa. This valve is particularly adapted to the controlling of the dampers and doors of stoves, and is connected with an alarm-clock, so that, as the alarm is sounded, mechanical devices are operated to release a chain or other connection. A circular backplate is adapted to be attached to the clock and has an annular flange at its edge projecting from one face to eugage with the clock. A lug attached to the plate projects from a break in the flauge and acts as the fulcrum of a lever having one arm projected through the break in the flange and lying alongside of the inner face of the plate. An arm rigid with the plate projects ontwardly therefrom adjacent to the lug. A finger is pivoted to the

HAND-STAMP .- CALEB LEE. Homeworth. O. The purpose of this invention is to provide a stamp designed for use in post-offices, business-houses, and the like. The device comprises a revoluble inking-pad mounted yieldingly, a platen arranged adjacently to the inkingpad, a revoluble stamp-carrier holding a number of stamps, and controlling the movement of the inkingpad, a spring-pressed shaft formed with a spiral groove and mounted to turn and to slide, and a spring pressed pawl engaging the groove to turn the shaft on its return novement.

COMPRESSED-AIR WATER-ELEVATOR .- WIL-LIAM A. MITCHEIL, Nashville, Tenn. The water-eleva-tor forming the subject of this invention is so constructed, that water may be supplied from a cistern to any point in a building or to any point removed from the source of supply, it being possible to discharge any water that may be in the pipes, and to refill the pipes quickly with fresh water, thus obviating the necessity of using water that may have become stale by stagnation. A self-filling water-cylinder is provided which is placed in the source of water-supply. A return-pipe is connected with the service-pipe and with the cistern or source of water supply, and is adapted to conduct water from the service-pipe into the cistern in such a manner, that the water delivered by the returnpipe, together with any air that may be within the return-pipe, will agitate and purify the water in the cistern. fresh cool water, as previously stated, simultaneously entering the service-pipes from the cistern.

FILTER.-ALBERT L. MCLANE, Laredo, Tex. With basin, a series of filters are connected, each having porous walls and chambers. Each of the filters has a valve controlled connection with a discharge-pipe. A flushing or service-pipe is provided with which each of the filters has a valve-controlled connection. In operation the basin is filled and the several filters are entirely submerged. The water will percolate through the porous material and will then be discharged from chambers into the main pipe.

TYPE-WRITER CABINET .- PHILIP E. WHITING, Carmi, Ill. This inventor has devised a cabinet in which everal compartments are provided for the machine and for supplies. These compartments have doors, which are connected with one another, and with a drawer that supports the type-writer. When the drawer is pulled out, the type-writer compartment and the supply-compariments are opened. The compartments are closed by pushing the drawer in.

#### Designs.

TIP-CAT.-ROBERT A. NAGLER, New York city. The tip-cat of this inventor differs from most others in being made of elastic rubber, whereby the cat, upon being struck upon one of its pointed ends, will bound to a greater height and distance than is usual in wooden cats. The sides of this rubber cat are hollowed to enable it to be readily picked up.

BADGE.-LAHVESIA P. C. LOCKWOOD, Lake Maitand, Fla. The leading feature of this design consists in two plates, one pendent from the other. Upon one plate a pig is drawn ; upon the other plate a man is pictured in kneeling position. The design represents figuratively. Spain begging peace from the United States.

Note.-Copies of any of these patents will be furnished by Munn & Co. for 10 cents each. Please send the name of the patentee, title of the invention, and date of this paper.

## NEW BOOKS, ETC.

A SHORT MANUAL OF ANALYTICAL CHEMISTRY: QUALITATIVE, QUAN-TITATIVE, INORGANIC AND ORGANIC. By John Muter, Ph.D. Philadelphia: Blakiston, Son & Company. 1898. p. 228. 8vo. Illustrated. Price P. J Pp. \$1.25.

The present manual is the second American edition adapted from the eighth British edition, which shows that the book has been received with great favor. It is designed to introduce students to the chief developments of analytical chemistry, from the simplest operations upward, and including many organic questions generally overlooked in elementary books. By working through it a student will become familiar with a great variety of esses, and will then be in a position to use with satisfaction the exhaustive treatises dealing with any spe-cial branch he may wish to follow. The book is illustrated and is accompanied by a large number of analytical tables.

A TEXT BOOK OF MINERALOGY. With an Extended Treatise on Crystallo-graphy and Physical Mineralogy. By Edward S. Dana. New York : J. Wiley & Sons. 1898. Pp. 593. 8vo. 1,000 illustrations. Price \$4.

The "Text Book " is a very old friend and has always maintained the reputation of being one of the best and most usable books ever published on the subject in any language. The remarkable advance in the science of mineralogy during the years that have elapsed since the "Text Book " was first issued in 1877 has made it necessary in the preparation of a new edition to rewrite the whole, as well as to add much new matter and many illustrations. All who are in any way interested in mineralogy cannot fail to receive a vast amount of information from this book. It is a standard reference book which we keep on our table to settle all questions of mineralogy. We know of no book on the subject in the English language which is so thoroughly good. It is, perhaps, too advanced for the beginner, but fortunately the Danas have three books, in which the subject is carefully graded. The present volume might be called the intermediate one.

# Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in the following week's issue.

Marine Iron Works. Chicago. Catalogue free,

" U. S." Metal Polish. Indianapolis. Samples free. Gasoline Brazing Forge, Turner Brass Works, Chicago. Yankee Notions. Waterbury Button Co., Waterb'y, Ct. Schwaab Stamp & Seal Co., Milwaukee. Send for cat'g. Send 8 cents for sample number of Model Engineer. Spon & Chamberlain, 12 Cortlandt St., New York

Gear Cutting of every description accurately done The Garvin Machine Co., Spring and Varick Sts., N. Y.

FERRACUTE Machine Co., Bridgeton, N. J. Full line of Presses, Dies and other Sheet Metal Machinery.

Easy Experim'ts of Organic Chemistry. Book by Prof. Appleton. 60 cents. Snow & Farnham, Providence, R. I. Hub, spoke, wheel, bending, and handle machinery,

Single machines or full equipments, by the Deflance Machine Works, Deflance, Ohio, U. S. A.

The celebrated "Hornsby-Akroyd" Patent Safety Oll Engine is built by the De La Vergne Refrigerating Ma-chine Company. For t of East 138th Street, New York.

The best book for electricians and beginners in elec-ricity is "Experimental Science," by Geo. M. Hopkins. tricity is By mail, \$4. Munn & Co., publishers, 361 Broadway, N.Y.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway New York. Free on application.



HINTS TO CORRESPONDENTS.

- Names and Address must accompany all letters or no attention will be paid thereto. This is for our or no attention will be paid thereto. information and not for publication.
- a constant will be part interest.
  a constant will be part interest.
  a constant interest in the part interest interest interest interest.
  a constant interest interest interest interest interest.
  a constant interest int

- scientific American Supplements referred to may be had at the office. Price 10 cents each. Books referred to promptly supplied on receipt of

Minerals sent for examination should be distinctly marked or labeled.

(7516) H. J. L. asks: Can the alternatng current be changed into a continuous current? If so, how? A. If you have an alternating current dynamo, it can be changed to give a continuous current by putting a commutator upon the axle in place of the collector ringe. If, however, the alternating current is obtained from a street line, it can be changed to a continuous current by a rotary transformer in which the alternating current drives the motor part, and in turn by a commutator a direct current is taken off, of such voltage as may be required.

# INDEX OF INVENTIONS

# For which Letters Patent of the United States were Granted

# **NOVEMBER 1, 1898,**

AND EACH BEARING THAT DATE.

1	See note at end of list about copies of these pat	ents.]
1	Advertising device, A. A. Du Bois Advertising vehicle, T. J. King Aerating liquids or beverages, apparatus for,	613,503
4	Advertising vehicle, T. J. King	613,634
4	Koopig & Flanger	612 276
1	Koenig & Erlanger Alarm. See Leak and fire alarm.	010,010
1	Aldehydes, making aromatic, P. P. Monnet	613.460
4	Animaltran J K Chass	613 559
4	Animal trap, E. Piggott	613,304
1	Atomizer, A. M. Foster	612 604
í	Back nedaling brake, F. L. Clann.	613.619
ī	Audiphone. A. Ross. Back pedaling brake, F. L. Clapp Back pedaling brake, W. D. Robinson	613,477
i	Bag fastening, C. Le Duc. Bag fastening, C. Le Duc. Bags, portmanteaus, etc., securing, N. Buxton Ballot box, McCarron & Montgomery. Barrel and binding therefor, knockdown, F. W. C. Schaperkotter Basket, folding, R. H. & W. A. McNair.	613,580
1	Bake, portmanteaus, etc., securing, N. Buxton	612 904
i	Barrel and hinding therefor knockdown h' W	010,291
1	C. Schaperkotter	613.531
I	Basket, folding, R. H. & W. A. McNair	613,387
ļ	Basket, knockdown. A. R. Tiffany Battery. See Water battery.	613,335
i	Battery. See Water battery.	
ł	Bayonet and gun sight, combined, B. Burton	613.49
î	Bed, collapsible, W. J. Curry	613.49
Ī	Belting, protective covering or shield for chain,	010,100
	Bayonet and gun sight.combined, B. Burton. Bearing, ball, J. (J. Buebler	613,63
ļ	Bicycle, C. C. Chrisman	613,24
ł	Bicycle, J. E. Praul.	613,60
i	Bicycle gear case R Ramaay	613.46
ì	N. C. Base ett. Bicycle, C. C. Chrisman. Bicycle, J. E. Praul. Bicycle brake, S. S. Goldman. Bicycle brake, S. S. Goldman. Bicycle sadle. B. McGregor. Bicycles, etc., pedal mecbanism for, C. Meler. Billardt table cushion, T. R. S. Bullock. Bit. See Drill bit.	613.29
Ì	Bicycles, etc., pedal mechanism for, C. Meier,	613.45
ļ	Billiard table cushion, T. R. S. Bullock	613,40
-	Bit. See Drill bit.	
ł	Boat and sled, combined, W. A. Kirby Boiler. See Steam boiler.	613,57
i	Boiler furnace, downdraught, G. H. Watson	613.61
i	Boiler gage, N. H. Hiller	613.44
ļ	Boiler gage, N. H. Hiller Bottle cap, A. Mazzanovich	613.28
ļ	Bottle or similar receptacle, Hoffman & Frist	613,37
1	Bottle stoppers, feed chute for crown, F. O.	612 94
1	Woodland Bottle washer. A. Bosanko Bottles, articles of glass, etc., appliance for pack-	613.23
ī	Bottles, articles of glass, etc., appliance for pack-	010,40
	ing, H. B. Roxburgh Bottles. device for preventing fraudulent refili-	613,52
1	Bottles, device for preventing fraudulent refill-	
1	ing of, N. Nelson Box. See Ballot box. Cock box. Folding box. Mail box. Match box. Pencil box. Tele-	013,40
ſ	Mail box. Match box. Pencil box. Tele-	
1	Box assembling machine, J. F. Gilliland	613.62
ļ	Box assembling machine, J. F. Gilliland Box fastener, L. C. Dickerman Bracket. See Car dowr bracket. Lantern bracket. Braiding machine, L. L. F. Malhere	613,50
ł	Bracket. See Car door bracket. Lantern bracket.	e11 20
ł	Brate See Back nedsling brake Bicycle brake	013,30
i	Bridge safety gate. Heffron & Rice	613.56
1	Brake. See Back pedaling brake. Bicycle brake. Bridge safety gate, Heffron & Rice Bronzing machine. Emmerich & Vonderlehr	613,41
ļ	Button fastener, T. E. Jones.	613,37
1	Can cover milk C Congdon	613.44
ì	Builton fastener, T. K. Jones, Gauera, foldinu, H. M. Reichenbach. Can cover, milk. C. fongdon. Car coupling, W. F. Richards. Car coupling, J. H. Simcox.	613.31
ì	Car coupling, J. H. Simcox	613,42
	Car coupling, automatic, C. Mehring	

posts are formed with ledges on their upper ends, upon which ledges a covering-piece is adapted to rest. This covering-piece is provided with a door. Locking-devices connect the side-pieces of the upper section with the end-pieces of the upper section.

JAR-CLOSURE. - JOHN SCHIES, Anderson, Ind. This invention aims to provide a simple and novel form of fastener and of stopper, trgether with a mouth and neck conformed to and co-operating therewith, by which a secure and tight closure is effected, the whole present ing an attractive appearance. By employing a clamping bar or rod of especial construction, the stopper may be heid firmly in the mouth of the jar and may, with equal readiness, be removed.

PACKING FOR PUMP-PISTONS .- FREDERICK VAN DEN POSCH, Parker's Landing, Pa. The inventor claims that his packing possesses the elasticity of a leather cup without becoming soft in oil or hard in sait water. The packing in question consists of a body formed of fibrous material, and of a base-ring made of vulcanized rubber united with the lower edge of this fibrous body and possessing greater rigidity than the latter.

arm and is engaged with the outer end of the lever. By ANNEALING-POT. - WILLIAM P. DOULIN and FRANCIS W. RAYMOND, Wheeling, W. Va. To over- this means the finger is held until the lever is thrown.

ROCEEDINGS OF THE FIFTEENTH AN-NUAL CONVENTION OF THE NA-TIONAL CONFECTIONRRS' ASSOCIA-TION OF THE UNITED STATES. Held Chicago, Ill., June 1 and 2, 1898. Official Records of Reports, Circulars, and Communications for the year 1897-1898. Philadelphia: Confec-1897-1898. Philadelphia: Continers' Journal. 1898. Pp. 279.