RECENTLY PATENTED INVENTIONS.

Mechanical Devices.

DRILL-CHUCK. - WILLARD H. MERREL. Oneida. N. Y. To provide means whereby a drill or like tool may be firmly held in place to prevent it from turning in the jaws, this inventor provides a chuck whose bodyportion has a transverse seat. Two jaws slide toward and from each other in this seat and meet at the center of the chuck. Interlocking fingers on the jaws hold the drill. The jaws have respectively right and left hand threads at one side, and at opposite sides are provided with shoulders. The enlarged end portions of a screw-rod bear against shoulders on the body, are oppositely threaded and are engaged respectively with the threads on the jaws. By this means the jaws are advanced and retract Two screws working in opposite sides of the body and having heads engaged with the shoulders on the jaws, lock the jaws in place.

MAGAZINE BOLT-GUN.-JOHN H. BLAKE, NEW York city. The fire-arm patented by this inventor is capa ble of being used either for single or for magazine firing, a simple and easily operated cut-off being provided, by means of which the magazine may be brought into or thrown out of action as desired, the magazine when not in action remaining in the gun. A cartridge-packet is also provided in which a number of cartridges may be quickly placed. Only a single packet is placed in the magazine-chamber. This magazine-chamber is so constructed that the packet, while normally concealed, may be rendered visible at any moment. The packets are made so as to be carried loaded in a belt as is customary in carrying single cartridges, thus enabling a marksman to substitute quickly, a loaded for an empty packet in the magazine, a cartridge being at the time within the barrel ready to be fired. The bolt is so made that its parts may be easily separated and assembled again. In addition to its usual function, the sear in this gun is employed to prevent a rocking movement of the bolt when the latter is in firing position.

WEIGHING AND FILLING APPARATUS .- Jo-SEPH E. J. GOODLETT, Memphis, Tenn. In this invention we find means for filling receptacles with liquids, for delivering a predetermined quantity of the fluid, and for cutting off the delivery automatically. The apparatus includes, as its chief features, a weighing scale upon which the liquid receptacles are placed to be filled, a filler proper, which is provided with automatic valve and trimechanism for controlling the flow and delivery of liquid and an electrical switch and circuit and co-operating de vices for actuating the trip mechanism when the weight of the liquid delivered into a receptacle reaches the predetermined limit.

Railroad Appliances.

COMBINED DUST-GUARD, CAR-AXLE LUBRI-CATOR, AND HOT-BOX INDICATOR .- JAMES S PATTEN, Baltimore, Md. The dust-guard provided for in this invention has, connected with the axle-box, a curved supporting spring whose convex portion bears upon the bottom and outer end of the axle-box and whose extended outer end rests upon the bearing of the journal, whereby the dust-guard is elastically held in place. The lubricator consists of a roller running in a stratum of oil and so pivoted to the upward and recurved rear ends of the spring that it will take up and transfer oil to the journal. The "hot-box" indicator operates in a box or holder having open perforations and means for supporting the latter in the axle-box above the oil-space and holding it in contact with the bearing. In the box a substance is placed capable of emitting a strong, easily perceiv d odor when the oil runs out and the friction heats the substance, thus indicating the presence of a

CAR-COUPLING .- HERMENEGILDE and AIME LOI-SELLE, Winnipeg, Canada. The purpose of this invention is the provision of a simple and effective car-coupling, which shall couple cars automatically when they come together, which shall not come apart accidentally nor cramp and bind in turning curves and which shall be adapted to couple cars having the ordinary construction of draw-bar and the ordinary link and pin coupling. The coupling has a pair of jaws pivoted on horizonta axes and having tapered noses and grappling surfaces. each face having a central recess with a lip at top and hottom. A lug partly closes one end of the recess and has a notch at the top and bottom of the lug for the purpose of locking the jaws against vertical as well as horizontal motion.

CAR COUPLING -VALENTINE ERBACH, Scranton Pa. This coupler is of the knuckle-type and is so constructed that it will be of less dimensions than ordinary knuckle-couplers, will not present any unnecessary side projections and will be simple and durable. In this coupling a draw-head is provided having a long and a short horn at opposite sides, the long horn being chambered and having a shoulder formed between its ends A knuckle mounted to swing in the chamber of the long horn has a vertical shoulder in line with the shoulder in the long horn, and at its pivot point has its lower surface engaging correspondingly-inclin face on the draw-head. A release lever is pivoted to the knuckle and is adapted to engage with its head an oppos ing knuckle when two draw-heads are brought togethe. and are in coupling position.

BICYCLE SADDLE .- Louis P. Wellmann. Union, Hudson County, N. J. This saddle is made to form a flexible seat which may vield with the motions of the rider and which may be adjusted in width. The saddle has two independent seat-portions each with a depression of irregular shape in its upper face, which depression is adapted to fit the body. A stem is formed integral with each seat-portion, the stem and seat-portion being composed entirely of rubber, whereby the seatportion will yield to the weight of the rider and bend as a whole with respect to the stem so as to conform with the position of the thigh.

SASH-FASTENER - LEWIS H. BOWMAN Walls Walla, Wash. The purpose of this invention is the provision of a fastener which shall lock a sash in any desired position without rattling and which shall make a tight joint between the sash and casing. The sashholding device comprises a vertically moving sashlocking member, a horizontal lever pivoted beneath the window-sill, connections from one end of the lever to the sash-locking member, a bent hand-lever pivoted by chine Company. Foot of East 138th Street, New York,

one end beneath the sill and having an arm lying flush with the sill when the window is locked, and a link connecting the lever near its bend with the other end of the first-named lever. The pivots on the hand-lever and its connected link are nearly in line when in locked position, the center pivot being sufficiently at one side of the center line to hold the parts locked.

SNAP-HOOK. - CHARLES F. FRANCISCO, Lakeside Cal., and EUGENE E. SHAFFER, San Diego, Cal. This invention has for its purpose the provision of a simple, cheap, and efficient snap-hook which remains firmly in locked engagement with the ring or buckle to which it is coupled. The snap-hook comprises a frame portion having a hooked portion and three cross-pieces, of which which the first two are at the lower side, with an open space between them, the third cross piece being arranged at the upper side and between the first two cross-pieces A U-shaped spring has its lower bent end hooked over the second cross-piece, its middle bend surrounding the first cross-piece and its free end pressing upwardly. A latch is arranged within the frame above the free end of the spring.

HARNESS ATTACHMENT.-WILLIAM R. PHILLIPS Pomona, Cal. The attachment provided for by this inventor may be applied to any harness, and is arranged to hold the lines in proper position so as to prevent entanglement with other parts or with the horse's tail. The attachment comprises a loop having at one end means for securing it to a strap and having its rear member split or separated to form an opening for the entrance and removal of a line and provided with lugs for engaging apertures in the strap to which the loop is at-

PIPE-COLLAR .-- EDWARD J. MALLEN, New York city. This pipe-collar is made with a body plate constructed in removable sections. Clamping plates are adjustably and removably held in the body plate and are made of spring-material. End clamping plates are mounted to slide in engagement with a central clampingplate, each clamping-plate having a pipe-receiving opening and divided at a portion in its surface. This division extends from the pipe-receiving openings to the outer edges of the plates. The device is applicable to all kinds of pipes and will not mar the appearance of a ceiling or wall. Fire-proof material may be filled in around the pipes, thus deadening all noise and prevent ing dirt from dropping down.

Designs.

HOSE REEL SPOOL,-HARRY E. DONNELL, New York city. This design consists of a hub from each end of which extend spokes arranged in pairs, the inner end of the spokes of a pair being separated and the outer ends being joined and terminating in a circular rim. The inner end of one spoke in a pair, joins the inner end of the adjacentspoke of the next pair.

GAME-BOARD.-WILLIAM B. GILES, New York city In this design, the surface of a game-board is divided into two parts or fields, with a groundwork of contrasting colors and with a series of disk-like figures, the color of one series of figures differing from that of another.

Note.-Copies of any of these patents will be furnished by Munn & Co. for 10 cents each. Please send the name of the patentee, title of the invention, and date of this paper.

NEW BOOKS, ETC.

Logic, Deductive And Inductive. By Carveth Read, M.A. London: Grant Richards. 1898. Cloth, 12mo. Pp. 323. Price £0.6.

This work more definitely separates logic, pure and simple, from all other studies, and especially from psychology and metaphysics. It is, in fact, a concise and comprehensive textbook of logic, the mastering of which is made more easy by the aid of questions that are introduced as an appendix.

ELECTRO-DYNAMICS-THE DIRECT CUR-RENT MOTOR. By Charles Ashley Carus-Wilson, M.A. London and New York: Longmans, Green & Company, 1898. Cloth, 16mo. Pp. Company. 1898. 298. Price \$1.75.

The aim of this volume is to apply the principles of electro-dynamics to the direct current motor. As it is a work intended for the enlightenment of electrical engineers, the author takes it for granted the reader i familiar with the use and design of motors; but he in the main avoids all technicalities, hoping thereby to render the volume useful to engineers generally.

THE CURE OF WRITER'S CRAMP AND THE ARM TROUBLES OF TELE-GRAPHERS AND BALL PLAYERS. By S. H. Monell, M.D. New York: J. B. Taltarall. 1898. Pp. 49. Paper 8vo. Price 50 cents.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line Advertisements must be received at publication office as early as Thursday morning to appear in the follow

Marine Iron Works. Chicago. Catalogue free. "U. S." Metal Polish. Indianapolis. Samples free. Gasoline Brazing Forge. Turner Brass Works, Chicago

Yankee Notions. Waterbury Button Co., Waterb'y, Ct. For bridge erecting engines. J. S. Mundy, Newark, N. J.

FERRACUTE Machine Co., Bridgeton, N. J. Full

line of Presses, Dies and other Sheet Metal Machinery Improved Bicycle Machinery of every description The Garvin Machine Co., Spring and Varick Sts., N. Y.

For Sale-Recent patent. 608,480, on apparatus fordraw ing liquids. A. Wahl, 96 Hoboken Av., Jersey City, N. J

The celebrated "Hornsby-Akroyd" Patent Safety Oil

The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4. Munn & Co., publishers, 361 Broadway, N. Y.

The Raw Silk Machine Wipers that are manufactured by the American Silk Mfg. Co., of Philadelphia, have attracted the attention of the government arsenals as being the best and really the most economical article of the kind. They are considered to be far superior to cotton waste, as thorough cleansers, and are, therefore, well adapted for use in intricate gun machinery and delicately made instruments. They are exceedingly soft to the touch, and as they can be thoroughly cleansed when soiled by means of ordinary soap and hot water, their great saving will be at once apparent. These silk machinewipers have long been favorites in many of the best engineers' and machine shops in the country, and they will undoubtedly be found of great value to our army and navy departments. Wherever used they have been praised, and the order duplicated, which speaks well for both their efficiency and economy.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.



HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters or no attention will be paid thereto. This is for our information and not for publication.

References to former articles or answers should give date of paper and page or number of question.

Inquiries not answered in reasonable time should be repeated: correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.

Buyers wishing to purchase any article not advertised in our columns will be furnished with addresses of houses manufacturing or carrying the same.

Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.

Scientific American Supplements referred to may be had at the office. Price 10 cents each.

Books referred to promptly supplied on receipt of price.

Minerals sent for examination should be distinctly

Minerals sent for examination should be distinctly marked or labeled

(7472) W. H. M. writes: In the May 15, 1897, issue of your paper, you have an interesting article on a toy caloric engine. You state that they are simple and reliable; that they have been known for years. This being the case, allow me to ask you why small and light ones of from 1 to 4 horse power have not come into general use for running fans, launches, etc.? There must be some drawback, and for the benefit of several of your readers here, please state it in the Notes and Queries. A. The caloric engine is rather beavy for the power produced, and has never seemed successful in very small powers—although largely in use for domestic pumping. For power purposes, the explosive motor, which is of much less weight in proportion to power, has almost displaced the caloric engine

(7473) J. H. W. L. says: Will you advise me what is a good tonic to prevent hair from falling out of the head?

A.	Quinine sulphate 2	90	gru.
	Tincture of cantharides	2	fl. drm.
	Fluid extract of jaborandi	2	**
	Alcohol	2	fl. oz.
	Glycerine	2	**
	Bay rum	6	**
	Rose water-enough to make	15	

The auinine is dissolved in the alcoholic liquids by warming slightly, then the other ingredients are added.

TO INVENTORS.

An experience of fifty years, and the preparation of more than one hundred thousand applications for patents at home and abroad enable us to understand the laws and practice on both centinents, and to possess unequaled facilities for precuring patents everywhere Asynopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business, Address MUNN & C... office SCIENTIFIC AMERICAN, 361 Broadway. New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

AUGUST 2, 1898,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Abrasive hand tools, files, etc., carrier for, H.	
Fooko	C 08.513
Focke	C08.363
Air compressors, automatic switch for regulating	•00,000
electric, Moseley & Funck	C 08,340
Animal trap. T. E. Troutt	C08,493
Armature for dynamo electric machines, Ander-	400,100
Armature for dynamo electric machines, Ander-	608,277
son & Thomson	000,211
Asphaltum and manufacturing same, s. 11.	608,372
Dubbs. Axle lubricator. car, E. W. Hancock.	608.329
Axle setting and straightening teel, B. F. Smith.	C08.528
Ax le setting and straightening too, h. F. Smith.	C08.357
Badge, A. H. Adams	C08.172
Bale or box hook, D. M. Botulinski	400,112
Bales, apparatus for unwinding cynnurical cot-	608.399
ton, Bosca & Benner	608.563
Baling press, N. B. Wilder	
Ball working machine, H. Meltzer	CO5,470
Bath. See Galvanic bath.	
Battery zinc, D. O gden.	608,216
Bed, cot, I Coburn	C08.547
Bed crib attachment, M. C. Lucas	608,523
Bed. spring, N. J. Shields	608,232
Bedstead, I. Coburn	608.546
Beehive swarm preventer, J. Koopman	608,261
Bell, bicycle, H.S. Fullman	C08,478
Bell, bicycle, E. H. White	608.499
Belt regulator, O. K. Sletto	608,486
Beverage cooler. L. Baumeister	608.169
Bicycle, C. E. Stockford	608,350
Bicycle attachment, J. S. Lord	603,262
Bicycle attachment, W. B. Spencer	608,235
Bicycle crank fastening device. E. V. Gauthier	608,448
Bicycle crank shaft, S. A. Donnelly	C08,445
Bicycle crank shaft. A. Levedahl	C08.369
Bicycle gear, H. Wilburn	CO8,241
Bicycle mud guards, machine for making, G. L.	
Allen	608,313
Bicycle speed signal. G. Dittmar	C08,511
Bicycle steadying device. F. Barto	C08,539
Bicycle support O. P. Breithut	609,543
Bicycle support, Jackson & Britten	COO 2012

V) R	109
Bicycle support, A. W. Lewis. Billiard cue, B. Hutzel. Binder, T. Wright. Blower, rotary, N. W. McIntosh. Boiler tube cleaner, F. W. Bradley. Book, note, C. H. Hastings. Book support, W. F. Frazee. Boot tree or stretcher, P. J. Parmiter. Bottle, etc., stopper, C. J. Muldoon. Bottle valve stopper, E. M. Raiguel. Bottles, etc., stopper, E. M. Raiguel. Bottles, etc., stopper for, G. Koch. Bowling alley pin, H. H. Luke. Box. See Mail box. Box making machine, Keunen & Hogfeldt Brake. See Car brake. Brake. See Car brake. Brake. W. H. Sauvage.	
Brake rod, B. Haskell Bread cutting knife, W. Merkle Broom clasp. W. H. Cason Brush, F. Goehring Bucket, H. F. Rigg	608,392 608,337 608,510 608,365 608,304
Burner. See Gas burner. Hydrocarbon burne Burnerand chimney holder, J. H. Moss. Bushing, tap hole, C. Hammer. Button, C. W. Stimson. Button, two part separable, O. L. Mahon. Cabinet, kitchen, W. Lackey	608,395 608,196 608,487 608,410 608,336
Cabinet table, kitchen, J. L. Huestis. Calipers, center finding register, G. W. Davis. Cap tasto, P. Benson. Car brake, automatic, F. A. Perry. Car, combined ventilating and refrigerator, Thompson. Car draught rigging, railway, D. Loomis. Car floor frame, railway, C. C. Wentworth. Car heating system. J. F. McElroy. Car journal box, railway, F. Hotzl. Car replacer. C. E. Dailey. Car step, folding. T. Kendrick. Cars, adjustable rack for railway, M. Butler. Carbureter, J. R. Stephenson. Cards for use in Jacquard machines, apparat for preparing, R. G. McCrum. Cash register, Hoffman & Norton. Cash register, and indicator, L. S. Burridge. Cash register, and indicator, L. S. Burridge. Cash register, autograph, J. A. Hoff. Casket stand, G. Cromniller. Cattle guard, P. H. Hazel. Celluloid press and vulcanizer. J. C. Dixon. Chain, sprocket, H. E. Stahl. Chair. See Reclining high chair. Chuck, screw machine, E. V. Gauthier. Churn, N. Isachson. Churn operating mechanism, L. Reed. Cigar holder and tobacco pipe, J. Bigelow. Clamp. See Floor clamp. Clasp. See Broom clasp. Cleaner. See Boiler tube cleaner. Pipe cleaner.	G08,183 G08,278 G08,429 F. G08,522 G08,522 G08,414 G08,212 G08,332 G08,332
Car sten, folding, T. Kendrick. Cars, adjustable rack for railway, M. Butler. Carbureter, J. R. Stephenson. Cards frumers, Stephenson. Cards frumers, Frumers, McCount. Cash register, Hoffman & Norton. Cash register Hoffman & Norton. Cash register and indicator, L. S. Burridge. Cash register suitograph J. A. Hoff.	608,335 608,437 608,531 318 608,551 608,551 608,551 608,509
Casket stand, G. Crommiller. Cattle guard, P. H. Hazel. Celluloid press and vulcanizer. J. C. Dixon Chain, sprocket, H. E. Stahl. Chair. See Reclining, high chair. Chuck, screw machine, E. V. Gauthier Churn, N. Isachson. Churn operating mechanism. J. Reed.	
Clock, repeating alarm, W. D. Davies	608,424 e 608,468 608,205
Cock and waste, stop, J. F. Coffey Coin wrapper, metallic, H. H. & T. S. Hipwell. Commutator, W. B. Potter Cooler. See Beverage cooler. Corn husking implement J. F. Rife	608,179 608,521 608,209
Coupling. See Thill coupling. Crane, H. Sawyer. Cranes, apparatus for producing traversing in tion of overhead traveling, J. G. & E. G. F. gehen. Cream separator, J. W. Thayer. Creamer, F. E. Sargent. Cultivation, apparatus for steam, Fowler & Be stead. Cultivator, H. E. Dodson. Cultivator, D. M. Motherwell.	608,311 608,482
Current induction motor, alternating, C. S. Braley. Cushion. See Slate frame cushion. Cutter, See Paper cutter. Cuttorhand I W Subhishor.	ad- 6 08,249
Deaf to hear, appliance for enabling the, R. B. Gardner. Derrick for raising or lowering telegraph pol M. T. Gordon. Domestic press, G. W. Pelton. Door check, P. J. Lennart. Drill, Columbus & Hesseltine Drill. See Electric drill. Drum, beating, C. B. Touvyille.	608,255 es, 608,193 608,268 608,462 608,548
Deaf to hear, appliance for enabling the, R. B. Gardner. Berrick for raising or lowering telegraph pol M. T. Gordon. M. T. Gordon. Door check, P. J. Lennart. Drill, Columbus & Hesseltine Drill. See Electric drill. Drum, heating, C. B. Tourville. Dye, brown black sulfur, H. R. Vidal. Dye, green alizarin, K. Thun. Dyes, making violet, H. R. Vidal. Electric combination lock, H. G. Carleton. Electric conductor joint, Patten & Maver. Electric drill, reciprocating, H. Casler. Electric lock, H. G. Carleton. Electric lock, H. G. Carleton. Electric lock H. G. Carleton. Electric lock G. G. Carleton. Electric machines, regulating dynamo, C.	608,335 608,238 608,324 608,320 608,412 608,175 608,343
Electrical distribution, C. P. Steinmetz. Electrical distribution system. C. P. Steinmetz Electrode, battery, H. E. Wilkinson. Electrolytic apparatus, J. G. A. Rhodin. Electromechanical lock, H. G. Carleton.	608,307 608,308 608,537 608,537 608,300
son. Elevator safety stop or brake, W. G. McGee Emery wheel protective cover, G. Benicke Engine. See Gas engine. Rotary engine. Tr tion engine.	608,550 608,297 608,417 ac-
Engines, igniting mechanism for explosive, Lizotte. Excelsior machine, rotary, J. Rollins. Explosive and making same, G. Beneke. Eyeglass stud, J. H. Nason. Farm gate, B. J. Huckey. Fastener, C. V. Walter. Feed water purifying device, J. S. Calkins. Fence gate, wire. F. G. Gorman. Fence post, S. C. Horn. Fire escape, Buck & Meaker. Fish hook, J. M. Stadel. Ffoor clamp, E. C. Ingersoll. Form, dress or garment, A. B. Friel. Fruit knife, A. Partridge. Furnace. See Heating furnace. Smoke consulng furnace.	(108,3116) (108,214) (108,367) (108,495) (108,495) (108,495) (108,495) (108,495) (108,419) (108,419) (108,418) (108,418) (108,418) (108,418) (108,418) (108,418)
Gage. See Presure and vacuum gage. Galvanic bath, C. E. Schnee	608,316
Gament and tent, convertible, F. Terramorse Garment holder, E. S. West. Gas burner, A. Beler. Gas engine, J. J. The Gas from kerosene, etc., by means of wicks, generating, J. H. Moss. Gas generator, acetylene, H. J. Bell. Gas generator, acetylene, Reith & Byrne. Gas generator, acetylene, Powers & Reynolds. Gases, capsule or container for containing c	en-
Gas generator, acetylene. Powers & Reynolds. Gases, capsule or container for containing co pressed or liquefied, E. Sterne. Gate. See Farm gate. Fencegate. Mine gate Gate, E. J. Hicks. Gate, M. K. Lewis. Gate, M. K. Lewis. Generator. See Gas generator. Steam gene	608 220
Generator. See Gas generator. Steam genetor. Glass articles, reheating and finishing machifor, Kay & Adams. Glass press, G. B. Lamb. Glove, boxing, W. G. Wood. Grain conveyer driving mechanism, J. • M. gan.	ine 608,427 608,204 608,434

Giass press, G. B. Lamb.

Glove, boxing, W. G. Wood.

Glove, boxing, W. G. Wood.

Grain conveyer driving mechanism, J. • Morgan.

Grain feeder and conveyer, B. S. Constant.

Grate. Norton & Neemes.

Grate. Norton & Grate.

Grate. Norton & Grate.

Grate. Norton & Grate.

Grate. Norton & Grate.

Headlight lamp, electric, H. P. Wellman & Grate.

Grate. Norton & Grate.

Grate. Norton & Grate.

Grate. Norton & Grate.

Headlight under. & Grate.

Grate. Norton & Grate.

Heating and drying system Cr. Barbour. & Grate.

Grate. Norton & Grate.

Heating furnace, E. Norton & Grate.

Heating furnace, E. Norton & Grate.

Heating furnace, E. Norton & Grate.

Heinge and door cheek. Combiued, F. & H. F. Keil Grate.

Hinge, mirror, C. W. Judson & Grate.

Hook. See Bale or box hook. Fish hook.

Hub attaching device. G. W. Emerick. & Grate.

Grate. See See Grate.

Grate. Grate. & Grate.

Grate. & Grate. &

(Continued on page 110)