

a cheap substitute for more durable material, and presents a handsome appearance. It consists of plaster of Paris mixed with cement and fibrous materials. The arch proper is built of wood and looks not unlike a well built scaffold. This is being entirely overlaid with staff, and the figures will be placed in position at the proper time. Some of the larger pieces will be modeled directly in place, but most of the sculpture has been enlarged in the Madison Square Garden, where our staff photographer has been able to get some photographs of the animated scene by flashlight, for in the mad rush against time there is no chance for posing.

The sculptor makes his model in his studio, generally 2 or 3 feet high; he then obtains a plaster model from it, and this is taken to Madison Square Garden, where it is enlarged under the direction of Carl Beil, who had charge of the men who did the same work at the World's Fair. Usually the head and hands are modeled full size in the sculptor's studio. A wooden carcass is built to support the head and hands, and then the work of building up the man 12 feet high is begun. All of the trunk and legs are outlined with wire netting, the staff being applied over this. Pieces of wire cloth, burlap, and even excelsior are freely used. The plaster is brought in pans and is applied with trowels and coarse modeling tools. Drapery is readily obtained by using burlap dipped in the plaster. Some of the sculptors do their own work, others employ professional modelers. The proportions are kept with calipers and by means of plumb lines and scales which correspond to the ruled squares of a painter's cartoon. There is not very much finishing, except to face and hands, and the bodies are freely shaped with hatchets and rasps. Some of the figures were modeled full size, as in the alto-reliefs shown in one of our engravings; here the actual modeling clay and not the plaster is being used. A wooden framework blocks out the main masses and the clay is modeled directly on this. A small sketch a few inches high is of course made first.

The staff for the architectural part of the structure was modeled elsewhere, and the first piece was applied to the arch September 7. Admiral Dewey is certainly to be congratulated for the splendid trophy of victory, even though, a few days after the celebration, it will be only a memory.

THE Sanyo Railway of Japan has recently introduced dining cars, and sleeping cars are also to be run.

Amber in Eastern Prussia.

Amber is found all along the Prussian shores of the Baltic, but principally in the peninsula of Samland. All amber, found everywhere, is state property, but the state cannot mine amber without the permission of the owner of the ground. Before the beginning of the present century, digging was the only means employed for obtaining amber. It was done in an irregular manner, and in 1862 dredging was practiced. This was continued until 1890, when mining by means of shafts was also resorted to; diving has also been practiced with great success. Amber occurs in the so-called blue earth, a sandy clay with many grains of quartz and granite. In the dry state the earth is green, and when it is wet it becomes almost black. The blue earth is washed with water, the big lumps being reduced with the help of mallets, and passed over sieves, and the slime is returned to the sea. The shafts have a depth of from 30 to 60 feet, and further inland they may be double this depth. One mine has nearly a thousand employes. The inferior pieces of amber are made into what is called "ambroid." The pieces are washed and dried, coated on the outside with some chemical, and are then moulded with the aid of heat and pressure.

Our Trade with Africa.

Public interest in African affairs is very great at the present time, while that continent is in such an unsettled condition. Africa is regarded by many commercial nations as a great future market for exports, and the demand for United States goods is not at all backward. Exports from the United States to Africa were in the fiscal year of 1899 more than five times as great as they were in 1889, amounting in the former year to \$3,496,505, and in 1899 to \$18,594,424. From "Cape to Cairo" and from Liberia to Abyssinia American manufactures and American foodstuffs are steadily making their way into public favor, and the consumption is constantly on the increase. Railroad bridges in the Nile Valley, mining machinery in the gold and diamond districts, cloth and foodstuffs are all eagerly sought for. Exports from the United States to Africa have grown more rapidly since 1893 than those to any other of the grand divisions of the world, while Asia and Oceania come next, and they are followed by Europe, North America and finally South America.

It is an encouraging sign that not only are our exports to Africa growing rapidly, but they are evidently taking the place, to a greater or less extent, of those articles formerly supplied by other countries. The British South African Export Gazette says "that American competition has to be met in all departments of trade. This competition is also not to be ignored because the shipments in many cases are small in quantity and value, as this is a peculiarity incidental to the opening of all new markets. The energy which our transatlantic cousins put into all of their new departures is earnest of a sufficiently active exploitation in the near future. This can only be met by renewed care and energy on the part of English firms in cultivating the South African markets."

The Current Supplement.

The current SUPPLEMENT, No. 1237, has a number of most interesting articles. "Notes on Manila and Cavité" describes some curious features of our new possessions. "Victoria Regia" is the subject of a large engraving dealing with this curious aquatic giant. "Archaeological Discoveries at Carthage" refers to the important discoveries which have recently been made upon the site of one of the most interesting cities of antiquity. There are a number of articles devoted to trade besides the regular consular page. "Manufacture of Carbons" describes most ingenious automatic machinery for plating the carbons and presses and baking furnaces. "The Relations of Physics and Astronomy to the Development of the Mechanic Arts" is the conclusion of Prof. Abbe's interesting paper.

Contents.

(Illustrated articles are marked with an asterisk.)

Africa, our trade with.....	188	Hydrogen, igniting jet of.....	182
Air compressed system*.....	177, 184	Iceberg, collision with a.....	182
Amber in Eastern Prussia.....	188	Insects, can they count?.....	182
Arch, the Dewey*.....	187	Inventions, index of.....	189
Arctic port, Russian.....	186	Inventions recently patented.....	188
Automobile news.....	179	Fig. 61*.....	189
Battleship, our fastest.....	178	Liquid air as an explosive.....	179
Books, new.....	189	Manufactures, record year for.....	186
Car couplings in England.....	186	Octopus, large*.....	180
Centerboard*.....	186	Plant, textile.....	185
Commission, work of the In- dustrial.....	173	Rapid transit.....	178
Compressed air system*.....	177, 184	Repairing vessels at Cavité.....	182
Congress at Columbus, scientific.....	179	Rotary engine*.....	181
Cross-cut saw*.....	180	Russia, commercial education in.....	182
Dust from Africa in Europe.....	186	Science notes.....	183
Electrical notes.....	183	Shamrock, our chances with.....	178
Engineering notes.....	185	Silk, artificial.....	178
Films developing in onestrip.....	185	Supplement, current.....	188
Fires in mines, extinguishment of.....	182	Territories, trade with our newly acquired.....	178
		Wood seasoning by electricity.....	182

RECENTLY PATENTED INVENTIONS.

Agricultural Implements.

HARROW.—CHARLES OHAVEN and FRED P. UHIG, Fort Madison, Iowa. This clip-guard harrow-tooth holder has a solid front recessed for the reception of the tooth and adapted at the same time to strengthen and hold the tooth fast in place. The clip-guard is drawn together by means of a bolt and nut at the back of the bar through holes made for the bolt in the ends of the clip combined with the bar, tooth and bolt. This device differs from tooth-holders made of two pieces and bolted together at the back of the bar, as these give an opportunity to the clip to spring from its work and loosen the tooth.

Bicycle Appliances.

AUTOMATICALLY-OPERATED BICYCLE-PUMP. JOHN S. BUBB, Kittanning, Penn. This invention provides improvements in bicycle-pumps connected with the bicycle frame and adapted to be conveniently shifted into and out of operative position by the rider while mounted on the machine. In its essential features the invention comprehends a novel construction of pumping and distributing mechanism adapted to be disposed within the frame-tubing, and so arranged as to be operated by an eccentric of crank-mechanism connected with either the drive-wheel axle or the crank-axle.

Electrical Apparatus.

ELECTRIC METER.—ALBERT PELOUX, Geneva, Switzerland. The invention provides an electric meter of the motor-type, in which a motor system moves a metallic disk or cylinder. The disk, in turning between the poles of permanent magnets or electromagnets, acquires a speed of rotation in proportion to the electric energy expended. The meter has the merit of dispensing with movable wires upon the armature, thus making an exceedingly strong apparatus, as the movable part consists only of a spindle, two iron cores, a disk, and a movable brush. The meter may be employed for a three or five-wire system.

ELECTRIC SWITCH.—ALBERT E. WELLS, Pittsfield, Mass. The electric switch has a terminal-block box provided with a cover having a slot registering with a slot in one side of the box proper. A two-armed shutter within the box has one of its arms pivoted on the inside of the box, the arms of the shutter being adapted to close the slots. This switch is simple in construction, positive in its action, large in capacity, and is arranged to insure a simultaneous breaking of all points in a circuit, and to reduce the arcing to a minimum.

VISUAL SIGNAL APPARATUS.—RUDOLF EINHIGLER, Manhattan, New York city. The invention provides an electrical signal device particularly adapted for use in offices or buildings, and comprises a series of main annunciators placed in a suitable position and upon the inner or normally-hidden side of each one of which is placed a numeral designating a person to be called. In connection with each one of the main annunciators an auxiliary annunciator or a series of auxiliary annunciators is provided, electrically operated and controlled from various points of a building or the like, remote from the main board, so as to indicate the calling person to the person called.

Engineering-Improvements.

CUT-OUT COCK FOR ENGINEERS' VALVES. DENNIS BROWN, Somerset, Ky. This cut-out or stop-cock is especially designed for use when a number of locomotives are coupled to a single train, the arrangement then enabling a connection to be established between the train-line pressure and the train-pipe gage, so that each engineer can see what pressure is in the train-pipe and what is drawn off by the engineer of the leading engine. Should the leading engine not charge or control the brakes, the engineers of the other locomotives can instantly charge and handle the brakes.

GOVERNOR CUT-OFF.—MARTIN O. ARNEGAARD, Hillsborough, N. D. The governor cut-off is an improvement on a similar device patented by the same inventor. The novel features of the present invention are found in the construction of the pivoted bar forming a flexible downward extension of the vertically-slidable governor "shaft" or bar, in the tension adjustment for the spring-counterbalance for the governor shaft or bar, whereby the speed of the engine may be changed at will without materially affecting the sensitiveness of the governor, and in the improved attachment of the governor-arms to the cross-head of the sliding shaft or stem.

Mechanical Devices.

WAVE-MOTOR.—WILLIAM A. NORTON, Port Richmond, Richmond, New York city. The wave-motor comprises two connected floats, on one of which a rock-shaft is mounted operatively connected with the other float. Gear-wheels have clutch-connection with the power-shaft and are engaged by racks operated alternately in opposite directions by the rock-shaft. A water-motor is connected with the power-shaft. Mechanism actuated by the rock-shaft supplies water to the motor. The waves rock the floats, thereby operating the racks to impart motion to the power-shaft. At the same time water is supplied to the motor. The rack-and-gear motion is designed to start the operation.

STENCILING MACHINE.—STUART B. MOORE, Brooklyn, New York city. In shipping goods it is always desirable to stencil the address. But to use metal stencils for each shipment would be too costly. It is therefore desirable to be able to make paper stencils which shall last a reasonably long time. A machine for forming such stencils is provided by the present invention. The machine comprises two superposed connected disks respectively carrying dies and punches adapted to receive the stencil-sheet between them. An index plate or disk is fixedly secured to the punching-disk and is carried above the frame. The disks are pivoted to rotate upon a block reciprocated with the disks in the guideway of a frame.

BOX-SEALING MACHINE.—JOSEPH T. CRAW, Jersey City, N. J. This machine is adapted to seal the flaps of paper boxes after the boxes have been filled and is of such simple construction that the boxes may be conveniently manipulated by a single operator. The invention provides for the distribution of cementing or gluing material to the portions of the flaps to be sealed. The cement or glue is automatically applied and the flaps folded to a sealing position. The operator has merely to feed the filled boxes to the machine.

AUTOMATIC LATHE. LUCAS A. CARSON, Hopevale, Ohio. The object of this invention is to provide an improved lathe designed for automatically turning,

borings, sawing off, and completely finishing small articles of wood. The lathe comprises a support for a stick. The stick is moved in the support by a spiked wheel which can be rotated intermittently in opposite directions and through different distances. The stick can be held in the support against accidental movement, and can be operated upon by various tools in the different positions to which it is moved.

COMPUTING-MACHINE.—JOHN J. WALL and HERMAN ROGALSKY, Buhler, Kans. This invention provides for the use of merchant and custom millers, a convenient computing-machine for the purpose of finding out at a glance how many pounds of flour or feed are to be given in exchange for a certain amount of bushels or pounds of wheat at a certain number of pounds to the bushel, thus saving much valuable time in computing and also avoiding the possibility of error in separately figuring the accounts.

HOOP-MACHINE.—JAMES FOWLEY, Cobden, Ill. This machine makes barrel-hoops directly from the log, with one end tapered to a thin edge to form the lap and the other end pointed to form the outer wrap. With the vertical or slicing saw are connected a series of five vertical cutter-heads arranged in front of the saw, one set having relatively stationary bearings and the other set having respectively blades with V-shaped cutting edges and plain blades, means being provided for giving them an automatic motion to and from the log to form pointed ends and bevel-faces on the opposite ends of the log.

ANIMAL-TRAP.—WILLIAM H. HARDEN, Quitman, Ga. The self-setting trap has an entrance-compartment connected by a passage with a second compartment. In the passage is a tilting platform. A gate controls the opening of the passage into the second compartment, the platform tilting into and out of register with the gateway of the gate. Connections between the gate and the tilting platform cause the platform to open the gate as it moves into register with the gateway. A clock-mechanism readjusts the tilting platform. The various operations described are effected by the animal as it seeks to escape.

MOTOR.—EDGAR L. GARVEY, Gainesville, Tex. The present invention provides a fan or like motor in which the energy is stored up by a spring and conserved efficiently. Operatively connected with a rotatable spring-carving and spring-actuated drum is a train of gear-wheels which drive a shaft. A pinion is splined on the shaft and is adapted to slide thereon in order to engage the different gear-wheels to vary the speed.

RATCHET-MECHANISM.—LOUIS P. WELLMAN, Taunus, N. J. This mechanism is designed to convert reciprocating into rotary motion. The ratchet-wheel has teeth provided with sloping side surfaces. An operating lever is provided formed in two separable halves having a common pivot and drawn together by connecting springs. The tooth-engaging ends of the lever have their inner ends beveled and slightly rounded at the corners. The device is particularly designed for use with mechanisms driven by the reciprocation of the feet or hands.

MACHINE-GUN.—HON. EDWIN M. CAPPS, San Diego, Cal. The invention relates to improvements in rapid-firing machine-guns; and it refers particularly to guns in which the barrel and firing mechanism are arranged to operate in conjunction with the cartridge-holders, having a series of cartridges arranged to be successively fed

into a firing position. The invention provides a novel barrel and firing mechanism and automatically-fed cartridge-holders designed to fire any of the ordinary forms of military cartridges in which premature firing is rendered impossible and in which non-explosion will not impede the firing action of the gun. The invention also furnishes a novel method of sighting by means of stadia measurement.

Miscellaneous Inventions.

PACKING-CASE.—THOMAS MILLER, Jr., and WILLIAM O. JOSLIN, Springboro, Ohio. This invention seeks to provide a knock-down tobacco-case with a simple fastening device for securing the several parts together and so arranged that there are no projections to prevent several cases from being packed closely together. The end-pieces of the case have cleats on the inner side. The top, bottom, and side pieces have also cleats on the inner side. Through openings in the cleats fastening bolts pass, each consisting of sections arranged at right angles to each other. A shoulder on one of the sections engages the inner side of the case; and nuts engage the screw-threaded portions of the bolts. By loosening the nuts on the sides, the case expands and can then be readily lifted from its contents.

DUST-CART.—FRANZ LOOS, Carlsbad, Austria-Hungary. The cart can be filled without causing unpleasant dust and can be automatically dumped at the desired place. A special feature of construction is a portion forming a dust inlet and having a sliding bottom and a sliding cover, both connected with a bell-crank lever whereby they are operated. Swinging on the cart is a dust-box having a sliding cover, which dust-box is capable of being connected with the sliding bottom, the cover of the box being engaged by the bell-crank lever.

WAGON-STANDARD.—REINHOLD KLATT, Strong City, Kans. The standard has a body and base, the latter being provided with a downwardly-extending marginal flange inclosing the end of the bolster. Fastening devices are passed through the bolster and the base of the standard. A strap is fastened down on the top of the bolster and has engagement with the base of the standard. The standard does not in any way weaken the bolster to the extent necessary in the application of the ordinary standards.

ACETYLENE GAS MACHINE.—JACOB D. KAUFMAN, CHARLEY B. TITUS, and ADNAH E. VANARSDALE, Little River, Kans. It is the object of this invention to provide an acetylene-apparatus having a large carbide capacity and so arranged that the generator is completely surrounded by water, thus keeping the gas cool. Within the gasometer the generator is arranged. Removably placed in the generator are carbide-holders, each having a perforated top or cover through which water is passed. A gas-pipe leads from the lower portion of the generator and upward into the gasometer and has a portion coiled around the generator. Distributing and blow-off pipes are provided.

SHADE-FRAME.—FRANKLIN E. HOWARD, Buffalo, N. Y. This shade-frame for electric lamps has supporting-arms adapted to engage the lamp. To the arms a continuous ring is attached having tapering sides on which the shade is supported. A continuous flange is projected upwardly from the inner edge of the ring and is capable of yielding inwardly to admit the shade to the ring. The flange stands out normally to hold the shade in place.

ELEVATOR-CARRIER.—EGBERT J. HOOKER, Poulney, Vt. The present invention provides a carrier adapted for use in quarries, which carrier is so constructed that it will travel on an elevated track or cable at any desired speed, it being possible to stop the carrier at any desired point on the cable or track.

EXERCISING DEVICE.—ABRAM A. HENRICKSON, Jamaica, Queens, New York city. This invention provides a novel handle for exercisers, consisting of a handle-bar having a frame upon which a finger-bar is adapted to slide longitudinally, the elastic cord being attached to the bar. The handle-bar is held in the palm and the fingers are passed over the finger-bar.

HAND-STAMP.—HENRY H. HARRISON, Manhattan, New York city. This invention provides a hand-stamp for making reproductions from copying-ink, the printing surface being formed of a plastic or viscous compound mounted or run into the proper form and then permitted to set. The stamp has a body curved in the arc of a circle and provided with a handle-bar running between its ends, so that the stamp may be held in the hand, and its arc-shaped printing surface rocked over the surface to be printed, all of which provides a much more effective and expeditious arrangement than that in which the surface to be printed is laid down on a stationary printing pad or form.

EXTENSION-TABLE.—WILLIAM R. HALLETT, Hamburg, Ill. The inventor has devised a table provided with simple means for automatically raising the intermediate leaves into place while the table is being extended, and for lowering the leaves while the table is being shortened. The table comprises two frames mounted to slide one relatively to the other. To each frame a table-top section is rigidly secured. Plates are mounted to swing on the inner surface of one of the frames and are engaged by intermediate leaves. Rock-bars have cam ends engaging the plates; and from the rock-bars yielding tappets extend down and are engaged by a cross-bar carried by one of the frames.

ORE-CONCENTRATOR.—HENRY C. GRANNATT, Colorado Springs, Col. In the frame of the concentrator are a series of slats pivoted at their lower edges, each having a riffle extending along its pivoted edge. The slats are placed in successively lower planes so that the overflow from one is received by the next. The riffles extend from the feeding end of the slats a part only of their length and are of successively greater length. The frame can be reciprocated longitudinally of the slats; and the slats are simultaneously given a slight oscillation on their pivots. The device may be used in places where the supply of water is limited.

DEVICE FOR TEACHING MUSIC.—JOHN MORRIS, Marshall, Tex. The purpose of the inventor has been to provide an improved mechanical device whereby simple music in any key can be readily taught. The device comprises a modulator provided with columns containing characters indicating every semitone and tone within the total compass of the modulator, and also provided with rows of hooks adjacent to the characters. A tone-ladder is provided with arms to engage the hooks and to indicate the steps in the diatonic scales of the characters in the columns. Independent arrows are provided to indicate the tones contained in any desired scale or chord.

SEA-GOING RANGE-FINDER.—JOHN DONEGAN, Cincinnati, Ohio. The range-finder comprises two telescopes arranged in the same horizontal plane, one of the telescopes being pivoted to swing relatively to the other. A cylinder extends longitudinally of the telescopes and turns in unison with the swinging of the pivoted telescope. The cylinder is provided with rows of numerals indicating distances which can be read by a longitudinally-extending fixed bar. An indicator at the rear end of the cylinder indicates the row of numerals on the cylinder on which the distance is to be read. This indicator comprises a fixed disk having graduations corresponding with the graduations of the fixed bar. A pointer moves on the disk in unison with the cylinder and pivoted telescope.

COMPOSITION OF MATTER.—GUSTAV T. BRUCKMANN, Brooklyn, New York city. The purpose of the present invention is to provide a means whereby an oxygenated agent may be added to hydrogen peroxid in sufficiently large quantities to preserve the peroxid without producing the disagreeable and painful effect on the tissues incident to the use of mineral acids. To this end the inventor employs carbon dioxide, which disappears largely at the time the peroxid is medicinally used, and is present in large quantities only so long as its preserving action is required.

STRAP-PROTECTOR.—EDWARD G. AWCOCK, New Orleans, La. This simple, metallic, protective device for harness is entirely independent of the strap to which it is applied. The device is adapted for connection with a buckle and for receiving a ring, snap, or other connecting medium between straps in a harness. The loop-attachment of a buckle to a strap need not be dependent upon for security. The connections between the straps will not wear the leather.

WRENCH.—ALEXANDER ANDERSON, Greenville, Miss. The novel feature of this invention is found in a peculiar nut, slidable on the shank when in one position and locked against sliding when in another position, so that the jaw in one case can be moved, while in the other position it is locked against movement. The jaws are so arranged that they cannot readily become disarranged, and that they can securely grip an object without danger of the movable jaw's slipping or losing its hold on the object.

CONCENTRATOR.—JOHN C. and RICHARD C. WATERS, Romley, Colo. On a vertically-sustained pivot a head is mounted to rock. Two relatively adjustable arms are attached to and extend oppositely from the head. A third arm is secured to the head, and extends between the two first-named arms. On the three

arms a segmental table is mounted which is adjustably supported at its outer edge. A curved trough is secured at the inner edges of the table adjacent to the pivot; and a flange is located at one edge of the table adjacent to the trough, the opposite edge of the table being adapted to discharge the concentrates, and the curved trough being adapted to receive the tailings.

COMBINED ADVERTISING-CABINET AND BOOKCASE.—WILLIAM F. PATTON, Akron, Ohio. This device is designed for use in hotels and other public places and is arranged to display advertisements effectively and to contain books of reference. The bookcase used is provided with receptacles for books and has an advertising space at its front. Wings at the sides of the bookcase are arranged for displaying advertisements, and are adapted to be swung forward or rearward into angular positions relatively to the bookcase. A cap for the top of the bookcase is provided with advertising-spaces.

MAIL-BAG.—LOUIS SANDERS, Brooklyn, New York city. This invention provides a mouth-controlling and mouth-locking device which will effectually hold the mouth of the bag open to receive letters and packages and which will also hold the mouth closed. The mechanism at the mouth of the bag can be quickly operated. A receptacle is also provided for the destination card, in which receptacle the card is automatically retained when the controlling mechanism is locked, and released when the mechanism is opened.

CHANGE-MAKER.—PETER P. McMENAMIN, Jersey City, N. J. This invention provides an improved change-maker to enable cashiers and bartenders to make change quickly and correctly and to prevent so far as possible the occurrence of errors when paying out money or changing bills or coins of higher denomination. The change-maker is provided with cells for containing stacks of coins. Under each cell is a single slide for moving the bottom coin from under the stack. Each slide is manually operated and is arranged to be moved independently of the other slides. A series of slides can be mechanically operated at the same time.

SHIRT-BOSOM HOLDER.—CHARLES L. PASHLEY, Stamford, N. Y. In order to secure the opposite edges of a bosom to a vest so that the vest cannot spread and bend the shirt-bosom, the inventor provides a plate having prongs at one end for attachment to the vest, and a hook at the other end. The plate is extended inwardly from the edge of the front opening. A loop engaging the hook is removably connected with the shirt.

PACKAGE FOR INCANDESCENT-MANTLES.—HENRY ANHALTZER, Manhattan, New York city. The package comprises a casing, to the bottom of which a support for the mantle is secured. A supporting-bar extends through a loop at the top of the mantle and has its ends sprung into the upper portion of the casing, after which the casing is filled with collodion, alcohol, or ether. A mantle thus packed can be safely transported.

BATING PROCESS.—HENRY SCHLEGEL, Lapeer, Mich. After hides have been unhaired and before they are tanned, they are subjected to a "bating" process by which the lime is removed. Various acids have been used in the process, but bating has always required much care and skill. The inventor of the present process secures a simple bate by employing a solution consisting essentially of potassium bichromate.

DUST-GUARD.—JAMES S. PATTEN, Baltimore, Md. The guard is composed of sections of sheet metal slidable with relation to each other and having opposite, curved edges provided with integral bent portions forming seats for packing-strips. The guard can be cheaply constructed. The wearing parts can be readily renewed.

FOLLOWER FOR PACKING BARRELS.—NORRIS M. ROOT, Masonville, N. Y. This invention provides improvements in devices for packing or holding meat, pickles, fish, or the like, under brine in a barrel. The follower used for this purpose is easily adjusted to the varying diameters of a barrel and has no metal parts to corrode. The follower comprises a disk or plate having guide-strips extended in opposite directions, which strips have longitudinal slots provided with notches in their lower walls. Holding-arms and cross-heads on the arms project into the slots, one thickness of the portions of the cross-heads being substantially equal to the distance between the walls of the slots, and the thickness at right angles to the first-named thickness being greater than the distance between the walls of the slots.

COPY-HOLDER.—LOUIS HUDGIN, Lochiel, Arizona. This holder rests on the desk of a typewriter and holds the copy in an inclined position over the machine and directly in front of the eyes of the operator. It consists of a rectangular vertical support frame hinged to foot pieces which are fastened to the desk, and having two pairs of hinged arms projecting out at an angle from its front face, one pair being at the center of the frame and the second or shorter pair projecting from the top. These arms carry the copy-holder, which may be adjusted in position. The copy-holder has been designed with the especial object of doing away with the necessity of fastening the device to the desk or machine.

NOTE.—Copies of any of these patents will be furnished by Munn & Co. for ten cents each. Please state the name of the patentee, title of the invention, and date of this paper.

NEW BOOKS, ETC.

DIE FABRIKATION DER KAUTSCHUK-UND LEIMMASSE-TYPEN, -STEMPEL- UND DRUCKPLATTEN, SOWIE DIE VERARBEITUNG DES KORKES UND DER KORKABFÄLLE. Von August Stefan. Vienna: A. Hartleben. 1899. Pp. 296. Octavo. With 113 illustrations. Price, paper, \$1.25.

HANDBUCH DER RATIONELLEN VERWERTUNG, WIEDERGEWINNUNG, UND VERARBEITUNG VON ABFALLSTOFFEN JEDER ART. Von Dr. Theodor Koller. Vienna: A. Hartleben. 1899. Pp. 320. Octavo. With 22 illustrations. Price, paper, \$1.25.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in the following week's issue.

- Marine Iron Works. Chicago. Catalogue free.
"U. S." Metal Polish. Indianapolis. Samples free.
Gasoline Brazing Forge. Turner Brass Works. Chicago.
Yankee Notions. Waterbury Button Co. Waterbury Ct.
Handle & Spoke Mch. Ober Mfg Co. Chagrin Falls, O.
Hook and Eye Patent for Sale. F. J. Rappold, Erie, Pa.
Gear Cutting of every description accurately done. The Garvin Machine Co., Spring and Varick Sts., N. Y.
Ferracute Machine Co., Bridgeton, N. J. U. S. A. Full line of Presses, Dies, and other Sheet Metal Machinery.
"Criterion" Acetylene Generators, Magic Lanterns & accessories. J. B. Colt & Co., Dept. N. 3-7 W. 20th St., N. Y.
Machinery for R.R. contractors, mines, and quarries for hoisting, pumping, crushing, excavating, etc., new or 2d-hand. Write for list. Willis Shaw, Chicago.
The celebrated "Hornby-Akroyd" Patent Safety Oil Engine is built by the De La Vergne Refrigerating Machine Company. Foot of East 18th Street, New York.
The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4. Munn & Co., publishers, 361 Broadway, N. Y.
Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.

Notes & Queries

HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters or no attention will be paid thereto. This is for our information and not for publication.
References to former articles or answers should give date of paper and page or number of question.
Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and though we endeavor to reply to all either by letter or in this department, each must take his turn.
Buyers wishing to purchase any article not advertised in our columns will be furnished with addresses of houses manufacturing or carrying the same.
Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.
Scientific American Supplements referred to may be had at the office. Price 10 cents each.
Books referred to promptly supplied on receipt of price.
Minerals sent for examination should be distinctly marked or labeled.

(7720) P. S. asks: 1. How can I make luminous paint, a light color preferred that will not corrode iron? A. Send for three copies of our SUPPLEMENT, giving full directions for making luminous paint. As there are many difficulties connected with making it, the commercial article is recommended. 2. Would thin leather or buckskin do just as well as parchment for a small telephone? A. Use parchment paper or ferrotype plate for telephone diaphragm, not a soft substance such as leather.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Issued for the Week Ending

SEPTEMBER 5, 1899,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

- Alarm. See Burglar alarm.
Alarm lock. D. L. Taylor. 632,328
Alarm lock, burglar. E. M. Wagner. 632,664
Alarm through agency of smoke or other gases, means for giving. H. C. Baer. 632,546
Alkali nitrates, decomposing. H. K. Baynes. 632,394
Alloy. J. C. Bull. 632,233
Alloy. R. C. Carpenter. 632,443
Amusement device. T. W. Lacombe. 632,587
Annular cutter. C. E. Wymoth. 632,604
Articles from elevated positions, device for removing. S. M. Wright. 632,330
Axl, D. Rinpe. 632,538
Axes and journals, means for reducing friction of. V. J. Brewer. 632,438
Back pedaling brake. Hearson & Shaw. 632,460
Bait, artificial. E. T. Dukes. 632,554
Ball forming machine. M. F. Christensen. 632,355
Balls, machine for rectifying. Dupeyron & Phallemph. 632,403
Basket, collapsible fruit. O. C. Fenlason. 632,344
Battery. See Electromedical battery.
Bean shooter, magazine. W. M. Hervey. 632,526
Bed bottom frame. F. M. Tinkham. 632,478
Bed, spring. F. H. Heterich. 632,412
Beds, sofas, etc., spring bottom for. B. B. Fiken. 632,520
Bedstead coupling, iron. W. L. Dismukes. 632,354
Bell, bicycle. H. Q. Plummer. 632,427
Bell, bicycle. W. Wilton. 632,611
Bell, bicycle pedal. H. Q. Plummer. 632,471
Bell, door. H. G. Voight. 632,236
Bicycle. E. S. Bryant. 632,284
Bicycle, chainless. F. E. Mathewson. 632,623
Bicycle driving gear. F. Bartlett. 632,623
Bicycle propelling mechanism. E. B. Parkhurst. 632,536
Bicycles, variable speed gear for. F. E. Beaumont. 632,627
Binder and ledger, loose leaf. S. Adler. 632,392
Binder, temporary. C. H. Hiscock. 632,491
Binding and facing, dress. A. M. Weber. 632,383
Bir. See Bridle bit.
Blind fastener. E. Hughes. 632,571
Boat mooring device. B. J. Christensen. 632,238
Bobbin holder and thread catcher. J. Roney. 632,473
Boiler. See Steam boiler.
Book support. M. E. Welch. 632,439
Book support, open. A. M. Riddell. 632,409
Root, shoe, or slipper holder. W. S. Hallowell. 632,524
Bottle closure. W. D. Kilbourn. 632,575
Bottle, non-refillable. A. G. Ely. 632,455
Box. See Collapsible box. Mail box. Shipping box.
Brace. See Furniture brace.
Bracket. See Sash holding bracket.
Braiding and winding machine spool carrier. J. McCabe. 632,318
Braiding machine spool holder. P. Mundt. 632,534
Brake. See Back pedaling brake.
Bride bit. W. P. Brown. 632,439
Broom moistener. W. Hardin, Jr. 632,263
Brush, tooth. A. V. Gotterman. 632,524
Bucket, dumping. J. F. O'Rourke. 632,323
Building construction, metallic. T. Bailey. 632,669
Burg hole and bushing. W. G. Gardiner. 632,457
Burglar alarm. C. Coleman. 632,512
Burglar alarm system, electrical. C. Coleman. 632,513
Burner. See Gas burner. Incandescent burner.
Button, glove. C. R. Weidmuller. 632,606

- Cake tin. R. B. Williamson. 632,505
Can. See Milk can.
Camera, photographic. F. E. Ives. 632,574
Camera, photographic. G. Sigler. 632,451
Carbolizer. J. P. Carter. 632,426
Car brake mechanism, railway. J. H. Neal. 632,319
Car, convertible open and closed. H. Trost. 632,608
Car coupling. S. Reynolds. 632,366
Car coupling. J. T. Wilson. 632,382
Car, dump. F. S. Ingoldsby. 632,650
Car or train ventilation, railway. J. McCreery. 632,483
Car wheel. F. Clark. 632,337
Cars, detachable door for dumping. C. P. Ludwig. 632,315
Cars or locomotives, replacing frog for. B. E. Tilden. 632,476
Carbureter. W. E. & F. O. Stanley. 632,376
Carbureting device for gas or explosive engines. S. A. Ayres. 632,509
Carriage, child's folding. Burghardt & Rogers. 632,671
Case. See Ticket case.
Casein, producing. W. A. Hall. 632,408
Casting apparatus. H. Aiken. 632,351
Castings, for making material for making metallic. A. G. Lundin. 632,579
Ceilings, metallic center piece for. R. Oebing. 632,584
Cellulose esters, making. Weber & Cross. 632,605
Centrifugal machine. B. Alfven. 632,616
Chandelier, combined gas and vapor burning. A. Kitch. 632,626
Check marker. F. E. Housh. 632,393
Chocolate drops, etc., machine for dipping. P. Panoulas. 632,535
Chopper. See Cotton chopper.
Choppers, case for food. L. T. Snow (reissue). 11,771
Chuck, hole. Parkin. 632,460
Crank cutter and lighter. E. A. Johnson. 632,418
Circuit breaker for controllers. W. H. Conrad. 632,516
Circuit controller. A. Lunken. 632,367
Cistern cleaner. H. F. Mueller. 632,468
Clamp. See Rope clamp.
Clasp. See Shirt clasp.
Clasp. C. H. Westcott. 632,483
Claw bar. J. P. Turner. 632,200
Cleaner. See Cistern cleaner. Tobacco pipe cleaner.
Clod crusher. P. F. Glassbrenner. 632,259
Clothes drier. J. T. & B. A. Best. 632,625
Coal and coke, conveying. 632,566
Cold storage apparatus. J. T. Ludlow. 632,556
Collapsible box. D. Drawbaugh. 632,451
Commutator grinding rig. F. Wilkie. 632,666
Copying apparatus, hectographic. E. Arm. 632,419
Copying press, letter. N. C. Stiles. 632,374
Cork tapper. A. N. Kissely. 632,260
Corset steel and clasp. Hatfield & Brigham. 632,489
Cotton chopper. W. McGillivray. 632,470
Cotton gin. A. D. Thomas. 632,616
Cotton press. C. E. Mallet (reissue). 11,769
Coupling. See Car coupling. Thill coupling.
Cover for cooking utensils, detachable. L. Clark. 632,307
Crate or coop, folding. L. W. Copeland. 632,444
Cream separator, centrifugal. M. Johnson. 632,664
Crusher. See Clod crusher.
Crusher gages, making. H. C. L. Holden. 632,462
Crest crushing instrument. H. P. J. F. Chausseaud. 632,443
Cultivator. H. Brown. 632,333
Cup. See Grease cup.
Curd agitator. A. Robinson. 632,397
Curtain fixture. T. A. Esser. 632,345
Curtain pole. C. W. Leake. 632,420
Cutter. See Annular cutter. Cigar cutter.
Cutter head. C. Anderson. 632,618
Cycle seat or saddle support. P. R. Gulden. 632,564
Cyclometer. J. E. Bean. 632,382
Damper regulator, automatic. J. J. Roy. 632,571
Dash rail, vehicle. J. Leach. 632,361
Dead center. F. White. 632,386
Dice shaker. C. J. Lehmann. 632,320
Dish cover support or holder. F. E. Hansen. 632,291
Door check. Voight & Hurd. 632,491
Door holder. T. J. Gibern. 632,609
Door holder. C. Beck. 632,390
Doors, automatically operating. J. H. Whitaker. 632,299
Drawer or slide equalizer. H. L. Wernicke. 632,607
Drier. See Clothes drier.
Drying apparatus. W. E. Allington. 632,508
Drill. See Rock drill.
Drilling machine. H. Stapelmann. 632,594
Driving forces, mechanism for increasing effectiveness of. J. Whittinton. 632,608
Dust arrester. L. Rossier. 632,370
Dye, brominated. Bally. 632,621
Dyeing. A. Philips. 632,505
Dyeing apparatus. C. K. Middleton et al. 632,514
Electric cable. C. Coleman. 632,514
Electric traction system. E. Vedovelli. 632,543
Electricity from car wheel axles, means for generating. M. Moskowitz. 632,414
Electromedical appliance. J. A. Freeman. 632,559
Electromedical battery. C. Marus. 632,216
Elevator car arrester with movable guide strips. J. H. Johnson. 632,414
Elevator door operating means. E. S. Robison. 632,369
Elevator safety stop, automatic. J. H. Johnson. 632,415
Elevator stop, automatic. J. G. Gracey. 632,347
Elevators, automatic car safety device for electric. J. H. Johnson. 632,451
Embossing dies, apparatus for making. A. G. Beater. 632,626
Engine. See Fire engine. Rotary engine. Steam engine.
Equipage weight, revolving adjustable. W. D. Hooker. 632,684
Evaporator, fruit. P. B. Viele. 632,602
Evaporators, etc., apparatus for cleaning tubes of. C. Markwort. 632,532
Exhibition jar. J. P. O'neil. 632,321
Eyeglass or spectacle cases, device for holding. T. Gaskin. 632,510
Fabric trimming machine. R. Lefort. 632,256
Farm gate. M. M. Dungan. 632,255
Fence twisting tool. J. H. Pottenger. 632,324
Fence wire. F. R. Parker. 632,585
Fibrous materials, preparing machine for. J. Pilling. 632,474
Filter. T. Howard. 632,520
Filter. J. A. Maigen. 632,466
Filter, water. C. B. Darling et al. 632,359
Filters, means for automatically cleaning. Hoffmann. 632,461
Fire alarm apparatus, automatic code telegraph. R. Pearson. 632,591
Firearm, magazine. G. W. Chandler. 632,253
Fire engine, electric. W. H. H. Whiting. 632,465
Fireproof construction. G. Fugman. 632,523
Fireproof structure. W. H. Hull. 632,528
Fish plate slotting punch. B. Charlton. 632,337
Fish plates, machine for removing saw burrs from. H. B. Charlton. 632,254
Flag. H. B. Macartney. 632,540
Fluid under pressure, system for distributing. A. Kitson. 632,490
Fly extender. G. A. Carpenter. 632,314
Fly trap. F. A. Lane. 632,303
Fly trap. E. Vuereff. 632,303
Fumes, machine for generating and utilizing noxious. W. T. Hanaway. 632,566
Furnaces, open fire door for. A. Alexander. 632,615
Furniture. See Manufacture of mantles or incandescent elements for. O. B. Heinze. 632,349
Gas generator, acetylene. W. M. Clark. 632,511
Gas generator, acetylene. F. M. Comstock. 632,615
Gas generator, acetylene. F. A. Feldkamp. 632,679
Gas generator, acetylene. Hanson & Stewart. 632,488
Gas generator, acetylene. A. Rieffel. 632,567
Gas lighting appliance. A. Frank. 632,522
Gas purifier. B. E. Chollar. 632,397, 632,399, 632,401
Gas purifier manhole cover. B. E. Chollar. 632,398
Gas, purifying. B. E. Chollar. 632,400
Gate. See Farm gate. Sliding gate.
Gate. J. M. Tanner. 632,298
Gear, roller. C. L. Travis. 632,470
Gearing, variable speed. W. E. Simpson. 632,91
Generator. See Gas generator. Magneto electric generator. Zone generator.
Glass blowing machines, automatic blast regulator for. H. J. Colburn. 632,486
Grader and ditcher, road. G. F. Eubank. 632,491
Grain cleaning machine. N. Brooker. 632,613
Grease cup. J. Trux. 632,480
Gully trap for drains. J. Brightmore. 632,396
Gun mount. P. Berger. 632,614
Hame and trace connector. H. Dodson. 632,551
Hammer, drop. J. A. Horton. 632,285
Hammer, pneumatic. E. Gunnell. 632,261
Hand shield. M. F. Barth. 632,547
Handle. See Stamp handle.
Harness and thill attachment. J. H. Prall. 632,276
Harrow, H. Adler. 632,228
Harrow, disk. W. H. Traphagen. 632,470
Harvester and shucker, corn. N. Denning. 632,648
Hay press. J. Ross. 632,539
Hay rack loader or unloader, automatic. W. H. Becker. 632,229
Heating and ventilating or refrigerating apparatus and system. W. E. Allington. 632,506

(Continued on page 190)