

SCIENTIFIC AMERICAN

ESTABLISHED 1845

MUNN & CO., Editors and Proprietors

Published Weekly at

No. 361 Broadway, New York

TERMS TO SUBSCRIBERS

One copy, one year for the United States, Canada, or Mexico, \$3.00
 One copy, one year, to any foreign country, postage prepaid, £0 16s. 5d. 4.00

THE SCIENTIFIC AMERICAN PUBLICATIONS.

Scientific American (Established 1845).....\$3.00 a year
 Scientific American Supplement (Established 1876)..... 3.00
 Scientific American Building Monthly (Established 1885)..... 2.50
 Scientific American Export Edition (Established 1878)..... 3.00
 The combined subscription rates and rates to foreign countries will be furnished upon application.
 Remit by postal or express money order, or by bank draft or check.
 MUNN & CO., 361 Broadway, New York.

NEW YORK, SATURDAY, AUGUST 16, 1902.

The Editor is always glad to receive for examination illustrated articles on subjects of timely interest. If the photographs are sharp, the articles short, and the facts authentic, the contributions will receive special attention. Accepted articles will be paid for at regular space rates.

NEEDLESS ANNOYANCES IN FERRYBOAT TRAVEL.

Although the ferryboat system of New York city is probably the best in existence, it is marred by a few serious drawbacks which the companies could easily remove if they set about to do so. In each case the trouble, which amounts to a positive nuisance, results from the extensive use of the ferries which is made by horse-drawn vehicles. We refer, in the first place, to the preventable and extremely annoying delays which occur at periods of high tide, owing to the inability of overloaded teams to mount the hinged bridges connecting the shore with the ferryboats, and in the second place to the intolerable odor which, in hot weather, pervades the wagon drives which extend through the central gangway of the boats. Primarily the delay which occurs when stalled teams are being coaxed up the incline is due to the fact that they are grossly overloaded; but since overloading unfortunately seems to be an evil that is going to stay with us, it is the duty of the ferryboat companies to provide some means by which a stalled team or wagon can be assisted onto the boat. This might be done either by providing an extra hand-winch on the ferry pier and a snatch block on the ferryboat, so that a rope could be run to the boat and back to the wagon, and the team assisted up the ferry slip by the operators who warp the boats to the slip; or, a small steam winch (of a few horse power) might be placed at the front end of each engine house of the ferryboats for use in emergencies of the kind.

The unsanitary condition of the carriage and wagon driveways is altogether inexcusable, since it is entirely owing to the fact that wooden floors are used where asphalt or some similar impervious material should be laid down. If an asphalt surface were provided and a length of hose connected up in each gangway, the surface could be kept perfectly sweet and clean, and a nuisance which at present calls loudly for the interference of the Board of Health would be at once abated.

NEW METHOD OF ARMOR PLATE MAKING.

A new process of super-carbonization, or "face-hardening" of armor plate has been developed by an officer in the American navy which promises to exert a greater influence upon the struggle for supremacy between guns and armor than was produced either by the American Harvey, or the German Krupp processes before it. The method of increasing the resistance of homogeneous armor plate by hardening its face may be said to have originated in this country when Harvey introduced his process of increasing the hardness by causing the surface of the plate to take up an excess of carbon during treatment in the furnace. Armor with a hard face upon a tough back had, it is true, been already produced abroad, the compound armor, which so many of the old English battleships carry, being of this character. But compound armor had the serious defect that the hard face consisted of a separate plate of steel welded upon a backing of softer and tougher metal. The hard face was secured at the expense of homogeneity, and the serious nature of this defect was realized at the proving grounds when the surface flaked and broke away from the softer back, leaving the plate open to penetration by shells of small caliber. The incontestable superiority of the Harvey armor led to its all but universal adoption throughout the world. Krupp eventually improved upon it, substituting gas treatment in place of the layer of carbonaceous material used in the Harvey method, and also improving the quality of the plate by very careful attention to the details of the furnace treatment. While the high quality of Krupp plate is unquestionable, its excellence is gained at enormous cost, as high as \$550 per ton having been paid for this class of armor.

The invention of Lieut. Cleland Davis, of the navy, marks, both in effectiveness and in cost of manufacture, a great advance upon the Krupp system. His method includes the substitution of electrical currents for the heat of the gas-fired furnace, and the direction of these currents against the face of the armor plate while it is in a heated condition by means of massive carbon anodes, in form not unlike the carbons used in arc lights, but of vastly greater size. During his course of experiments, Lieut. Davis found that if a current of electricity were sent from a carbon into the surface of a plate, it carried with it a certain amount of the carbon and implanted it within the body of the metal. The depth of the hardening is determined by the period of time during which the current is applied, and it is claimed that not only is the surface thus treated harder than that treated by the Krupp process, but the depth to which the hardening is carried is increased. The economy of the process may be judged from the statement that while the Krupp plate is kept in the soaking pits at a red heat for from fifteen to twenty days, the same amount of impregnation with carbon is obtained with the Davis process in five hours.

The experimental plate was made at the works of the Bethlehem Steel Company. A moderate thickness, five inches, was chosen, and the only complaint made against the quality of plate was that the hardening of the face was not uniform, a fault which is attributed by the inventors and makers entirely to the experimental nature of the electrical appliances employed and not to any inherent defect in the process. In the next plate that is fabricated, carbon rollers are to be substituted for the present anodes, and with these it is expected that a uniform depth and hardness of carbonizing will be secured. It is estimated by Lieut. Davis that as compared with Krupp plate of equal resistance, the new system will produce plates from 20 to 30 per cent lighter in weight. Further developments of this process will be watched with the greatest interest, and should it prove possible to secure these remarkable results on a commercial scale, the effect upon warship construction will be more radical than anything that has happened in the naval and coast defence world for many years.

It is possible that in the new plate the navy has made answer to the new army high-explosive shell.

MID OCEAN WIRELESS TELEGRAPH STATION.

A scheme is on foot in Liverpool which, it is claimed by the English shipping journals, will soon be in commercial operation for utilizing wireless telegraphy in a mid-ocean post office and signal station. It is the intention to permanently moor at a point 110 miles west of the Lizard a ship which will be equipped with a search-light and a complete set of Marconi apparatus. As the water at the point selected will involve the use of a mooring chain 400 or 500 feet in length, the weight of which would prevent the bows from riding buoyantly over the heavy seas, the vessel will be provided with a horse-pipe placed in the keel of the foremast. The search-light is to have a vertical beam for the purpose of illuminating the clouds and enabling the floating post office to be picked up at night from a distance of 60 miles or more. As the vessel will be located in the fair way of the English Channel, it will be advantageously placed for the distribution of orders sent from shore by the owners to vessels which are passing in or out of the Channel. Thus a ship coming in from the west or from the south could be directed as soon as it picked up the station, to proceed either to Liverpool, Bristol, or an English Channel port. By this means pilotage and port dues would be reduced, and, of course, there would be a considerable saving of time. The vessel will serve as a floating station, which can be approached in any state of the weather, and picked up for wireless communication. The value of this form of post office is expected to be very great. Moreover, lying at the junction of the three great thoroughfares of British and continental marine traffic the station should prove particularly valuable in salvage work. The scheme on the face of it appears to be thoroughly practicable, and if carried out it should prove to be of considerable service in the maritime world.

SOME FURTHER GUNNERY EXPERIMENTS WITH THE "BELLEISLE."*

BY OUR ENGLISH CORRESPONDENT.

The Naval Department of the British government has carried out further elaborate gunnery experiments with the obsolete battleship "Belleisle," to ascertain the relative penetrating power of modern projectiles

* The following account of the "Belleisle" trials makes no pretensions to give any detailed account of the destruction in the interior of the vessel, but is merely a description of the purpose and scope of the trials, and the effect of the gun-fire as seen by our correspondent from the outside of the cordon of vessels which was established by the government around the "Belleisle." It is impossible to secure any detailed facts regarding the condition of the ship after the attack for the reason that the Navy Authorities have taken elaborate precautions to prevent such facts becoming public.

discharged from heavy guns, and the resisting power of modern armor. This is the third test of a similar character carried out by the British Admiralty during the past two years, and much valuable data, otherwise unobtainable, has been gathered. Naval experts and theorists have maintained that the armor generally employed for protecting battleships is proof against gun-fire as it will be delivered under battle conditions, but these practical tests have conclusively proved that the balance of power is yet distinctly in favor of the gun. That is to say, the progressive development of the weapon in respect to velocity, weight, and explosive potency of the shell is superior to the protective armor, and that the thickness of the latter, and its resisting qualities, have not developed commensurately with the improvement of the former. The effect has been of far-reaching importance to the British authorities, since owing to the results obtained with the two previous experiments with the "Belleisle," which were duly and fully related in the SCIENTIFIC AMERICAN at the time, several important alterations have been made in connection with the armor belts and deck defences of the latest English war vessels. For instance, the second experiment unexpectedly proved that the 4-inch armor was quite easily penetrated by 6-inch projectiles. This thickness of armor had been already fitted or ordered for several of the new cruisers. The authorities at once altered the protection for the new vessels to 6-inch armor.

For this latest experiment the "Belleisle" was once more patched up, and placed in a condition similar to that which would exist in an actual naval engagement. An ammunition hoist replete with electrical fittings and trucks was placed in precisely the position relative to the armor which it would occupy in action. The hoist was erected in a battery behind compound armor. The object of this particular arrangement was to enable the Admiralty to ascertain exactly what would ensue if a shell exploded in the vicinity of the ammunition hoist, and how far the machinery of the latter would be deranged by the force of the explosion.

The test was also undertaken to illustrate one or two other important points in connection with naval gunnery, upon which there is considerable divergence of opinion, and also to determine whether certain innovations in connection with projectiles and charges recently carried out in the navies of the various powers are advantageous. For example, England still adheres to cordite as a propelling charge, while other powers employ nitro-cellulose powder. Also, the Johnson cap is regarded dubiously by the British naval authorities. It has been contended that these two acquisitions have resulted in great efficiency and superiority in certain navies. The United States 100-pound projectile, discharged with nitro-cellulose powder, gives a muzzle velocity of 3,000 feet to the missile, as compared with 2,400 to 2,600 feet obtained with a cordite charge, and the former shell with a Johnson cap will penetrate over 10 inches of armor, while its penetration is several inches less without this cap.

Another important feature of the trial was to ascertain the efficiency of a new explosive, similar to maxinite, which has been introduced into the British navy as a shell filler.

The "Belleisle" was towed from Portsmouth and anchored off Bembridge as before. Two gunboats, one carrying a 6-inch gun, and the other a 9.2-inch weapon, were selected for firing. The first gunboat stood off at 1,000 yards from the "Belleisle" and fired a shell from the 6-inch weapon, the precise point of attack on the target being the exposed starboard central battery. The shell crashed through the torpedo netting, and pierced the side of the "Belleisle" just above the water line. The armor belting at this spot was of compound type, in vogue twenty-five years ago. A moment after the shell disappeared through the side of the vessel there was a terrific explosion, and a huge column of black dust was hurled high into the air, proving that the shell had penetrated to the coal bunkers and had there exploded.

Another shell was then discharged from the 6-inch gun. The point of attack this time was the conning tower. The shell struck with precision, as the white paint indicating the mark was completely blotched out. The next 100-pound shell was fired at the central battery. A great column of dust was blown into the air, and fragments of steel and splinters of wood were thrown to a distance of 200 yards.

The fourth 100-pound shell was fired at the conning tower, but it did not cause any serious damage so far as could be ascertained from an external examination.

The 9.2-inch gun was then brought into action, and a 380-pound shell was fired at the hulk from the same range of 1,000 yards. The first shot was directed at the central battery. It tore a big hole in the compound armor, and exploded with such violence that the "Belleisle" listed heavily.

A second 380-pound shell was then fired at the conning tower, with the result that the deck was torn up for several yards, and the bridge, situated just above