



HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters or no attention will be paid thereto. This is for our information and not for publication.

References to former articles or answers should give date of paper and page or number of question.

Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all either by letter or in this department, each must take his turn.

Buyers wishing to purchase any article not advertised in our columns will be furnished with addresses of houses manufacturing or carrying the same.

Special Written Information on matters of personal rather than general interest cannot be expected without remuneration.

Scientific American Supplements referred to may be had at the office. Price 10 cents each.

Books referred to promptly supplied on receipt of price.

Minerals sent for examination should be distinctly marked or labeled.

(9420) I. H. C. asks: 1. What power would be required to operate a fan 7 feet diameter of the best design to carry air into a cylinder the same diameter at the speed of 6,000 feet per minute? A. A 7-foot fan cannot be practically driven to a greater speed than 500 revolutions per minute, at which speed it should deliver 160,000 cubic feet of air per minute with a velocity through a 7-foot tube, without back pressure, of 4,210 feet per minute. To run the above fan at 500 revolutions per minute will require 36 horse-power. 2. What pressure would be exerted upon a circular surface 7 feet in diameter by a wind blowing 70 miles per hour? A. The pressure of wind on a flat surface at 70 miles per hour is 26 pounds per square foot, or 1,000 pounds on a circular surface 7 feet in diameter.

(9421) F. G. B. writes: About a year or two ago, in your column of answers to correspondents, there was given a solution of the problem of obtaining the number of feet, board measure, in a telegraph pole. Please give me the date of paper. A. To obtain the contents of a telegraph pole in board measure, add together the squares of the diameters of each end in feet or decimals of a foot and the product of the diameter of each end. Multiply this sum by 0.7854 and the product by the length of the pole in feet and divide the last product by 3 for the cubic feet. For the board measure multiply the cubic feet by 10 to allow for scarfs and waste.

(9422) J. M. S. writes: There is some device on the market for cooling water, etc., without the ice coming in contact with the water. There is a container that you put the freezing matter in and set it right into the pitcher or vessel or whatever you wish to cool. We saw an item concerning this in the SCIENTIFIC AMERICAN about a year ago, but we were not interested then very much. Will you be kind enough to advise us what you know about it, and greatly oblige? A. The material used for cooling is nitrate of ammonia dissolved in its bulk of water, in which the temperature falls from 50 deg. to 4 deg. F. Thus, by setting a vessel of water into an ordinary water cooler with water and dropping in the nitrate in small portions, the water in the inner vessel will soon be cool enough for drinking and may be frozen with a full charge of the nitrate. The method you describe is also a practical way of cooling a pitcher of water by filling a tin cylinder with equal parts of nitrate of ammonia and water and setting it in the pitcher for a few minutes. See SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 32 and 605, for illustrated examples of this class of domestic refrigeration, ten cents each mailed.

(9423) A. T. L. asks: 1. Suppose a jar which is a perfect vacuum to be instantly opened, will there be a time when the air that fills the jar would be at a greater density than the air on the outside of the jar? A. If a small opening were made into a jar in which was a perfect vacuum, the air rushing in would fill the jar slowly. In this case the rushing current of air would be diminished in quantity gradually until the jar was full, when it would cease. 2. If there is a time when the air in the jar is at a greater density than that on the exterior would this density be increased by holding a funnel over the mouth of the jar while the air is rushing in to fill said jar? A. If the opening into the jar were very large as compared with the size of the jar, so that the time of filling the jar would be very short, it is probable that the air would rush in with a concussion, and would oscillate somewhat to and fro before it settled to rest. This is because the air is an elastic body, and would rebound upon itself. In this latter case it might be that the air within the jar would be momentarily at a greater density than the air on the outside of the jar. If now the air were passed into the jar through a funnel, the action would be no different from that in the first case supposed, since the funnel would simply constitute a small opening into a larger place, and there would probably be no time when the air within the jar was denser than the external air. 3. Suppose the ground connection of a lightning arrester for a telephone or dynamo to be con-

nected to a steam boiler, would the lightning passing through that ground affect the steam boiler? A. The question you propose concerning a lightning arrester connected to a steam boiler as a ground, may be answered by saying that the lightning would pass through the steam boiler to the earth. We do not see that the metal of the steam boiler could have any electrical effect upon the lightning. The case is perfectly parallel to that of iron ships at sea. They are frequently struck and the lightning passes off from the hull into the water without damaging the hull.

(9424) J. K. asks: Will you please tell me if a lightning rod placed on a pole a few feet from a barn will insure the safety of the barn. In other words, if lightning is in a straight course for a building with a pole and rod placed in said position attract the lightning from its course? A. A lightning rod standing above a building but attached to a pole several feet from the building will make it less likely that the building will be struck by lightning. It does not act in the manner you describe, by drawing a discharge which is aimed at the building and is coming through the air from its source and away from the building. A flash of lightning takes place in some such way as this: A cloud comes over a place. The cloud is charged with electricity. This attracts electricity of the opposite kind from the earth and into the highest objects of the earth under the cloud. These charges of electricity in the cloud and the earth react upon each other until they pull strongly enough upon each other to rupture the air between them and then the flash which signals their coming together is seen. If the most intense part of the charge on the earth is in the building, the flash will go to the building; if it is in the lightning rod the flash goes to the rod. Now the chance is that the highest objects will be most highly charged by the action of the cloud, and thus be the points to be struck. No power can divert the discharge when once it starts for its destination, which is the most intense place charged by the opposite kind of electricity to that of the cloud. It goes to that point and to no other. Nor are we to think that the flash always starts from the cloud and falls to the earth. It as likely starts from the earth as from the cloud, and starts from both at the same instant. It sometimes flies back and forth many times from cloud to earth and from earth to cloud before the surging action dies out. Rods protect by furnishing an easier path for the discharge since they are metal. Much may be learned upon this topic from Thompson's "Electricity and Magnetism," price \$1.50 by mail.

(9425) J. J. A. asks: Please answer the following: Is it possible to recharge a dry cell? If so, let me know the proper way. A. A dry cell can be recharged in the same way as a storage cell is recharged, by sending a current through it in the opposite direction to that in which the current comes from the cell when it is furnishing current. Connect the positive pole of the charging current to the carbon of the dry cell and the negative pole of the current to the zinc of the dry cell. We have published a good mode of doing this in our SCIENTIFIC AMERICAN SUPPLEMENT No. 1451, price ten cents.

(9426) A. F. asks: 1. What are the advantages of using unsaturated (superheated) steam in running an engine? The superheated steam arrives at the cylinder having a high temperature, consequently there seems to be a small loss in condensation in the pipe conducting the steam from the boiler to the engine. The pressure, however, of this steam is not higher than that of the saturated steam in the boiler. What I would like to know is this: Is the small condensation in the steam-conducting pipe the only advantage of using superheated steam, or has it any special qualities or advantages when working in the cylinder? It seems the latter is not the case, because the pressure is the same as that of the saturated steam in the boiler—say 90 to 95 pounds—and hence for doing an equal amount of work, the engine would apparently consume an equal amount of saturated or unsaturated (superheated) steam. A. The advantages claimed for the use of superheated steam in engines are the saving from loss by condensation in the steam pipe, steam chest, and cylinder, and the gain from expansion of its volume by its increase in temperature; against which are the loss of lubrication of the cylinder walls by the condensing of wet steam and the cost of superheating, unless it is done by waste products of combustion after they leave the boiler. 2. Can superheated steam be used in any engine or is a compound or expansion engine necessary to utilize it? A. Superheated steam may be applied to any engine, but is most effective in compound engines. 3. Please to explain the expression, "the engine consumed 7.2 kg. steam per K. W. hour." (This expression was used in a German article.) A. The expression means 15.84 pounds of steam per 1.34 horse-power or 11.84 pounds of steam per horse-power hour. 4. Are steam turbines of about 60 horse-power manufactured in this country? Which seems to be more economical, especially regarding the steam question, engine or turbine, for electric lighting? A. Steam turbines are favorably considered for electric lighting on account of their high speed. 5. If electricity is always on the surface of a conductor why are larger wires not made hollow or also in thin strips whose surface would be

equal to that of the respective size of wire? Is the above common rule only correct for static electricity and not for currents? Why? A. Electric tube wires are more expensive than solid wire. Ribbon wire is not suitable or easily manageable in the wiring of electric plants. This form of wire is the same for static and electric currents.

(9427) B. J. B. says: Please inform me through the columns of your valuable paper concerning "The White Horse of the Chalk Cliffs of England" and oblige a diligent but unsuccessful searcher. A. The "White Horse of the Chalk Cliffs of England" is an image of a horse which may be seen near Ashdown in Berkshire, on the cliff which rises above the valley. The legend ascribes it to Alfred the Great, who overcame the Danes in the valley below, and had the horse cut in memory of his victory. The white horse was the common emblem of the Saxons. This image is frequently alluded to in the opening pages of "Tom Brown at Rugby."

(9428) J. N. H. says: 1. Of what is sewer gas composed? A. Sewer gas is composed of the gases of fermentation and foul odors which are conveyed in the moisture-saturated air, all holding the germs of disease that are constantly poured into the sewers. See SCIENTIFIC AMERICAN SUPPLEMENT No. 1037 on "Analysis of Sewage Water," and No. 418 on the "Dangers of Sewer Gas," ten cents each, mailed. 2. Why will plumber's wiping solder remain in a molten state longer than pure pig lead? The former is composed of forty parts tin to sixty parts lead and therefore melts at considerably lower temperature. A. Plumber's solder is fluid at a greatly less temperature than lead and the heat lost is in proportion to the fluid temperatures. Hot bodies cool faster than cooler ones.

(9429) J. W. V. asks: A very long and narrow strip of country near here has lately been swept almost bare by a "cyclone" or tornado. Not only were the few houses in its path demolished, but large trees in comparatively deep and narrow valleys were uprooted, parts of barb wire fences taken out of the ground and the wire inextricably tangled, and, it is said, even rocks weighing several hundred pounds and lying flat on the ground were moved considerable distances. Can you give me a brief explanation, in your paper, of how such results are accomplished? Is there any foundation for the current belief that a "vacuum" exists in the center of the whirlwind, which assists in doing so much destruction? I cannot see how a vacuum anything like complete or sudden enough to cause the air contained in houses to burst the walls outward by its expansion, as is said to be the case, could be formed. A. The tornado is a violent, whirling storm, usually moving with considerable velocity over the country. It may be but a few rods wide. It is believed that the uprush of air in the center of the storm sometimes reduces the pressure of the air by as much as a fourth of the normal pressure. This reduction would be 533 pounds per square foot. This amount of pressure is sufficient to move stones and almost any other objects with great violence. Such a diminution of pressure will burst a house outward, as is often done, and scatter the debris far and wide. The upward motion of the air in the center of these storms has carried objects up into the air and dropped them at great distances from the point from which they started. Thus a piece of tin roofing has been carried 17 miles, and a letter has been found 45 miles from the place where it was when the tornado struck it. It is pretty certain that the wind in a tornado attains a velocity much more than 100 miles per hour, some say 300 to 500 miles per hour.

(9430) R. M. C. asks: Will you please inform me through your "Notes and Queries" how to make a simple device for varying the speed of a small battery motor, one that runs on three or four cells of battery (or advise me where I can find this information)? A. The simplest method of regulating the current from a primary battery is to raise or lower the plates of the battery by some mechanical device so that less or more of them may come into action according as you desire less or more current. You can in this way secure the amount of current necessary for running a motor at various speeds. A form of battery for this purpose is described in our SUPPLEMENT No. 792, which we will send for ten cents. Should you desire, however, to construct a rheostat or current regulator with wire in the usual form, you will find descriptions which will aid you, accompanied by diagrams, in our SUPPLEMENT Nos. 865 and 985, price 10 cents each. Of course you will require only a small apparatus for three or four cells of battery, and would better use rather a large wire, perhaps No. 16 iron wire. We think, however, the first method which we suggest would be the more satisfactory.

(9431) F. H. asks: 1. What are the chemicals used for the purification of air after it has been breathed? I have seen the statement several times that there are such chemicals, and I would like to know what they are. A. To secure pure air, pass the air through clean cotton to remove dust; then through sulphuric acid to remove ammonia and moisture; then through calcium hydrate and potassium hydrate to remove carbon dioxide; then through a solution of lead acetate to remove sulphur compounds, and lastly, through calcium chloride and soda lime, to remove the

last traces of moisture and other impurities. There will be nothing remaining but pure oxygen, nitrogen, and argon. 2. What is the difference between static and dynamic electricity? A. Says that they are the same, and B says that they are different. A claims that if the secondary of an induction coil gives static electricity, that they are the same. He asks the question: "Can a Wimshurst machine be used to light lamps, or drive motors?" "If it can," he says, "static and dynamic electricity are the same, but if it cannot, then an induction coil does not give static electricity, as a transformer is nothing but an induction coil." A. Static electricity is electricity in the condition of a charge upon a body. The word static means without motion. The charge is at rest, but under tension, ready to move. Dynamic electricity is electricity in motion in the condition of an electric current. The distinction is radical and not dependent upon the apparatus by which the condition is produced. A Wimshurst machine when in operation but not producing a spark is in a static condition; when a spark is passing the discharge is a current and is dynamic. It is of enormously high potential and low amperage, and is momentary in duration. It will not light a lamp, because of these conditions. An incandescent lamp, 16 candle power, requires considerable current at a low voltage and continuing for a time to bring it to the temperature of incandescence. Nor will an induction coil light such a lamp, and for the same reasons. An induction coil arranged to transform a current at the proper voltage and amperage will light a lamp, but is not then in a static condition. It is sending current, which is dynamic. When a dynamo is running but no current is being drawn from it, the potential is there as in static charge, and the machine would charge a condenser. The circuit is then in a static condition. Turn on lamps or a motor and current flows. The machine has become dynamic. It is a dynamo now, as its name implies; it is sending current through its circuit. A's arguments are sometimes right and sometimes wrong. He does not seem to keep in mind the meaning of the terms he is using. 3. We have an alternating current here for lighting, of 220 volts. I can short-circuit this through an ordinary quart fruit jar, filled with water, and with two lead plates, about one inch wide by five long, in it. Can I get a spark with an induction coil as long, using this current without a condenser, as I can using batteries with a condenser? A. When you put the poles of the alternating current into a jar of water as described you have a water rheostat, which can be used to control the amount of current which shall flow for any purpose. It is quite commonly in use for this purpose. You can in this way run an induction coil for any desired length of spark. Such coil does not require a condenser. 4. How many amperes can No. 20 B. & S. magnet wire carry without becoming perceptibly heated? A. At an allowance of 400 circular mils per ampere, No. 20 B. & S. wire of copper can safely carry 2½ amperes. This will raise its temperature of course above that of the air. Any current will raise the temperature of a wire. No carrying capacity is given for wires under No. 18, since the Fire Underwriters do not allow them to be used in lighting and power circuits, and carrying capacity has no significance except in relation to lights and dynamos and motors.

NEW BOOKS, ETC.

ROOF FRAMING MADE EASY. By Owen B. Maginnis, Architect. New York: Industrial Publication Company, 1903. 8vo.; pp. 150. Price, \$1.

The fact that this small handbook has reached its second edition is sufficient evidence that it has been found most valuable by architects and builders. The author treats very explicitly of the construction of all sorts of roofs, such as roofs for studios, towers, etc. The book is thoroughly practical in character, and is well illustrated by nearly one hundred cuts.

PRACTICAL LAWS AND DATA ON THE CONDENSATION OF STEAM IN COVERED AND BARE PIPES. To which is Added a Translation of Péclet's "Theory and Experiments on the Transmission of Heat Through Insulating Materials." By Charles P. Paulding, M.E. New York: D. Van Nostrand Company, 1904. 8vo.; pp. 102. Price, \$2.

The object of this monograph is to give to engineers a rational method of estimating the loss of heat from steam pipes and boilers covered with any of the standard non-conducting materials. Far from being new, the method to which attention is here called was worked out by the French physicist Péclet in 1850, but, in the absence of translations of Péclet's pamphlet, his deductions seem to have been generally overlooked in this country. The principles involved are so general that the loss of heat from covered pipes is only one of their many practical applications. To those who have to deal in any way with the problems of cold storage and refrigeration, the information and the formulas given in this volume will be especially useful.

THE LOCOMOTIVE SIMPLY EXPLAINED. By Charles S. Lake. London: Percival Marshall & Co., 1903. 16mo.; pp. 72. Price, 25 cents.

This handbook forms No. 17 of the "Model Engineer" series, and it was written to describe

in a popular way many of the main features of modern English locomotives, which are not familiar to the ordinary layman. It is illustrated with some twenty-five cuts, among which are several half-tones of English locomotives.

VADE MECUM GUIDE. A Popular Guide to Mineral Collections. With a Chapter on the Development of Mineralogy. By L. P. Gratacap, A.M. New York: The Broadway Press, 1904. 12mo.; pp. 178.

This is of a convenient size to slip into the average coat pocket, making it an especially handy and useful reference book for the frequenter of collections. The writer observes the order followed by Dana in the fifth edition of his "System of Mineralogy," supplementing the discussion with an index of minerals alphabetically arranged, so that any required description may be readily found. There are a number of full-page plates of crystals from notable American collections, and numerous figures illustrative of the methods of classification.

TWENTIETH CENTURY HANDBOOK FOR ENGINEERS AND ELECTRICIANS. With Questions and Answers. By C. F. Swingle, M.E. Electrical Division by Henry C. Horstmann and Victor H. Tousley. Chicago: Frederick J. Drake & Co., 1904. 12mo.; pp. 500; 300 illustrations. Price, \$2.50.

The "Twentieth Century Handbook," phrased in simple language and lavishly illustrated, aims to aid the man of limited education in increasing his practical knowledge and extending his usefulness. There are chapters of practical instruction in the care and management of steam engines and boilers. Problems and calculations in hydraulics are worked out in plain figures, without resorting to the use of algebra, and simple arithmetical rules are given for the solution of these problems. Particular attention has been paid to indicator work, and to evaporation tests. The electrical chapters deal with the principles, construction, and operation of dynamos, motors, lamps, storage batteries, etc. There are tables that will, in many instances, do away with the necessity of figuring. In a word, the papers give, thoroughly, and yet in as simple a manner as possible, just that knowledge of electricity which a steam engineer is apt to find himself in need of. The volume is bound in full leather, pocketbook style, the back cover being extended to form a protecting flap with snap fastening.

MINERAL TABLES FOR THE DETERMINATION OF MINERALS BY THEIR PHYSICAL PROPERTIES. By Arthur S. Eakle, Ph.D. New York: John Wiley & Sons, 1904. 8vo.; pp. 73. Price, \$1.25.

This book of tables was compiled in order to aid students in the natural method of identifying minerals, namely, by noting their peculiarities of color, luster, hardness, specific gravity, and the like. The tables include all the common minerals and a few others of local prominence, which are generally considered as rare. The minerals are arranged primarily according to streak and color, while under each color the arrangement is according to hardness. The chief difference between these tables and those of Welsbach is that in the present book luster is regarded as an unimportant division. Various mineralogical works were consulted in preparing the tables, which will be found quite complete and valuable.

POINTS FOR BUYERS AND USERS OF TOOL STEEL. By George W. Alling, M.E. New York: David Williams Company, 1903. 8vo.; pp. 224. Price, \$2.

This book was primarily written for the benefit of those who have not a technical education. It is designed chiefly for the use of the mechanic and tool maker; and while it does not go into details as far as percentages of carbon and chemical construction of steel are concerned, it should help the mechanic to avoid many of the difficulties found by every tool maker, who has to make numerous kinds of tools from the many varying sorts of steel which he obtains from the steel makers. Chapters on defects in steel, how produced, and how detected; how to test the quality and uniformity of steel; preparing steel for hardening, and hardening and hardening appliances, are among the most valuable in the book. Some sixty illustrations of samples of steel and of tools add to the value of the book, while a number of useful tables are contained in an appendix.

ELEMENTS OF INORGANIC CHEMISTRY. By Harry C. Jones. New York: The Macmillan Company, 1903. 8vo.; pp. 343. Price, \$1.25.

This book, which is considered as an elementary textbook, treats the science of chemistry in an up-to-date manner, and while the older generalizations have been thoroughly discussed, those generalizations which have been more recently made are incorporated in the text. Thus, while the atom is still used as the smallest indivisible particle of matter, the ion, which is a later conception of an atom as carrying an electrical charge, is also thoroughly discussed. Another generalization which is treated is that concerning the law of Faraday as the basis of chemical valence. The physical properties of substances are treated more fully than in earlier textbooks, and are described in every instance after the chemical properties. The experiments on each substance are placed at the end of the chapter describing

said substance, and are followed by the problems to be solved. Such portions of the author's "Principles of Inorganic Chemistry" as were considered adapted to the beginner are also contained in this book, which will be found an admirable textbook for the use of beginners in chemistry.

A LABORATORY GUIDE TO QUALITATIVE ANALYSIS WITH THE BLOWPIPE. By F. W. Martin, Ph.D., Analytical Chemist. New York: John Wiley & Sons, 1903. 12mo.; pp. 41. Price, 60 cents.

Believing that the use of the blowpipe, which has long been recognized as an indispensable apparatus in the study of mineralogy, has been largely restricted to that science, and been used to a very limited extent in other branches of analysis because there has been no manual on the subject treating of its use with compounds in general, the author has prepared this small volume for use as a laboratory guide by students of qualitative analysis, and as a work of reference by practising chemists. A systematic course of analysis for a long list of elements and compounds is succinctly given in these pages.

MODERN MICROSCOPY. By M. I. Cross and Martin J. Cole. Chicago: W. T. Keener & Co., 1903. 8vo.; pp. 285; 76 cuts. Price, \$1.50.

This handbook is designed to give to the novice information and advice in choosing his microscope and accessories, and to direct him as to the proper way of using them. The book, which has reached its third edition, is in three parts. The first part, by Mr. Cross, treats of the microscope and accessory apparatus, and gives instructions for their use; the second part, by Mr. Cole, treats of microscopic objects, and tells how to prepare and mount them; while the third part, which is the new part of this edition, and which was specially prepared by Mr. G. West, of the Botanical Laboratory at Edinburgh, is on the choice and use of microtomes, or machines for cutting microscopic sections. All three parts are clearly and concisely written, and the book as a whole forms a complete handbook for the tyro microscopist.

TESTING OF ELECTRO-MAGNETIC MACHINERY AND OTHER APPARATUS. By Bernard Victor Swenson, E.E., M.E., of the University of Wisconsin, and Budd Frankenfield, E.E., of the Nernst Lamp Company. New York: The Macmillan Company, 1904. 8vo.; pp. 420. Price, \$3.

This book is the first of two volumes which are intended for use as a college textbook and as a work of reference for engineers. The first volume deals with direct-current electro-magnetic machinery and apparatus, and it is almost exclusively confined to dynamo-electric machinery. It has been the aim of the authors to impart a thoroughly practical knowledge of dynamo machinery and apparatus to the student, and the book can be used as a textbook for a practical dynamo laboratory course. For this reason the numerous experiments which the book describes are divided into (1) a review of the theory; (2) to the particular experimental method involved; and (3) to practical applications of the particular subject. Questions which bear directly on the subject are asked at the end of many of the experiments, with the object of stimulating independent thought and observation. These questions bear upon important, though less evident, relations of the phenomena involved. The book contains a complete list of references to other works on the subject.

THE LAYOUT OF CORLISS VALVE GEARS. By Sanford A. Moss, M.S., Ph.D. New York: D. Van Nostrand Company, 1903. 24mo.; pp. 108. Price, 50 cents.

This small volume, which is a reprint from the American Machinist, with revisions and additions, treats of the Corliss valve gear from a theoretical point of view. The "single eccentric" motion is treated from a rational standpoint, and a complete discussion is given of the theoretical principles underlying the kinematic design or "layout." Explicit instructions are given for making a layout on the drawing board. These instructions are so simple that a layout can be made by anyone at all familiar with the common slide valve and other valves for steam engines. The book is theoretical in character, the kinematic features rather than the constructive features of the valve gear being described.

INDEX OF INVENTIONS

For which Letters Patent of the
United States were Issued
for the Week Ending
July 5, 1904

AND EACH BEARING THAT DATE

[See note at end of list about copies of these patents.]

Acid, making, hydrocyanic, W. Feld, 764,443
Advertising display apparatus, J. I. Wiley, 764,510
Aerating apparatus, liquid, F. G. Hamp, 764,461
Agricultural machine, G. L. Bradley, 764,034
Air brake, automatic, H. McCleary, 764,142

Air brake system for railway trains, N. M. Tiffany, 764,217
Air compressor, Dieckrich & Cramer, 764,182
Air heater, W. J. Perkins, 764,004
Air ship, J. D. McFarland, Jr., 764,198
Air ship propelling apparatus, A. V. Winegarden, 764,512
Alarm system apparatus, F. McGloin, 764,199
Ammonium nitrate, producing, E. Naumann, 764,251
Aniline device, A. F. Bingenheimer, 764,171
Animal trap, W. Walton, 764,085
Animal trap, B. De Mecker, 764,432
Arch construction, concrete, W. C. Parmley, 764,302
Aseptic napkin receptacle, A. A. H. Hamer, 764,188
Autographic register, E. J. Barker, 764,030
Automatic brake, adjustable, M. P. Carpenter, 764,038
Automobile driving mechanism, H. B. Maxwell, 764,063
Automobile engines, means for cooling, J. G. Anderson, 763,949
Automobile self-locking steering gear, R. O. Stutsman, 764,161
Awning, R. Lane, 764,245
Axle box dust guard, T. H. Symington, 764,162
Axle shafts of carriages, etc., antifriction mechanism for, J. E. Cooper, 764,427
Balance, P. G. Richter, 764,377
Bale tie, A. A. Cee, 764,351
Baling press band tying mechanism, J. L. Towner, 764,318
Barber's sectional sterilizer, C. B. Hypes, 764,242
Bath tub seat, J. P. Eustis, 764,232
Battery cell, W. O. Duntley, 764,252
Bed heater, spring, J. W. Amrath, 764,263
Bed, folding, D. F. King, 764,475
Bed, invalid, G. H. Miller, 764,141
Bed or bed couch, sofa, L. H. Bullard, 763,958
Bedstead, folding, M. Benz, 764,414
Beet toppler, J. M. Caraway, 764,423
Belt cleaning apparatus, Donaldson & McGargle, 764,435
Bicycle sled runner attachment, Erickson & Larson, 764,442
Binder, W. K. Tewksbury, 764,019
Binder attachment, A. M. Davis, 764,431
Binder, loose leaf, Robson & Blackmer, 764,502
Binder, temporary, J. W. Amrath, 764,263
Binder, temporary, G. D. Emerson, 764,284
Binder, temporary, A. T. Baxter, 764,413
Blinds, cord guiding and gripping device for, Venetian, G. F. French, 764,047
Block, See Building block.
Boat, folding, C. E. Kilgore, 764,473
Boat, water bicycle, C. Wasek, 764,086
Boiler furnace, steam, J. W. Stillwell, 764,314
Boiler tube fastening, G. Wettels, 764,088
Book, loose leaf, H. W. Ayres, 764,102
Book, sales, E. J. Brant, 764,173
Boot or shoe jack, J. Beauray, 764,335
Brush, temporary, J. F. Ziegler, 764,285
Bottle, M. J. & D. J. Flynn, 763,973
Bottle, non-refillable, Alberty & Nixon, 763,948
Bottle, non-refillable, G. A. Clavin, 764,041
Bottle stopper, automatic, W. J. Burchett, 764,225
Bottle washing machine, T. Grebe, 764,456
Bottles, cans, etc., top or closure for teeth powder, H. B. Kent, 763,986
Brake mechanism, J. G. Heaslet, 764,357
Brake shoe, E. W. Robinson, 764,306
Brick or tile cutting machine, W. R. Cunningham, 764,272
Brick tongs, S. E. Langford, 764,058
Brush handle, H. A. Hayter, 764,124
Brush holder, H. G. Reist, 764,400
Bucket support, intermediate, A. R. Dodge, 764,433
Buckle, M. M. Askey, 764,029
Buckle, J. E. Mitchell, 764,065
Building block, S. D. Hackman, 764,450
Building construction, C. W. Stevens, 764,313
Buildings, construction of, H. F. Lightner, 764,061
Bung, E. N. Greenwood, 764,120
Burglar alarm window fastener, J. Lyon, 764,534
Bushing, machine, J. A. Anderson, 764,330
Buttercup cutter, J. E. Blair, 764,337
Calculating machine, F. C. Rinsche, 764,008
Calculating machine, R. E. Spivey, 764,387
Calculating mechanism, E. H. Palmer, 764,068
Calculator, Pollen & Barr, 764,074
Camera, H. Goodwin, 764,288
Can, See Display can.
Can spout, oil, J. H. McGinty, 764,537
Candy pulling machine, F. H. Richards, 764,538
Cane, spring map roller, O. L. Osborn, 764,301
Car body bolster, J. M. Hopkins, 763,978
Car brake operating mechanism, W. W. Hopkins, 764,127
Car brakes, means for automatically adjusting, J. A. Rubel, 764,380
Car cinder guard, J. W. Harrison, 764,462
Car coupling, Scannell & Dugan, 764,308
Car coupling, J. E. Wade, 764,323
Car doors, detachable hood for freight, D. Tatum, 764,215
Car draft rigging, A. C. McCord, 763,998
Car, dump, Hart & Meissner, 764,355
Car, dumping, M. Boyle, 764,417
Car, dumping, V. Keuns, 764,476
Car fender, A. Robinson, 764,255
Car fender, P. Tade, 764,317
Car or wagon coupling locker, automatic railway, W. Skerman, 764,503
Car, railway, J. Dew, 763,968
Car, railway freight, J. G. Stoller, et al., 764,300
Car sign, changeable street, W. I. Larzere, 763,988
Car step, J. W. Buchanan, 764,420
Car step, automatic, J. L. Hines, 764,467
Car ventilator, F. W. Symmes, 764,078
Carbon sheets, automatic feeding device for, G. W. Donning, 764,436
Carburetor, M. D. Colbath, 763,965
Cards, machine for repeating pattern, R. Johnston, 764,129
Carpet sweeper, L. P. Halladay, 764,050
Carriage top, W. H. Kelly, 763,985
Carriage top, J. F. Swares, 764,364
Carton, sector shaped, H. P. Shotts, 764,154
Cash register, W. H. Muzzy, 763,997
Cash register, E. H. Chapman, 764,425
Cattle guard, S. A. & H. W. Armstrong, 764,514
Cement composition, magnesia, H. Mielck, 764,256
Cement, manufacturing, G. Sr., & G. Geissler, Jr., 764,453
Cement or cementitious materials, making products of, W. E. Jaques, 764,361
Chain, C. W. Levalley, 764,246
Chain, pitch, F. Ley, 764,298
Chair backs, adjustment for typewriter or other, J. Gilson, 764,287
Chimney cleaner, M. Wensauer, 764,265
Chuck, milling, J. & W. R. Thomas, 764,316
Churn, C. Sailer, 764,075
Churn, E. P. Noerd, 764,147
Cigar cutting and branding device, combined, H. F. Brandenburg, 764,035
Cigar maker's machine, E. Winterer, 764,024
Cigarette machine, continuous, F. J. Ludwig, 763,991
Clamping dog, work, F. L. Curtis, 764,523
Cleaning machine, V. Ciralli, 764,426
Clothes drier, G. Horvath, 763,979
Clutch, friction, T. W. Barber, 764,104
Clutch, friction, E. F. McMahon, 764,146
Coach, motor, R. Stone, 764,283
Cock, stop, W. T. Wiegand, 764,322
Coffee roasting apparatus, G. R. Cottrell, 764,226
Coil and making same, field, W. D. Litchfield, 764,481
Coin controlled operating machine, D. James, 764,056
Collar shaping and drying device, S. B. Dane, 764,524
Column, sectional, J. D. Buckley, 763,957
Comb, K. Tezzetti, 764,165
Commercial instrument and book, O. C. St. Clair, 764,262
Compass and level attachment for vehicles, R. Finkelson, 764,444
Computing register, automatic, B. M. Desjardins, 763,966
Concentrator, C. H. Muhleman, 764,187
Concrete building blocks, car for drying, W. E. Ellenberger, 764,184
Conduit coupling, F. A. Houdlette, 764,054
Conometer, J. A. Perkins, 764,263
Controller, E. B. Wharton, 764,402
Converter, R. Bagdaley, 764,332
Conveyor, M. C. Schwab, 764,012
Cooker, sectional, C. W. Stokes, 764,078

Cooking and warming apparatus, A. T. Bradshaw, 764,107
Cooking device, C. C. Overton, 764,496
Cooking pot or the like, Clayton & Crump, 763,962
Corn husker, F. D. Kees, 763,984
Corn husker and fodder shredder, T. A. Galt, 764,234
Corn shocker, F. A. Ryther, 764,381
Cot, folding, N. E. Nelson, 764,388
Cotton picker, C. G. Mercer, 764,365
Cotton picker's truck, J. French, 764,447
Cream separator, K. McLeod, 764,459
Cultivator, J. M. W. Long, 764,062
Cultivator, C. S. Ruef, 764,257
Cut-off mechanism, automatic spout, F. G. Dieterich, 764,277
Cut out, thermal, R. R. Read, 764,372
Cutter head, J. Villiger, Jr., 764,399
Cutting, folding, and winding strips of flexible material, machine for, A. L. Adams, 764,328
Cycle, motor, J. S. Copeland, 764,113
Dam and constructing same, J. A. Copple, 764,422
Dental cuspidor, H. E. Welch, 764,022
Denture, artificial, O. C. & J. R. Halderman, 764,528
Die, See Screw cutting die.
Die head, W. J. Smith, 764,356
Display and reserve stock case for thimbles, J. B. Ingalls, 764,529
Display apparatus, automatic electrical, B. A. Gilbert, 764,539
Display cabinet, Duerr & Mortland, 764,239
Display can or box, sheet metal, B. H. Larkin, 764,296
Display case, J. M. Alfaro, 764,297
Display hanger, E. E. Guilford, 764,028
Display rack, J. E. Rees, 764,256
Display rack, adjustable, R. R. Edwards, 764,046
Distilling apparatus, crude oil, J. C. Malencee, 764,138
Doors, automatic screen for the slots of edgewise moving, Newell & Schuyler, 764,000
Doors, automatic unlocking device for, J. C. May, 764,535
Draft appliance, J. R. Kelly, 764,296
Draft equalizer, O. A. & W. A. Westerson, 764,087
Drawing instrument, Bowass & Jones, 764,033
Dress shield fastener, C. C. & L. C. Lindehl, 763,990
Drying apparatus, J. A. Ridings, 764,150
Electric apparatus, starter for vapor, C. W. Denny, 764,181
Electric circuit controlling apparatus, J. P. Tirrell, 764,218
Electric circuit cut out, C. & C. Johnston, 764,293
Electric light hanger for walls, W. H. Lau, 764,135
Electric light hanger handle, P. J. Cahill, 764,037
Electric meter, A. Peloux, 764,253
Electric motor, controlling system, A. C. Eastwood, 764,439
Electric switch, J. F. Hardy, 764,189
Electric switch, J. L. Steeb, 764,505
Electrical connection, E. A. G. Street, 764,391
Electrical distribution system, C. P. Steinmetz, 764,213
Electrical heat meter, H. Bremer, 764,518
Electricity meter, C. Clerici, 764,112
Electromassage device, L. J. Chapman, 764,349
Elevator attachment, C. Christiansen, 763,990
Elevator cars and counterweights, safety catch, H. P. Curney, 763,976
Elevator electrohydraulic valve mechanism, H. F. Hinman, 764,240
Elevator gate, M. Kaw, 764,130
Elevator safety appliance, sidewalk, M. Galfin, 764,236
Embroidering machine needle inserter, C. A. Gonzenbach, 764,119
Engine, G. R. Kendrick, 764,185
Engine fly wheel, explosion, W. B. Hayden, 764,356
Envelope, W. H. Croom, 764,271
Envelope fastener, W. W. Palmer, 764,252
Etching machine, Therpe & Fischer, 764,164
Etching printing plates, W. G. Thorne, 764,032
Evaporating apparatus, pile vacuum, T. Suzuki, 764,393
Evaporating closet, portable, F. P. Smith, 764,261
Excavations, apparatus for removing dirt from, W. J. Newman, 764,201
Excelsior making machine, Niemeyer & Godman, 764,492
Exerciser, M. Duffner, 764,118
Extractor, See Stump extractor.
Extracts, increasing the solubility of, J. Maggi, 764,483
Eyeglasses or spectacles, G. F. Applegate, 764,109
Eyelets, coating, I. W. Giles, 764,454
Fabric tenting and drying machine, Ratignier & Clerc-Renaud, 764,254
Fare register and recorder, W. I. Ohmer, 764,494
Fastener, D. A. Breaux, 763,955
Fastener, R. S. Hamilton, 764,238
Fastener, safety, A. Schaeffer, 764,153
Fastening device, P. Morrison, 764,487
Feed trough, S. J. Betha, 763,951
Feed water heater, E. R. Gustavus, 764,457
Fence, G. L. Ricks, 764,378
Fence post, J. S. & T. Shull, 764,468
File, order and record, H. J. Rieck, 764,379
Filtering, G. Moore, 764,486
Finger ring, F. R. Stafford, 764,504
Fire curtain, Uncapher & Andrus, 764,083
Fire escape, Gilmore & Perry, 764,187
Fire escape, G. Blumenthal, 764,339
Fire resisting shutter or door, J. Velp, 764,219
Firearm, F. K. Young, 764,513
Firearm magazine attachment, T. C. Johnson, 764,243
Fishing reel, W. Carter, 764,348
Fishing reel, G. W. Upton, 764,348
Flash, W. L. Casaday, 763,959
Flexible coupling, G. Baehr, 764,103
Floor clamp, E. M. & L. W. Jeffords, 764,128
Flower pot support, W. Cobbett, 764,042
Flower stand, F. Scallill, 764,307
Fluid meter system, H. Aiken, 764,329
Folding table, E. H. Huffman, 764,359
Fuel, artificial, M. C. Gama, 764,526
Fuel burner and mixer, T. M. Dudgeon, 764,279
Funnel, W. E. Burgess, 764,422
Fur or hair from water, means for removing, W. V. Hupchen, 763,981
Fuses, protecting cap for projectile, K. Wieser, 764,405
Game apparatus, E. A. Cannon, 764,179
Game of cards, A. Semle, 764,209
Game, tenpin, A. Ferland, 764,185
Gas burner valve mechanism, M. W. Lewis, 764,364
Gas generator, acetylene, N. Goodyear, 764,046
Gas generator, acetylene, J. Fraiser, 764,446
Gas heater, L. L. Rowe, 764,010
Gas, making, D. Turk, 764,320
Gas pressure regulator, R. A. Gillespie, 764,186
Gas producer superheater, A. B. Duff, 764,437
Gas service pipes, antifluator for, J. E. Broderick, 764,269
Gas washer, O. N. Guldin, 764,019
Gases, separating mechanically entrained globules from, T. A. Edison, 764,183
Gear wheel, V. W. Mason, Jr., 763,993
Generator and combustion chamber, combined, H. Ragot, 764,149
Glass, manufacture of, S. O. Richardson, Jr., 764,501
Glass melting furnace, W. T. Nichols, 764,300
Governor, high speed engine, E. A. Edwards, 764,228
Grain bin drying apparatus, A. R. Hagner, 764,237
Grain separator, F. L. Lewis, 764,478
Grain treating apparatus, seed, A. M. Halderman, 764,122
Grapple, W. A. Duncan, 764,281
Grate bar, hollow blast, J. A. Willard, 764,511
Griddle and turner, pancake, W. A. Saunders, 764,382
Grinding mill, A. H. Patch, 764,071
Grinding or polishing machine, W. V. Robinson, 764,151
Grip, telescopic, F. H. McGowan, 764,144
Gun with protecting shield offset from the trunnions, transportable, O. Lauber, 764,477
Hammer self feeding, J. W. Thompson, 764,216
Harness tree seat, R. Miller, 763,994
Harvester, A. B. Reynolds, 764,205
Hat stand, milliner's, H. L. Oliphant, 764,429
Headlight, locomotive, E. A. Edwards, 764,295
Heater, See Air heater.
Heater, H. F. Hoeman, 764,191
Heater and ventilator, Johnson & Sheridan, 763,983