

machine for cutting the buckets of the turbine wheels. The whole wheel is made out of a single disk of steel, the buckets being integral with the wheel. The machine for cutting the buckets resembles a double-spindle lathe. The work is held in a horizontal position on the tail stock, and two cutters alternately advance toward the rim of the wheel, make a cut of the desired curvature and recede, leaving the wheel free to revolve sufficiently to bring the next bucket into position for another cut. One cutter operates on one wall of the bucket, and the other on the opposite wall. The result is a wheel of perfect form, carrying a highly finished surface. It should be mentioned here that the remarkably high efficiency in speed and range of the new torpedo is due to the use of a superheating process applied to the compressed air. This consists of a flame which is automatically ignited, the instant the torpedo is launched from the tube, and which burns during the entire run. The compressed-air flask contains a burner or pot, the flame of which is fed automatically with alcohol. The flow is so regulated that an even and steady temperature is maintained in the air flask.

During the past few months, the company has been carrying out a series of very exhaustive tests on board the proving steamer "Sarah Thorpe," which is anchored in the secluded waters of Noyak Bay, near Sag Harbor, Long Island. Here each torpedo is tested and brought up to the required standard of efficiency in speed and range before being turned over to the torpedo station at Newport. The Navy Department assigned a lieutenant and several gunners to witness and record the run of each torpedo. The target is a submerged net, 100 feet in length, which is located 1,200 yards from the point of fire. The torpedo breaks through the meshes, and after each shot the net is hauled up, and the exact striking point is located by the tear in the net. The maximum deviation in the range allowed is 15 feet to the right and left of the bull's eye, and 30 inches above and below at five feet of depth. Each torpedo must come within these measurements in three out of five trial runs, in order to be accepted. The average speed of the run is 36 knots, and the time run is about  $60\frac{1}{4}$  seconds for 1,200 yards. The cost of the 18-inch torpedo is about \$5,000, and the 21-inch torpedo costs proportionately more.

#### Preserve Your Papers; They Are of Permanent Value.

By taking a little trouble, when a paper first comes to hand, it may be preserved to form a permanent and valuable addition to the reading matter with which everyone should be supplied. We furnish a neat and attractive cloth board binder, which will be sent by mail, prepaid, for \$1.50. It has good strong covers, on which the name SCIENTIFIC AMERICAN or SCIENTIFIC AMERICAN SUPPLEMENT is stamped in gold, and means by which the numbers may be securely held as in a bound book. One binder may thus be made serviceable for several years, and when the successive volumes, as they are completed, are bound in permanent form, the subscriber ultimately finds himself, for a moderate cost, in possession of a most valuable addition to any library, embracing a wide variety of scientific and general information, and timely and original illustrations. Save your papers.

#### The Current Supplement.

Jacques Boyer opens the current SUPPLEMENT, No. 1566, with an interesting article on the truffle industry in France. Excellent illustrations accompany his text. The manufacture of rosin oils is thoroughly discussed by E. Rabaté. Sepia watertone papers, simple to work and cheap, can easily be made by the amateur photographer, if he follows the method outlined in the current SUPPLEMENT. Notwithstanding the fact that much of the music produced by chimes is rendered with discords, a peal of bells always finds ready listeners. The late George M. Hopkins describes in a painstaking article how an electric chime may be made by any one at a comparatively small expense. Major Ronald Ross, to whom we owe the discovery that mosquitoes are purveyors of malaria, has computed the number of mosquitoes which infest a given area. The method which he pursues is very carefully set forth. Curves in pattern work is the subject of an article which must be of interest to the foundryman. In a very brief and yet comprehensive article Mr. E. F. Chandler tells how to construct an electrothermostat. The telemobiloscope is the invention of a German scientist. Its purpose is to discover the nearness of one vessel to another at sea during foggy weather, in order to avoid collisions. The invention is described and illustrated.

#### The Poisons of an Egg.

M. Gustave Loisel, in a paper recently read before the Academie des Sciences, describes some experiments he has been making in regard to the toxicity of certain glands of different animals, vertebrate and invertebrate, and also finds the same result in the case of eggs. He uses in this case eggs from the duck, chicken,

and turtle. As to the toxicity of the duck's egg, he makes the following experiments: First, relating to the venous injection of yolks of the eggs which are emulsified in distilled water. By injecting this emulsion into the veins of rabbits, he finds that seven adult animals are killed by 8 cubic centimeters of the yolk on an average. The animals die in a variable time, from some minutes to two hours, showing at first a contraction of all the members, followed by paralysis. Second, the injections were made with extract from 21 yolks of eggs dried and reduced to powder, extracting with salt water. Using 10 grammes of this powder, treated to 100 cubic centimeters of salt water (1 per cent) then filtered, the solution caused the death of three rabbits when injected into the veins in the proportion of 80 cubic centimeters per kilogramme weight of the animal. Chickens' eggs have about the same effect, but in a somewhat less degree, while turtles' eggs (from the Mauritanian tortoise) have a greater effect, especially for the mature ovules taken directly from the ovaries. Not only does the yolk cause the rabbits to succumb with convulsions and tetanic contractions, but the albumen forming the white of the turtle's egg has an equally powerful effect. Sub-cutaneous injections have the same action. In the case of the yolk, a series of check experiments was made, using an emulsion of oil and salt water, but this had no effect upon the rabbits.

#### AUTOMATIC WATERING POT.

Our article, with its illustrations, concerning an automatic apparatus for watering plants, recalled to Mr. M. M. Moore, a subscriber, a device which he used upon the suggestion of a "forty-niner."

A few years ago Mr. Moore lived upon a small ranch,



AN AUTOMATIC WATERING POT.

where the only water supply was a small well. In order to have a few plants and flowers, he gathered a number of tin cans—tomato, corn, etc.—cut out the top so that it held by an inch or so, bent it back, so that it could be nailed to a stick, punched a very small hole in the bottom, through which he drew three or four inches of cotton cloth or string, drove the stick near the plant he wished to water, so that the can was eight or ten inches above the ground, filled the can with water, and then drop by drop the water fell upon the ground near the plant all day, sometimes all day and night. The ground soon became saturated, the plant thrived, and the quart of water did as much good as an all-day rain.

The accompanying sketch will give an idea of the device.

#### A New Ozone Apparatus.

The ozone apparatus for medical use which are employed at present do not always work perfectly, as they are more or less influenced by the state of the weather, and besides, the ozone which is produced is often mixed with combinations of gases, nitrogen, ammonia, also phosphorus or metallic oxides, which result from the contact of the ozone and the metallic poles when a too dense charge is produced. To overcome these difficulties, M. Breydel, a Belgian scientist, brings out a new process in which the electric discharge is obtained between plates of large surface which have a special insulating coating. In this way he prevents the spark discharges and the volatilization of the metal at the electrodes. He finds that when above 20 degrees C. the ozone tends to be transformed to oxygen, and thus the amount of ozone depends upon the temperature and also the degrees of the ozonized gas. For this reason he uses poles which are placed in a medium having a somewhat low temperature. The air is well dried before going into the apparatus. A funnel-shaped opening allows of making inhalations, placing the face some eight inches off, or a narrow

opening can be used, for local treatment. The ozone can also be passed through liquids, where needed. The new apparatus gives a much larger quantity of ozone than can be obtained by other forms, and it has a great advantage in not being influenced by the weather.

#### Engineering Notes.

Shipping circles in Great Britain are closely interested in a new experiment in ship construction that is being carried out in a shipbuilding yard on the northeast coast by the inventors of the turret ship, which is now such a popular type of freight vessel. This boat is being constructed without beams and is practically an application of the cantilever principle to shipbuilding. Instead of the beams crossing over the hold, stout stanchions are raised nearly flush with the sides of the vessel and, when these have been brought to a certain height, equally strong diagonal joists are raised from them to the upper decks, thus forming a bracket or cantilever at each side. The stanchions and joists closely follow the lines of a turret ship and thus take up little room. The advantages of this design are that the vessel has a lighter draft in proportion to dead weight, while at the same time it gives greater freedom for shipping long and bulky goods.

Propeller design with the turbine is more difficult than with the reciprocating engine, because the conditions are entirely different from those which have hitherto obtained, and there is so little experience with propellers running at speeds of over 1,000 revolutions a minute in the case of small ships, or at 500 to 750 in the case of large ones. The Cunarders' propellers, it is understood, are to be limited to 180 revolutions per minute. For it must be remarked that in spite of the fact that we now have very clear and logical rules for the design of propellers under existing circumstances logically worked out, nevertheless these rules and formulæ came after the experience rather than before. This matter, however, can undoubtedly be cared for, and when more experience has been gained the design of propellers will be as easy for existing conditions.

Of the various materials used for lagging, magnesia may be considered one of the best and most practicable for use in connection with locomotive service. This composition is of a strict neutrality, and composed of inert mineral matter that will exert no chemical action, corrosive or otherwise, upon any metallic surface with which it may be brought in contact. It will remain unaltered under all conditions of heat and moisture which confront the coverings of locomotive boilers. It has qualities of lightness, firmness, structural strength and porosity, the latter quality especially, upon which depends largely the efficiency as a non-heat-conductor; and this quality being most pronounced in magnesia, it affords the greatest resistance to the transmission of heat. It can also be molded into sectional blocks of any form and size desired for ready application and removal.

As a superintendent of motive power a generation ago, a good mechanic sufficed. He was an old locomotive runner, or a shop foreman promoted, and he was usually called "master mechanic." It was but a short and comparatively easy step from the locomotive, or the shop, to the position of head of the department. In the present day of record-making, of heavy locomotives, large-capacity cars, strenuous operation, large shops and intricate labor problems, such a step is now a hopelessly long one. The sort of man who successfully directed the department twenty-five years ago would find his ability overtaxed to properly manage a single busy roundhouse to-day. A different kind of ability is now required to direct the mechanical department of a single progressive road, and as great roads combine into systems still another new kind of a man will be needed. He must soon be ready, for his work is even now waiting. Is this appreciated? Are the men being prepared?

An interesting new machine has been installed at the yards of the well-known British shipbuilding firm of Messrs. Beardmore & Co., Ltd., for bending ship beams. The general practice of rounding deck beams is by means of powerful hydraulic pressure applied section by section to the member for which the camber is required. With this new appliance, however, the beams are bent and completed with the greatest rapidity notwithstanding their dimensions or caliber. The machine consists essentially of rollers which are set vertically and can be made to suit any degree of camber or curvature. These rollers operate upon the steel beam just as it arrives from the steel-works. It passes quickly through the machine, and is then ready for working into the hull of the ship for which it is intended, the beam being quite completed when it leaves the bender. Any type of beam can be handled, from the heaviest to the lightest, and angle or T-shape, with equal facility. The apparatus is being utilized for cambering the T-beams, 12 inches deep, required for the British battleship "Agamemnon" now in course of construction by this firm.