

## SCIENTIFIC AMERICAN

ESTABLISHED 1845

MUNN &amp; CO. - Editors and Proprietors

Published Weekly at

No. 361 Broadway, New York

## TERMS TO SUBSCRIBERS

One copy, one year, for the United States, Canada, or Mexico.....\$3.00  
 One copy, one year, to any foreign country, postage prepaid, \$3.16. 5d. 4.00

## THE SCIENTIFIC AMERICAN PUBLICATIONS

Scientific American (Established 1845).....\$3.00 a year  
 Scientific American Supplement (Established 1876)..... 5.00  
 American Homes and Gardens..... 3.00  
 Scientific American Export Edition (Established 1878)..... 3.00  
 The combined subscription rates and rates to foreign countries will be furnished upon application.  
 Remit by postal or express money order, or by bank draft or check.  
 MUNN & CO., 361 Broadway, New York.

NEW YORK, SATURDAY, FEBRUARY 23, 1907.

The Editor is always glad to receive for examination illustrated articles on subjects of timely interest. If the photographs are sharp, the articles short, and the facts authentic, the contributions will receive special attention. Accepted articles will be paid for at regular space rates.

## THE "LARCHMONT" DISASTER.

The awful disaster which occurred on the evening of Lincoln's birthday off Block Island, and resulted in the sinking of the steamer "Larchmont" with a loss estimated at not less than 150 souls, is not only one of the most tragic events in the history of navigation of Long Island Sound, but there are disquieting elements connected with the event, which may well shake the faith of the public in the safety of the older boats, and in the skill and heroism of the navigation and seamanship in these famous and much-traveled waters. The conditions under which the collision occurred, so far as they can be gathered from published reports, are altogether bewildering. Here, in comparatively sheltered waters, on a clear and starlit night, in spite of the fact that the captains of the two vessels, one a three-masted schooner, the other a side-wheel steamer, distinctly saw each other's lights when they were fully half a mile away—in spite of all this and the further fact that they had deep water and ample sea room, we find these two vessels so handled as to crash one into the other at full speed, and with all the appearance of deliberation. It is useless to speculate on the facts as here presented, and for an explanation we must be content to await the searching inquiry which must follow. It is certain, however, that the sailing vessel had the full right of way, and that it was the duty of the steamer to avoid her. The fact that the schooner rammed the steamer bow on would seem to indicate that the captain of the latter had made the too-frequent mistake of supposing that the superior speed of his ship would enable him to cross the bows of the sailing vessel.

Another feature which is disquieting, and certainly does not ring true with the best traditions of the sea, is the fact that so large a number of the officers and crew were saved, or at least got away in boats, while so many of the passengers, among them several women, went down on the vessel. In the presence of such a fact one's mind harks back to that fine old legend of the sea to the effect that the captain is always the last to leave his ship. On this point also will the public look for further and very definite information; and we can only hope that facts may be developed at the investigation which will give this phase of the question a more wholesome complexion than it wears at present. That the "Larchmont" should have foundered so rapidly after receiving the blow of the schooner proves once more how utterly unfit are some of these older steamers on the Sound and in the sheltered waters of our harbors and rivers for the safe carrying of passengers. It is certain either that there was no safety bulkhead construction in the hull of the "Larchmont," or that, if it existed, it was of a flimsy and practically worthless character. According to one account, the ship had transverse bulkheads built up of six-inch timber, but this, unless it was very heavily braced, would be altogether inadequate to withstand the water pressure, especially when the water in the hold was surging, as it would be, against the bulkheads with a momentum due to the rolling and pitching of the vessel. As a matter of fact, this question of non- or inefficiently-bulkheaded passenger vessels, whether for harbor or Sound travel, is one of wide significance, and fraught with untold danger to the passenger. If the traveling public knew how many of these vessels would prove, in case of collision, to be mere death traps, the shrinkage of travel upon them would be such as to compel the substitution of more modern and safer ships. If it shall result in stringent legislation to debar all but thoroughly well-bulkheaded vessels from the passenger-carrying trade, the loss of life on the "Larchmont" will not have been altogether in vain.

## TREND OF MOTOR-BOAT DEVELOPMENT.

One of the most prominent facts connected with the present development of the motor boat is the waning interest in craft of the lightly-constructed and over-powered racing type, and the growing popularity of the more stanchly-built, roomy, seagoing boat of moderate power, with ability to make an extended cruise without replenishing the fuel supply. The decline in popularity of the type which is built exclusively for racing has been gradual, but decided, and particularly so during the past two years. It is unquestionable that there is a fascination about mere speed, which appeals strongly to the public mind; and in the earlier development of any of the high-speed devices which have figured prominently in the great field of sport and pastime, the accomplishment of high speed has appealed to the imagination and stimulated the efforts of designers and builders, largely to the exclusion of other and more valuable considerations. In the later years of the past, and the opening of the present, century this has been particularly true, as witness the construction and development of the yacht, the bicycle, and the automobile. But because of the great cost and limited usefulness of all mechanical creations which sacrifice every other consideration to that of high speed, the cost is so exceedingly high as to place them within reach only of men of considerable wealth and leisure. History shows us that when the possibilities of speed have been pretty well exhausted there is an inevitable reaction in favor of more moderate speeds and more durable and reasonable construction. The "speed mania," however, has always left behind it a valuable legacy in the way of useful knowledge as to the strength of materials, and as to just how far bulk and weight may be cut down without any sacrifice of absolutely essential strength.

The motor-boat industry may be said to have now passed from the first to the second and more important stage of its development, and although the high-speed races of the last year or two have shown that there still exists some enthusiasm in this form of sport, the number of extreme racing craft that is being built on the orders of private yachtsmen is relatively diminishing, while the orders for stancher vessels, of the fast and moderate-speed cruiser type, are increasing at a really remarkable rate. To-day not many of the extreme racing craft are built on private orders, the predisposing motive for such of these craft as are constructed being found in the desire of the makers and builders of engines and hulls to demonstrate the high quality of their product, by exhibiting it under the severe conditions necessary in the construction of a successful racing machine.

The popular type of motor-boat to-day is a moderate-powered cruiser, provided with a roomy cockpit and a substantial cabin with ample headroom, one or more staterooms, abundant lockers, a toilet, galley, and pantry, and all the accessories necessary for comfort on a cruise of several days' duration. Of course, the meeting of these requirements has necessitated an increase in size, and particularly in boats intended for deep-sea cruising, or for an extended trip in the more sheltered waters of Long Island Sound, or the extensive harbors of the South. Hence, the dimensions of a modern cruiser will be represented by a vessel from 30 to 60 feet in length, and furnished with engines of from 20 to 100 horse-power.

Perhaps the most potent influence in the development of this type of craft has been the institution of the long-distance races, which have grown in frequency and popularity during the past few years. Confined at first to courses laid through the Sound from New York to some point on the Massachusetts coast, these races have developed fast cruising boats, of such power and excellent sea-going qualities, that in the present year two important races are being run over ocean courses; one from Miami, Fla., to Nassau, a distance of 190 miles, and the other from New York to Bermuda. The latter is, of course, the more formidable undertaking, and the restrictions which have been laid down regarding the size and construction of the contesting boats have been so well drawn that there is no reason why all the contestants should not make the 700-mile trip in safety.

Although the flimsy racing craft has waned in popularity relatively to the moderate-powered cruiser, there will always be a demand for high-speed yachts, capable of averaging about 18 knots an hour, for what is coming to be known as "ferry" service, or the work of carrying business men to and fro between New York or other maritime cities and their distant summer residences. These craft run in length from 75 to 100 feet or over, and carry engines capable of giving them a sustained speed in sheltered waters of from 16 to 20 knots an hour. They are provided with ample deck space and spacious cabin accommodation, while frequently they will have a dining room and galley sufficient to enable the owner and guests to dine aboard if they should so wish.

The question has been asked as to whether the gasoline engine will be applied to ocean-going yachts of a size capable of making the transatlantic passage.

One of our leading naval architects has recently expressed the opinion that in the present condition of the art this is not practicable, because of the prohibitive cost of the fuel. Moreover, it is undeniable that many prospective yacht owners would be deterred by considerations of the supposed risk attaching to the storage of large supplies of gasoline; although, as a matter of fact, by the use of proper precaution, the danger may be so greatly reduced as to be practically negligible. It is likely that under the stimulus afforded by the introduction of free alcohol, the designers of internal-combustion engines will succeed in designing motors so well suited to the use of this fuel, that it will ultimately prove to be more economical than gasoline; and there is not the slightest doubt but that with the more extended use of alcohol the price must ultimately come down to a point which will render it as economical as gasoline. When that point is reached, the added advantages of safety and absence of odor, etc., will render it such an ideal fuel that we may look for its extended use in the larger sizes of yachts, even in those capable of making the transatlantic passage.

Furthermore, the internal-combustion engine has several collateral advantages which must commend it strongly to the prospective yacht owner. By saving the expensive installation of boilers for a steam plant, the first cost of a gasoline or alcohol plant will be considerably less; and there will be a decided saving in the important matter of space. Also, for the same bunker or tank capacity, the steaming radius, or sailing radius, will be much larger than where steam power is used; while the comfort of the owner will be further assured by the absence of smoke and ashes, and the inevitable dust and disfigurement attendant upon coaling. Already, the way for the appearance of the large ocean-going gas-driven yacht has been prepared by the successful operation of the large auxiliary schooners, in some of which gasoline engines of considerable power have been installed and successfully operated.

## GYROSCOPIC ACTION OF MARINE TURBINES.

We are most of us familiar with that ingenious device for preventing, or rather modifying, the rolling of ships, which consists of a heavy gyroscope, placed with its axis of rotation transverse to the longitudinal axis of the ship. The machine works on the principle that, to change the plane of rotation of a swiftly-rotating body by tilting the axis, requires an amount of effort which is determined by the weight and rotative speed of that body. The anti-rolling gyroscope, rotating in a plane at right angles to the direction in which movements of rolling of the ship take place, tends to resist those motions and modify their extent.

Simultaneously with the appearance of this device, and possibly suggested by it, there has arisen a discussion of the action upon turbine-driven vessels of the heavy and swiftly-rotating rotors of the steam turbine; for these, in addition to their proper work of driving the ship, undoubtedly act, because of their weight and high speed of rotation, with a powerful gyroscopic effect upon the pitching motion of the vessel. In this case, however, the gyroscopic action is felt in the direction of the longitudinal axis of the ship, and not, as in the case of the anti-rolling device, transversely thereto. Moreover, just as the anti-rolling gyroscope tends to modify rolling, so the gyroscopic effect of the heavy rotors of the steam turbines must tend to modify pitching, or vertical movement in a plane passing through the keel. Whatever modifying effect the device above referred to may have upon the rolling of a vessel, it is certain that the gyroscopic action of the turbine rotors can have none, or practically no effect upon the pitching. But since the gyroscopic resistance of the heavy rotors to a change of position of their plane of rotation is present and is considerable in quantity, it follows that they must exert a stress of no little amount upon the framing of the vessel itself. The proportion which these stresses will bear to the normal stresses for which the hull was designed will be largest in the case where turbines of great weight and high speed of rotation are carried in a long, shallow, and lightly-constructed hull, as in the case of a high-speed turbine torpedo-boat destroyer. These stresses would act very materially to increase the bending stresses which occur when a torpedo boat is being driven rapidly across the seas. In such a vessel they would become so large as to call for an increase in the scantling of the vessel, beyond that which would be necessary were reciprocating instead of turbine engines installed.

In the course of a valuable analysis of this action of a steam turbine, Mr. A. H. Gibson, of the Institute of Civil Engineers of Great Britain, some months ago called attention to the fact that the "Cobra," one of two high-powered turbine destroyers, built several years ago for the British government, and capable of steaming 36 knots an hour, broke her back and went down during a gale in the North Sea. This destroyer was built of the same scantlings as other destroyers in the British and Japanese navies, the difference be-