

The fact that the most important section of New York city is located on a long and narrow island, flanked by broad and deep rivers and waterways, is largely .responsible for the present activity in the construction of subways and tunnels. In the earlier days of the history of the city, passenger traffic was taken care of by lines of surface cars and ferries. These were supplemented, about thirty years

ago, by the construction of four lines of elevated railways running the entire length of Manhattan Island. The Brooklyn Bridge, opened some five years later, afforded a greatly needed relief to the rapidly growing travel between New-York and Brooklyn. The next step in the development of facilities was the electrification of the surface roads, which was followed in its turn by a change from steam to electric traction on the elevated system. Concurrently with these last developments, the construction of three additional bridges of unusually large capacity was commenced across the East River. One of these, the Williamsburg Bridge, was opened some four or five years ago; the Blackwell's Island Bridge will be opened as soon as the necessary changes to render it usable have been made; and the Manhattan Bridge should be thrown open to the public within the next two years.

In spite of the greatly increased accommodations provided by these enterprises, it became evident, even before they were completed, that the rapid growth of the city, and the even more rapid growth of travel, would necessitate the provision of additional means of transportation; and that any future roads which might be built must be placed below street level. It was realized, moreover, that the construction of bridges across the Hudson River was too difficult and costly for the city to depend upon any relief in this direction. After a protracted discussion of its feasibility, the question of constructing a subway system was submitted to the public vote, and a decision was given in its favor. A Rapid Transit Commission, consisting of leading men of affairs in the city, was formed and under their very able direction a comprehensive scheme of subways was laid out, and the portion of it which is now in operation constructed. The first section to be completed extends from the City

Hall, New York, to Kingsbridge beyond the Harlem River, with a branch running from Ninety-sixth Street northeasterly to the Bronx. From City Hall Park to Ninety-sixth Street there are four tracks, the two outer tracks for local service, and the two inner tracks for express trains. North of Ninety-sixth Street, on the westerly branch of the road, the Subway contains, first three tracks and then two; the easterly branch from Ninety-sixth Street contains two tracks. Subsequently, a two-track Subway was constructed from City Hall Park to Flatbush Avenue, Brooklyn, the route lying below Broadway to the Battery and then under the East River in two tube tunnels. The section of the road from City Hall northward was opened in 1904, and the section from City Hall to Flatbush Avenue in Brooklyn, in 1907. The contract for the first section was let for \$35,000,000; the equipment, power station, nurchase of the real estate. etc., cost an additional \$12,000,000, bringing the total cost up to \$47,000,000. From the very first the Subway has proved an unqualified success. The express trains on certain sections of the line reach a speed of 45 miles an hour between stations, and run at an average speed. including stops, of between

Scientific American

25 and 30 miles an hour, the average depending upon the delay at stations. Express trains are made up of eight cars, of which five are motor cars. Local trains, which have a speed of about 16 miles an hour, including stops, are made up of six cars, four of which are motors. Before the opening of the line, it was hoped by the most optimistic that the system would develop a maximum capacity of from 375,000 to 400,000 passengers a day. As a matter of fact, on holidays and other special occasions, over 600,000 have been carried. The opening of the Brooklyn tunnel afforded greatl**f** needed relief to the Brooklyn Bridge. It be-



Showing projecting roof for protecting workmen while blasting out a projecting reef of rocks.

SECTIONAL VIEW OF HUDSON RIVER SHIELD.



December 5, 1908.

came immediately popular, and the city, as soon as funds are available, will build a branch line through southern Brooklyn to Coney Island. At present, there is under construction a loop-line which will connect the Manhattan terminals of the Williamsburg and Brooklyn bridges. In the first section to be completed the tunnels were built chiefly by the cut-and-cover method, and, except where they pass through rock, they are built of steel I-beams and structural shapes imbedded in concrete. For the later construction reinforced concrete was used. In view of the speed and rapidity of the service and the enormous volume of

traffic handled, the New York Subway must be regarded as the most successful, as it is the largest and most important underground railway in the world. It is operated on the thirdrail system.

To provide the necessary power for operating the Subway, which, as we have noted, has carried over 600,000 passengers in a single day, has called for the construction of what is to-day the largest power station of its kind in the world. The plant, which is located at Fifty-ninth Street, is housed in a building 200 feet in width by '690 feet in length, which is divided centrally by a wall separating the engine room from the boiler room and coal bins. These coal bins, which are located immediately below the roof and above the boiler room, have the enormous capacity of 25,000 tons of coal. The coal is fed by gravity to the hoppers of the mechanical stokers, from which it is automatically fed to the furnaces.

One who has never visited a plant of this character can have no idea of the imposing appearance presented by the long line of engines and generators in the engine room. In the present case the equipment consists of nine reciprocating engines, the largest of their type ever built, and three steam turbines. The reciprocating engines are of the well-known type developed by the Allis-Chalmers Company of Milwaukee, Wis., and they are superb specimens of the engine builder's art. Because of the advent of the steam turbine with its peculiar fitness as a drive for large generator units, it is probable that these engines will stand as the "last word" in the history of the development of the reciprocating engine. When standing in the gallery at the power station and looking down the long perspective of the engine room, one cannot but feel that, whatever advantages of an economical kind the steam turbine has introduced, it has robbed the engine room

of much of its spectacular features. New York city was already familiar with the Allis-Chalmers engines of this type because of their installation in that other great power plant, at Seventy-fourth Street and the East River, which provides power for the operation of the elevated roads. The Fifty-ninth Street engines are generally similar to these; but they include certain improvements in valve gear and in some minor details. The engines are rated at 8,000 horse-power, with a maximum overload of 12.-000. Each consists of two compound condensing engines, one at each end of the crankshaft, with the alternator carried at the center of the shaft between the engines. The 44-inch high-pressure cylinder is horizontally, and placed the 88-inch , low-pressure cylinder vertically, with the two connecting rods of each engine taking hold of a common crankpin. The stroke is 60 inches. The two cranks are set at an angle of 135 degrees to each other, an arrangement which gives eight impulses to the shaft at equal intervals in each revolution. The crankshaft has a diameter of 37 inches at the center and 34 inches at the bearings. The crankpins measure 18 inches by 18 inches, and the crosshead nins are 12 x 12 inches. The weight of

These caissons, 45 feet wide, 45 feet deep, and 10614 feet long, the largest ever constructed, are built of reinforced concrete. They provide a double-deck system which eliminates dangerous crossovers between trains running in opposite directions.

HUGE DOUBLE-DECK CAISSONS AT JUNCTIONS OF HUDSON RIVER TUBES WITH THOSE ALONG THE JERSEY SHORE.

December 5, 1908.

each pair of engines is 720 tons. The steam pressure is 175 pounds, and the steam consumption at the rating of 8.000 horse-power is about 13 pounds per horsepower per hour. At the far end of the station are three Westinghouse turbines of 1,250 kilowatts rating. The maximum horse-

power of this station, under overload, is about 130,-000 horse-power.

Next in importance to the Rapid Transit Subway, which, it should be mentioned, is owned by the city, is an elaborate system of subways and tunnels, constructed by an independent concern known as the Hudson Companies, to afford direct rail communication between Jersey City and New York. For the beginnings of this enterprise we have to go back twenty-five years, to the time when Mr. De Witt Clinton Haskin, one of the active spirits in the building of the Union Pacific Railway, commenced the construction of a tunnel for the use of steam trains. The scheme met

Scientific American

in New Jersey, and enables passengers to transfer, under cover, to trains which carry them direct to the shopping, hotel, and financial districts on Manhattan Island.

The system consists in Jersey City of a two-track

at Ninth Street to connect with the Rapid Transit Subway. Below the Pennsylvania station, at a depth of 80 feet, there has been constructed a large station. access to which will be had by elevators from the Pennsylvania terminal. From this station twin tubes

This power station, the largest for traction purposes in the world, is 300 feet wide by 790 feet long It contains non reciprocating Allis-Chalmers engines of 12,000 overload horse-power and three steam turbines of 1,800 horse-power. 1

THE NEW YORK BAPID TRANSIT SUBWAY POWER STATION AT FIFTY-NINTH STREET.

with many difficulties and disasters. It was abandoned in 1882; started again in 1890 by an English company; and ultimately was taken in hand by a corporation known as the New York and New Jersey Railroad Company; which, ultimately, under the successive names of the Hudson Companies and the Hudson and Manhattan Railway Company, succeeded in pushing the great scheme through to completion. The credit for this enterprise is chiefly due to President McAdoo. The great value of the road lies in the fact that it intersects the trunk roads which have their termini

road, placed in two separate 15-foot tubes, which extends from the Delaware, Lackawanna & Western Railroad terminal south to the terminal station of the Pennsylvania Railroad. Ultimately, it will be carried down to connect with the terminal of the Central Railroad of New Jersey. At Fifteenth Street it is intersected by twin tunnels which pass beneath the Hudson, and are carried up Sixth Avenue to Twenty-third Street, and ultimately will be extended to Thirty-third, where they will be in touch with the Pennsylvania Railroad terminal. A branch line will be constructed

line them entirely with concrete. After they had been driven, however, it was found that they presented such absolute stability as to render the use of concrete unnecessary. Instrumental observations have failed to show any signs of settlement; and, as far as their stability is concerned, the tubes may be pronounced a decided success. Records for rapidity in driving were broken during the prosecution of the work, the rapid advance being due to the adoption of a method altogether novel and bold. In previous work with (Continued on page 414.)





extend below the

Hudson River

and Manhattan

Island to a large terminal station

between Cort-

landt and Fulton

streets, above

which has been

constructed the

large terminal of-

fice building to which reference

is made elsewhere

Because of the difficulties encoun-

tered .in passing

beneath the Hud-

son River, and

the novel meth-

ods which were

adopted to meet

them, the engi-

neering features

of this system are

particularly interesting. All four

tunnels were driven by the

shield method,

which is too well

known to call for

any description at

the present time. The tunnels are

15 feet in diam-

eter internally,

and it was originally intended to

in this issue.



If we include the footwalk across the elevated tracks, there are six separate levels for travel shown in the above view of conditions as they will ultimately exist at 33d Street.

SECTIONAL VIEW SHOWING HOW NEW YORK USES BOTH ELEVATED, SURFACE, AND TUNNEL ROADS IN PROVIDING FOR ITS EVER-GROWING TRAFFIC.

External diameter, 23 feet; internal diameter, 19 feet. Driven by the shield method. Maximum rate of advance through mud and silt, 3714 feet per day.

THE PENNSYLVANIA RAILROAD TUNNEL TUBES BELOW THE HUDSON RIVER.

Scientific American

DECEMBER 5, 1908.



THE CATSKILL WATER SUPPLY. (Continued from page 396.) in height and 171/2 feet wide, which will be built partly by the cut-and-cover method and partly in tunnel. It will extend to the westerly bank of the Hudson River, which will be reached at a point between Cornwall and West Point. Originally it was the intention to carry the aqueduct below the Hudson River at New Hamburg; but the preliminary borings at this and other sites proved that it would be difficult to find a rock sufficiently clean from fissures and other imperfections. An examination of various sites by geologists led to the ultimate selection of the crossing near Cornwall. where it was believed that a thoroughly sound and suitable rock would be found at a depth not too prohibitive. The aqueduct passes through the mountains and reaches the westerly shore of the Hudson River at an elevation of 400 feet above tide level. Here a vertical shaft will be sunk to a depth of probably not less than 700 feet below the river surface, or 1.100 feet below the level of the aqueduct. In the bottom of the shaft a tunnel will be driven horizontally beneath the river to connect with another vertical shaft of practically equal depth on the easterly bank of the river. From this point it will be constructed through the mountains until it reaches the new Croton reservoir. Here connections will be made to enable the water to be drawn directly from the Ashokan reservoir into the Croton reservoir, with a view to augmenting the Croton supply until such time as the aqueduct from Ashokan to New York city shall have been completed. From the Croton reservoir the aqueduct will be continued south to Kensico reservoir, which will be enlarged to include Rye Pond and will form an auxiliary storage reservoir at an elevation of 355 feet above mean tide, capable of containing 25 billion gallons, or sufficient to supply the city at the rate of 500 million gallons per day for a period of fifty days. About four miles south of Kensico, at Scarsdale, there will be built a large fil-

tering plant, and at Hillview, six miles to the south of this, will be another storage reservoir. With these two auxiliaries or emergency reservoirs provided, the city will be secured against any sudden interruption of its supply through failure of the 69 miles of aqueduct lying to the north of them. By the construction of a tunnel of 200 million gallons daily capacity below the East River, Brooklyn and Staten Island will be provided with a supply of 100 million gallons daily, and this aqueduct will terminate in a large reservoir to be constructed in Forest Park. From the point where this tunnel reaches the shores of Long Island, a line of 20 million gallons capacity will be built through Brooklyn and below the Narrows for the supply of Staten Island.

TUNNELS AND SUBWAYS. (Continued from page 405.)

the shield it was customary to allow the silt, etc., to pass into the interior of the tunnel as the shield was advanced, and take it away in cars. The Hudson Companies' engineers decided, however, to try the plan of pushing the shield ahead



Had You Thought of Giving This **Book as a Christmas Present?**



The Most Remarkable Book of the Age! A Wonderful and Extraordinary Book! That's the only way HEART THROBS can be described. The usual book of selections, mark you, is made up of things that a few "high-browed" scholars have thought that the people *ought* to like. But the selections in HEART THROBS are those that the people themselves say they actually do like. Do you see the difference? Do you see how this makes HEART THROBS an absolutely unique book, one that appeals to people in every walk of life.

Nothing Could Speak More Eloquently of the Affection of the Giver Than Heart Throbs.

Nothing like this book ever has appeared before in any language.

Men have written things that appealed to them, and perhaps these writings have appealed to the peo-ple and perhaps they have not.

Others have selected things that appealed to them, and perhaps these writings have appealed to the people and perhaps they have not.

But this book was made up by the people themselves !

In the truest sense HEART THROBS is a book of the people, by the people and for the people. In response to an offer of \$10,000

in prizes, more than 50,000 of what Lincoln called "the plain people of America" sent to the publishers selections of poems, stories and anecdotes that had comforted them in affliction, cheered them in adversity, inspired them with nobler ideas of living, gave them new heart and courage to face the battle of life, or brightened a gloomy day with wholesome good cheer, humor, wit and hearty laughter, and it is these prize selections that make up HEART THROBS, the book.

Just think of it ! Here are hundreds of selections that, beyond question, are dear to the hearts of thousands of the best people whom Lincoln loved. Often clipped or culled by toil-stiffened fingers and age trembling hands, yellow with years of preservation, soiled by frequent handling, stained with tears, scented with lavender, rose and orris these contributions came in, each self-proven to be a veritable heart's treasure-trove. Heart throbs of happiness! Heart throbs of courage ! Heart throbs of righteousness! Heart throbs of tender, beautiful and exquisite sentiment-they are all here for you.



compris atest desirable features in gas en-gineering. 2½ to 15 horse power. by displacement; that is to say, they ROYAL EQUIPMENT CO. 145 Housatonic Ave., Bridgeport, Conn

simple, compact motor of strong

Wizard Repeating 🔚 LIOUID PISTOL

Will step the most virians dog (or man) wilhout permanent in jury. Per-tetly sate to carry without danger of leak age. Fires and recharges by pulling mel coding. All dealers, or by mail South & Steps The South & Steps With Pistol, 35c, Moneyorderor U.S. stamps. No coins. PIRKEN SOUTH SO PARKER, S'TEARNS & CO., 226 South Street, Dept. G, New York



closed the doors in the front face of the shield, and tried the experiment of pushing the shield bodily through the silt, Nickel-plt causing the latter to flow over and around the tube by displacement. The plan succeeded beyond expectations, and the later work was all done by this method. One of our illustrations shows the way in which the engineers overcame a serious obstacle, in the shape of a ledge of ALL THE NEWS OF rock, which projected from the river bot-MOTION PICTURES tom and covered the lower half of the Lecture and song slides every week in the leading journal of the trade. path through which the tunnel was to

be driven. To meet the emergency, a Best Medium for Advertisers heavy iron working roof was built in ICc per copy, \$2 per year. MOVING PICTURE WORLD front of the shield, and under this the 125 E. 23d St., New York City | workmen were enabled to set up their Nearly 500 pages, Handsomely bound in \$1.50 cloth, gold, illuminated cover, postpaid,

Edition de luxe, full Morocco and gold \$3.00

At All Bookstores or Direct from Publishers, Using the Coupon

Money Returned if Not Entirely Satisfactory CHAPPLE PUBLISHING CO., BOSTON, MASS.

GENTLEMEN: Enclosed find \$..... for which please send me "Heart Throbs."

Name Address It is a great and good book, and

a wonderful book. It is a book for you to give to every friend and loved one, especially those who need to be comforted and inspired anew.

And it is a book for you yourself to keep by you always.

Most books you cast aside as soon as you fnish reading them—they can give you pleasure for only a short while. But this is a book that will mean more and more to you as the years go by. It will be a sympathetic friend and kind helper whenever the skies become overcast.

Scientific American

DECEMBER 5, 1908.



VOLNEY W. MASON & COMPANY, Inc. Providence, R. I., U.S. A.

wide, 45 feet deep, and 1061/2 feet long, bigger than anything of the kind heretofore constructed, are built of reinforced concrete. The walls were first sunk to the desired depth, the necessary openings being left for connection with the tunnel tubes. Then the floor, the intermediate deck, and the roof were built, leaving the huge box-like structure ready for connection with the tubes and the laying of the tracks. The construction is clearly shown in our sectional view of the same. The plans of the Pennsylvania Railroad Company for establishing a large STORM SHOE terminal station for their system in the center of Manhattan Island, and connecting it with their trunk line to the West and the extensive system of roads of the

Long Island Railroad Company to the East, has involved the construction of subaqueous tunnels of even greater importance than those of the Hudson Companies above referred to. Access to Manhattan Island is obtained by two single-Soc. can Waterpoor-ing, 35c. Wm.N. Gokey Shoe Co. JAMESTOWN, N. Y. Son Companies' tunnels, those of the Pennsylvania Company are much larger, Paradox Gas Engine heavier, and more expensive to build. It was considered at the very outset that special strength and solidity would be necessary to safely carry the heavy transcontinental trains of Pullman cars. Accordingly, the tubes were made of an external diameter of 23 feet; and the segments were cast with an unusually heavy shell and deep flanges amply provided with bracing. The interior of the tube is lined with no less than two feet of concrete; and, in addition to this, the concrete is carried up parallel with the sides of the cars to the height of the window sills, where a broad shelf, wide enough to permit the passengers to walk in case of a breakdown, is provided. This shelf is formed integrally with the concrete lining of the tunnel. In the preliminary investigation of the problem, it was considered possible that the impact of the heavy trains upon the floor of the tunnel would tend to cause some settlement of the tubes in the silt in which they had

GIFTS **Diamonds** Credit For Christmas Presents

OFTIS Old Reliable, Original Diamond and Watch Credit House anss.a ce. Bept. M 160, 92 State St., Chicage, III



Hon, William H. Taft

written by Dr. E. E. Slosson after a personal tour of inspection. Also a series of articles by John Barrett, Director of the Bureau of American Republics on Business Opportunities in South America.



The Sixtieth Anniversary

THE INDEPENDENT was founded in 1848 and our issue for December 10, 1908, celebrates our Sixtieth Anniversary. Editors and friends contribute to tell the dramatic and varied history of the magazine in that number.

Character of The Independent

Count Leo Tolstoy



THE INDEPENDENT is an illustrated WEEKLY magazine. Every issue contains an eight-page summary of the news of the week thruout the world, followed by illustrated articles and editorials on subjects of current interest. The contributors, in addition to those whose pictures here appear, include, among others, Luther Burbank, Alfred Austin, Bernard Shaw, Charles M. Sheldon, Andrew Carnegie and Edward Everett Hale. To read THE INDEPENDENT is to keep informed of the best that is thought and done the world over !

Special Offer to New Subscribers

price, we will enter your name on our list fourteen months

from the time your order is received. Remember that THE

INDEPENDENT comes fifty-two times a year, and in this way.

you will get over sixty copies for about three cents each.

On receipt of two dollars, the regular yearly subscription

Hon. Justin McCarthy

Hon. James Bryce Copyright 1904 E. Chickering

THE INDEPENDENT **130'FULTON STREET, NEW YORK**

The History of Elevators

Tells the story of the phenomenal development of Manhattan Island. The upper section of the double page picture in the center of this magazine shows the types of buildings used before commercial architecture. had been appreciably affected by the elevator, there being then, with less than 1,000 elevators in the city, no high speed lifts for both the passenger and freight service such as characterize the elevator plants of today, with over 21,000 elevators in service in the borough. The contrast between the four and five story buildings of the earlier period with the skyscrapers of today is striking, both architecturally and as an example of the remarkable results that have been accomplished, for modern commercialism, in one line of engineering since the pioneer efforts of Elisha G. Otis towards the present end.

OTIS ELEVATOR COMPANY

December 5, 1908.



been driven; and, as a provision against this, the original plans provided for sinking hollow cast-iron piles through the floor of the tunnel to bedrock, and laying the tracks upon a system of longitudinal girders within the tunnel, which would serve to transfer the trainloads directly to the piles, and so relieve the tubes themselves from all stresses due to live loads. These piles were to be 27 inches in outside diameter, with a shell 11/2 inches in thickness. After the tubes had been driven, the satisfactory behavior of the Hudson Companies' tubes, which were built without any pile supports and have failed to show any settlement after many months of operation, convinced the engineers that the Pennsylvania tubes would be sufficiently stable without the supporting piles; and, consequently, this feature has been omitted. The tubes were driven by the shield method, and the work was pushed through without developing any problems of a serious or unusual character. The same may be said of the building of the tunnels across Manhattan Island, where the work consisted for the most part of straight rock excavation. With a view to accommodating the heavy future increase in suburban traffic to Long Island, the company determined to build four separate tubes beneath the East River. Because of the difficult character of the material encountered, the work on these tunnels has been somewhat protracted, many blowouts having developed, necessitating the construction of a false bottom to the river above the heading of the tubes by dumping in many thousand cubic yards of material from scows. All obstacles, however, have been overcome, and the whole of this vast tunnel system will have been completed before another twelvemonth has gone by. The total length of the run in tunnel from the portal in Jersey City to the portal on Long Island is 5.3 miles. The total length of single-track tube tunnels under the two rivers is 6.8 miles, and the total length of single-track tunnel under the land is also 6.8 miles. The total length of track in tunnels exclusive of the yard tracks and the station will be 16½ miles. Contemporaneously with the execution of the above work, the financial interests which are responsible for the operation of New York city's subways were engaged in constructing a twin-tube tunnel below Forty-second Street and the East River

Forty-second Street and the East River from the Grand Central Station, Manhattan, to Long Island City. The tubes are similar in dimensions and general construction to those which form the connecting link at the Battery between the Manhattan and Brooklyn Subway systems: The tunnel was built under an old franchise granted many years ago, and it has been offered for purchase by the city at a price of \$7,000,000.



(Continued from page 412.) trolley system consists, for each track, of two steel messenger wires below which is carried, by means of triangles of steel tubing, the %-inch copper trolley wire. In the early days of the operation of the system, difficulties developed, due to the hammering of the collector shoes as they passed the points of suspension of the wire at the apex of the triangles. This was cleverly overcome by suspending a second wire below the first by means of clips attached to the upper wire midway between its points of suspension from the triangle. The arrangement has provided a system which combines great stiffness with uniform flexibility of the trolley wires; and the troubles of sparking, wear, and breakage have been practically eliminated. The electric locomotives, which because of their short wheel base were found to sway heavily at high speed, have later been provided with end trucks of ingenious design, which have completely eliminated the trouble, and rendered these locomotives as steady in their running as a Pullman car. The whole of this work was done by the



Chicago, Ill.; Cincinnati, Ohio; St. Louis. Mo.; San Francisco, Cal.; Seattle, Wash.; Portland, Oregon

> Agencies in all principal cities of America and foreign countries

America's Greatest Safe and Vault Builders

Is Your Patent For Sale?

or do you wish to enlist capital or obtain a partner? If so, we have something interesting to say to you whereby you should be able to reach the proper parties at small expense. For full information address

Business Dept. Scientific American 361 Broadway, New York City Our large Engineering Department is at your disposal for special designs and specifications free of cost.

70 YEARS IN BUSINESS

Buildersof over 470,000 Fireproof Safes Builders of over 6,000 Bank Vaults



From a photograph owned by the Otis Elevator Co.

LOWER NEW YORK AS IT APPEARED IN 1875. REPRODUCED FROM A PHOTOGRAPH TAKEN FROM



Copyright 1908 by George P. Hall & Son.

SKYLINE OF LOWER NEW YORK AS IT APPEARS TO-DAY WHEN VIEWED FROM

American



THE TOP OF THE BROOKLYN TOWER DURING THE CONSTRUCTION OF THE BROOKLYN BRIDGE.



THE TOP OF THE BROOKLYN TOWER OF THE NEW MANHATTAN BRIDGE.

© 1908 SCIENTIFIC AMERICAN, INC